which was reassimilated during photosynthesis, a considerable portion appeared in D-glucitol after 6 hr.

4. To a small extent, D-glucuronic acid appeared to be converted into D-glucitol without rupture of the carbon chain.

5. When D-[1-¹⁴C]glucitol was fed to plum leaves, only about 20 % of the activity was detected in the leaves after 5 hr. and over 80 % of this was still present in D-glucitol.

The investigation formed part of the programme of the Food Investigation Organization of the Department of Scientific and Industrial Research.

REFERENCES

- Abdel-Akher, M., Hamilton, J. K. & Smith, F. (1951). *J. Amer. chem. Soc.* **73**, 4691.
- Altermatt, H. A. & Neish, A. C. (1956). *Canad. J. Biochem. Physiol.* **34**, 405.
- Anderson, J. D., Andrews, P. & Hough, L. (1961). *Biochem. J.* **81**, 149.
- Andrews, P. & Hough, L. (1958). *J. chem. Soc.* p. 4483.
- Bassham, J. A., Benson, A. A., Kay, L. D., Harries, A. Z., Wilson, A. T. & Calvin, M. (1954). *J. Amer. chem. Soc.* **76**, 1760.
- Bernstein, I. A. (1953). *J. biol. Chem.* **205**, 309.
- Brice, C. & Perlin, A. S. (1957). *Canad. J. Biochem. Physiol.* **35**, 7.
- Fenton, H. J. H. & Jackson, H. (1899). *J. chem. Soc.* **75**, 1.
- Folkes, B. F., Willis, A. J. & Yemm, E. W. (1952). *New Phytol.* **51**, 317.
- Gibbs, M. & Kandler, O. (1957). *Proc. nat. Acad. Sci., Wash.*, **43**, 446.
- Grant, J. (1945). In *Pregl's Quantitative Organic Micro-Analysis*, 4th ed., p. 60. London: J. and A. Churchill Ltd.
- Hers, H. G. (1958). *Proc. int. Symp. Enzyme Chem., Tokyo-Kyoto*, p. 109. Tokyo: Maruzen Company Ltd.
- Hers, H. G. (1960). *Biochim. biophys. Acta*, **37**, 120, 127.
- Hockett, R. C. & McClenahan, W. S. (1939). *J. Amer. chem. Soc.* **61**, 1667.
- Hough, L., Jones, J. K. N. & Wadman, W. H. (1950). *J. chem. Soc.* p. 1702.
- Hough, L. & Pridham, J. B. (1955). *Arch. Biochem. Biophys.* **59**, 17.
- Hutchinson, A., Taper, C. D. & Towers, G. H. N. (1959). *Canad. J. Biochem. Physiol.* **37**, 901.
- Kessler, G., Neufeld, E. F., Feingold, D. S. & Hassid, W. Z. (1961). *J. biol. Chem.* **236**, 308.
- McClenahan, W. S. & Hockett, R. C. (1938). *J. Amer. chem. Soc.* **60**, 2061.
- Markham, R. (1942). *Biochem. J.* **36**, 790.
- Moore, S. & Link, K. P. (1940). *J. biol. Chem.* **133**, 293.
- Muntz, J. A. & Carroll, R. E. (1960). *J. biol. Chem.* **235**, 1258.
- Rees, W. R. & Reynolds, T. (1958). *Nature, Lond.*, **181**, 767.
- Salomon, L. L., Burns, J. J. & King, C. G. (1952). *J. Amer. chem. Soc.* **74**, 5161.
- Shibko, S. & Edelman, J. (1957). *Biochim. biophys. Acta*, **25**, 642.
- Slater, W. G. & Beevers, H. (1958). *Plant Physiol.* **33**, 146.
- Trevelyan, W. E., Procter, D. P. & Harrison, J. S. (1950). *Nature, Lond.*, **166**, 444.
- Vargha, L. von (1935). *Ber. dtsh. chem. Ges.* **68**, 18.
- Verley, A. & Bölsing, F. (1901). *Ber. dtsh. chem. Ges.* **34**, 3354.

Biochem. J. (1962) **84**, 146

Automatic Analysis of Amino Acids by Polarographic Estimation of their Copper Complexes

BY M. C. CORFIELD AND A. ROBSON
Wool Industries Research Association, Leeds 6

(Received 22 January 1962)

Spackman, Stein & Moore (1958) described an automatic recording apparatus for amino acid analysis that used the photometric ninhydrin method to estimate the amino acids. Similar analysers have been described (Simmonds, 1958; Woods & Engle, 1960), and several automatic amino acid analysers of this type are now available commercially.

We have previously determined amino acids as their copper complexes (Blackburn & Robson, 1953; Corfield & Robson, 1953), and have used this analytical method in the construction of an automatic amino acid analyser. During the

development of this apparatus, we considered the possibilities of measuring the copper in the amino acid complexes by radiometric, colorimetric and polarographic methods. The radiometric method was rejected because ⁶⁴Cu has too short a half-life, and the colorimetric method was technically too complicated. The polarographic estimation of copper complexes of amino acids has been used for the quantitative analysis of amino acid mixtures resolved by chromatography on paper (Martin & Mittelman, 1948), on starch columns (Kemula & Witwicki, 1955) and on cation-exchange-resin columns (Blaedel & Todd, 1961), but no compre-

hensive and automatic scheme of amino acid analysis by this method has yet been described.

This paper outlines the construction and operation of an automatic amino acid analyser that uses the polarographic technique to determine the amounts of amino acids separated by ion-exchange-resin chromatography. A brief account of this work was given by Corfield & Robson (1961).

EXPERIMENTAL

General description of apparatus. A schematic diagram of the apparatus is shown in Fig. 1. The pump, *B*, takes buffer from a reservoir and delivers it at a constant rate to a cation-exchange-resin column previously loaded with the amino acid mixture to be analysed. The pump consists of a stainless-steel cylinder filled with paraffin oil and fitted with a piston driven by a synchronous motor through a conventional gear-box. As the piston moves at a fixed speed, it displaces the oil into a glass cylinder filled with aqueous buffer which is in turn displaced down the resin column. The pump can deliver at rates between 5 and 40 ml./hr. and will work satisfactorily at pressures up to 60 lb./in.². A DCL micro-pump (Distillers Co. Ltd., Epsom, Surrey) is also satisfactory. Part of the effluent is removed continually by a two-tube peristaltic pump and mixed with an equal volume of pH-adjusting solution from a second reservoir. After passing through a mixing coil maintained at 30° the resultant solution, now at pH 9.2, flows down a column of copper phosphate mixed with Cellulapapver (ethanol-treated cellulose powder, Grycksbo Pappersbruk, Grycksbo, Sweden) that converts the amino acids into their copper complexes. A stream of nitrogen saturated with water vapour sweeps the solution, via a spiral of glass capillary maintained at 30°, into a specially constructed polarographic cell (Fig. 2). The cell, also maintained at 30°, has separate outlets for nitrogen,

mercury and aqueous effluent. A potential difference of 0.7 v is applied across this cell, and the amplified diffusion current is fed to a recorder.

The amounts of amino acids present in the mixture under examination are determined from the areas of the corresponding peaks on the record; the proportionality factor between area and amount of amino acid is determined for each amino acid by assay of standard mixtures. Citrulline, which does not normally occur in protein hydrolysates, is added to the unknown amino acid mixture as an internal standard to provide a check on the reproducibility of the cell response.

Amino acid separations. The acidic and neutral amino acids are separated on 0.9 cm. $\times$ 150 cm. columns of Zeo-Karb 225 (X8) cation-exchange resin in the form of 20–30 μ beads. This resin was separated from a through-200-mesh sample by the flotation method of Hamilton (1958), and was preferred to crushed resin of the same particle size because it showed no change in its resistance to buffer flow with ageing. Acetate–chloroacetate buffers are used for elution since citrate ion forms a complex with copper. The change from buffer at pH 3.18 to buffer at pH 4.25 is made 15 ml. after the emergence of the proline peak, and the column is maintained at 50° throughout. The basic amino acids are separated on a 0.9 cm. $\times$ 15 cm. column of the same cation-exchange resin maintained at 50° and eluted with acetate buffer, pH 5.28.

The conditions for chromatography are thus essentially those used by Spackman *et al.* (1958) except for the compositions of the buffers (see below). Typical records of the amino acid separations are shown in Fig. 3.

Buffers and pH-adjusting solutions. The acetate–chloroacetate buffers at pH 3.18 and 4.25 are formulated to meet the following requirements: (a) the Na⁺ ion concentration is 0.2M in both buffers to prevent disturbance of the resin bed by the buffer change; (b) both buffers have the same chloroacetate ion concentration to avoid the unwanted pH changes that occur in the effluent during the buffer change if there is chloroacetate in the buffer at pH 3.18 and acetate only in the buffer at pH 4.25; (c) the free acid concentrations are the same in both buffers to facilitate their subsequent adjustment to pH 9.2 when mixed with an equal volume of pH-adjusting solution I (see below).

With these requirements in mind, the buffers can be conveniently prepared by the following procedure. A solution of mixed acids is prepared by dissolving 118.3 g. of 99% (w/w) chloroacetic acid in 250 ml. of 1.60N-acetic acid. (This solution is referred to subsequently as 'mixed acids'.) For the buffer at pH 3.18, 13.41 g. of sodium acetate trihydrate and 5.95 g. of NaCl are dissolved in 975 ml. of water. The resulting solution is boiled under paraffin oil to remove air and, while the solution is warm, 10 ml. of benzyl alcohol and 5 ml. of thiodiglycol are added. The solution is cooled and mixed thoroughly with 25 ml. of mixed acids. For the buffer at pH 4.25, 27.22 g. of sodium acetate trihydrate are dissolved in 975 ml. of water and the resulting solution is treated in the same way as for the buffer at pH 3.18 with the same additions of benzyl alcohol, thiodiglycol and mixed acids. No detergent must be added to these buffers as it interferes with polarography. Both these buffers can be adjusted to pH 9.2 by mixing with an equal volume of pH-adjusting solution I, which is prepared by dissolving 14 g. of Na₂HPO₄, 38 g. of Na₂B₄O₇·10H₂O and 10 g. of Na₂SO₃·7H₂O in 1 l. of 0.164N-NaOH.

Fig. 1. Schematic drawing of amino acid analyser. *A*, Buffer reservoir; *B*, high-pressure pump; *C*, 0.9 cm. $\times$ 150 cm. Zeo-Karb 225 (X8) resin column; *D*, outlets to waste; *E*, reservoir of pH-adjusting solution; *F*, two-tube peristaltic pump; *G*, glass capillary mixing coil at 30°; *H*, copper phosphate column; *I*, nitrogen inlet; *J*, glass capillary coil at 30°; *K*, polarographic cell; *L*, galvanometer-d.c. amplifier; *M*, recorder.

The pH 5.28 buffer is prepared by dissolving 47.64 g. of sodium acetate trihydrate in 1 l. of 0.080 N-acetic acid. This can be adjusted to pH 9.2 by adding an equal volume of pH-adjusting solution II, prepared by dissolving 14 g. of Na_2HPO_4 , 38 g. of $\text{Na}_2\text{B}_4\text{O}_7 \cdot 10\text{H}_2\text{O}$ and 10 g. of $\text{Na}_2\text{SO}_3 \cdot 7\text{H}_2\text{O}$ in 1 l. of 0.080 N-NaOH.

Copper phosphate column. A 14:1 (w/w) mixture of Cellulosapulver and powdered copper phosphate is made into a slurry with phosphate-borax buffer, pH 9.2 (Blackburn & Robson, 1953). This is poured into a 0.9 cm. $\times$ 11 cm. glass column fitted with a polythene sinter, and allowed to settle to a height of 10 cm. The column is connected to the flow line from the peristaltic pump with total exclusion of air. The Cellulosapulver acts as an inert support for the powdered copper phosphate, and prevents back-pressure in the flow that occurs if powdered copper phosphate alone is used.

A transit time of 20 min. for the passage of solution down the column is allowed for the quantitative conversion of amino acids into their copper complexes, and the flow rate is therefore fixed at 10 ml./hr. This in turn fixes the rate at which effluent can be taken from the resin columns at 5 ml./hr., but in no way affects the ultimate polarographic determinations of the amino acid complexes, as this measurement depends on the concentration of the measured substance.

Polarographic cell. A drawing of the cell is shown in Fig. 2. The drop rate of the dropping-mercury electrode is fixed at 1 drop/3 sec. and its voltage at -0.7 v. The nitrogen used to sweep the solution into the cell also serves to maintain an oxygen-free atmosphere above the solution. The volume of solution in the immediate vicinity of the mercury drop is approximately 0.1 ml. and at a flow rate of 10 ml./hr. it will be changed about every 30 sec.

We have found that the most likely source of trouble and error lies in the performance of the polarographic cell. This will function satisfactorily provided that the following precautions are rigidly observed. (i) Only triple-distilled mercury is used. Occasionally the capillary of the dropping-mercury electrode may become blocked, and in our experience this only occurs when 'dirty' mercury is used. To obviate the necessity for a dropping electrode, we have tried various types of rotating electrodes, but these were not suitable for continuous measurement as their surface areas changed owing to irregular electrolytic deposition. (ii) The solution entering the cell must be perfectly clear and free from suspended matter. Since the solution is clear after passage down the copper phosphate column, extraneous matter can only be introduced in the nitrogen gas stream, and this is filtered out by a water bubbler, which serves to saturate the nitrogen with water vapour and prevent evaporation of solution in the cell. (iii) The cell temperature must be rigidly controlled. The water to jacket the cell is maintained at $30 \pm 0.02^\circ$.

Measuring and recording equipment. The current flowing through the polarographic cell is fed to a galvanometer-type d.c. amplifier. The light reflected from the galvanometer mirror is divided by a prism and falls on two photo-cells. Any difference between the two photoelectric currents is amplified, and a proportion fed back to the galvanometer circuit in a direction such that the galvanometer deflexion is held to a minimum. With this negative feed-back system, any current through the galvanometer from the polarographic cell produces a proportional feed-

back current, whose magnitude can be controlled by suitable feed-back resistors, and this is used to operate a high-impedance pen recorder. Resistance-capacity combinations in the feed-back chain stabilize the loop, and also give the arrangement an overall time-constant of about 8 sec., which is sufficiently long to damp the current fluctuations of the cell.

Separate variable stabilized d.c. supplies, incorporating Zener diodes, provide the polarizing voltage for the polarographic cell and the zero control current of the galvanometer. The latter is used to 'back-off' the 'background current' from the cell, which is due to the small, constant concentration of Cu^{2+} ion, and hence to position the recording pens at suitable places on the chart of the recorder. The recorder is a six-pen Kent recorder, but only two pens are in use. One pen has a full-scale deflexion of $1 \mu\text{A}$ and records at intervals of 1 min.; the second pen has a full-scale deflexion of $3 \mu\text{A}$ and also records at intervals of 1 min., but these are arranged so that it records 30 sec. after the first pen. The chart moves at 2 in./hr. Any commercial record-

Fig. 2. Scale drawing of polarographic cell. A, Dropping-mercury electrode; B, B14 socket; C, nitrogen outlet; D, inlet for nitrogen and solution; E, level of solution; F, outlet for water at 30° ; G, inlet for water at 30° ; H, mercury-pool anode; I, mercury outlet; J, solution outlet.

ing polarograph would be suitable for this part of the analyser.

Amino acid estimations. Typical chromatograms are shown in Fig. 3. The weights of amino acids are proportional to the areas of their corresponding peaks on the record. Proportionality factors, which depend on the natures of the copper-amino acid complexes and their diffusion coefficients, are found from peak areas obtained with known amounts of amino acids. The most accurate method of determining peak areas that we have used is to cut out the peaks from the paper and weigh them. When the amino acid trace has to be preserved, tracings of the peaks are made, cut out and weighed.

RESULTS

Before the analyser was used for amino acid estimations, experiments were carried out to assess the changes that occur in the diffusion current from the polarographic cell with variations in: (a) the amount of diffusing species, (b) the flow rate through the cell and (c) the transit time of amino acid down the copper phosphate column.

For Expt. (a), increasing amounts of lysine were dissolved in 0.35M-acetate buffer, pH 5.28, and 1.0 ml. samples of these solutions passed in turn through the peristaltic pump, mixed with the pH-adjusting solution II, passed down the copper phosphate column and thence into the polarographic cell. Between samples, the 0.35M-acetate buffer, pH 5.28, was passed through the pump to record the cell blank and also to purge the cell. Throughout the experiment, the dropping rate of the dropping-mercury electrode and the temperature were constant, and the dropping-mercury-electrode potential was -0.7 v. The peak areas, measured by cutting the peaks off the record and weighing them, were proportional to the amounts of lysine added.

For Expt. (b), 16.7 μ moles of lysine were dissolved in 12 ml. of 0.35M-acetate buffer, pH 5.28, and 12 ml. of pH-adjusting solution II and a few mg. of copper phosphate added. The solution was well mixed, allowed to stand for 2 hr. and filtered. A blank solution was similarly prepared, without the lysine. Samples (1.0 ml. and 0.5 ml.) of the lysine-copper-complex solution were pumped through the cell at different flow rates, and between samples the blank solution was passed to purge the cell and to record the cell blank. Peak areas corresponding to the lysine-copper complex were measured as described above, and the temperature, dropping-mercury-electrode dropping rate and potential held constant as in Expt. (a). The results are given in Table 1. If the rate of flow through the cell has no effect on the diffusion current recorded, then the ratio of the peak area multiplied by the flow rate to the amount of lysine complex passed (Av/x in the Table) should be constant. (This takes

account of the fact that the recorder-chart speed is the same for all measurements, whereas the transit time of the lysine complex in the cell varies.) For rates of flow between 4.3 and 18.5 ml./hr. the diffusion current peak does not change, but at faster flow rates the peaks are relatively broader.

In Expt. (c), samples of 0.667 μ mole of lysine in 1.0 ml. of 0.35M-acetate buffer, pH 5.28, were pumped through a copper phosphate column, after mixing with an equal volume of pH-adjusting solution II, at different flow rates and their diffusion current peaks recorded. The column was 0.9 cm. $\times$ 6 cm. and had a measured 'dead volume' of 3.0 ml.; thus at a flow rate of 3 ml./hr. a solution would take 1 hr. to pass through. A sample (0.667 μ mole) of lysine-copper complex, prepared as described above, was then passed through the polarographic cell to record its current peak as a standard. The results (Table 2) show that for transit times of 2.5 min. or more the reaction

Fig. 3. Separations of a synthetic mixture of amino acids: (a) 0.9 cm. $\times$ 150 cm. column of Zeo-Karb 225 (X8) resin eluted at 15 ml./hr. and 50°; (b) 0.9 cm. $\times$ 15 cm. column of Zeo-Karb 225 (X8) resin eluted at 30 ml./hr. and 50°. For amino acid loads see text.

Table 1. Relationship between recorded peak area for an amino acid-copper complex and flow rate through the polarographic cell

For experimental details, see text.

Flow rate (v) (ml./hr.)	$10^2 \times$ Area of peak (A) (μA hr.)	Lysine-copper complex (x) (μ moles)	Av/x
18.5	6.65	0.695	177
14.7	8.36	0.695	178
11.8	10.2	0.695	174
9.6	12.8	0.695	178
7.4	8.19	0.347	177
5.7	11.0	0.347	182
4.3	14.7	0.347	184

Table 2. *Relationship between rate of flow of lysine through a copper phosphate column and its conversion into lysine-copper complex*

The sample (0.667 μ mole) of lysine was passed down a 0.9 cm. $\times$ 6 cm. column of copper phosphate. For 100% conversion into lysine-copper complex, $Av/x = 176$.

Flow rate (v) (ml./hr.)	$10^2 \times$ Area of peak (A) (μA hr.)	Av/x	Conversion into copper complex (%)
147.5	0.69	153	87
73.5	1.59	175	100
37.0	3.18	177	100
29.4	3.87	172	98
23.6	4.94	175	100
14.8	8.08	179	102
8.6	13.6	176	100

Table 3. *Test of reproducibility of areas of amino acid peaks*

For experimental details, see text.

Run no.	...	Area of peak (cm. ²)			Mean peak area (cm. ²)
		1	2	3	
Amino acid					
	Cysteic acid	20.4	19.5	18.9	19.6
	Aspartic acid	20.2	20.5	20.1	20.3
	Threonine	19.7	20.1	19.2	19.7
	Serine	18.4	19.2	18.6	18.7
	Glutamic acid	15.3	14.8	14.4	14.8
	Citrulline	15.1	15.1	15.1	15.1
	Proline	13.4	13.5	13.3	13.4
	Glycine	18.2	18.5	17.7	18.1
	Alanine	15.3	15.2	15.2	15.2
	Cystine	15.1	15.2	15.0	15.1
	Valine	18.2	18.2	18.3	18.2
	Methionine	16.2	15.6	15.9	15.9
	allo-Isoleucine	1.4	1.3	1.5	1.4
	Isoleucine	16.1	16.2	16.4	16.2
	Leucine	17.9	17.4	17.0	17.4
	Tyrosine	16.9	17.2	16.4	16.8
	Phenylalanine	16.7	16.9	16.9	16.8

between Cu^{2+} ions and the amino acid is quantitative. It is inadvisable to use columns of lengths 2 cm. or less, since 'channelling' of the solution may occur over short lengths of column and conversion of an amino acid into its copper complex may be only 30% of the expected value. On the analyser, the use of copper phosphate columns 10 cm. in length and a transit time of 20 min. ensures complete conversion.

The reproducibility of the peak areas when a mixture of amino acids is estimated by the analyser is exemplified in Table 3, which gives the results of three consecutive runs (1-3) on the 150 cm. column with identical amino acid loads. Each load contained 2.0 μ moles of valine, 1.66 μ moles of isoleucine, 0.14 μ mole of allo-isoleucine and 1.79 μ moles of all the other amino acids. This Table

shows that reproducibility is $100 \pm 3\%$, comparable with the results of Spackman *et al.* (1958).

Table 4 shows the results obtained by analysis of 2.25 mg. of an hydrolysate of ox insulin (prepared by hydrolysis for 16 hr. in 5.7N-hydrochloric acid under reflux). The values for serine and threonine have been corrected for estimated hydrolytic losses of 10 and 5%, respectively. The results are the means of duplicate analyses expressed as residues of amino acid/molecule of insulin, and are compared with those of Harfenist & Craig (1952) on a 20 hr. hydrolysate. The actual values for these amino acid residues are derived from Sanger's formula for ox insulin (Ryle, Sanger, Smith & Kitai, 1955).

The low values obtained for the amino acids isoleucine, valine, lysine and alanine indicate that the peptides Lys-Ala and Ileu-Val are incompletely hydrolysed under the conditions used.

DISCUSSION

The automatic amino acid analyser differs in two important respects from that of Spackman *et al.* (1958): the amino acids are estimated as their copper complexes by polarography, and chloroacetate-acetate buffers are used for their separations on the ion-exchange-resin columns. At present, the 150 cm. resin columns are eluted at 15 ml./hr. and the 15 cm. column at 30 ml./hr. Under these conditions a complete amino acid analysis takes 48 hr., but more suitable high-pressure pumps are being installed to reduce this time to 24 hr.

The polarographic method of amino acid estimation is no more sensitive than the ninhydrin method

Table 4. *Amino acid composition of ox insulin*

For experimental details, see text.

Amino acid	Amino acid residues/mole of insulin		
	Present work	Ryle, Sanger, Smith & Kitai (1955)	Harfenist & Craig (1952)
Aspartic acid	3.18	3	2.89
Threonine	1.04	1	0.97
Serine	3.18	3	2.89
Glutamic acid	6.95	7	6.74
Proline	1.00	1	1.07
Glycine	4.23	4	3.95
Alanine	2.69	3	2.95
Cystine	3.12	3	2.91
Valine	4.26	5	4.73
Isoleucine	0.60	1	0.66
Leucine	6.06	6	5.85
Tyrosine	3.96	4	3.98
Phenylalanine	2.99	3	2.98
Lysine	0.87	1	1.01
Histidine	2.07	2	2.00
Arginine	0.98	1	1.02

except in the estimation of histidine, which forms a complex of 1 molecule of histidine and 1 atom of copper, but the apparatus required is simpler to construct and the somewhat messy ninhydrin reagent is avoided. However, many substances which react with ninhydrin to give the characteristic blue colour will not form copper complexes, and will be missed by the analyser. These substances include β - and γ -amino acids and ammonia. Though this would be an obvious disadvantage for some analyses, it may be an advantage when estimations of protein amino acids alone are required, and their chromatographic separation and estimation would be confused by the presence of other ninhydrin-positive peaks. In addition to providing a useful alternative to the ninhydrin method, the analyser could also be used to follow the chromatography of peptides. Both large and small peptides will form copper complexes and these might be estimated polarographically.

The chloroacetate-acetate-buffer system used for elution of the 150 cm. resin column gives amino acid separations similar to those of Spackman *et al.* (1958). Though it appears to be slightly inferior to the citrate-buffer system in separating threonine from serine, it gives better separations of glutamic acid from proline, and of tyrosine from phenylalanine.

Use can be made of citrulline as an internal standard, to avoid re-determination of the proportionality factors for the amino acids after replacement of the capillary of the dropping-mercury electrode or changes in its dropping rate. This amino acid is not a normal constituent of proteins, and a known amount can be added to all protein or peptide hydrolysates before analysis. Siegel & Roach (1961) recommended the use of β -thien-2-yl-DL-alanine as an internal standard for amino acid analyses with the Spackman *et al.* (1958) analyser.

Blaedel & Todd (1961), in the polarographic estimation of amino acid-copper complexes, converted these complexes into copper-EDTA complexes to make 'the polarographic response non-specific for the different amino acids' because 'the various copper-amino acid chelates have different diffusion coefficients'. Though the second statement is correct, the first statement seems to be based on the erroneous assumption that an equal number of moles of amino acid anions combine with the same amount of Cu^{2+} ion, at pH 9.2, to give complexes of the general formula CuA_2 . If

this assumption were correct, then the extra conversion step used by Blaedel & Todd would be greatly advantageous, since equal numbers of moles of amino acids would give the same peak areas; but Woiwod (1949), and the present authors, have shown that amino acids do not all form complexes stoichiometrically. Therefore the conversion of amino acid-copper complexes into copper-EDTA complexes seems to be an unnecessary complication.

SUMMARY

1. The construction and performance of an automatic amino acid analyser are described.

2. The amino acids are estimated by polarography of their copper complexes; thus β - and γ -amino acids, and ammonia, which do not form copper complexes, cannot be determined.

3. The sensitivity of the instrument is similar to those based on the ninhydrin method for estimation of amino acids, and its accuracy is $100 \pm 3\%$ for all protein amino acids.

4. The performance of the analyser is exemplified by an analysis of an hydrolysate of insulin.

The authors are greatly indebted to Mr R. Gibson for the design and construction of the galvanometer-amplifier used in the analyser, and for the other electronic equipment. Part of the cost of construction of the analyser was paid by the Agricultural Research Service of the United States Department of Agriculture under the authority of Public Law 480.

REFERENCES

- Blackburn, S. & Robson, A. (1953). *Biochem. J.* **54**, 295.
Blaedel, W. J. & Todd, J. W. (1961). *Analyt. Chem.* **33**, 205.
Corfield, M. C. & Robson, A. (1953). *Biochem. J.* **55**, 517.
Corfield, M. C. & Robson, A. (1961). *Biochem. J.* **80**, 37p.
Hamilton, P. B. (1958). *Analyt. Chem.* **30**, 914.
Harfenist, E. J. & Craig, L. C. (1952). *J. Amer. chem. Soc.* **74**, 4216.
Kemula, W. & Witwicki, J. (1955). *Roczn. Chem.* **29**, 1153.
Martin, A. J. P. & Mittelmann, R. (1948). *Biochem. J.* **43**, 353.
Ryle, A. P., Sanger, F., Smith, L. F. & Kitai, R. (1955). *Biochem. J.* **60**, 541.
Siegel, F. L. & Roach, M. K. (1961). *Analyt. Chem.* **33**, 1628.
Simmonds, D. H. (1958). *Analyt. Chem.* **30**, 1043.
Spackman, D. H., Stein, W. H. & Moore, S. (1958). *Analyt. Chem.* **30**, 1190.
Woiwod, A. J. (1949). *Biochem. J.* **45**, 412.
Woods, K. R. & Engle, R. L. (1960). *Ann. N.Y. Acad. Sci.* **87**, 764.