Journal of Zhejiang University SCIENCE B

ISSN 1673-1581

<http://www.zju.edu.cn/jzus>

E-mail: jzus@zju.edu.cn

Study on NO₂ absorption by ascorbic acid and various chemicals^{*}

LI Wei (李伟)¹, WU Cheng-zhi (吴成志)¹, FANG He-liang (方和良)²,SHI Yao (施耀)^{†‡1}, LEI Le-cheng (雷乐成)¹⁽¹⁾Institute of Environmental Engineering, Zhejiang University, Hangzhou 310027, China)⁽²⁾Institute of Catalysis, Zhejiang University, Hangzhou 310028, China)[†]E-mail: yaoshi@zju.edu.cn

Received Aug. 10, 2005; revision accepted Sept. 29, 2005

Abstract: Study on NO₂ absorption aimed at seeking a better NO₂ absorption chemical at pH 4.5~7.0 for application to existing wet flue gas desulfurization (FGD). The results from the double-stirred reactor indicated that ascorbic acid has very high absorption rate at this pH range. The rate constant of ascorbic acid reaction with NO₂ (0~1000×10⁻⁶ mol/mol) is about 3.54×10⁶ mol/(L·s) at pH 5.4~6.5 at 55 °C.

Key words: NO₂, Absorption, Rate constant, Ascorbic acid

doi:10.1631/jzus.2006.B0038

Document code: A

CLC number: X511

INTRODUCTION

Nitrogen oxide (NO_x) is one of the main air pollutants found in the flue gases from chemical and power plants belching acid rain and photochemical smog. Over 90 percent of all man-made nitrogen oxides that enter our atmosphere are produced by the combustion of various fuels. Compared with the advanced stage of SO₂ gas removal technologies development, the removal of NO_x gases is still in the initial stages of development as roughly 90 to 95 percent of NO_x emitted in combustion processes appears in the form of NO which is comparatively inactive and insoluble. To reduce the generation and emission of NO_x to the atmosphere, it is necessary to use low nitrogen fuel, low NO_x burners and implement more stringent air pollutant emission standards, it is necessary to setup and operate NO_x control devices for further reduction of pollutions. Some processes have been dis-

cussed, such as SCR (selective catalytic reduction), SNCR (selective non-catalytic reduction), NSCR (non-selective catalytic reduction) and adsorption. Wet FGD (flue gas desulfurization) scrubbers are very efficient to remove SO₂ from flue gas, but cannot remove NO because of its low solubility in aqueous solution. Research efforts to modify existing wet FGD processes for simultaneous control of SO₂ and NO_x emissions led to several new approaches to enhance NO_x absorption in scrubbing liquors.

One promising approach to simultaneously remove SO₂ and NO_x from flue gas is the combination of NO oxidation to NO₂ and conventional wet scrubbing. The possible NO oxidants include KMnO₄ (Kobayashi *et al.*, 1977), hydrogen peroxide (Thomas and Vandescheren, 1998), NaClO (Chien and Chu, 2000), P₄ (Chang and Lee, 1992), etc. The NO oxidation product, NO₂, can be absorbed by several chemical reagents, although most chemical reagents for NO₂ absorption are effective only at high pH range. In this work, our research is aimed at finding a better NO₂ absorption chemical effective at pH 4.5~7.0, which is the application pH range for existing popular wet limestone/lime FGD.

[‡] Corresponding author

^{*} Project supported by the National Natural Science Foundation of China (No. 20176052) and the Scientific Research Foundation for Returned Overseas Chinese Scholars, Ministry of Education, China

EXPERIMENTAL DETAILS

Chemicals

L-ascorbic acid (99%), thiourea (99%), 2,4-pentanedione (99%), 2,3-pentanedione (97%), barbituric acid (99%), oxalic acid (98%), glyoxal (40 wt%), di(ethylene glycol) (99%), were all obtained from Shanghai Chemical Reagent Co., China and used without further purification. The gases used included 5.0% NO₂ in N₂ and 99.99% N₂. All other chemicals were analytical grade reagents.

Apparatus and procedure

Experiments on NO₂ absorption were carried out in a highly characterized double-stirred reactor with a planar gas-liquid interface, which was mentioned in our previous papers (Shi *et al.*, 1996; 1997). The double-stirred reactor had a gas-liquid interface that was planar to a close approximation. The reactor was 80 mm in diameter and equipped with four vertical baffles and two stirring blades. A water jacket of the reactor is used to maintain the desired temperature by circulating water from a constant temperature water bath. The reactor had continuous gas flow rate of 1000 ml/min. Five percent (V/V) of NO₂ was diluted by carrier nitrogen gas. The inlet concentration of NO₂ in this experiment ranged from 0~1000×10⁻⁶ mol/mol. All the experiments were conducted with liquid stirring speed of 150 r/min and gas stirring speed of 900 r/min. The experimental setup includes a flue gas simulation system, a double-stirred reactor, and analysis system shown in Fig.1.

Fig.1 Experimental setup for measurement of NO absorption

1, 2: NO₂, N₂ cylinder; 3: Attenuator; 4: Gas flowmeters; 5: Gas/liquid control valve; 6: Driving motors; 7: Stirred cell reactor; 8: Stirring speed controller; 9: Cold trap; 10: Gas analyzer; 11: Entrance of liquid

The liquid phase was a deionized water solution of chemical reagents. The solution pH was adjusted by adding small amounts of concentrated NaOH or H₂SO₄. The volume of the aqueous solution in the reactor was always 310 ml. For the case of SO₃²⁻ solution preparation, the deionized water was boiled for 10 min to remove the dissolved oxygen, then cooled down no oxygen atmosphere. All the experiments were performed at 55 °C (normal temperature of conventional wet FGD) in stirring reactor and operated in batch mode. The gas film mass transfer coefficient of the apparatus (K_{GNO_2}) was 2.04×10^{-5} kmol/(m²·s) and the liquid-side mass transfer coefficient (K_{KNO_2}) was 3.96×10^{-6} kmol/(m²·s) (Shi *et al.*, 1996).

The inlet and outlet gas concentration of NO₂ were measured with a chemiluminescent NO_x analyzer with independent outputs for NO, NO₂, and NO_x. A cold trap was used to remove moisture before the gas entered the analyzers. During the experiments, NO₂ and NO_x in the simulated flue gas were examined.

RESULTS AND DISCUSSION

Comparison of NO₂ absorption rate by various chemical reagents

To search for ideal chemical to absorb and reduce NO₂, numerous chemicals were tested in the stirring reactor. The NO₂ absorption rates of various chemicals, including thiourea, urea, sodium sulfide, 2,4-pentanedione, 2,3-pentanedione, barbituric acid, oxalic acid, sodium sulfite, sodium thiosulfate, L-ascorbic acid, glyoxal, di(ethylene glycol) and water, were determined with different pH. The results of comparison of the rate of NO₂ absorption into these chemical reagents with various pH values are depicted in Fig.2.

Effect of ascorbic acid concentration on the absorption rate

Fig.3 shows the effect of the square root of ascorbic acid concentration on the absorption rate. The absorption rate increases linearly increasing ascorbic acid concentration (C_{B0}) from 0~25 mmol/L. On the basis of mass transfer model with chemical reaction, there should be a linear relationship between

Fig.2 Effect of the aqueous solution pH on the rate of NO₂ absorption by various chemicals

Gas flowrate: 1000 ml/min; NO: 500×10^{-6} mol/mol; C_{B0} : 0.05 mol/L; T : 55 °C

Fig.3 Effect of ascorbic acid concentration on the absorption rate

T : 55 °C; pH: 5.4~6.0; NO: 500×10^{-3} mol/mol; Gas flow rate: 1000 ml/min

NO₂ absorption rate and the square root of the ascorbic acid concentration in a second order reaction (first order with respect to ascorbic acid and first order with respect to NO₂). The prediction was confirmed in the range of low concentration of ascorbic acid, 0~25 mmol/L. When concentration was higher than 25 mmol/L, the absorption rates remained almost steady at 1.4×10^{-5} mol/(m²·s), which probably indicated that the reaction was a fast gas-liquid surface reduction during the concentration range.

Chemical and physical properties of NO₂

The kinetics and chemistry of NO₂ absorption into aqueous solution is complicated. Schwartz (1983) reviewed the chemical equilibria in detail, including the Henry's law (solubility) equilibria of the reactive oxides NO₂ and N₂O₄, etc. Henry's coefficient, H_{NO_2} , and the rate of the second-order hydrolysis reaction, k_2 , are two key parameters required for characterizing heterogeneous process involving NO₂ (g). However, even after numerous studies, uncertainty still exists in the values of these two parameters. Literature values range from 7×10^{-8} to 2×10^{-7} mol/(L·Pa) for H_{NO_2} , and from 10^7 to 10^8 mol/(L·s) for k_2 at 25 °C. These uncertainties are mainly due to the complexity of NO₂ aqueous interaction.

In our research, the diffusion coefficient of dissolved NO₂ (D_{NO_2}) was taken to be 3.28×10^{-9} m²/s (Shen and Rochelle, 1998; Wilke and Chang, 1955) at 55 °C. Henry's coefficient of NO₂, H_{NO_2} , was taken to be 1.4×10^{-7} mol/(L·Pa) at 25 °C in recent research results of Cheung *et al.* (2000). No existing data on H_{NO_2} at 55 °C was found a way must be found to estimate it.

The solubility of gases decreases with increasing temperature. According to the relation of Henry's coefficient and the temperature, H_{NO_2} at 55 °C could be estimated by the following Clausius-Clapeyron equation (Manahan, 1999):

$$\text{Log}(C_2/C_1) = (\Delta H / 2.303R) \times (1/T_1 - 1/T_2), \quad (1)$$

where C_1 and C_2 denote the gas concentration in water at absolute temperatures of T_1 and T_2 , respectively; ΔH is the heat of solution; and R is the gas constant. The value of R is 8.314 J/(K·mol), which gives ΔH units of J/mol. However, due to the complexity and uncertainty of ΔH , we have to take the data from Cheung *et al.* (2000), $H_{\text{NO}_2} = 1.4 \times 10^{-7}$ mol/(L·Pa) at 20 °C and 2.3×10^{-7} mol/(L·Pa) at 0 °C, and the Clausius-Clapeyron equation to extrapolate Henry's constant at temperature of 55 °C. Henry's constant of NO₂ at 55 °C is estimated to be 6.8×10^{-8} mol/(L·Pa) by the above means.

Estimate of NO₂ reaction rate constant

According to Danckwerts theory (Danckwerts, 1970), in fast pseudo- m -order reaction, there is linear relationship between the absorption rate and square root of the ascorbic acid concentration if C_{B0} the concentration of ascorbic acid in the bulk liquid, is much larger than the NO₂ concentration at the interface, that is: $N_A \propto C_{B0}$. To a close approximation, the absorption rate for a pseudo- m th order reaction is given by

$$N_A = \sqrt{2k_{m+1}DC_i^{m+1}C_{B0}/(m+1)}, \quad (2)$$

where D is the diffusivity in liquid phase, m²/s; m is the reaction order; N is the absorbing rate; k is the rate constant; A is dissolved gas (NO₂); B is the liquid-phase reactant; i is the gas-liquid interface and 0 is initial value.

Fig.3 shows a linear relationship between the absorption rate and square root of the ascorbic acid concentration of 0~25 mmol/L, which verifies that the

value of m in Eq.(2) should be 1.0. Hence, this absorption is the fast pseudo-first order reaction when the ascorbic acid concentration is 0~25 mmol/L. The reaction rate constants between NO₂ and ascorbic acid can be obtained from Eq.(2) using the experimental data and the above estimated chemical and physical parameters. The calculating results on reaction rate constants are shown in Table 1. The rate constant of ascorbic acid reaction with NO₂ is about 3.54×10^6 mol/(L·s) at pH 5.4~6.5 at 55 °C.

The chemistry of NO₂ absorption into aqueous phase of SO₃²⁻ or other reagents is complicated. The reduction of NO₂ was found to be first order with respect to SO₃²⁻ and first order with respect to NO₂ by Takeuchi *et al.*(1977). Shen and Rochelle (1998) indicated that the reactions between NO₂ and sulfite (SO₃²⁻), bisulfite (HSO₃²⁻) and thiosulfate (S₂O₃²⁻) were first order in NO₂ concentration. Their rate constants at 55 °C in this work and in other reports are also listed in Table 1.

Table 1 Values of NO₂ reaction rate constant, k_2

Reagent	Investigator	k_2 , mol/(L·s)
Ascorbic acid (pH 5.4~6.5)	This work	3.54×10^6
SO ₃ ²⁻ /HSO ₃ ²⁻ (pH 5.4~6.5)	This work	1.05×10^6
Sodium thiosulfate (pH 5.4~6.5)	This work	3.37×10^5
SO ₃ ²⁻	Shen and Rochelle (1998)	1.12×10^6
HSO ₃ ²⁻	Shen and Rochelle (1998)	2.8×10^4
S ₂ O ₃ ²⁻	Shen and Rochelle (1998)	5.4×10^3
SO ₃ ²⁻	Takeuchi <i>et al.</i> (1977)	6.6×10^5

CONCLUSION

The results from the double-stirred reactor indicated that ascorbic acid has very high absorption rate at the wet limestone/lime FGD pH 5.0~7.0, the order of NO₂ absorption rate is as follows, ascorbic acid>2.4-pentanedione>SO₃²⁻/HSO₃²⁻>S₂O₃²⁻>2.3-pentanedione>barbituric acid>thiourea>oxalic acid>glyoxal>citrate>H₂O. The calculated results on reaction rate constant of ascorbic acid reaction with NO₂ is about 3.54×10^6 mol/(L·s) at for pH 5.4~6.5 at 55 °C.

References

Chang, S.G., Lee, G.C., 1992. LBL PhoSNOX process for

- combined removal of SO₂ and NO_x from flue-gas. *Environ. Prog.*, **11**(1):66-73.
- Cheung, J.L., Li, Y.Q., Boniface, J., Shi, Q., Davidovits, P., 2000. Heterogeneous interactions of NO₂ with aqueous surfaces. *J. Phys. Chem. A*, **104**:2655-2662. [doi:10.1021/jp992929f]
- Chien, T.W., Chu, H., 2000. Removal of SO₂ and NO_x from flue gas by wet scrubbing using an aqueous NaClO₂ solution. *J. Hazard. Mater.*, **80**:43-57. [doi:10.1016/S0304-3894(00)00274-0]
- Danckwerts, P.V., 1970. Gas-Liquid Reaction. McGraw-Hill, New York.
- Kobayashi, H., Takezawa, N., Niki, T., 1977. Removal of nitrogen oxides with aqueous solutions of inorganic and organic reagents. *Environ. Sci. Technol.*, **11**:190-192. [doi:10.1021/es60125a011]
- Manahan, S.E., 1999. Environmental Chemistry, 7 Ed., Lewis Publishers, USA.

- Schwartz, S.E., 1983. Trace Atmospheric Constituents—Properties, Transformations and Fates. John Wiley & Sons, New York.
- Shen, C.H., Rochelle, G.T., 1998. Nitrogen dioxide absorption and sulfite oxidation in aqueous sulfite. *Environ. Sci. Technol.*, **32**(13):1994-2003. [doi:10.1021/es970466q]
- Shi, Y., Littlejohn, D., Chang, S.G., 1996. Kinetic of NO absorption in aqueous iron (II). Bio(2,3-dimercapto-1-propanesulfonate) solutions using a stirred reactor. *Ind. Eng. Chem. Res.*, **35**(5):1668-1672. [doi:10.1021/ie950655m]
- Shi, Y., Wang, H., Chang, S.G., 1997. Kinetics of NO absorption in aqueous iron (II) thiochelatate solutions. *Environ. Prog.*, **16**(4):301-306.
- Takeuchi, H., Ando, M., Kizawa, N., 1977. Absorption of nitrogen oxides in aqueous sodium sulfite and bisulfite solutions. *Ind. Eng. Chem. Process Des. Dev.*, **16**:303-308. [doi:10.1021/i260064a009]
- Thomas, D., Vandescheren, J., 1998. Removal of NO_x from flue gases using solution containing hydrogen peroxide. *Chem. Eng. Technol.*, **21**(12):975-980. [doi:10.1002/(SICI)1521-4125(199812)21:12<975::AID-CEAT975>3.0.CO;2-H]
- Wilke, C.R., Chang, P., 1955. Correlation of diffusion coefficients in dilute solutions. *AIChE J.*, **1**:264-270. [doi:10.1002/aic.690010222]

Editors-in-Chief: Pan Yun-he & Peter H. Byers
(ISSN 1673-1581, Monthly)

Journal of Zhejiang University

SCIENCE B

<http://www.zju.edu.cn/jzus>

jzus@zju.edu.cn

JZUS-B focuses on "Biomedicine, Biochemistry & Biotechnology"

➤ Welcome Your Contributions to JZUS-B

Journal of Zhejiang University SCIENCE B warmly and sincerely welcome scientists all over the world to contribute to JZUS-B in the form of Review, Article and Science Letters focused on **Biomedicine, Biochemistry and Biotechnology areas**. Especially, Science Letters (3–4 pages) would be published as soon as about 30 days (Note: detailed research articles can still be published in the professional journals in the future after Science Letters is published by JZUS-B).

➤ Contributions requests

- (1) Electronic manuscript should be sent to jzus@zju.edu.cn only. If you have any question, please feel free to visit our website: <http://www.zju.edu.cn/jzus>, and hit "For Authors".
- (2) English abstract should include Objective, Method, Result and Conclusion.
- (3) Tables and figures could be used to prove your research result.
- (4) Full text of the Science Letters should be in 3–4 pages. The length of articles and reviews are not limited.
- (5) Please visit our website (<http://www.zju.edu.cn/jzus/pformat.htm>) to see paper format.