Technical notes

Olecranon fractures – a reliable technique for accurate positioning of the tension band wire

Simon Paul Smith

Princess Elizabeth Orthopaedic Centre, Royal Devon and Exeter Hospital, Exeter, UK

Background

Tension band wiring as described by the AO group is the treatment of choice for simple displaced fractures of the olecranon.¹ The most frequent complication of this procedure is symptomatic prominence of the wires.² Most descriptions of this procedure emphasise the importance of inserting the Kirschner wires and the proximal loop of the tension band wire deep to the triceps tendon (Fig. 1) if such problems are to be minimised,¹⁻⁴ but do not describe how to pass the proximal loop of the tension band wire.

Method

In this technique, an 18-gauge tension band wire is fed into a standard vacuum drain tube. The trocar of the drain is then passed beneath the triceps tendon from medial to lateral, avoiding the ulnar nerve and adjacent to the protruding 1.6 mm Kirschner wires (Fig. 2). The tension band wire is then pulled through into the optimal position by the drain following the trocar. The vacuum drain can subsequently be used to drain the surgical site at the surgeon's discretion.

Discussion

This technique provides a straightforward, reliable way of optimally placing the tension band wire for the treatment of

Figure 1 Kirschner wire and tension band wires deep to triceps tendon.

Figure 2 The use of vacuum drain tubing and trocar as a means of accurately positioning the tension band wire.

olecranon fractures and thereby minimising the complications of wire misplacement. We have also used it successfully for tension band wiring fractures of the patella and femoral greater trochanter.

References

1. Muller ME, Allgower M, Schneider R, Willenegger H. *Manual of Internal Fixation*, 2nd edn. New York: Springer, 1970.
2. Macko D, Szabo RM. Complications of tension band wiring of olecranon fractures. *J Bone Joint Surg Am* 1985; **67**: 1369–401.
3. Browner BD, Jupiter JB, Levine AM, Trafton PG. *Skeletal Trauma: Fractures, Dislocations, Ligamentous Injuries*, 2nd edn. New York: WB Saunders, 1992.
4. Mathewson MH, McCreath SW. Tension band wiring in the treatment of olecranon fractures. *J Bone Joint Surg Br* 1975; **57**: 399.

Correspondence to: Simon Smith, 70 Waterside, Exeter EX2 8GY, UK. E-mail: simonpsmith@bigfoot.com

The transmission of MRSA via orthopaedic marking pens – fact or fiction?

RJ Thomas¹, C Goodbourne², B Goldie¹

Departments of ¹Orthopaedic Surgery and ²Microbiology, Whipps Cross University Hospital, London, UK

Background and Method

To determine whether alcohol-impregnated marking pens were potential vectors in the transmission of methicillin-

resistant *Staphylococcus aureus* (MRSA), and whether the time between the marking of patients affected transmission, 27 pens were collected.^{1,2} Eight had been used in orthopaedics and 19 pens were brand new. Five were cultured directly onto plates (controls), and seven administered to the authors' upper and lower limbs and plated at different times within 30 min. The remainder were introduced to seven vials containing different concentrations of MRSA, and plated at different times of exposure over 10 min. The tips were inoculated onto plates of blood agar and mannitol-salt-agar, incubated, and then examined for colony forming units. Bacterial isolation, classification and sensitivities were undertaken.^{3,4}

Results

The study demonstrated that pens with alcohol-impregnated tips were sterile on purchase, and remained so for up to 3 months. Although organisms were isolated on older pens, no evidence of MRSA was found. Pen tips were only able to harbour micro-organisms for 4 min before they were destroyed by the alcohol. In order to transmit MRSA to patients via marking pens, the tips required exposure to concentrations of MRSA above those commonly found on human skin, and the patient marked within 10 min of exposure to MRSA.

Discussion

From the above study, it is recommended that to reduce the transmission of pathogens between patients, more than 10 min is allowed to elapse between the marking of patients. Pens which are over 3 months old should be replaced as they are at an increased risk of transmitting pathogens.

Acknowledgements

We would like to thank the Microbiology Department at Whipps Cross Hospital, London for their advice and expertise, and the use of their materials.

References

1. Datz C, Jungwirth A, Dusch H *et al*. What's on a doctor's ball point pen? *Lancet* 1997; **350**: 1824.
2. Banerjee D, Fraise A, Chana K. Writing pens are an unlikely vector of cross-infection with methicillin resistant *Staphylococcus aureus* (MRSA). *J Hosp Infect* 1999; **43**: 73–5.
3. Cohen HA, Amir J, Matalon A *et al*. Stethoscopes and otoscopes – a potential vector of infection? *Fam Pract* 1997; **14**: 446–9.
4. Cohen HA, Liora H, Paret G *et al*. Aurioscope earpieces – a potential vector of infection? *Int J Pediatr Otorhinolaryngol* 1998; **45**: 47–50.

Correspondence to: Rosalind J Thomas, Bower Cottage, 5 Alton Road East, Poole, Dorset BH14 9LH, UK.
E-mail: drjrjthomas@hotmail.com

A cast handle to protect extensor mechanism repair

DPS Baghla, T Peckham

Department of Orthopaedics, Basildon Hospital, Essex, UK

Background

The use of the long leg/cylinder cast following repair of the extensor mechanism of the knee (quadriceps or patella tendon rupture), or for conservative management of a fractured patella, is standard practice. However, on straight leg raising, the quadriceps (especially rectus femoris) contracts with considerable force threatening the viability of the repair.¹ We offer a simple modification of the cylinder cast, which provides a loop to allow the patient to elevate the limb using upper limb strength.

Figure 1 Circumferential handle

Figure 2 String supplemented longitudinal handle.

Technique

A standard long leg cast is applied² using an initial stockingette with softband padding supplemented by additional felt pressure support over the malleoli. Three or four rolls of 4-inch Scotchcast (3M-Santé, Avenue du 11 novembre, Pithiviers Cedex, France) are applied depending on limb size, and allowed to dry. There are two methods of providing the loop. First, a circumferential 2-inch Scotchcast is applied which can be twisted/rolled to offer an ergonomic handle. This is then re-inforced with further 2-inch Scotchcast to prevent delamination (Fig. 1). The second method is to cut a three-layer 10 x 5 cm Scotchcast strip and create a loop that runs along the long axis of the cast, again re-inforced with a 2-inch roll of Scotchcast. The use of string/foam passed through the loop acts as the handle (Fig. 2). The exact position of the loop is debatable; distal loops provide a better lever arm to lifting, but increase the force required of the upper limb due to the distance. We recommend placing the loop at the level of the tibial tuberosity.

Discussion

The addition of the handle to a long leg cylinder cast protects the underlying repair as well as providing a comfortable method to straight leg raise. There are numerous other ways to create the handle, but the underlying principle remains the same. Because of the very positive feedback received from patients, we recommend this technique.

Acknowledgements

The authors are grateful for the assistance of the plaster technicians (Glen Gould, Anne Crocombe, Geoff Sales, Paula McCornak and Veronica Reynolds) at Basildon Hospital who have provided material and technical support throughout.

References

1. Soderberg GL, Cook TM. An electromyographic analysis of quadriceps femoris muscle setting and straight leg raising. *Phys Ther* 1983; **63**: 1434–8.
2. Miles S, Barr L, *A Practical Guide to Casting*. Hull: Smith and Nephew Medical, 1991; 63.

Correspondence to: DPS Baghla, 2 Beech Grove, Hainault, Essex IG6 3AR, UK. E-mail: paul@baghla.freeserve.co.uk

Wound irrigation: simple delivery by the litre

J McKenzie, JP Cashman

Department of Orthopaedics and Trauma, Royal United Hospital, Bath, UK

We describe a novel and simple system that provides large volumes of saline for irrigation using a controllable and effective technique.

Figure 1 Photograph of the irrigation device.

Method

The equipment needed is simple and readily available in all clinical areas. A bag of saline (any size), a 1-ml syringe and a pair of scissors are the only requirements. The syringe is prepared by removing the plunger and cutting off the finger-holding flange at the end of the barrel. The saline bag is prepared by snipping off the second (injection) port at its base. The cut end of the syringe is then inserted into the open port forming an easily controllable irrigation device capable of flow rates over one litre per minute (Fig. 1). The flow can be adjusted by squeezing the bag or by simple modification of the nozzle. The tapered part of the nozzle can be cut off using stout scissors. Alternatively, a needle or intravenous cannula can be added to the intact nozzle.¹ The latter can be especially useful for directing fine streams for irrigation of eyes, ears or small joints of the hand.

Discussion

We have used this arrangement to irrigate many types of wound effectively without observed complications. This method has advantages over other syringe techniques² in that it provides larger volumes more effectively. The materials are sterile packed so the method can be used in theatre if a more expensive mechanical pulsed-lavage system is unavailable or undesirable.

References

1. Stevenson TR, Thacker JG, Rodeheaver GT, Bacchetta C, Edgerton MT, Edlich RF. Cleansing the traumatic wound by high pressure syringe irrigation. *J Am Coll Emerg Phys* 1976; **5**: 17–21.
2. Lam DGK et al. Wound irrigation: a simple, reproducible device. *Ann R Coll Surg Engl* 2000; **82**: 346–7.

Correspondence to: James McKenzie, Department of Paediatric Orthopaedics, Bristol Royal Hospital for Children, Bristol, UK. E-mail: watatu@btinternet.com

Technical tips

Bending the rule of thirds: an accurate method for planning a long posterior flap transtibial amputation

MF Caruana, IS Osman

Suffolk Vascular Unit, Ipswich Hospital NHS Trust, Ipswich, Suffolk, UK

Background

We describe a simple modification to the rule of thirds long posterior flap technique¹ to avoid tension arising in the middle of the flap at the point where it crosses the anterior tibial border.

Method

A line is drawn along the circumference of the calf at a point measured one hand-breadth distal to the tibial tuberosity. The circumference measured along this line is then divided into thirds from a point aligned with the anterior tibial tuberosity.

Figure 1 Diagram indicating points of incision.

The posterior third forms the base of the posterior flap of the amputation stump. The sides of the posterior flap are created by incising distally along longitudinal lines from the ends of the base of the flap. This is for a distance equal to one-third of the original circumference.

To create the distal end of the flap, incisions are made from both sides of the flap to meet in the midline posteriorly. Each incision should start from a point 1-cm proximal to the distal end of the sides of the flap.. The two incisions should join at a point in the midline posteriorly, which is 2 cm distal to the origin of these incisions (rather than parallel to the starting points of the incisions) as shown in Figure 1. The tibia is then divided 1 cm proximal to the anterior skin margin. The bulk of solcus is excised and the myo-cutaneous flap is constructed on the belly of gastrocnemius.

Discussion

In our experience, this method consistently results in accurate apposition of the flap over the anterior tibial border producing a tension-free, well-shaped stump. We therefore recommend its use.

Reference

1. Sanders RJ, Augspurger R. Skin flap measurement for below-knee amputation. *Surg Gynecol Obstet* 1977; **145**: 740–2.

Correspondence to: IS Osman, Consultant Vascular Surgeon, Suffolk Vascular Unit, Ipswich Hospital NHS Trust, Heath Road, Ipswich, Suffolk IP4 5SW, UK. Tel: +44 7473 703444; E-mail: ossy1@aol.com

Knee-stabilising device for lower limb orthopaedic procedures

Vinod K Panchbhavi

Orthopaedic Department, Poole Hospital NHS Trust, Poole, UK

Background

To perform operative procedures such as the intramedullary nailing of the tibia or the retrograde nailing of the femur, flexion at the knee joint is necessary to gain access into the medullary canal. Bolsters or pillows in sterile drapes can keep the knee flexed.^{1,2} However, they are cumbersome, affect imaging quality and do not provide a sturdy support. The knee-supporting device, developed by the author, addresses these issues. This device is reported to facilitate leg positioning and stability during fibular flap harvesting for mandibular reconstruction.³ Use of this device in lower limb orthopaedic procedures is described.

Figure 1 Knee-supporting device under knee during tibial nailing with imaging, the inset shows the device on an instrument trolley. [Enquiries should be addressed to the author by email]

Technique

The knee-supporting device is a non-equilateral triangular frame (Fig. 1). It is sturdy, radiolucent and autoclavable. To perform nailing of tibia or retrograde nailing in femur, the fracture is pulled out to length by choosing that corner of this device which would provide the required height under the knee to do so. Ipsilateral tibial and femoral nailing can be performed with the device under knee, through single incision in front of knee, without the need for change in positioning of the patient or traction as is necessary if a fracture table was used.

When fixing tibial plateau fractures, the knee is placed in different degrees of flexion as necessary to visualise the plateau and fix the fracture. When fixing Lisfranc injuries with percutaneous screws under fluoroscopy, a plantigrade position of the foot on the operating table is obtained with the device under knee, not requiring an assistant to hold foot in position.

References

1. Moed BR, Watson JT, Cramer KE, Karges DE *et al.* Unreamed retrograde intramedullary nailing of fractures of the femoral shaft. *J Orthop Trauma* 1998; **12**: 334–42.
2. Tornetta P, French BG. Compartment pressures during

non-reamed tibial nailing without traction. *J Orthop Trauma* 1997; **11**: 24–7.

3. Anand R, Brennan PP, Panchbhavi VK, Illankovan V. Stabilising the leg to harvest a fibular flap: a new device. *Br J Oral Maxillofac Surg* 2002; **40**: 438–9.

Correspondence to: Vinod K Panchbhavi, Assistant Professor in Orthopaedics, 2.616 Rebecca Sealy Hospital, 301 University Blvd, Galveston, Texas 77555-0165, USA. E-mail: vpanch@hotmail.com

A novel technique for testicular tunnelling

AW Lambert

Paediatric Surgical Services, Ministry of Defence Hospital Unit and Derriford Hospital, Plymouth, UK

The stages of inguinal orchidopexy include testicular mobilisation, tunnelling and dartos pouch fixation. Traditionally, a forcep is passed from the scrotal incision cephalad into the groin wound to retrieve the testis from its proximal location,

Figure 1 Tunneller head adjacent to mobilised testis.

Instead, when sufficient cord length has been achieved, the testis is attached to the shaft of a unidirectional tunneller (Impra Tunneller, Bard Ltd, UK) which is passed through the groin incision into the scrotum. By cutting against the 'olive', a dartos pouch can be created and the instrument is pulled through in the same direction. The testis is fixed and the wounds are closed in the standard fashion. The technique described in this paper removes the necessity to pass an instrument in two directions through the groin, simplifying the tunnelling procedure and reducing surgical trauma.

Correspondence to: Mr AW Lambert, Consultant Surgeon, Level 4, Derriford Hospital, Plymouth PL6 8DH, UK. Tel: +44 1752 517536; Fax: +44 1752 792537; E-mail: anthony.lambert@phnt.swest.nhs.uk

Preparing digital images for publication

Christopher Hogg

Specialist in Orthodontics, London, UK

The ideal picture is easily recognised with its main area of interest sharply focused against a background free from distractions such as blood, cement or other intrusive debris. Unfortunately, digital cameras deceive. An excellent screen image may typically print poorly and invite editorial rejection. Figure 1 shows how sufficient image resolution is achieved.

Figure 1 For close-up shots (*i.e.* macro photography), digital cameras should be set on macro mode as shown by the flower head in the monitor screen. The macro setting ensures pictures are sharply focused throughout. This Olympus Camedia camera is set to macro mode with the top button; other cameras use, for instance, a mode button – always consult the manual! The HQ (high quality) picture setting automatically delivers sufficient resolution and the correct file format setting.

Reference

1. Hogg CM, Pollard D, Porter SR. Dental photography CD ROM available gratis as C A L 25: contact <www.londondeanery.ac.uk/dental>.

Correspondence to: Mr CM Hogg, Angle House, 54 High Street, Edgware, London HA8 7EJ, UK. E-mail: chris@abc4.demon.co.uk

An easy method of passing a cerclage wire around a fractured patella

Chris Curwen, Chris Barringer, Ashley Blom

Department of Orthopaedic Surgery, Gloucester Royal Hospital, Gloucester, UK

Cerclage wiring is a well-recognised method of treating patellar fractures, particularly comminuted fractures. Passing the wire around the patella can both frustrate and time consuming. We have found the following method to be both easy and quick.

1. Approach the patella through a standard anterior midline incision.
2. Take an 8 mm vacuum drain and bend the trochar to conform approximately to the curve of the superior pole of the patella.
3. Using the trochar, pass the drain around the patella.
4. Insert the end of the wire into the free end of the drain.
5. Pull the drain out, trochar end first, and the wire will follow.

Correspondence to: Mr AW Blom, 23 Old Sneed Avenue, Stoke Bishop, Bristol BS9 1SD, UK.