How to avoid a second 10-mm port during laparoscopic appendicectomy and laparoscopic hernia repair

I SINGH, N PANESAR, P NG
University Hospital Lewisham, London, UK

CORRESPONDENCE TO

I Singh, Department of Surgery, University Hospital Lewisham,
Lewisham High Street, Lewisham, London SE13 6LH, UK
E: indie@doctors.org.uk

BACKGROUND

Laparoscopic surgery for the treatment of appendicitis and hernia repair have gained wide clinical acceptance. Trocar-site herniation can occur if a 10-mm trocar is used.¹ Herniation through a 5-mm port site is, however, rare.² The underlying fascia is closed when using trocars of 10-mm or more, but also when extensive manipulation is performed through a 5-mm trocar port, causing extension of the incision. Conventionally, a 10-mm port is required for the camera, whilst a second 10-mm port is needed to retrieve a large appendix during an appendicectomy³ or for the insertion of a 20 cm x 20 cm mesh during hernia repair. We describe a method that avoids the need of a second 10-mm port in both of these cases.

TECHNIQUE

A standard 10-mm umbilical port is used for insertion of the camera. This is followed by two 5-mm ports to allow mobilisation of the appendix and its ligation. Conventionally, one of the 5-mm ports would then be converted to a 10-mm port to allow retrieval of the appendix. We describe a method to avoid this. The appendix is held at one end with a grasper (via the 5-mm port) and passed into the 10-mm trocar (intra-abdominally, under

constant vision) following the tip of the camera whilst the camera is reversed out of the 10-mm trocar (Fig. 1). Similarly, when inserting the mesh for hernia repair, a 5-mm port allows the passage of a 15 cm x 15 cm mesh but needs to be converted to a 10-mm port to allow a larger mesh to be passed through (as the trocar is too narrow). Instead, the grasper, which is through the 5-mm port, is passed into the 10-mm trocar (intra-abdominally) following the camera tip as it is reversed out of the trocar (Fig. 1). Once, the grasper is through the 10-mm trocar, the trocar is removed leaving the grasper pointing out of the abdomen. A mesh is placed in the grasper which is then pulled back into the abdominal cavity.

DISCUSSION

We have successfully performed this technique on numerous occasions. It avoids the need of a second 10-mm port (and the need to close it). This facilitates safe and efficient removal of an appendix during an appendicectomy or insertion of a mesh during hernia repair. This method does not require a 10-mm telescope to be changed to a 5-mm one (as not all hospitals have one) or the need to extend a 5-mm port incision.⁴

References

1. Tonouchi H, Ohmori Y, Kobayashi M, Kusunoki M. Trocar site hernia. *Arch Surg* 2004; **139**: 1248–56.
2. Nezhat C, Nezhat F, Seidman DS, Nezhat C. Incisional hernias after operative laparoscopy. *J Laparoendosc Adv Surg Tech A* 1997; **7**: 111–5.
3. El-Dhuwaib Y, Hamade AM, Issa ME, Balbisi BM, Abid G, Ammori BJ. An 'all 5-mm ports' selective approach to laparoscopic cholecystectomy, appendectomy, and anti-reflux surgery. *Surg Laparosc Endosc Percutan Tech* 2004; **14**: 141–4.
4. Jain PK, Sedman P. Appendix retrieval after laparoscopic appendectomy: a safe and inexpensive technique. *Surg Laparosc Endosc Percutan Tech* 2003; **13**: 322–4.

Figure 1 Demonstrating the grasper (via 5-mm trocar) entering the mouth of the 10-mm trocar following the tip of the camera.

Knee traction technique for inserting an antibiotic spacer

DM ROPCKE, A ODGAARD
Department of Orthopaedics, Aarhus University Hospital,
Aarhus, Denmark

CORRESPONDENCE TO

A. Odgaard, Consultant Orthopaedic Surgeon, Aarhus
University Hospital, Aarhus Sygehus, Tage-Hansens Gade 2,
8000 Aarhus C, Denmark
E: andod@as.aaa.dk

BACKGROUND

The two-stage revision of infected total knee replacement includes inserting an antibiotic cement spacer. The conventional

Figure 1 Implanting the spacer in the gap that is firmly secured by the traction.

method to provide traction at the knee joint while inserting a static spacer has involved manual traction. This is an impractical method. We hereby describe a handy and easy-to-apply alternative technique using an ankle sling known from ankle arthroscopy to create a steady traction at the knee joint.

TECHNIQUE

After removal of infected knee implants and debridement of infected tissue, an ankle sling is placed around the foot with the components positioned behind the tendo-Achilles and over the dorsum of the foot. The pulling string of the sling is attached ventrally to a belt around the waist of the assistant situated at the patient's feet. When the assistant leans backwards, the tibia and femur are efficiently pulled apart. The surgeon can now implant the spacer in the gap that is firmly secured by the traction (Fig. 1). The method is comfortable for both surgeon and assistant. Maintaining tension and alignment, while the cement sets, is easy.

DISCUSSION

This is an easy method to obtain proper limb alignment and force of traction for insertion of a static spacer in the knee joint. The advantages are: (i) the traction created is steady and easily applied; (ii) it is inexpensive; and (iii) it secures a suitably shaped and sized spacer. Preformed moulds for creating moveable spacers intra-operatively are commercially available. These have the advantage of allowing early ROM-exercises, but these moveable spacers are often impractical.

A method preventing circlage wire displacement in intra-operative proximal femoral fractures

S HOSKINSON, I GILL, P FADERO

Department of Orthopaedics and Trauma Surgery, Mayday University Hospital, Croydon, UK

CORRESPONDENCE TO

Simon Hoskinson, Department of Orthopaedics, Mayday University Hospital, 530 London Road, Croydon CR7 7YE, UK
E: simon.hoskinson@mayday.nhs.uk

BACKGROUND

Intra-operative fractures of the proximal femur can occur during hip hemi-arthroplasty. One method of management is with circlage wires which prevents fracture propagation and allows fixation.¹ However, due to the funnel shape of the proximal femur, wires can slip on the femoral shaft. We describe a method of circlage wire placement to prevent this.

TECHNIQUE

This technique requires a 2.5-mm drill-bit, and an appropriate diameter of wire (18-gauge). A hole is drilled within the cortex of the calcar in an anterior-posterior direction, the wire is then passed through the drill hole and looped around the proximal femoral shaft twice and tied (Fig. 1). Effort must be made to ensure that the drill hole is placed entirely within the cortex and does not breach the intramedullary canal. If this occurs, the wire will be passing through the canal and have the potential to affect stem fixation.

DISCUSSION

This method has the advantage of anchorage of the wire loop through bone preventing wire slippage and fracture displacement.

Figure 1 Sawbone model showing wire *in situ* around proximal femur. (A) Anterior-posterior view; (B) lateral view.