MOTOR NOTES FOR MEDICAL MEN.

By H. MASSAC BUIST.

THE DEVELOPMENT OF COAL GAS AS A MOTOR FUEL.

NECESSITY being ever the mother of invention, since last I wrote in these pages on the subject of the utilization of coal gas as an alternative motor fuel to spirits, which are becoming available in ever diminishing quantities, matters have marched rapidly as regards the evolution, and even the production, of new devices for containing the one form of motor fuel in these islands which is not experimental and the increasing use of which is all to the gain of the Ministry of Munitions, in that the more coal gas produced the greater the proportion of the necessary residuary products for the manufacture of high explosives, and so on.

We are now arrived at the fourth licensing term since the introduction of petrol rationing. Happily, the work medical men do is regarded as of national importance. Therefore there is no question that those who hold licences will secure renewals of sorts. The new order, which comes into force on November 1st, specifically permits the use of petrol or petrol substitute "in the conveyance of a duly qualified medical practitioner or veterinary surgeon while it is being used by him for the purposes of his profession." But it is equally plain that the amount which it has been possible to allot medical men in the past has been wholly inadequate. It is scarcely less plain that the amount it will be possible to allot in the future will be still less adequate. This is to be accounted for under many heads, perhaps the chief of which are that great increases have been made in the provision of agricultural motor machinery over what was anticipated earlier in the year, with the result that there are at least 6,000 tractors in this country to-day and there can scarcely be fewer than 15,000 available from the early part of next year onwards. Hence, a vast extra demand for motor fuel will arise under this head. It is of an essential nature, as brought out by the Premier last week in an address to farmers in regard to the urgency for their producing an unprecedented amount of cereals in these islands next year. The second head is the expansion of the Allied air services, including not merely the British, but the very ambitious American programme also, which is due to be launched any time from a couple of months onwards. Every gallon of motor fuel to operate it will have to be sea-borne to France and will therefore make additional demands on the strictly limited though, fortunately, increasing amount of tank-vessel tonnage available.

AT LEAST AN AUXILIARY FUEL FOR MEDICAL MEN.

It being certain that, under the new licensing scheme, the average medical man will not be able to obtain sufficient motor spirit for his needs, and the nature of the bulk of his work consisting of runs each of relatively brief distance, he may be classed as among the sections of motor owners for whom the use of coal gas as an alternative fuel is admirably suited, and almost imperative. Moreover, the approach of winter is a signal, on the one hand, for less economical consumption by reason of cold and windy weather, and on the other for experiencing greater difficulty in starting engines on motor spirits owing to their failing to vaporize satisfactorily while the carburettor intake pipes are chilled and the cylinders are cold. When coal gas is used as an alternative fuel to eke out petrol supplies it is found that, in practice, the engine will start up much more readily in cold condition on coal gas than on motor spirit, because, with the former, the explosive mixture is ready made.

THE PROBLEM OF OBTAINING SUPPLIES.

The Government having tardily announced the appointment of various men to offices alike concerned with economizing the use of motor spirits and with encouraging the development of coal gas, the individual medical man may take it for granted that in a short time the present problem of inadequate supplies of gas for motor traction purposes will have been solved. At the moment, however, despite the exhortations of the Ministry of Munitions that gas should be used for power plant to increase the production of by-products for the making of high

explosives and other munitions of war, the Sheffield Gas Company, to take an instance, is unable to undertake any measures to supply gas for motor traction owing to a shortage of labour, which is the sole trouble, for this particular company has both the plant and the coal; therefore, in that centre some enthusiastic pioneers in the use of coal gas for motor traction are unable to get their requirements. It may, however, be taken for granted that this problem of providing the necessary labour for the manufacture of gas will be readily solved, not merely in one locality, but in all localities where it may occur at present.

Nor should the medical man, as an individual, be discouraged from the use of coal gas for traction purposes by the present problem of guaranteeing users the provision of supply stations at the necessarily frequent intervals. In face of the fact that the range of gas fuel contained in fabric bags at atmospheric pressure is rarely more than from twelve to twenty miles per charge, and, in steel cylinders under compression, is fifty miles per charge, it will be appreciated that many medical men can make most of their journeys quite safely without risk of being stranded between supply stations. Besides, inasmuch as a medical man is assured of a certain proportion of petrol supplies being allowed during the next six months, he could always ensure against being stranded on the road by carrying petrol in his tank, on which he could fall back in the event of the supplies in his gas container becoming exhausted *en route*. Such petrol as he is licensed to buy could be kept, besides, in reserve for such long distance journeys as he may be called on to make occasionally.

Not quite so simple a problem at the moment, however, is the matter of his obtaining supplies anywhere he may chance to find himself. With characteristic enterprise, the Manchester Gas Department, which went full early into this matter, has advocated a standard set of filling arrangements throughout the district. This may be taken as the basis for a scheme which should obtain throughout the country. Indeed, the Government is to blame in not having anticipated the Manchester Gas Corporation in having both devised and determined the standard methods and systems of distribution.

A MODEL DISTRIBUTION SCHEME.

The Manchester scheme is so admirable that I give a summary of it here.

Meters.—Automatic type, 100-light size, fitted with special quick opening and instantaneous closing valve, the valve having a gas way equal in area to a 2-in. pipe, to be operated by a metal token (not coin size), each token representing 100 cubic feet of gas.

Fittings.—The outlet of meters to be fitted with flanges for 2-in. iron pipe, into which a 2-in. iron full-way plug cock is fitted. Each installation to be supplied with a 20-ft. length of 2-in. rubber packed flexible metallic tubing, fitted each end with a 2-in. gas thread female flat-face union.

Position of Meters.—Meters to be fixed at garages or similar establishments on all main roads, and to be fixed free of charge to tenant. The tenant to be allowed a rebate of 10 per cent. on the face value of all tokens collected from the meter fixed on his premises as a remuneration for rent and any trouble he may be caused in connecting up to vehicles, although it must be made clear that the responsibility for connecting up rests entirely with the driver of the vehicle.

Price of Gas.—4d. (fourpence) per 100 cubic ft.

Tokens.—Tokens (each being value for 100 cubic ft.) may be purchased at gas offices or other convenient places at 4d. (fourpence) each for cash, and must be stamped with the name and address of the gas undertaking issuing them.

Interchange of Tokens.—Arrangements are to be made whereby foreign tokens collected from a meter may be returned to the issuing office, who should give either a credit note or cash for the face value of such tokens, or tokens of similar value, to the collecting company.

Working Instructions.—An enamelled plate to be fixed in a prominent position close to each meter, lettered somewhat as follows:

Instructions.

1. Connect up union end of flexible tube to inlet pipe of gas container, taking care that all joints are gas-tight.
2. If the vehicle is fitted with a main cock in the inlet pipe to gas container, see that it is open. See that the engine control cock is closed. See that main cock fitted to outlet of meter is closed.
3. Insert one or more tokens and turn handle in the direction of the arrow.
4. When gas container is filled:

Close the main cock on meter.

Close main cock on inlet of gas container.

Disconnect flexible tubing.

Advertising.—The situation of these (meters, and the hours the establishment is open and the meter available for a supply of gas, to be stated by the gas undertakings joining in this scheme.

The whole of the information thus obtained to be issued in a booklet and distributed free of charge to owners of motor vehicles on application.

Enamelled plates to be provided and fixed in a prominent position on the premises in which meters have been fixed, indicating that motor vehicles may be charged up with coal gas.

Standard Pipe Fittings for Motor Vehicles.—If 2 in. gas thread is adopted as the standard fitting on the flexible tube, the gas undertakings joining in this scheme should advise all vehicle owners (and assist if necessary) to fit up their vehicles with the inlet pipe to gas container fitted with a similar size thread—namely, 2 in. gas. A drawing of a vehicle fitted up in the way advised should be made and a line block made from it. This block should be reproduced in the booklet referred to, together with a copy of the working instructions and advice as to how the best results from coal gas may be obtained.

OCCASIONAL EXPLOITATION OF THE USER NEEDS PROHIBITING.

That is a sound and simple working basis. The first point that strikes one about it is that Manchester does not mean to utilize this new market for fuel as a means of profiteering by exploiting motor users in their extremity. The price of gas is fixed at 3s. 4d. per 1,000 cubic feet, which is practically equivalent to petrol at 10d. per gallon, representing an enormous economy, and being, therefore, of direct interest to the average medical man.

Unfortunately, the integrity of the Manchester Gas Department, and those at Windsor and many other districts, is not at present universal. Thus there are gas companies in London—which is greatly backward in this matter—which are seizing the opportunity to charge motorists *more for the act of filling* their containers at mere atmospheric pressure than they are for the actual gas put into them.

For example, while the price of gas in some western districts is 3s. 4d. per 1,000 cubic feet, a 200 foot container which should be filled at atmospheric pressure for a charge of 8d. is, nevertheless, charged at a cost of 2s. 2d., representing an extortionate demand of no less than 1s. 6d. for the mere act of filling.

If we were dealing with gas supplied to steel cylinders under compression the matter might be different. As it is, there is no excuse for this sort of thing, particularly inasmuch as all gas so sold is additional to the gas companies' ordinary profit-making scheme, in that its dead charges for plant, rates, rents, taxes, and so forth do not increase, but only those for the bare raw materials and for labour. Inasmuch, too, as the additional residuary products suitable for the making of munitions of war are also saleable to the Government on most profitable terms, and as such extra supplies could not be available for sale at profit unless motorists come to take the extra supply of gas made at the given factory, there is no excuse for allowing London gas companies to act as Manchester ones

do not. Lastly, all gas companies' charges are arrived at on a profit-paying basis, and it does not matter in the least to the individual gas maker what use is made of his commodity after he has produced it—that is say, whether it is used for lighting, for cooking, for power plant in a factory, or for motor traction on the road.

We may with reasonable confidence, therefore, look to the Government promptly to take measures, both in the interests of the prosecution of this war and in the interest of those in need of medical attention, as a single and ever-present section of the community, to ensure that the gas

companies shall not hold up to ransom those patriotic motorists of all classes, from lorry to limousine users, who have had, or who will have, their vehicles adapted to run on town gas, with the dual aim of relieving the demands on motor spirit and of enabling them each to get through more of their given national work in the course of every twenty-four hours. The medical man without the freest possible facilities for getting about is perforce restricted in the amount of work he can do in a day.

POINTS FOR AND AGAINST THE VARIOUS GAS HOLDERS AVAILABLE.

The medical man's difficulty in the matter of dealing with gas as a motor fuel is its bulk. Containers at atmospheric pressure and fashioned of fabric are ideal for his purpose from every point of view save as regards volume. The fact that an individual container will hold a charge barely sufficient for more than twelve to twenty miles range does not matter to him particularly, because he has his petrol rations to fall back on for long journeys, and because, doubtless at no distant date, the Government will order the gas companies to approve and cause to be installed certain apparatus, much on the Manchester scheme, which could be set up even at the individual's house on extremely moderate terms, so that the

cost could be saved by the individual user on a month's fuel bill at the outside. But whereas omnibuses or cabs kept in large, specially built motor houses, or the average utility vehicle run by big firms, also provided with specially built accommodation, could carry a flexible fabric gas container on its roof, the entrance to the average medical man's motor house

is too shallow to admit a vehicle of such depth as, say, a limousine, a landaulette, or an ordinary touring collapsible hood kept up permanently with an inflated gas bag on the top of it. The ingenuity of designers and manufacturers may, perhaps, eventually overcome this objection.

But inasmuch as the average medical man has no call to motor either fast or far on each journey there is no reason why he should not with advantage employ the trailer scheme, such as has been devised and used successfully even on such heavy vehicles as those carrying four-ton loads, for which it will suffice for a twenty miles run per charge. As applied to the private motor vehicle, such

FIG. 1.—B.S.A. landaulette, belonging to the Evesham Motor Engineering Co.

FIG. 2.—Gas container (280 cubic feet) on two-wheel Cox trailer coupled to car. A flexible coupling leads from gas bag to carburettor.

devices as Cox's gas trailer of 200 cubic feet capacity, or Barton's, are well worth the consideration of the average medical man, particularly if he has occasionally to make longer journeys than ordinary, and therefore to run on his petrol rations instead of gas. Then the trailer can be readily detached, and the car is available for use in normal condition.

The disadvantage of gas bags that can be contained in, say, the back of the car, is that their capacity is too limited; also on occasion the medical man has need of the full seating capacity of his vehicle. True, an alternative scheme to this has been evolved by Mr. F. A. Wilkinson of Hatfield, Herts, which is akin to two large square flexible trunks carried on the grid at the back of the car without undue overhang, and giving six miles range on a single charge. Such a device is also readily detachable when the medical man is running on an alternative fuel.

GAS UNDER COMPRESSION:

Assuming that the medical man can obtain supplies of one or another of the many devices employing metal cylinders for containing gas under compression, he has to consider various points before deciding to adopt such apparatus. The great advantages of compactness and of giving much greater vehicle range for each charge—say, up to fifty miles, against twenty on gas at atmospheric pressure only—is offset, first, by the problem of weight. A set of cylinders rarely weighs less than 6 cwt., while the lighter single cylinder scales something in the neighbourhood of 112 lb. That becomes an important item in these days of constantly deteriorating road surfaces, putting additional strain on springs, which are generally extremely hard to obtain as spares in the event of a spring breaking. Secondly, a certain amount of cost must obviously attach to supplying cylinders that take gas under high compression, whereas the filling of a collapsible fabric bag at mere atmospheric pressure is a matter involving no cost.

Nevertheless, a wide variety of steel gas cylinder devices has been forthcoming, one of them even employing the one-wheel auto-trailer scheme carrying a nest of five cylinders. Most gas cylinders, however, are carried on the vehicle, as for instance the triple cylinder Pulham scheme introduced by the Marine Garage of Bexhill-on-Sea, and containing about 300 cubic feet of gas for each charge at a pressure of 150 lb. per square inch, or, approximately, 10 atmospheres, and giving a range of about twenty-three miles for a weight of 650 to 675 lb.

Against this the advantages of the collapsible fabric gas holder at atmospheric pressure of 14.7 lb. per square inch include the fact that there is no weight whatever. In this connexion the following summary of facts in regard to gas holders has been drawn up by Mr. Edmund Dangerfield's organs, the *Commercial Motor* and the *Motor*, which have done most of the spade work in compelling the authorities to give attention to the very important proposition of the use of coal gas as an alternative fuel.

Gas-holder Capacities.

Type of Holder and Size.	Cubic Capacity at Atmospheric Pressure, 14.7 lb. per sq. in.	Capacity.		
		At 200 lb. Pressure above Atmosphere.	At 500 lb. Pressure above Atmosphere.	At 1,000 lb. Pressure above Atmosphere.
	Cubic ft.	Cubic ft.	Cubic ft.	Cubic ft.
Flexible holder—12 ft. x 5 ft. x 5 ft. ...	300	—	—	—
Railway cylinders—5 ft. 6 in. x 1 ft. 8 in.	12.2	170	—	—
CO ₂ cylinders—4 ft. 2 in. x 5 in. ... Special high pressure cylinders.	0.6	8.4	21	42

Flexible holders are obtainable in all sizes.

Railway cylinders are obtainable in sizes from 3 ft. 6 in. up to 9 ft. in length x 2 in. diameter; also 4 ft. 6 in. x 2 ft.; 6 ft. 4 in. x 2 ft.; 4 ft. 6 in. x 18 in., and 10 ft. 3 in. x 18 in.

CO₂ cylinders are obtainable in sizes from 4 ft. to 5 ft. x 5 in.

Standard gas filling connexions recommended:

Meter: 100-light automatic type.

Meter fittings: Meter outlet with flanges for 2 in. iron pipe, with 2 in. iron full-way stopcock. Installation to be supplied with 20 ft. length of 2 in. rubber packed metallic tubing fitted at each end with a 2 in. gas thread female flat-face union.

Car: Gas container to have a main cock on the inlet male union to fit end of tubing from meter installation.

LENGTH OF WEARING LIFE OF APPARATUS.

A not unimportant point in connexion with the fitting of apparatus of this sort is the question of its wearing life. Obviously, the life of metal cylinders is long. As far as I am aware, none has yet been known to wear out, though small parts, such as valves and so forth, may need renewal from time to time, and are easily replaceable at a moderate cost. The railway type of cylinder, is of course, no experiment.

Until the Ministry of Munitions releases the metals and materials necessary for real progress in the matter of supplying coal gas under compression, however, it will be difficult to move rapidly or extensively in this particular direction, especially since manufacturers are not eager to spend time and money on experiments which cannot yet be followed up by quantity production of the article evolved. Doubtless, however, this unsatisfactory condition of affairs will be altered now that the Government is setting to work.

An alternative scheme is to attempt something in the nature of gas compression in non-metallic fabric containers, such as that which Messrs. Wood-Milne, Ltd., are endeavouring to produce to withstand high internal pressure.

Much, however, might be done in the way of using discarded gas holders from railway coaches, each vessel with about 12 cubic feet capacity, capable of being charged up to 14 volumes of gas.

In regard to fabric containers for holding gas at atmospheric pressure, one has been in service for twelve months on the top of a single decker omnibus which has run more than 20,000 miles on coal gas; it is found to show little signs of wear to-day. Indeed, it seems to be agreed that, in regard to this class of apparatus, a generous maximum is to put depreciation at one-tenth of a penny a mile run, with the largest sorts, and about half that for passenger car types. If the apparatus is carried on the top of a vehicle, as is not likely in the case of an ordinary doctor's car for reasons previously specified, care must be taken in regard to driving lest overhanging branches or other projecting obstacles cause a ripping of the fabric of the holder. Even so, doubtless the individual when taking to the use of a gas holder can arrange with his insurance company that his car policy will cover anything occurring to any such attachment. In any case, he could insure against it for a purely nominal sum.

A PRACTICAL MAKESHIFT.

Flexible holders cost from £10 upwards, and are so light that they can be easily supported.

Admittedly, the atmospheric pressure scheme is neither more nor less than a war time makeshift; but that is all the medical man is asking for. His case is not that, say, of a commercial motor owner using gas, which may become a permanent form of fuel for such purposes.

After the war the market will be flooded with a large number of motor spirits, while the sudden cessation of the enormous demands for campaign purposes, with the continual increase in the building of tank vessels, will certainly ensure plenty of liquid fuel being available for motoring in this country, particularly because the present situation has given a great impetus to steam wagons operating with coal fuel, and because coal gas will probably remain a very favourite form of motor fuel for commercial motor vehicles on grounds of economy alone, and will doubtless be introduced within a season or so, at the outside, for agricultural motoring.

Obviously, the atmospheric pressure scheme is the best for the medical man, not only because metal containers for holding gas under pressure are not to be obtained in unlimited numbers, but also because the necessary apparatus for compressing the gas is not generally available. The medical man's point of view is that he must do something at once, and here is an available and non-experimental alternative, as instance the report issued last August by the British Commercial Gas Association, representing the

leading gas companies of the United Kingdom, which gives data on the subject of the utilization of coal gas for traction purposes. A copy of the report is obtainable from the Association at 47, Victoria Street, London, S.W.1.

Even when coal gas costs as much as 4s. per 1,000 cubic feet, it is equal to petrol at 1s. a gallon only. In England and Scotland coal gas is being used, particularly for omnibus and char-a-banc services, with thoroughly satisfactory results, and nearly always at merely atmospheric pressure, as instance the services operating at Edinburgh, Birmingham, Bristol, Bournemouth, and Eastbourne, and the rapid increase in the numbers of utility motor vehicles on the same scheme in Manchester and elsewhere.

Inasmuch as progress is being made so extremely rapidly that an increasingly large number of firms all over the country are laying themselves out specially to fit cars to run on town gas, the individual medical man may be recommended to read the *Motor*, which publishes a list, brought up to date weekly, of the various firms throughout the country that manufacture gas holders or which are laying themselves out for fitting the necessary, simple adaptor apparatus to individual cars.

Coal gas is clean in use, it needs no vaporization, the fuel control need call for no alteration; no carbon deposit is left; and the power obtainable is at least 85 per cent. of the efficiency of the best petrol.

[We are indebted to the *Commercial Motor* for the use of the two illustrations.]

PERMITS FOR THE USE OF PURE WHEATEN FLOUR FOR INVALIDS.

THE following memorandum has been issued by the Ministry of Food, after consultation with the War Bread Medical Subcommittee:

Memorandum.

Since some misunderstanding appears to exist as to the granting of permits to use white flour, it seems advisable to indicate the procedure adopted in dealing with applications. These are considered in the first instance by the Scientific Adviser to the Food Controller acting under the guidance of the War Bread Medical Subcommittee of the Royal Society. After this first sifting of applications doubtful cases are referred to certain members of the subcommittee, who have agreed to act as referees, or they are laid before the whole subcommittee. It should be understood that applications are becoming so numerous and the necessity for economizing wheat so imperative, that it is not possible to accede to all the requests sent in. The committee is of opinion that in many cases no substantial grounds exist for the applications, which appear to be made merely to satisfy some whim of the patient and not because the Government regulation flour has been found to be deleterious. Speaking generally, it may be said that unless some affection of the digestive organs is present which, in the opinion of the War Bread Medical Subcommittee justifies the use of pure wheaten flour, an application cannot be granted. Thus, for instance:

1. *Acute affections of the stomach* (acute gastric catarrh, ulcer in its acute stages, etc.). In these cases the use of any form of bread whilst the disease is at its height is probably inadmissible. During the convalescent stages the prescription of pure wheaten flour for a limited period may be permissible if rusks and breakfast biscuits or ordinary bread boiled and sieved, or bread jelly, do not meet the case.

2. *Chronic affections of the stomach.* In chronic functional disorders of the stomach (which make up the majority of cases of chronic dyspepsia) the use of pure wheaten flour can rarely be allowed, for the reason that such cases are so numerous and so protracted in their course that it would be impossible to meet demand without seriously depleting the wheat supply of the rest of the population. The use of the present bread, well toasted and thoroughly chewed, or of biscuits and rusks, should be recommended. In chronic organic disease of the stomach (carcinoma and chronic ulcer) white flour may sometimes be advisable if the patient is able to take bread at all.

3. *Acute affections of the intestine* (acute diarrhoea, enteritis, colitis, ulcerative conditions, etc.). In these

cases the same remark applies as in acute affections of the stomach.

4. *Chronic intestinal affections* (chronic diarrhoea, chronic colitis, malignant disease, etc.). In some of these the use of white flour may be desirable; but evidence would be required to show that ordinary bread, toasted and thoroughly chewed, and the use of other measures, have failed to relieve the symptoms.

5. Cases of disease of the nervous, circulatory, or respiratory systems, or of the urinary organs or skin, or such general conditions as anaemia and diabetes, can rarely be considered suitable for grants.

6. As regards tuberculosis, there is no evidence that the present bread is injurious. Inquiries have been made from the principal sanatoriums for the treatment of this disease, and in the great majority of cases the medical superintendents support the above opinion. No institution for the treatment of this disease is receiving grants of pure wheaten flour.

To sum up, there are very few conditions, in the opinion of the War Bread Medical Subcommittee, in which the use of pure wheaten flour is essential.

The subcommittee is well aware of the difficult position in which the medical practitioners are placed; but it is necessary to conserve the wheat supplies of the country, and every means of doing this must be adopted, and if need be enforced. Refusal to give a permit does not imply that the medical certificate has been disregarded, but merely that the need of other applicants appeared to be more urgent. Above all, it is important that no discrimination be made between rich and poor in recommending these grants. Nothing is easier to arouse or more difficult to allay than a suspicion that the poor are denied what the rich find no difficulty in obtaining.

Under war conditions, when variety in foods is limited, the bread made from Government regulation flour is probably a more wholesome article of diet than that made from fine wheaten flour in pre-war time. The flour contains more lime salts than fine wheaten flour, and presumably is therefore more suitable for growing children. It contains a greater variety of proteins, which it is important to have, especially if bread enters largely into the dietary. It contains more "germ," which adds to the proteins and increases the fat. It also contains more of the class of substances known as "vitamines," about which our knowledge is far from complete, but it is known that a deficiency of these profoundly impairs nutrition. The bread requires to be thoroughly masticated, but if chewed well, or eaten as toast which necessitates chewing, or, finally (in the case of invalids), if it be used as indicated in paragraph 1, there are very few people with whom it could disagree.

THE twenty-sixth meeting of the Congress of the Italian Society of Internal Medicine will be devoted to diseases among troops—icterus, malaria, cardiac affections, renal diseases and tuberculosis. It is to be held at the end of October in some city within the war zone, the name of which, together with the exact date of meeting, will be published later. Professor Luigi Lucatello, director of the medical clinic at Padua, is president of the organizing committee.

THE total number of medical students in Switzerland in the summer semester of 1917 was 1,823. These were distributed in the five universities as follows: Bâle 227, including 13 Swiss women and 48 foreigners, of whom 2 were women; Berne 407, including 14 Swiss women and 168 foreigners, of whom 29 were women; Geneva 488, including 17 Swiss women and 334 foreigners, of whom 84 were women; Lausanne 208, among whom were 11 Swiss women and 92 foreigners, of whom 20 were women; Zürich 493, including 52 Swiss women and 177 foreigners, of whom 40 were women.

IT was stated recently on the authority of the Federal chemist of Kansas that court plaster full of tetanus bacilli was being sold throughout the State. This report led to the arrest of five Germans, and samples of the plaster were submitted to the United States Department of Justice for examination. It is now officially announced that the Director of the Hygiene Laboratory of the United States Public Health Service has reported that among thirteen specimens of plaster purchased in the ordinary way in Washington and one from the Ohio Department of Health two contained tetanus bacilli. He states that there is no reason to believe that the contamination was intentional.