with panophthalmitis in 5 cases, septic infiltration of the cornea in 3 cases, irido-cyclitis in 1, and glaucoma in 5. In 60 cases iritis occurred, ending in recovery in 41 cases, in occlusion in 13 cases, and in partial occlusion in 6 cases.

A CASE OF CAVERNOUS ANGIOMA OF ORBIT.

By C. H. USHER, M.B.,

Ophthalmic Surgeon, Royal Infirmary, Aberdeen, etc.

G. C., aged 40, a farmer, came to the Aberdeen Royal Infirmary on October 12th, 1897.

History.—For about eighteen months he had noticed his left eye gradually "getting bigger" (some time later he stated that someone had noticed this for five or six years). It had never been painful, only slight irritation and watering caused by the wind. The sight of his left eye had been getting gradually worse; a year ago he could read large print with it. The eye had never been injured. For many years he had been subject to headaches, usually frontal and on the left side the pain was often very severe, keeping him awake at night.

State on Admission.—Left eye, V=p.l., very great proptosis. The eyeball projects straight forwards, its movements are fairly free, they are limited mostly in an upward direction. The proptosis is not appreciably diminished on pressing the globe backwards, there is no tenderness, no pulsation, and no *bruit*. No growth can be felt in the orbit; cornea clear; pupils equal; left pupil acts sluggishly to light. Tension normal. Fundus imperfectly seen owing to vitreous opacities; optic disc is pale. Right eye appears normal, but V is only $\frac{1}{2}$, no hypermetropia, vision not improved by lenses. Reads i J. at 9 ins. Field full.

Description of Growth.—The growth was situated within the muscular cone and was removed subsequent to enucleation of the globe. It had a dark blue smooth surface, studded with small nodules, and had considerable elasticity.

A DEMONSTRATION

OF A

NEW AND ORIGINAL METHOD OF MAKING CASTS.

Given before the Surgical Section of the British Medical Association at Edinburgh, July, 1898,

By GEO. A. PETERS, M.B., F.R.C.S.ENG.,

Associate Professor of Surgery and Clinical Surgery, University of Toronto, Toronto, Canada.

It has long been desirable to have a better method of casting living objects, anatomical subjects, and pathological specimens than that which has hitherto been in vogue. Up to quite a recent period plaster of paris has been the material almost universally employed, and certainly many useful casts have been made by its use. Recently Cathcart and others have used gelatine, papier maché, wax, etc., and for certain subjects these substances fulfil many desirable conditions.

Some six or seven years ago I began to work with paraffin wax in a molten state, and after considerable experimenting and many failures I have elaborated the apparatus which I am about to describe, and with which I gave several demonstrations at the recent meeting of the British Medical Association at Edinburgh, and subsequently in Dr. Sims Woodhead's laboratory at Examination Hall, London.

Paraffin wax possesses many qualities desirable in a material for making moulds. It is a clean, inert, homogeneous, workable substance, capable of taking a finer impression than almost any other material, and contracting but little in passing from a hot liquid state to a firm solid mass. It "works" easily, and can be used over and over again with but little deterioration in quality. Hard wax, with a melting point of about 125° F., is the quality which I have found most useful. Moreover, it possesses another quality which I find is appreciated to its full extent by those only who have had experience in the older method of casting from plaster-of-paris moulds, namely, the mould can be separated from the cast with the greatest possible facility simply by immersing

the whole mass—cast and mould—in warm water until the wax becomes soft and plastic. In fact, in very delicate subjects the whole of the wax may be melted away, though this is rarely necessary. In this way the laborious process of chiselling away the waste mould, with the attendant anxiety for the safety from injury of the contained cast, is entirely got rid of, and the mould comes away with almost as much ease as one would lift a layer of gauze from the surface of the body, and with quite as little damage to the underlying surface.

One disadvantage of this process is that the apparatus is somewhat expensive and cumbersome, the principal expense being in connection with the "electric motor" and air pump. The place of this may be taken for ordinary work by a pump worked by hand or foot power, and connected to an air cylinder properly fitted with valves. It is necessary, however, to furnish oneself with a pressure of some 10 or 12 lbs. to the square inch, and this in considerable volume.

Briefly it may be stated that the process consists in spraying melted paraffin over the whole surface, cooling it by spraying ice-cold water at the same time, strengthening the mould with plaster-of-paris, and removing it in as many sections as the nature of the subject calls for.

THE APPARATUS.

Fig. 1.—A. The "jacketed" paraffin container, with "jacketed" tube leading to C, the paraffin ejector. B. Tank containing ice-cold water, with single tube leading to D, the cold-water ejector. E. The "pressure blower," or air pump, which forces air into the air cylinder F, which is provided with four exit pipes guarded by stop-cocks. (The pressure may be regulated with great nicety by opening or closing a greater or lesser number of these). G. The electric motor.

Having been melted in a water bath, the paraffin is placed in a tin tank (Fig. 1, A) capable of holding about a gallon. This tank is provided with an exit pipe a quarter of an inch in diameter, placed in the side of the tank about half an inch from the bottom, to which the rubber tube leading to the ejector (Fig. 2) is attached. The tank is then suspended within a larger tank or pail by means of three ears which arch across from the outside of the inner pail to the inside of the outer pail, where they are received into corresponding slots formed on the inner surface of the hot water tank by straps of tin soldered at each end. A metal pin or some sort of fastening then secures these ears in position, otherwise the inner pail will float up, as it is gradually emptied during the spraying process. The outer or larger pail contains the "jacket" of hot water, by which the paraffin is retained in a molten state, and the sizes of the pails should be so adjusted that the inner one is surrounded by about an inch and a half of hot water below and on all sides. The outer pail is also provided with an exit pipe about three-quarters of an inch in diameter, and placed opposite the pipe from the inner pail. To this pipe a rubber tube of corresponding size is attached, and passing over the paraffin tube furnishes a continuous "jacket" till it reaches the ejector (Fig. 2). This double pail is shown in Fig. 1 (A). The other tank (B) shown in this figure contains ice-cold water, and is not, of course, "jacketed." A single tube leads from it to the cold water ejector (D), to be described presently. The length of these tubes is purely a matter of convenience. Those I use are about $5\frac{1}{2}$ feet long. The tanks should be suspended over pulleys, at a height of about 4 feet above the object to be cast.

THE EJECTOR.

Fig. 2.—The ejector. P. Paraffin compartment. W. Hot-water jacket. A. Air channel. O. Overflow or waste tube for hot water. N. Adjustable nozzle.

The middle tube seen in Fig. 1 is the conduit for air from the air cylinder (F) to the ejector. It branches by a Y-shaped tube so as to supply air for the spray both to the paraffin ejector (C) and the cold water ejector (D). Each tube is provided with a stop-cock, though in practice this is seldom used. The two tubes are represented in the figure as being attached to a

piece of wood a short distance on the proximal side of the ejectors. This also is a matter of convenience merely, and the ejectors may be used separately and have separate air tubes if desired. The ejectors themselves must not be fastened to the wood, as it is requisite that they should be movable so as to be able to converge towards one point as will be explained later.

The ejector is made of brass, and its construction will be readily understood from the drawing (Fig. 2). The paraffin compartment (B) projects beyond the hot-water compartment (W) in order that the tube from the paraffin tank may be readily attached. At the end of the hot-water compartment nearest the nozzle a small tube (O) is inserted in order to allow the hot water to escape as it flows down the jacket, the stop-cock in (O) being turned to stop the flow when the jacket gets hot enough to melt the wax which may have hardened in the paraffin tube. It is not necessary to keep the hot water flowing constantly. The air-tube (A) it will be observed passes to the centre of the paraffin compartment by a double bend, so that the channel of discharge is exactly opposite the opening in the nozzle. Note also that its extremity is made slightly bulbous in order that by screwing the adjustable nozzle (N, Fig. 2) backwards the flow of paraffin may be shut off or regulated with great nicety. The nozzle should be large enough to provide a good hold for the thumb and finger, and should have a deeply milled circumference, otherwise it is sometimes difficult to adjust it properly when the fingers are perhaps slightly covered with paraffin. The thread of the screw should be fine and close fitting in order to avoid leakage. The back of the inside of the nozzle is carefully bevelled so that when screwed home in a backward direction it fits accurately against the bulbous front end of the air-tube, thus completely stopping the flow of paraffin.

The ejector for the cold water (D, Fig. 1) is precisely similar, except that it is not provided with a "jacket," and hence is of simpler construction. No further description will therefore be necessary.

An ejector of convenient size would have, approximately, the following dimensions: Length of hot water jacket, 5 cm.; diameter of hot water jacket, 1.7 cm.; diameter of overflow pipe, 0.5 cm.; diameter of paraffin tube (inside), 0.6 cm.; diameter of air tube, 0.5 cm. This tube is contracted at its outlet, so that it has about half the sectional area of the outlet in the adjustable nozzle.

The size of the outlet in the nozzle will depend upon the size of the spray one wishes to produce. Experience shows that nothing is to be gained by increasing the size beyond a certain maximum, unless for very large surfaces. The diameter of the one I use is as nearly as possible 0.25 cm.

The tube for the paraffin is necessarily about 2 cm. longer than the water jacket, because room is required for the attachment of its corresponding rubber tube behind, and for the adjustable nozzle in front.

The form of air pump (Fig. 1, E) to be used is quite immaterial, provided it will supply a large volume of air at a good pressure—say, 10 or 12 lbs. to the square inch. The cylinder (Fig. 1, F) into which the air is pumped need not be large—about a litre—but should be provided with three or four outlet pipes furnished with stopcocks. These are not all in use at once, but they will be found useful in various ways, as will be described later.

The motor (Fig. 1, G) which I use to drive the pump is about one-third horse power, and requires a current of about 105 volts.

PREPARATION OF SURFACE.

A moist fresh surface, such as a heart, stomach, tumour, etc. (Fig. 4), requires no preparation whatever. The mould will also separate fairly well from the unprepared skin, but it is better to apply a minute quantity of some very fine oil or vaseline. I use a very fine spray of albolene—I believe this is also known as paroline—as this does not in the least obscure the minutiae of the surface—(See Fig. 5.)—and greatly facilitates the removal of the mould. Where the surface is covered with short fine hairs, the oiling requires to be more thorough, or, better still, the part should be shaved. In casting parts or surfaces thickly covered with hair, as the head, pubes, or the fur of an animal (see Fig. 4), the preparation is made in such a way as to secure a more or less accurate cast

of the hair itself. The part is prepared as follows: A sort of cream is made by mixing corn flour, alcohol, and glycerine together. The glycerine is added merely to hold together the particles of flour after the alcohol has evaporated. The proportion of about 3j of glycerine to 3j of alcohol is found to work very well. This cream is sprayed upon the hairy parts by means of the simplest form of spray apparatus—namely, that in which a jet of air is directed across the narrowed end of a tube which dips below the surface of the cream. As the spray reaches the surface the alcohol evaporates, leaving a surface coating of flour sufficiently firm to support the fine spray of paraffin. Thus the paraffin is prevented from running into the hair and sticking to it in such a way as to prevent easy removal.

DIVISION OF THE MOULD.

In the case of those objects in which it is necessary to remove the mould in two or more pieces, the division is effected by placing silk threads upon the surface in suitable positions, so that when the mould is completed they may be "cut out" in such a way as to divide it into sections. It is very seldom, indeed, that it is necessary to make more than two sections. The living head, for instance, is cast in two sections by placing a thread in front of the right ear, over the vertex, and behind the left ear. When it is "cut out" from this position, the mould is divided in such a way that the posterior section contains the mould of the right, and the anterior section of the left, ear. Accordingly, while removing, if the anterior section is swung towards the left, and the posterior towards the right, perfect casts of both ears may be obtained. The mould of the hand, foot, leg, or arm, if it is desired to show both surfaces, must of course be cut into two sections, but an object, such as the guinea-pig in Fig. 4, may be—as this was—cast in a single piece.

SPRAYING THE PARAFFIN.

Fig. 3.—The mould in process of being formed. The two ejectors are held in the left hand, the right being free to adjust the nozzles, or for any other work that may be required, for example, directing an air current or ether spray for cooling purposes. The foot is shown covered with a thin layer of the solidified paraffin.

Though the paraffin used melts at 125° F., it will be readily

understood that it is judicious to have the water in the jacket a good deal hotter than that. Nothing is more aggravating than to find that while the mould is being made the temperature of the water in the jacket falls so low that the paraffin solidifies in its tube, or more likely just at the mouth of the ejector. Hence before starting the spray, care should be taken, not only that the water in the jacket is hot enough, but that it has been so, long enough to completely liquefy the paraffin to the very nozzle of the ejector. It will be found convenient to have a basin of water near the boiling point at hand into which the ejector can be dipped for a moment if it is seen that the wax is sinking nearly to its solidifying point. The hot water can at any time be renewed in the tube portion of the jacket by simply opening the waste water tap (o Fig. 2) for a moment, so that a fresh supply runs down from the tank above. When once the spraying is well under way the constant flow of the hot paraffin from the tank tends to keep up the temperature of the whole conduit; but if the surface to be cast is a large one it is well to renew the hot water in the jacket of the tube occasionally by turning the stopcock (o).

When it has been satisfactorily ascertained that the paraffin is ready to flow the motor is started and the adjustable nozzle (N) loosened from its contact with the bulbous end of the air tube (A) by turning it part of a revolution to the right. This allows the paraffin to flow, and as it passes through the same opening in the nozzle as the air, it is immediately thrown into a fine spray, which cools rapidly as it passes through the air. This spray—at a distance which can only be learned by experience, but which may be stated at from 2 to 4 inches—is directed against the surface of the object (Fig. 3), where it of course solidifies instantaneously, adapting itself as it does so to the minutest details of the surface. The spray should be moved rapidly over the surface so as to deposit a very thin layer at a time. This allows it time to harden, and is much more easily borne if the surface is a sensitive one. A stream of air from one of the extra stopcocks in the air cylinder (Fig. 1, F) may be directed upon the surface at the same time, considerably adding to the comfort of the patient. Recently in casting the head I have used a spray of ether for the same purpose, and found it to work admirably, though it is of course an additional trouble. If a very thin layer is put on at first the heat is not greater than will be well borne by a child of 5 or 6 years. After the surface is once covered even by a very thin layer, no discomfort whatever is experienced. By going over the surface in this way two or three times, an even continuous layer of solid paraffin, about $\frac{1}{8}$ in. thick, is soon formed (Fig. 3). The paraffin spray may now be stopped for a moment, while the whole surface is sprayed with the iced water. This is an advantage if the subject is liable to move at all, as it considerably strengthens the mould, and renders it less liable to be distorted by untimely movements on the part of the patient. It is not permissible, however, to use the water until the whole surface has been quite covered with a layer of paraffin. If it is not deemed necessary thus to cool the inner layer of the mould (and I very seldom find it so) as soon as the surface is seen to be covered, the cold water spray may be introduced and thrown at the same time and upon the same point as the paraffin. The convergence of the two sprays produces a most surprising effect. The instant a particle of paraffin touches a particle of cold water the former, of course, becomes solid. The result is that a sort of spongy tissue is formed with startling rapidity, in the cancellous spaces of which droplets of the cold water become imprisoned. The result is that not only does the cold water greatly facilitate the solidifying of the paraffin, but it enormously increases the speed with which the mould is thickened. This process is continued until the mould over its whole surface has attained a thickness of $\frac{3}{4}$ in., when the paraffin spray is stopped and the iced water continued for a few moments until the whole surface is quite firm.

The mould is then strengthened by being covered with a liberal coating of plaster-of-paris cream, mixed pretty thick. When this has reached the "curd cheese" stage of setting the threads are rapidly but very carefully cut out so as to divide the mould into the requisite number of sections. Experience has taught me that it is wise at this stage to mix another basin of plaster cream, which may be used to strengthen any parts of the mould that are manifestly weak.

Fig. 4.—Cast of a guinea-pig, with intestines exposed and partially distended with air. Note the absence of evidence of any compression.

or to patch any portions which exhibit a tendency to crack. In order not to have to wait long for this new coating to set, potassium sulphate, about a drachm to the pint, may be dissolved in the water used to make the cream. This greatly hastens the setting of the plaster. As soon as the plaster has set quite firmly the moulds may be carefully removed with any precautions that the exigencies of the case may suggest.

MAKING THE CAST.

After seeing that the surfaces of the mould are free from particles of plaster, etc., the different sections are fitted together, and the line of junction smeared with plaster cream. No preparation whatever of the surface of the mould, such as oiling, etc., is necessary. Thus no detail is blurred or rendered indistinct. Into the hollow mould thus formed the plaster cream for the cast is poured in the ordinary way.

REMOVING THE CAST FROM THE MOULD.

Fig. 5.—Cast of a hand.

Of all the advantages which this process may be considered to present over the older methods, it is my belief that the ease with which the mould can be separated from the cast is one of the most important. The method is as follows: As soon as the plaster in the cast has well set, the whole mass is put into a bath of hot water, say at 110° F. In the course of half an hour or an hour, the heat has penetrated through the

outer plaster casing, and warmed the paraffin, so that it becomes soft and plastic. The mass is then removed from the water, and the outer plaster mould broken away in large masses by means of a chisel. Then it will be found that the whole of the paraffin mould can be removed with the greatest ease, simply by seizing it with the fingers and lifting it away from the surface, as one would lift a piece of wet gauze. Thus there is, with ordinary care, no danger whatever of injuring the surface of the cast, and the whole process of separating the mould from the cast, which by the old plaster method of casting is so laborious and fraught with so much danger to the cast, can be done with absolute safety, with perfect ease, and in a very few moments. Moreover, "undercutting" is of no importance whatever, because of the plasticity of the mould, and the possibility of melting it out if necessary without any injury to the cast.

It may be objected that the apparatus is cumbersome and costly, and that the process involves some practice and a good deal of trouble. In reply I would merely say—look at the results. Has it ever before been possible to cast a hand showing such minuteness of detail as depicted in Fig. 5? Has it hitherto been possible to cast such a subject as Fig. 4 at all? In these two subjects are seen the delicacy of the molten paraffin in adapting itself to minute variations of surface (Fig. 5), and (Fig. 4), the absolute absence of the compressing effects which are so noticeable when plaster or other heavy materials are used.

CASES OF DIPHTHERIA TREATED BY INJECTION OF ANTITOXIC SERUM IN UNIVERSITY COLLEGE HOSPITAL DURING 1896 AND 1897.

BY

SIDNEY MARTIN, AND
M.D., F.R.S., Assistant Physician to the Hospital.

G. BERTRAM HUNT,
M.D., Resident Medical Officer.

IN the BRITISH MEDICAL JOURNAL of 1896, vol. i, p. 197, is a report by Drs. Martin and Smith of the cases of diphtheria treated in University College Hospital during the year 1895, the first antitoxic year, and a comparison of the results thus obtained with those of the four previous years in which antitoxin was not used. Although the belief in the antitoxic treatment is more widely and firmly held now than at the time of the last report, it seems desirable to continue these comparisons so as to include the last two years; not merely to add another proof of the efficacy of the treatment by antitoxin, but also to illustrate some still unsettled points connected with the proper dose and the best methods of using the serum.

During the years 1896 and 1897 there were 185 cases admitted into the diphtheria wards, but of these cases 7 are not available; 5 (which recovered) because no antitoxin was given as the cases were not considered to be true diphtheria; and 2 (1 fatal) because the antitoxin was only given by the mouth. There are thus left 178 cases treated by the subcutaneous injection of antitoxin to be compared with the cases treated without it. The severity of the cases admitted into University College Hospital, as we believe, in the other general hospitals, is on the whole rather above the average, since owing to the limited number of beds all cases of diphtheria seen as out-patients cannot be admitted, and preference is given to severe cases, especially those with