Published in final edited form as:

IEEE Trans Med Imaging. 2008 December ; 27(12): 1739–1753. doi:10.1109/TMI.2008.925080.

A Geometry-Driven Optical Flow Warping for Spatial Normalization of Cortical Surfaces

Duygu Tosun, Member IEEE and

D. Tosun was with the Department of Electrical and Computer Engineering, Whiting School of Engineering, Johns Hopkins University, Baltimore, MD 21218, USA. She is now with the Center for Computational Biology, Department of Neurology, School of Medicine, University of California Los Angeles, Los Angeles, CA 90095, USA

Jerry L. Prince, Fellow IEEE

J. L. Prince is with the Department of Electrical and Computer Engineering, Whiting School of Engineering, Johns Hopkins University, Baltimore, MD 21218, USA

Abstract

Spatial normalization is frequently used to map data to a standard coordinate system by removing inter-subject morphological differences, thereby allowing for group analysis to be carried out. The work presented in this paper is motivated by the need for an automated cortical surface normalization technique that will automatically identify homologous cortical landmarks and map them to the same coordinates on a standard manifold. The geometry of a cortical surface is analyzed using two shape measures that distinguish the sulcal and gyral regions in a multi-scale framework. A multichannel optical flow warping procedure aligns these shape measures between a reference brain and a subject brain, creating the desired normalization. The partial differential equation that carries out the warping is implemented in a Euclidean framework in order to facilitate a multi-resolution strategy, thereby permitting large deformations between the two surfaces. The technique is demonstrated by aligning 33 normal cortical surfaces and showing both improved structural alignment in manually labeled sulci and improved functional alignment in positron emission tomography data mapped to the surfaces. A quantitative comparison between our proposed surface-based spatial normalization method and a leading volumetric spatial normalization method is included to show that the surface-based spatial normalization performs better in matching homologous cortical anatomies.

Keywords

Index Terms; Cerebral cortex; spatial normalization; surface warping; optical flow; surface correspondence; multi-scale; multi-resolution

I. Introduction

Identification and localization of structures in anatomical brain images plays a major role in both neuroscience [1]–[4] and clinical medicine [5]–[7]. To aid in these tasks, a considerable amount of research has been directed toward the development of standardized templates of the human brain [8]–[11]. A standardized template provides a reference system for brain normalization, allowing anatomical and functional structures in new scans to be identified and analyzed in a single coordinate system. This process also facilitates the joint analysis of

large populations, from which knowledge of changes in brain structure and function in health and disease can be better understood. A major challenge in this work has been the development of a fully automated spatial normalization method that accurately and reproducibly aligns common key morphological features among brains. This paper addresses this problem.

Traditionally, scaled volumetric transformations are used to warp a “subject” brain into a reference three-dimensional (3-D) voxel-based coordinate system occupied by the “reference” brain [12]–[20]. The simplest approaches use affine transformations [12]; however, complex warping algorithms that have many degrees of freedom yield better tissue correspondence between the reference and the subject brains [13], [14], [16]–[18]. Matching local magnetic resonance image (MRI) intensities and regional features derived from these intensities are typical aspects of voxel-based normalization approaches, but accurate anatomical alignment is not guaranteed because these criteria do not attempt to align cortical folds (sulci and gyri) except where explicitly labeled by hand [15], [19].

The fact that the gray level intensities can be well-aligned while sulci and gyri are poorly aligned is demonstrated in Fig. 1. Figs. 1(a) and 1(b) show an axial cross-section of an atlas’s structural MRI volume and its corresponding gyral labels [21], respectively. A cortical surface estimated using the CRUISE method [22] is overlaid on these cross-sections. Fig. 1(c) shows the gyral labels on the cortical surface. Next, a subject’s MRI was normalized (using the HAMMER registration algorithm [17]) to the atlas, which permits the transfer of the atlas labels to the subject’s volume. Fig. 1(d) shows the transferred labels and Fig. 1(e) shows these labels on the subject’s estimated cortical surface (also found using CRUISE). It can be verified that the estimated cortical surface of the subject passes through the labels that mostly correspond to different gyral labels in the atlas. In other words, volumetric normalization has nearly successfully aligned cortical gray matter to cortical gray matter, which can also be verified by careful inspection of the warped MR image volume (not shown).

Further examination of Figs. 1(d) and 1(e), however, reveals problems in the actual alignment of the labeled structures. Unlike the clearly and correctly delineated gyral boundaries of Figs. 1(b) and 1(c), gyral labels are not falling on the correct gyri in all cases. For example, the precentral and postcentral gyri [see the oval in Figs. 1(c) and 1(e)], are not correctly labeled in the volumetric normalized result. The results shown in Fig. 1, while unique to this particular subject and registration algorithm, are quite typical of the types of failures that we have observed in other subjects and using other deformable registration algorithms. A better labeling is shown in Fig. 1(f); this is actually the result of the algorithm we present in this paper. A quantitative comparison is presented in Section IV-B to support our claim that the surface-based spatial normalization performance is better in matching homologous cortical anatomies.

Recent advances in the reconstruction of cortical surfaces from volumetric MR brain images have made the analysis and detailed comparison of cortical geometries possible via surface-based methods [7], [22]–[26]. Because of the high degree of variability among human brains, however, one-to-one matching of cortices between a subject and a reference (template or atlas) brain is challenging. Cortical unfolding procedures, the first step in matching cortices, create maps from subjects’s cortices to a standard manifold, making it possible to assign a coordinate system to cortices [25], [27]–[41]. It remains a major challenge, however, to reliably place key homologous anatomical features at the same location in the unfolded cortex coordinate system, thus yielding an anatomically sensible spatial normalization of the cortex with respect to a reference cortex.

In this paper, we present a cortical normalization procedure that takes place in the unfolded cortex domain. We aim to address some of the issues associated with the existing surface-based warping methodologies. A large number of existing methods either use manually identified landmarks and/or impose strict point correspondences in order to guarantee some measure of correct anatomical homology between subject and reference [25], [28]–[31]. Consider a cortical warping procedure driven by a set of manually identified landmark curves (e.g. [28], [42]). Although the mapping is smoothly extended to non-landmark surface points, it does not account for the quality of anatomical matching at these points. The overall quality of the anatomical match is therefore limited by both the number and the spatial arrangement of the selected landmark curves. Authors in [43] significantly improved the surface-based warping by formalizing a process driven by curvature features at every surface point; however, the chosen curvature feature (a convexity measure) creates maps that effectively match only the major sulci.

Our approach analyzes the geometry of the cortex in a multi-scale framework using two shape measures. These shape measures distinguish different folding patterns that are part of normal cortical geometry. Without requiring any manually identified landmarks or explicit point correspondences, this approach gives an implicit representation of the anatomical features present and allows us to imply a dense anatomical homology between a subject and a reference at each level of a multi-scale representation. Then, we use a regularized optical flow warping algorithm for hierarchical alignment of a wider spectrum of cortical features (i.e., from primary cortical folds to secondary cortical folds) in this multi-scale framework. A further advantage of our algorithm is that by building a scale space, we are able to handle shape variability on primary folds due to secondary folds and interruptions. In the following sections, first we briefly describe the cortical surface reconstruction and cortical unfolding methods used to initialize the proposed method. Then, we present a geometry-driven optical flow warping for spatial normalization of cortical surfaces and performance analysis studies.

II. Preliminaries

Several algorithms are used to prepare each MR brain image volume for use in the cortical spatial normalization procedure described herein. These algorithms are described in detail in the literature [22], [32], [44], but for completeness we now provide a brief overview of the major steps.

Cortical Surface Reconstruction

The *Cortical Reconstruction Using Implicit Surface Evolution* (CRUISE) method [22], [44] is used to generate a triangle mesh representation of the central cortical surface. MR images were obtained from the Baltimore Longitudinal Study of Aging (BLSA) [45]. All data set were acquired axially on a GE Signa 1.5 Tesla scanner using a T_1 -weighted SPGR imaging protocol (TR = 35ms, TE = 5ms, flip angle = 45°, NEX = 1, slice thickness = 1.5 mm, FOV = 24 mm, gap = 0, matrix = 256×256). The cerebellum, extracranial tissue, and brain stem (at the level of the diencephalon) were removed from each image data using a semiautomated approach [46]. The remaining image volume was then resampled to obtain isotropic voxels each having size of 0.9375 mm×0.9375 mm×0.9375 mm using cubic B-spline interpolation in order to make the subsequent processing less sensitive to orientation. Figs. 2(a) and (b) show cross-sectional views of the T1-weighted MR image and the resulting cerebral image volume.

The first step in the CRUISE processing pipeline is to apply a fuzzy tissue segmentation algorithm [47], [48], which is robust to both noise and tissue inhomogeneities. The fuzzy segmentation step yields three membership function image volumes representing the fractions of white matter (WM), gray matter (GM), and cerebrospinal fluid (CSF) within

each image voxel. The WM membership function is then processed using an automated algorithm that fills the ventricles and subcortical GM structures (e.g., putamen, thalamus, and the caudate nucleus) with “white matter” [49]. To compensate for partial volume effects in thin sulcal regions, CRUISE automatically enhances the GM membership functions by creating thin (artificial) CSF separations within sulci [50]. Cross-sectional views of the edited WM membership and the enhanced GM membership are shown in Figs. 2(c) and (d), respectively.

The next step in CRUISE is to generate a cortical surface representation that lies at the WM/GM interface, which serves as an initial surface for reconstructing the central cortical surface. Because of imaging noise and artifacts, an isosurface generated from the edited WM membership function invariably has non-spherical topology. A graph-based topology correction algorithm [51] is therefore used to further modify the WM membership function prior to using an isosurface algorithm, and together a WM/GM surface with the correct spherical topology is generated. Finally, a topology-preserving geometric deformable surface model [52], initialized at the WM/GM surface, is driven toward the geometric center of the GM using gradient vector flow (GVF) forces derived from the enhanced GM membership function [53]. Typical WM/GM and central cortical surfaces generated using CRUISE are shown in Fig. 2(e) and (f), respectively. Each reconstructed central surface is a triangle mesh comprising approximately 300,000 vertices. The *central* cortical surface representation is the starting point for the cortical unfolding and geometry analysis, as described in the following sections.

Cortical Unfolding

Central cortical surfaces found using CRUISE are mapped automatically to the unit sphere using the method described in [32], [39]. This method yields a separate map of each cortical hemisphere onto its own unit sphere, which is called a *hemispherical map*. These maps have been shown to preserve metric properties better than using a single sphere for the whole cortex [39].

Key components of the cortical unfolding method include parametric surface relaxation, iterated closest point registration, and conformal mapping with a minimal area distortion constraint. The first step is to bring each mesh node to the complex plane using a conformal flattening technique [37], as shown in Fig. 3(b). A fixed north pole on the cortical surface is required for conformal flattening using this method. A parametric surface relaxation followed by the iterated closest point registration to a reference brain surface is used to automatically identify the north pole point on the top of the corpus callosum, which therein provides a common position across all brains. A conformal transformation then adjusts the mesh nodes on the complex plane in order to line up the hemispheres and minimize area distortion, as shown (for the right cortical hemisphere) in Fig. 3(c). An inverse stereographic projection then brings the points on the complex plane to the sphere, as shown in Fig. 3(d). The last two steps are carried out for both hemispheres separately. Left and right cortical hemispheres are automatically identified by defining a surface cut around the corpus callosum using the knowledge of the locations of the anterior and posterior commissures.

This cortical unfolding procedure puts key anatomical landmarks — e.g., major sulci — onto approximately the same location on the hemispherical maps [32]. This reduces some uncertainty in the mapped location of cortical features, and thereby represents a good starting point for the geometry-driven surface normalization that we describe in this paper.

III. Spatial Normalization for Cortical Surfaces: Geometry-Driven Optical Flow Warping

Our overall goal is to align the geometric features of two brain cortical surfaces using the sphere as a canonical joint coordinate system. Having warped the features of one cortex into those of the other within the spherical coordinate system, the two hemispherical map functions induce a 3-D warp from one cortex to the other. As shown in the block diagram in Fig. 4, the algorithm first analyzes the geometry on the two cortices and then computes an optical flow field between them. The optical flow field provides a dense representation of the displacement that is required to warp one cortex so that it best matches the other. Our rationale for performing a pairwise warping rather than, for example, matching the subject's data to a statistical model [43] is that it should produce better atlas-based sulcal labels, which is our primary intended application. Our atlas comprises an MR brain image volume of one individual and an image volume of manually delineated anatomical labels on this individual brain.

A general warping procedure can be stated as following: Given two manifolds — a reference manifold $\mathcal{R}$ and a subject manifold $\mathcal{S}$ — and a similarity measure, find the best coordinate system transformation $\mathbf{u}(\mathbf{x}): \mathbb{R}^3 \rightarrow \mathbb{R}^3$ that associates any point $\mathbf{x} \in \mathbb{R}^3$ of $\mathcal{S}$ to a corresponding point $\mathbf{x} + \mathbf{u}(\mathbf{x}) \in \mathbb{R}^3$ on $\mathcal{R}$ while maximizing the similarity measure between the warped manifold $\mathcal{S}$ and the reference manifold $\mathcal{R}$. This framework is illustrated in Fig. 5. In our setting, the manifolds $\mathcal{R}$ and $\mathcal{S}$ are the corresponding hemispherical maps of a reference brain and a subject brain on the unit sphere surface (i.e., $\mathbb{S}^2 \subset \mathbb{R}^3$), respectively. We note that warping algorithm is applied to the left and right cortical hemisphere maps separately. In this section, we describe the key elements of the warping algorithm in detail.

A. Shape Measures

In this paper, a homology between the two cortical surfaces is defined on the basis of a similarity between the *shape* and *size* of the cortical folds. The two principal curvatures κ_1 and κ_2 (where $\kappa_1 \neq \kappa_2$) have the necessary information to fully describe the local shape of a given surface. But matching these two curvature measures between surfaces does not yield the desired geometrically meaningful shape matches since the two principle curvatures are functions of both shape and size and each fails in distinguishing certain geometries. The Gaussian curvature $K = \kappa_1 \times \kappa_2$ and mean curvature $H = (\kappa_1 + \kappa_2)/2$ measures are also candidates for matching shape; but they perform poorly as well for similar reasons. In particular, the Gaussian curvature vanishes at both planar points (i.e., $\kappa_1 = \kappa_2 = 0$) and parabolic points (i.e., $\kappa_1 = 0$ and $\kappa_2 = 0$), thereby failing to distinguish these two shapes.

The *shape index* and the *curvedness* measures, previously introduced as local measures of shape [54], turn out to be ideal for cortical shape characterization and matching. The shape index, SI, and the curvedness, C, are defined as

$$SI = \frac{2}{\pi} \arctan \frac{\kappa_2 + \kappa_1}{\kappa_2 - \kappa_1}, \quad (1)$$

$$C = \sqrt{\frac{\kappa_1^2 + \kappa_2^2}{2}}. \quad (2)$$

The shape index specifies the local surface geometry up to a scaling factor (i.e., similarity), and takes values in the interval $[-1, +1]$. The extreme values of the shape index represents

local shapes look like either the inside of a spherical surface ($SI = -1$) — i.e., spherical cup — or the outside of a spherical surface ($SI = 1$) — i.e., spherical cap. Intermediate values of SI correspond to local surface shapes that are smoothly morphed between these two extremes. The curvedness measure is proportional with the size of the local surface folding. The shape index and the curvedness measures complement each other in defining the local surface shape and the size, as shown in Fig. 6.

We computed the principle curvatures required for the shape index and curvedness computation by estimating the Monge representation of the local surface patch [55]. In particular, we defined a coordinate system with its origin at the surface mesh node under consideration and its z-axis pointing in the direction of the outward surface normal. Then, a quadratic surface was fit to the local surface patch defined over a circular geodesic neighborhood of radius 6 mm at the mesh node under consideration.

B. Focus on Prominent Features

Cortical folds, the gross anatomical landmarks of the cortex, vary considerably in shape and in number from one adult brain to another; however, there is considerable regularity in the formation and organization of these folds [56]–[60]. The cortical folds in the human brain have been classified as primary, secondary, and tertiary based on their time of formation, their variability (e.g., location, shape, orientation, and existence variations) in the general population, and their depth on the cortex. For instance, the primary folds (e.g., the central sulcus, Sylvian fissure, calcarine sulcus, parieto-occipital fissure, collateral sulcus, rhinal sulcus, callosal sulcus, superior frontal sulcus) appear at predictable points during the early stages of development, marking critical lobular and functional boundaries. The primary folds penetrate sufficiently deeper into the brain than the secondary folds (e.g., the precentral sulcus, postcentral sulcus, inferior temporal sulcus) and the tertiary folds (e.g., the paracingulate sulcus). Our spatial normalization primarily focuses on the prominent features (i.e., primary and secondary folds) that are common across individuals.

In order to focus on prominent cortical features, we compute our shape measures (SI and C) on the geometry of a *partially flattened cortical surface representation (PFC)* instead of the original central cortical surface representation. A partially flattened representation of the cortex is generated by smoothing the triangle mesh representation of the original central cortical surface using a parametric surface relaxation operator [32], [33], [36]; specifically, each mesh node is iteratively repositioned to the barycenter of its one-ring neighbors. The surface relaxation operator allows the preservation of the most prominent anatomical details representing the primary sulci while smoothing out the details.

Since we require a similar overall appearance of the two surfaces being matched, it is important that the PFC representations of the two are comparable. This is accomplished by stopping the parametric relaxation operator at a point where the two brains will have a similar appearance. As the stopping criterion, we use a global shape measure

$\|H\|_2 = \sqrt{\frac{1}{4\pi} \int H^2 dA}$, where H is mean curvature and dA is the surface area element. The surface integral of the squared mean curvature gives a shape descriptor that can be viewed as the bending energy of the surface. This measure is a function of both the number and the relative size of the ridges and furrows on the surface. Relatively consistent numbers and sizes of the primary cortical folds in normal brains allows us to generate similarly shaped partially flattened surface representations at the level $\|H\|_2 = \gamma$ for a given constant γ . The degree of geometric detail within a PFC is controlled by choosing γ , as illustrated in Fig. 7 (see [32] for details). While the primary folds (e.g., the central sulcus and Sylvian fissure) preserve their existence throughout the surface relaxation process, the secondary folds (e.g., the precentral sulcus) gradually disappear.

The mean curvature measure is inversely proportional with the size of the surface; the surface integral of the squared mean curvature is scale-invariant. It has been shown that $\int H^2 dA$ is a conformal invariant — and therefore invariant under Euclidean similarities [61], [62]. Therefore, our stopping criterion is independent of the area of the brain being considered, which further assures us that the shapes of the cortices should be similar for a given γ .

Fig. 8 shows the SI and C measures for the PFCs of two different brains (same γ). It is observed that SI successfully distinguishes the inward and outward cortical folds and that both SI and C are comparable in magnitude between two surfaces. In particular, Fig. 8(a) shows the boundaries of several primary sulcal regions (cf. [63]); it can be observed that the shape index patterns within these regions are very similar. Several sulcal fundi (cf. [64]) are plotted on the C maps in Fig. 8(b); these features have very similar curvedness patterns in their vicinity. Based on these visual assessments, we see that, the SI and C measures, together, characterize distinct features of the cortical gyri, which can be matched between different brains in order to create a homology.

The choice of γ has a significant impact on the appearance of SI and C, and therefore on the quality of the inferred homology (see Fig. 7). To permit matching at both coarse and fine levels of details, we use multiple PFCs computed using different γ 's. This is referred to as the *multi-scale approach* and γ_i for $i = 1, \dots, S$ is referred as the *scale*.

C. Geometry-Driven Optical Flow Warping

The two surfaces will be brought into correspondence using *geometry-driven optical flow warping (GDOF-warping)* on the hemispherical map domain, as illustrated in Fig. 5. In this section, we formulate the variational problem for GDOF-warping and derive the Euler-Lagrange equation of this variational problem.

Let $\mathbf{I}(\mathbf{x}, t) = [w_{SI_1} I_{SI_1}(\mathbf{x}, t), w_{C_1} I_{C_1}(\mathbf{x}, t), \dots, w_{SI_S} I_{SI_S}(\mathbf{x}, t), w_{C_S} I_{C_S}(\mathbf{x}, t)]^T$ be a *shape measure vector*, where I_{SI_i} and I_{C_i} , $i = 1, \dots, S$, are the shape index and the curvedness maps, and w_{SI_i} and w_{C_i} are scalar weights. The shape measure vector is a function of $\mathbf{x}$, which is a position on the unit sphere, $\mathbb{S}^2$. It is also assumed to be a function of (artificial) time — such that $t \in [0, 1]$ and $t = 0$ corresponds to the subject brain and $t = 1$ corresponds to the reference brain. The GDOF field vector $\mathbf{u}(\mathbf{x}) = [u_1(\mathbf{x}), u_2(\mathbf{x}), u_3(\mathbf{x})] \in \mathbb{R}^3$ defines the correspondence from one spherical map to the other. It is assumed that $\mathbf{u}(\mathbf{x}) \in \mathcal{F}$, where

$$\mathcal{F} = \left\{ \mathbf{u} \in W^{1,2}(\mathbb{S}^2), \text{ s.t. } \|\mathbf{u}(\mathbf{x}) + \mathbf{x}\| = \|\mathbf{x}\| \right\}, \quad (3)$$

and $W^{1,2}(\mathbb{S}^2)$ denotes a Sobolev space of functions whose derivatives have finite L^2 -norm. The constraint on $\mathcal{F}$ guarantees that $\mathbf{u}$ maps each point on the sphere to a point on the same sphere.

Ideally, the shape measure vectors for corresponding points are identical. Starting with this constant shape measure vector constraint, and using the chain rule of differentiation, we have

$$\begin{aligned} \mathbf{I}(\mathbf{x}, t) &= \mathbf{I}(\mathbf{x} + d\mathbf{x}, t + dt) \\ &= \mathbf{I}(\mathbf{x}, t) + \frac{\partial \mathbf{I}(\mathbf{x}, t)}{\partial x_1} dx_1 + \frac{\partial \mathbf{I}(\mathbf{x}, t)}{\partial x_2} dx_2 \\ &\quad + \frac{\partial \mathbf{I}(\mathbf{x}, t)}{\partial x_3} dx_3 + \frac{\partial \mathbf{I}(\mathbf{x}, t)}{\partial t} dt + \dots \end{aligned} \quad (4)$$

where the dots stand for higher order terms. Dividing through by dt and in the limit that dt tends to zero, this constraint is simplified to

$$\frac{\partial \mathbf{I}(\mathbf{x}, t)}{\partial x_1} \frac{dx_1}{dt} + \frac{\partial \mathbf{I}(\mathbf{x}, t)}{\partial x_2} \frac{dx_2}{dt} + \frac{\partial \mathbf{I}(\mathbf{x}, t)}{\partial x_3} \frac{dx_3}{dt} + \frac{\partial \mathbf{I}(\mathbf{x}, t)}{\partial t} = 0. \quad (5)$$

The required displacement $d\mathbf{x}/dt$ is the optical flow field vector $\mathbf{u}(\mathbf{x})$; hence this implies that

$$\nabla_{\mathbb{S}^2} \mathbf{I}(\mathbf{x}, t) \cdot \mathbf{u}(\mathbf{x}) + \frac{d\mathbf{I}(\mathbf{x}, t)}{dt} = 0, \quad (6)$$

where $\nabla_{\mathbb{S}^2}$ is the spatial gradient operator defined on $\mathbb{S}^2$. We refer to the constraint given in (6) as the *GDOF-constraint*. It is expected to be approximately true from the discussion given in Section III-B.

As in the classical aperture problem in optical flow, (6) gives only the component of displacement vector that is in the direction of the intensity gradient. To further define the displacement field, we assume that the field is approximately incompressible. Although true incompressibility makes no sense in this non-physical problem, this assumption helps to keep differential areas on one surface from getting either too small or too large. Finally, to complete the regularization process which permits robust computation of a displacement field, we assume that $\mathbf{u}(\mathbf{x})$ is a smooth function.

Putting these three features together in a variational framework leads us to minimize

$$\begin{aligned} E(\mathbf{u}, t) = & \int_{\mathbb{S}^2} \rho \left(\left\| \nabla_{\mathbb{S}^2} \mathbf{I}(\mathbf{x}, t) \cdot \mathbf{u}(\mathbf{x}) + \frac{d\mathbf{I}(\mathbf{x}, t)}{dt} \right\| \right) d\sigma(\mathbf{x}) \\ & + \alpha \int_{\mathbb{S}^2} \sum_{i=1}^3 \rho(\nabla_{\mathbb{S}^2} u_i(\mathbf{x})) d\sigma(\mathbf{x}) \\ & + \beta \int_{\mathbb{S}^2} \rho(\nabla_{\mathbb{S}^2} \cdot \mathbf{u}(\mathbf{x})) d\sigma(\mathbf{x}), \end{aligned} \quad (7)$$

where α and β are real constants. Equation (7) is a fairly standard expression for optical flow (cf. [65]), except that it is formulated to warp two spherical surfaces. As well, the function $\rho: \mathbb{R} \rightarrow \mathbb{R}$ is a robust error measure (defined below) that is used instead of the usual L^2 -norm in order to better handle discontinuities and outliers.

In order for $\mathbf{u}(\mathbf{x})$ to be a minimum of (7), it is required that any small variation on $\mathbf{u}(\mathbf{x})$ leads to a higher energy. We introduce a variation by adding a small test function $\varphi(\mathbf{x}) \in C_0^\infty(\mathbb{S}^2)$ — i.e., the space of smooth functions vanishing outside a compact subset of $\mathbb{S}^2$ — to $\mathbf{u}(\mathbf{x})$. This variation on $\mathbf{u}(\mathbf{x})$ is represented parametrically as

$$\mathbf{u}(\mathbf{x}, s) = \left[\frac{\|\mathbf{x}\| (\mathbf{u}(\mathbf{x}) + s\varphi(\mathbf{x}) + \mathbf{x})}{\|\mathbf{u}(\mathbf{x}) + s\varphi(\mathbf{x}) + \mathbf{x}\|} - \mathbf{x} \right], \quad (8)$$

where $s \in \mathbb{R}$. This definition of the variation on $\mathbf{u}(\mathbf{x})$ is the key to restricting the sought solution to $\mathcal{F}$ without imposing additional constraints on (7).

Computing $\frac{d}{ds}E(\mathbf{u}(\mathbf{x}, s))|_{s=0}$ gives the Euler-Lagrange equation displayed in Equation (9). In this equation, $\Delta_{\mathbb{S}^2}$ is the Laplace-Beltrami operator on the $\mathbb{S}^2$ surface, and ρ' is the gradient of ρ .

$$\begin{aligned}
 & \sum_{j=SI_1, C_1, \dots, SI_S, C_S} w_j^2 \left(\langle \nabla_{\mathbb{S}^2} I_j, \vec{u}(s) \rangle + \frac{dI_j}{dt} \right) \\
 & \left(\frac{\partial}{\partial x_k} I_j - \langle \nabla_{\mathbb{S}^2} I_j, \vec{y} \rangle y_k \right) \\
 & - \alpha \operatorname{div} \left(\frac{\rho'(\|u_k\|)}{\|u_k\|} \nabla_{\mathbb{S}^2} u_k \right) (u_k + x_k) \\
 & + \alpha \sum_{j=1}^3 \left[\operatorname{div} \left(\frac{\rho'(\|u_j\|)}{\|u_j\|} \frac{\nabla_{\mathbb{S}^2} u_j}{\|\vec{u} + \vec{x}\|^2} \right) (u_j + x_j) \right] (u_k + x_k) \quad (9) \\
 & + \beta \sum_{j=1}^3 \left[y_j \frac{\partial}{\partial x_j} \left(\frac{\rho'(\|\nabla_{\mathbb{S}^2} \cdot \vec{u}\|)}{\|\nabla_{\mathbb{S}^2} \cdot \vec{u}\|} \nabla_{\mathbb{S}^2} \cdot \vec{u} \right) \right] y_k \\
 & - \beta \frac{\partial}{\partial x_k} \left(\frac{\rho'(\|\nabla_{\mathbb{S}^2} \cdot \vec{u}\|)}{\|\nabla_{\mathbb{S}^2} \cdot \vec{u}\|} \nabla_{\mathbb{S}^2} \cdot \vec{u} \right) y_k \\
 & = 0, \quad k=1, 2, 3.
 \end{aligned}$$

$$\text{where } \mathbf{y} = \frac{\mathbf{u}(\mathbf{x}) + \mathbf{x}}{\|\mathbf{u}(\mathbf{x}) + \mathbf{x}\|} = [y_1, y_2, y_3] \in \mathbb{R}^3.$$

D. Eulerian Framework for Numerical Implementation

In this section we present a numeric solution to the GDOF's partial differential equation (PDE) given in (9). This requires discretization of the differential operators (i.e., $\nabla_{\mathbb{S}^2}$, $\Delta_{\mathbb{S}^2}$, and $\nabla_{\mathbb{S}^2}$) on the sphere. Rather than discretizing on a triangular mesh representing the sphere, we choose to embed the PDE in 3-D Euclidean space using the methods developed in [66]. Using this Eulerian framework, the differential operators are simpler to implement and this also yields a novel *multi-resolution scheme* for solving the PDE.

In this approach, we embed the sphere S^2 into $\mathbb{R}^3$ as the zero level set Ω_0 of the scalar function $\Phi(\mathbf{x}) = \|\mathbf{x}\| - R$, where R is the radius of the sphere. We then replace the differential operators in (9) as follows

$$\nabla_{\mathbb{S}^2} f = P_{\nabla\Phi} \nabla f \quad \text{and} \quad \Delta_{\mathbb{S}^2} f = \nabla \cdot (P_{\nabla\Phi} \nabla f), \quad (10)$$

where ∇ is the spatial gradient operator in the 3-D Cartesian coordinates. $\nabla\Phi$ gives the surface normal direction on Ω_0 and $P_{\nabla\Phi}$ is the operator that projects a 3-D vector onto the plane orthogonal to $\nabla\Phi$, defined as

$$P_{\nabla\Phi} = \text{Id} - \frac{\nabla\Phi \otimes \nabla\Phi}{\|\nabla\Phi\|^2}, \quad (11)$$

where Id is the identity operator and $\otimes$ is the vector product operator.

Fig. 9(a) shows a 2-D slice from the 3-D function $|\Phi|$. The intersection of the sphere Ω_0 is also shown in this figure (it is a circle) and an SI measure defined for a typical PFC is shown using the color scale shown in Fig. 8. In order to use the Euclidean framework to solve (9), it is necessary to extend each shape measure (SI and C) onto the entire domain $\mathbb{R}^3$. For the simple spherical geometry we are using here, data extension is accomplished by simple radial extension of the data, as shown in Fig. 9(b).

We have found that because of errors introduced in both the discrete curvature computations on the PFC surfaces and discretization anomalies in data extension, the SI and C measures are often somewhat noisy. It is therefore beneficial to apply an isotropic diffusion operator on these data prior to their use in solving (9). We use the following PDEs applied in the Euclidean framework to accomplish this smoothing,

$$\begin{aligned}\frac{dI_{SI_j}}{dt} &= \nabla \cdot (P_{\nabla\Phi} \nabla I_{SI_j}), \\ \frac{dI_{C_j}}{dt} &= \nabla \cdot (P_{\nabla\Phi} \nabla I_{C_j}).\end{aligned}\quad (12)$$

Here, I_{SI_j} and I_{C_j} , $j = 1, \dots, S$, are the shape measures (SI and C) computed at S different scales. This approach smooths the data within the sphere while simultaneously smoothing within the entire Euclidean computational domain (see [66] for details).

The PDE in (9) is discretized using forward differences in time and a combination of forward and backward differences in space. From the various possible combinations of the forward and backward differences, we use an upwinding scheme in the direction of $\nabla\Phi$ for the projected gradient computation and an upwinding scheme in the direction of $-\nabla\Phi$ for the divergence computation. We solve the resulting PDE in $\mathbb{R}^3$ but only at the *narrow-band points* that satisfy $\|\Phi(\mathbf{x})\| < h$ for a given constant h , large enough to compute required forward and backward differences, i.e., $h = 4.8$. This speeds up the numerical implementation for this variational problem. The solution at Ω_0 is a numerical estimate to the solution of the original PDE (9) defined on the sphere surface.

E. Multi-Resolution Scheme

In this section, we describe how to exploit the choice of R to form a multi-resolution scheme for solving (9). Assuming that R is in units of pixels, we see that choosing R small yields a small number of voxels by which to represent the data on Ω_0 . If R is large, then there are many voxels “covering” the sphere and that data on Ω_0 should be represented accurately. In transferring data from the highly detailed triangle mesh that represents the PFC mapped to the sphere, therefore, it is important to consider the size of the sphere.

Rather than simply choosing a large R and solving the PDE, we use a multi-resolution scheme, in which R is initially small and the PDE is solved on a “coarse” representation. The solution is then transferred to a slightly larger sphere (larger R) and solved again. At each level, shape features are mapped to the sphere of radius R and smoothed using (12). We stop growing the sphere at an R that gives a spherical surface area comparable to the actual cortical surface area. The strategy of increasing R is illustrated in Fig. 9(c).

This multi-resolution scheme allows us to achieve a coarse global feature alignment at the early stages and then focus on the alignment of fine details as R increases. When there are large deformations, proper convergence is much more likely to be achieved. The speed of overall convergence over solving either a PDE directly on the triangle mesh (Lagrangian approach) or solving at a single resolution R is much faster.

In the case of large deformations, there are alternatives to a multi-resolution scheme. For example, one can impose a specific form on the flow field vectors and add a regularity term quantifying the severity of the deformation. Lagrangian deformable template methods with continuum mechanical constraints are the well-known examples of this alternative approach [67]–[69]. The computational complexity and the computational time associated with these approaches are considerable. The hierarchical multi-resolution scheme described here is computationally efficient, permitting rapid convergence of the flow field estimates. Both

computational efficiency and large deformations are provided using the Eulerian scheme on down-sampled image data.

IV. Experimental Results

In this section, we present experiments that apply GDOF-warping to data from real brain images. Before presenting results, it is necessary to discuss algorithm parameter values used in the experiments. The parameters that are used in our algorithm are summarized in Table I.

A robust error measure is required in (7); we use the Lorentzian measure $\rho(s) = \log(1 + \frac{1}{2}(\frac{s}{\mu})^2)$ [70]. The scale parameter μ sets a fixed value on the gradient magnitude (i.e., $|\rho'(s)|$), beyond which its influence is reduced. The parameter μ was estimated using the method described in [70].

We use the geometry of four PFCs (i.e. $S = 4$) at the scale levels of $\gamma_1 = 30$, $\gamma_2 = 25$, $\gamma_3 = 20$, and $\gamma_4 = 15$. The weighting coefficients for the shape measure maps, w_j for $j = SI_1, C_1, \dots, SI_S, C_S$, were adaptively determined. The rationale for use of different weightings for SI and C is based on the desire for rapid convergence and the avoidance of local minima. At the coarsest level of the multi-scale framework, the SI and C measures will be in agreement better than when the process is at the finer shape scales. Therefore, we want the flow field estimation process to be initially driven by the SI and C measures at the scale that is in strong agreement. As the warping process continues, we want to increasingly invoke finer scales in order to make sure that finer details are appropriately matched. The dynamic update of the weighting coefficients ideally leads to the choice of equal weighting at the end; shape measures from different shape scales would have equal influence on the warping process as same level of anatomical alignment is achieved at each shape scale. In particular, we measured the degree of agreement between the subject's and the reference's SI and C measures at each shape scale by computing

$$DA_i = \sqrt{\int_{\mathbb{S}^2} \left(\left(\frac{dI_{SI_i}}{dt} \right)^2 + \left(\frac{dI_{C_i}}{dt} \right)^2 \right) d\sigma(\mathbf{x})}, \quad (13)$$

for $i = 1, \dots, S$. Then, the weighting coefficients at each multi-resolution iteration were set to

$$w_{SI_i} = w_{C_i} = \frac{1/DA_i}{\sum_{j=1}^S 1/DA_j}. \quad (14)$$

The coarsest level of multi-resolution started at $R_0 = 5$ and was gradually increased to $R_1 = 35$ in 7 multi-resolution steps — i.e., $M = 7$ — in a linear fashion.

We found it useful to choose α and β on the basis of a hypothetical underlying physical model. Young's elasticity modulus E relates the tension of the object to its stretch in the same direction, and Poisson ratio ($\nu \in [0, 0.5]$) gives the ratio between the lateral contraction and the axial extensions. The mathematical relationships between E , ν , α , and β are given as follows:

$$\beta = \frac{E}{4 \times (1 - 2\nu) \times (1 + \nu)} \quad (15)$$

$$\alpha = \beta \times (1 - 2\nu) \quad (16)$$

We used a fixed Poisson ratio, $\nu = 0.2$, and linearly decreased the Young's elasticity modulus starting with $E = 40$ at the coarsest resolution level to $E = 20$ at the finest resolution level.

Fig. 10 shows the GDOF estimation process for a typical experiment. The direction of the resulting flow field vectors are shown on the warped hemispherical map after three resolution levels. The field vectors are down-sampled for display purposes. The boundary of the central sulcus region of the reference brain (in magenta) and of the subject brain initially and after the GDOF-warping at these resolution levels (in yellow and cyan, respectively) are also shown in Fig. 10. Note that sulcal boundary information was not used in the warping process.

At the early stages of the multi-resolution scheme, the flow field yields large deformations to correct for the large dissimilarities. We also observe smaller deformation field in later iterations of the multi-resolution scheme, aiming to match fine details and correct for the size differences by causing stretch or shrinkage. This implies the efficiency of the multi-resolution scheme in correcting for large deformations.

A. Probabilistic Maps

In this section, we evaluate how well the common brain features map to similar locations on the sphere under the described spatial normalization method. We also use the analysis described in this section to justify the need for multi-scale approach in order to achieve the desired anatomical alignment.

We randomly picked 33 brain surfaces from our database of surfaces. The dataset was comprised of MR images of 16 females with an average age of 72.3 (63.4 – 84.4 years of age range) and 17 males with an average age of 69.8 (59.6 – 81.1 years of age range). Hemispherical maps of 32 subject brains were warped to a randomly selected reference brain's hemispherical maps using the proposed spatial normalization method. We analyzed the locations to which eight particular sulci (i.e., four sulci per cortical hemisphere) were mapped in 33 brains. Sulcal regions, defined as the buried cortex surrounding the sulcal spaces, were automatically segmented [63] and manually labeled on all brains. These sulcal regions are the central sulcus (cs), the superior frontal sulcus (sf), the cingulate sulcus (cn) and the parieto-occipital sulcus (po) on both left and right cortical hemispheres. The reason we selected these sulci is that it was reported in [71] that they could be consistently labeled across multiple scans of the same subject. These sulci are marked on the left hemisphere of one cortical surface in Fig. 11.

To see where the eight sulci (i.e., four sulci per cortical hemisphere) map to on the reference hemispherical map after spatial normalization, we generated separate probabilistic maps represented by the functions P_i , $i = \text{cs, sf, cn, and po}$, on the reference hemispherical map. Each P_i was initialized to one at each mesh nodes on the sulcal region of interest on the reference brain and to zero elsewhere. Then, for each reference mesh node, the value of P_i was incremented by 1 for each subject brain, if the corresponding point on the spatially normalized subject's hemispherical map has the same sulcal label. Finally, the P_i values were normalized to the range [0, 1] by dividing by 33. This gives a probabilistic map comprising an estimated conditional probability of the location of a sulcal region for these sulcal regions. To better understand the value that is added by GDOF-warping, we computed probabilistic maps for the same eight sulcal regions using the correspondence between the

reference and subject cortices just after the cortical unfolding, which is referred as the “before GDOF-warping” state in the following discussion.

Fig. 12 shows the probabilistic maps of the sulcal regions on the right cortical hemisphere both before and after the GDOF-warping. We calculated two measures to quantify the improvement in P_i functions after the GDOF-warping. First, we calculated the maximum value of P_i . Second, we calculated a *surface area ratio measure* defined as $A(P_i > p)/A(P_i > 0.0)$, where $A(T)$ is the surface area of a region T on the reference hemispherical map and $p \in [0.0, 1.0]$. Perfect spatial normalization of a sulcal region across all subjects will score a surface area ratio measure of 1.

The maximum value and the surface area ratio measures before and after the GDOF-warping are given in Table II. After the GDOF-warping, the maximum of P_i is unity for all sulcal regions, showing that at least one node has the same label in all normalizations. Loosely speaking, this shows that after the GDOF-warping, sulcal regions are more reliably mapped to the same position on the sphere than before warping. For all eight sulcal regions, the surface area ratio measure is significantly larger after the GDOF-warping. Unlike the large spread of P_i before the GDOF-warping, for each sulcal region, the spread P_i resembles the shape of that sulcal region on an individual subject brain. For example, multiple local maxima observed in P_{sf} after the GDOF-warping in Fig. 12(c) follows the interrupted (i.e., broken into more than one piece by a gyral ridge) nature of superior frontal sulcus. Improvements in both of these measures, and the visual inspection of the results shown in Fig. 12 show that GDOF-warping yields a significantly better sulcal alignment, and thereby anatomical alignment.

The results presented above were obtained by warping the subject to the reference based on shape measure maps from all four PFCs. In order to justify use of multiple PFCs, we repeated the same analysis by warping the surfaces using the shape measure maps of only one PFC. As in multi-scale case, the maximum of probabilistic maps are all equal to one; however, the surface area ratio measures, plotted in Fig. 13, show noticeable degradation when only a single PFC is used and also when the process is stopped at a lower resolution (R small). In these graphs, labels S1, S2, S3, and S4 refer to the single-scale case at the levels $\gamma_1 = 30$, $\gamma_1 = 25$, $\gamma_1 = 20$, and $\gamma_1 = 15$, respectively, and the label All4S refers to the multi-scale case. It is observed that use of all four resolutions is better in nearly every sulcal region and that stopping at the finest resolution sphere (largest R) is also better in nearly every case.

B. A Comparison Between Volumetric and Surface-Based Spatial Normalization Methods

In this section, we present a quantitative comparison between the matching performances of HAMMER, a leading volumetric spatial normalization method [17], and our proposed surface-based normalization method. The performance metric is based on the probabilistic maps generated by each algorithm for eight manually labeled sulcal regions: the central sulcus, the superior frontal sulcus, the cingulate sulcus, and the parieto-occipital sulcus on both left and right cortical hemispheres. Processing steps to compute the surface-based probabilistic maps and the statistics on the resulting probabilistic maps were described in Section IV-A. In this section, we first describe the analogous processing steps required to compute the volumetric probabilistic maps, and then describe the experimental results.

Sulcal labels are defined on the central cortical surfaces of our CRUISE-processed brains. Generating volumetric probabilistic maps requires the extension of each sulcal label onto a 3-D volume representing the cortical gray matter mantle of that label. We chose a Eulerian framework to perform this label extension. In particular, let f be a scalar sulcal label data function defined on the central cortical surface C , which is the zero level set of a scalar

function $\Phi: \mathbb{R}^3 \rightarrow \mathbb{R}$. In this work, Φ is a signed distance function generated by the CRUISE algorithms, and the triangulated surface C was obtained by applying a marching cubes algorithm to Φ [cf. [22]]. The label extension then satisfies $\nabla f \cdot \nabla \Phi = 0$; in this way the labels are extended in a direction normal to the surface. In order to restrict the label extension to the cortical gray matter mantle, the resulting label volume was masked by a binary image volume obtained by thresholding the gray matter membership function at a 0.5 value [cf. Section II]. Cross-sectional views from the resulting sulcal label volumes for a sample subject are shown in Fig. 14.

The next step in generating volumetric probabilistic maps was to warp the skull-stripped MR image volumes of 32 subject brains to the reference brain's skull-stripped MR image volume using the HAMMER algorithm [17]. Tissue segmentation results using CRUISE algorithms were used by the HAMMER algorithm. The subject data set and the reference brain were same as the ones used in the experiments described in Section IV-A. For each subject brain, a HAMMER deformation field from the subject space to the reference space was then applied to the subject's sulcal label volume, bringing each subject's sulcal labels to the reference image space. We used the HAMMER software package that is publicly available at <https://www.rad.upenn.edu/sbia/rsoftware.html>.

Separate volumetric probabilistic maps for each sulcal region — P_i^v , $i = \text{cs, sf, cn, po}$ — were generated in the reference image space. In particular, each P_i^v was initialized to unity at each reference image voxel in the sulcal region of interest on the reference brain and to zero elsewhere. Then, for each reference image voxel, the value of P_i^v was incremented by 1 for each subject brain if this voxel had the same sulcal label in the subject's transferred sulcal label volume. Finally, the P_i^v values were normalized to the range [0,1] by dividing by 33, yielding a volumetric probabilistic map for the sulcal region of interest. Sample cross-sectional views from the volumetric probabilistic maps of the sulcal regions on the right cortical hemisphere are shown in Fig. 15.

Now we can provide a quantitative comparison between our surface-based probabilistic maps presented in Section IV-A and these volumetric probabilistic maps. We calculated two measures: (1) the maximum value of P_i^v , and (2) a *volume ratio measure* defined as $V(P_i^v > 0.5) / V(P_i^v > 0.0)$, where $V(\Omega)$ is the volume of a region Ω in the reference image space. The volume ratio measure is formulated to be analogous to the surface area ratio measure. The maximum values and the volume ratio measures for the volumetric probabilistic maps are given in Table III.

To avoid any misleading performance comparison results due to the disparate performance measures (i.e., surface ratio volume ratio measures are only analogous) and due to the 3-D nature of the problem (i.e., nonuniform cortical gray matter thickness), we computed volumetric probabilistic maps for the same sulcal regions using our GDOF-warping methods. Using the point correspondence established between the reference and subject cortices, we mapped subjects' sulcal labels onto the reference brain's central cortical surface. These surface label maps were then extended onto the reference brain imaging space and the volumetric probabilistic maps for the same eight sulcal regions were computed using the methods described above. The maximum value and the volume ratio measures for the volumetric probabilistic maps using GDOF-warping are appended to Table III. Examination of the probabilistic maps generated with these spatial normalization methods revealed a very strong performance superiority of our surface-based warping normalization over that of a leading volumetric normalization procedure.

C. Analysis of Functional Brain Activation

The proposed spatial normalization approach aims to improve the alignment of anatomical features, which should also improve the alignment of function for gross tasks involving vision and speech in the major sulci. To test this hypothesis, in this section we demonstrate a potential use of our spatial normalization algorithm in functional imaging applications by analyzing functional images of regional cerebral blood flow using positron emission tomography (PET-rCBF) from older adults in the neuroimaging substudy of the BLSA [45].

For each neuroimaging session, three PET scans were performed during a rest state with ears and eyes unoccluded, a verbal delayed recognition memory task, and a figural delayed recognition memory task. For each scan, 75mCi of [^{15}O] water were injected as a bolus, and scans were acquired on a GE 4096+ scanner (resolution = 6 mm FWHM). The activation intensity range is [0,511]. Each PET image was preprocessed to compensate for the variability in global flow and aligned with the structural MRI following the processing steps described in [72]. Then the rCBF values were mapped onto the central cortical surface mesh nodes by integrating the rCBF values over a curvilinear line bounded by the gray matter tissue thickness at this point. The rCBF data on the central cortical surface was smoothed using the intrinsic isotropic diffusion operator in (12).

A sample cross-section from PET-rCBF image during the rest state after alignment with corresponding MRI data is shown in Fig. 16(a). The same PET-rCBF data after the smoothing mapped on the central cortical surface and right hemispherical map are shown in Figs. 16(b) and 16(c), respectively. Because of the limited field of view, the PET-rCBF image does not include the top of the brain, therefore the top part of the cortical surface appears blue with activity value 0.

To quantify the improvement in functional alignment, we estimated the mutual information before and after the GDOF-warping on the hemispherical map surfaces. Mutual information is widely used in the medical image registration techniques [73], [74] to measure the amount of information that is in common between two random variables. The PET-rCBF activation values mapped onto the surfaces are quantized into 256 levels. The probability that the activation level x occurs in brain X , $p_X(x)$, is estimated as $N(x)/\sum_i N(i)$, where $N(i)$ is the total surface area on the given hemispherical map with activation level $i \in [0, 255]$. The joint probabilities, $P_{XY}(x, y)$, are estimated in a similar fashion.

The joint probability distribution of a reference brain's and a subject brain's PET-rCBF activations before and after the GDOF-warping are shown in Fig. 17. We observe a subtle decrease in the spread of the joint probability distribution, and the peak values are larger after the GDOF-warping as well. Averaged over 32 subjects, we observe a 45% increase in the mutual information metric of PET-rCBF activation during rest. The improvement on the mutual information metric is 50% for PET-rCBF activation during the verbal and figural memory tasks. Therefore, we conclude that the proposed spatial normalization method improves the alignment of function as well.

V. Summary and Discussion

In this paper, we have described a spatial normalization method for cortical surfaces based on a geometry-driven optical flow warping technique. We analyzed the geometry of the cortical surface using two shape measures. The shape measures complement each other in defining the shape and the size of the local surface foldings while successfully distinguishing the sulcus/gyrus-like structures on the surface representation. These shape measures give an implicit representation of the anatomical features. Therefore, matching shape measures of individual brains on an unfolded cortex's coordinate system (i.e., the

hemispherical map coordinate system) yields a good anatomical alignment. Cortical unfolding is used to put each cortex into a canonical coordinate system. If an alternate cortical unfolding procedure were to be used, then the results would vary to some extent.

Computing the shape measures on the PFCs of the cortex instead of the original central cortical surface representation allows us to develop a warping procedure focused on matching prominent features such as the primary sulci that are common across multiple brains. Use of the multiple PFCs gives a multi-scale scheme which allows alignment of finer anatomical details in addition to dominant features.

A geometry-driven optical flow warping procedure that aims to match the shape measure maps of a reference brain and a subject brain on the unfolded map coordinate system by maximizing a similarity measure is developed. The variational problem to estimate the optical flow field was solved using a Euclidean framework, yielding a fast and stable numerical algorithm with a novel multi-resolution scheme to estimate the flow field vectors. Unlike the methods in [25], [28]–[31], the warping technique based on these shape measure maps does not require manually identified landmarks and does not require strict point correspondences throughout the estimation process. The presented multi-scale scheme improves the surface-based warping techniques (e.g. [43]) in hierarchical alignment of the anatomical details.

Based on comparison of feature alignment before and after the GDOF-warping, spatial normalization with respect to a reference cortical surface, when applied to multiple brains, gives an excellent alignment of major sulcal regions. This was validated quantitatively by computing the probabilistic maps of eight sulcal regions and comparing the maximum and the surface area ratio measures of the probabilistic maps before and after the GDOF-warping. In order to support our claim that the surface-based spatial normalization performs better in matching cortical geometry compared to volumetric spatial normalization, we also examined the alignment of the eight sulcal regions after a volumetric spatial normalization using the HAMMER algorithm. The performance comparison was based on the resulting probabilistic maps using either spatial normalization techniques. For each sulcal region, surface-based spatial normalization yields better statistics on probabilistic maps, compared with those of the volumetric spatial normalization. In addition to testing for alignment of anatomical features, we also examined the alignment of functional data before and after the GDOF-warping and quantify the improvement in functional data alignment by estimating the mutual information between the reference and the subject brains.

In this work, the performance of the proposed spatial normalization algorithm was tested on a single BLSA data set, which makes it difficult to assess the performance of the algorithm for additional datasets or different populations. We believe that by controlling the level of detail present at each level of the multi-scale cortical representation via the global shape measure $\|H\|_2$ and by allowing the shape measure weights w_j to adaptively change as GDOF-warping evolves, performance deviations due to the variability of individuals and across populations will be small. We hope to perform additional validation studies assessing the performance of the algorithm across a broader population through collaborations with other research groups.

The methods we develop to automatically analyze the geometry of the cortex in large numbers of subjects and to generate a standard cortical coordinate system via spatial normalization methods are useful in various neuroscience and medical applications. Application areas include generation of surface-based probabilistic brain atlas on structural and functional properties of both normal and diseased brains [2], [8]–[11], [26], automated parcellation and segmentation of cerebral cortex [71], [75], [76], automatic landmark and

correspondence generation to assist deformable cortical registration [15], [19], analysis of morphological changes in healthy aging and disease [77], averaging geometry (i.e., cortical thickness) and function (i.e., PET, fMRI) across population [43], statistical correlation studies of structural and functional relationships [78], [79].

Acknowledgments

The authors would like to thank Dr. Noor Kabani for constructing the atlas of anatomical features, Dr. Maryam E. Rettmann for manually labeling the sulcal regions, and Dr. Susan M. Resnick for her assistance in processing and analyzing the PET images. This work was supported by the NIH/NINDS under grant R01NS37747.

References

1. Mazziotta JC, Pelizzari CC, Chen GT, Bookstein FL, Valention D. Region of interest issues: the relationship between structure and function in the brain. *Journal of Cerebral Blood Flow and Metabolism*. 1991; 11(A):51–56.
2. Roland PE, Zilles K. Brain atlases — a new research tool. *Trends in Neurosciences*. 1994; 17:458–467. [PubMed: 7531886]
3. Fox PT, Lancaster JL. Mapping context and content: The brainmap model. *Nature Reviews/Neuroscience*. 2002; 3:319–321.
4. Bjaalie JG. Localization in the brain: New solutions emerging. *Nature Reviews/Neuroscience*. 2002; 3:322–325.
5. Kikinis R, Shenton ME, Iosifescu DV, McCarley RW, Saiviroonporn P, Hokama HH, Robatino A, Metcalf D, Wible CG, Portas CM, Donnino R, Jolesz FA. A digital brain atlas for surgical planning, model driven segmentation and teaching. *IEEE Trans Visualization and Computer Graphics*. 1996; 2(3):232–241.
6. Taylor, RH.; Lavalley, S.; Burdea, GC.; Mosges, R. *Computer-Integrated Surgery: Technology and Clinical Applications*. Cambridge, MA: MIT Press; 1996.
7. Fischl B, Liu AK, Dale AM. Automated manifold surgery: Constructing geometrically accurate and topologically correct models of the human cerebral cortex. *IEEE Trans Medical Imaging*. 2001; 20(1):70–80.
8. Evans, AC.; Kamber, M.; Collins, DL.; MacDonald, D. *An MRI-based probabilistic atlas of neuroanatomy*. Shorvon, SD., et al., editors. New York: Plenum Press; 1994.
9. Mazziotta JC, Toga AW, Evans A, Fox P, Lancaster J. A probabilistic atlas of the human brain: Theory and rationale for its development. *NeuroImage*. 1995; 2:89–101. [PubMed: 9343592]
10. Thompson, PM.; Mega, MS.; Narr, KL.; Sowell, ER.; Blanton, RE.; Toga, AW. *Handbook of Medical Imaging*. Bellingham, WA: SPIE Press; 2000. Brain image analysis and atlas construction; p. 1061-1129.
11. Mazziotta JC, Toga AW, Evans A, Fox P, Lancaster J, Zilles K, Simpson G, Woods R, Paus T, Pike B, Holmes C, Collins L, Thompson P, MacDonald D, Schormann T, Amunts K, Palomero-Gallagher N, Parsons L, Narr K, Kabani N, LeGoualher G, Boomsma D, Cannon T, Kawashima R, Mazoyer B. A probabilistic atlas and reference system for the human brain: International consortium for brain mapping (ICBM). *Philos Trans R Soc Lond B Biol Sci*. 2001; 356:1293–322. [PubMed: 11545704]
12. Talairach, J.; Tournoux, P. *Co-Planar Stereotaxic Atlas of the Human Brain. 3-Dimensional Proportional System: An Approach to Cerebral Imaging*. Stuttgart, New York: Thieme Medical Publisher, Inc; 1988.
13. Christensen GE, Joshi SC, Miller MI. Volumetric transformation of brain anatomy. *IEEE Trans Medical Imaging*. 1997; 16:864–877.
14. Collins, L.; Evans, AC. *Brain warping*. CA, USA: Academic Press; 1999. ANIMAL: Automatic nonlinear image matching and anatomical labeling; p. 133-142.ch. 8
15. Rohr, K.; Fornefett, M.; Stiehl, HS. Approximating thin-plate splines for elastic registration: Integration of landmark errors and orientation attributes. *Proc. of 16th Int'l Conf. on Information Processing in Medical Imaging, IPMI'99*; Visegrad, Hungary. June 1999; p. 252-265.

16. Hellier P, Barillot C, Mmin E, Prez P. Hierarchical estimation of a dense deformation field for 3d robust registration. *IEEE Trans Medical Imaging*. 2001; 20:388–402.
17. Shen D, Davatzikos C. HAMMER: hierarchical attribute matching mechanism for elastic registration. *IEEE Trans Medical Imaging*. 2002; 21:1421–1439.
18. Hellier P, Barillot C. Coupling dense and landmark-based approaches for non rigid registration. *IEEE Trans Medical Imaging*. 2003; 22:217–227.
19. Johnson HJ, Christensen GE. Consistent landmark and intensity-based image registration. *IEEE Trans Medical Imaging*. 2002; 21(5):450–461.
20. Rueckert D, Frangi AF, Schnabel JA. Automatic construction of 3D statistical deformation models of the brain using non-rigid registration. *IEEE Trans Medical Imaging*. 2003; 22(8):1014–1025.
21. Kabani N, MacDonald D, Holmes C, Evans A. 3D atlas of the human brain. *NeuroImage*. 1998; 7:S717.
22. Han X, Pham DL, Tosun D, Rettmann ME, Xu C, Prince JL. CRUISE: Cortical reconstruction using implicit surface evolution. *NeuroImage*. 2004; 23(3):997–1012. [PubMed: 15528100]
23. Essen, DCV.; Drury, HA.; Joshi, S.; Miller, MI. Functional and structural mapping of human cerebral cortex: Solutions are in the surfaces. *Proceedings of the National Academy of Sciences; Irvine, CA, USA*. 1998. p. 1-8.
24. Dale AM, Fischl B, Sereno MI. Cortical surface-based analysis I: Segmentation and surface reconstruction. *NeuroImage*. 1999; 9(2):179–194. [PubMed: 9931268]
25. MacDonald D, Kabani N, Avis D, Evans A. Automated 3D extraction of inner and outer surfaces of cerebral cortex from MRI. *NeuroImage*. 2000; 12(3):340–356. [PubMed: 10944416]
26. Thompson, PM.; Woods, RP.; Mega, MS.; Toga, AW. Mathematical/computational challenges in creating deformable and probabilistic atlases of the human brain. *Proc. of 6th Int'l Conf. on Functional Mapping of the Human Brain; San Antonio, Texas, USA: Academic Press; 2000*. p. 81-92.
27. Schwartz EL, Shaw A, Wolfson E. A numerical solution to the generalized mapmaker' problem: Flattening nonconvex polyhedral surfaces. *IEEE Trans Pattern Analysis and Machine Intelligence*. 1989; 11(9):1005–1008.
28. Thompson PM, Toga AW. A surface-based technique for warping three-dimensional images of the brain. *IEEE Trans Medical Imaging*. 1996; 15:402–417.
29. Essen DCV, Drury HA. Structural and functional analyses of human cerebral cortex using a surface-based atlas. *Journal of Neuroscience*. 1997; 17(18):7079–7102. [PubMed: 9278543]
30. Fischl B, Sereno MI, Dale AM. Cortical surface-based analysis II: Inflation, flattening, and a surface-based coordinate system. *NeuroImage*. Feb; 1999 9(2):195–207. [PubMed: 9931269]
31. Gu X, Wang Y, Chan TF, Thompson PM, Yau ST. Genus zero surface conformal mapping and its application to brain surface mapping. *IEEE Trans Medical Imaging*. Aug.2004 23:949–958.
32. Tosun, D.; Rettmann, ME.; Prince, JL. Mapping techniques for aligning sulci across multiple brains. In: Ellis, R.; Petters, T., editors. *Medical Image Analysis - Special issue: Medical Image Computing and Computer-Assisted Intervention -MICCAI 2003*. Vol. 8. 2004. p. 295-309.
33. Drury HA, Essen DCV, Anderson CH, Lee WC, Coogan TA, Lewis JW. Computerized mapping of the cerebral cortex: A multiresolution flattening method and a surface-based coordinate system. *J Cognitive Neuroscience*. 1996; 8(1):1–28.
34. Sereno MI, Dale AM, Liu A, Tootell RBH. A surface-based coordinate system for a canonical cortex. *Proc 2nd Int Conf Hum Brain Mapping, NeuroImage*. 1996; 3(3):S252.
35. Wandell B, Engel S, Hel-Or H. Creating images of the flattened cortical sheet. *Invest Opth and Vis Sci*. 1996; 36:S612.
36. Timsari B, Leahy R. Optimization method for creating semi-isometric flat maps of the cerebral cortex. *Proc SPIE Conf Med Imag*. 2000:698–708.
37. Angenent S, Haker S, Tannenbaum A, Kikinis R. On the Laplace-Beltrami operator and brain surface flattening. *IEEE Trans Medical Imaging*. 1999; 18(8):700–711.
38. Hurdal MK, Stephenson K, Bowers P, Sumners DW, Rottenberg DA. Coordinate systems for conformal cerebellar flat maps. *NeuroImage*. 2000; 11(5):S467.

39. Tosun, D.; Prince, J.L. Proc of SPIE Medical Imaging. Vol. 4322. SPIE Press; Bellingham, WA: Feb. 2001 Hemispherical map for the human brain cortex; p. 290-300.
40. Ju, L.; Stern, J.; Rehm, K.; Schaper, K.; Rottenberg, DA.; Hurdal, MK. Cortical surface flattening using least square conformal mapping with minimal metric distortion. Proceedings of the 2004 IEEE International Symposium on Biomedical Imaging: From Nano to Macro; Arlington, VA, USA. IEEE. April 2004; p. 77-80.
41. Pons, J-P.; Keriven, R.; Faugeras, OD. Area preserving cortex unfolding. In: Barillot, C.; Haynor, DR.; Hellier, P., editors. Proc of 7th Int'l Conf on Medical Image Computing and Computer-Assisted Intervention, MICCAI'04, ser Lecture Notes in Computer Science. Vol. 3216. Saint-Malo, France: Springer; Sep. 2004 p. 376-383.
42. Wang, YL.; Lui, LM.; Chan, TF.; Thompson, PM. Optimization of brain conformal mapping using landmarks. Proc. of 8th Int'l Conf. on Medical Image Computing and Computer-Assisted Intervention, MICCAI'05; 2005. p. 675-683.
43. Fischl B, Sereno MI, Tootell RB, Dale AM. High-resolution intersubject averaging and a coordinate system for the cortical surface. *Human Brain Mapping*. 1999; 8(4):272–284. [PubMed: 10619420]
44. Tosun D, Rettmann ME, Resnick SM, Pham DL, Prince JL. Cortical reconstruction using implicit surface evolution: Accuracy and precision analysis. *NeuroImage*. 2005
45. Resnick SM, Goldszal AF, Davatzikos C, Golski S, Kraut MA, Metter EJ, Bryan RN, Zonderman AB. One-year age changes in MRI brain volumes in older adults. *Cerebral Cortex*. May; 2000 10(5):464–72. [PubMed: 10847596]
46. Goldszal AF, Davatzikos C, Pham DL, Yan MXH, Bryan RN, Resnick SM. An image processing system for qualitative and quantitative volumetric analysis of brain images. *J Computer Assisted Tomography*. 1998; 22(5):827–837.
47. Pham DL, Prince JL. Adaptive fuzzy segmentation of magnetic resonance images. *IEEE Trans Medical Imaging*. 1999; 18(9):737–752.
48. Pham, DL. Robust fuzzy segmentation of magnetic resonance images. Proceedings of the Fourteenth IEEE Symposium on Computer-Based Medical Systems (CBMS2001); IEEE Press, Somerset, NJ. 2001. p. 127-131.
49. Han, X.; Xu, C.; Rettmann, ME.; Prince, JL. Automatic segmentation editing for cortical surface reconstruction. Proc. of SPIE Medical Imaging; SPIE Press, Bellingham, WA. Feb 2001; p. 194-203.
50. Xu, C.; Han, X.; Prince, JL. Improving cortical surface reconstruction accuracy using an anatomically consistent gray matter representation. Proc. of 6th International Conference on Functional Mapping of the Human Brain; Academic Press, San Diego, CA. June 2000; p. S581
51. Han X, Xu C, Braga-Neto U, Prince JL. Topology correction in brain cortex segmentation using a multiscale, graph-based algorithm. *IEEE Trans Medical Imaging*. 2002; 21:109–121.
52. Han X, Xu C, Prince JL. A topology preserving level set method for geometric deformable models. *IEEE Trans Pattern Analysis and Machine Intelligence*. 2003; 25:755–768.
53. Xu C, Prince JL. Snakes, shapes, and gradient vector flow. *IEEE Trans Image Processing*. Mar; 1998 7(3):359–369.
54. Koenderink JJ, van Doorn AJ. Surface shape and curvature scales. *Image and Vision Computing*. 1992; 10(8):557–565.
55. Carmo, MPD. Differential Geometry of Curves and Surfaces. Prentice Hall College Div; 1976.
56. Welker, W. Why does cerebral cortex fissure and fold? a review of determinants of gyri and sulci. In: Jones, EG.; Peters, A., editors. *Cerebral cortex*. Vol. 8b. New York: Plenum Press; 1990. p. 3-136.
57. Ono, M.; Kubick, S.; Abernathey, CD. Atlas of the cerebral sulci. New York: Thieme; 1990.
58. Zilles K, Schleicher A, Langermann C, Amunts K, Morosan P, Palomero-Gallagher N, Schormann T, Mohlberg H, Burger U, Steinmetz H, Schlaug G, Roland PE. Quantitative analysis of sulci in the human cerebral cortex: development, regional heterogeneity, gender difference, asymmetry, intersubject variability and cortical architecture. *Human Brain Mapping*. 1997; 5:218–221. [PubMed: 20408218]

59. Beatty, J. The Human Brain: Essentials of Behavioral Neuroscience. Thousand Oaks, California: Sage Publications, Inc; 2001.
60. Garel C, Chantrel E, Brisse H, Elmaleh M, Monique L, Dominique JFO, Sebag G, Hassan M. Fetal cerebral cortex: Normal gestational landmarks identified using prenatal MR imaging. *Am J Neuroradiol*. 2001; 22:184–189. [PubMed: 11158907]
61. Willmore TJ. Note on embedded surfaces. *An Sti Univ Al I Cuza Iasi, Sect Ia Mat*. 1965; 11B: 493–496.
62. White JH. A global invariant of conformal mappings in space. *Proc Amer Math Soc*. 1973; 38:162164.
63. Rettmann ME, Han X, Xu C, Prince JL. Automated sulcal segmentation using watersheds on the cortical surface. *NeuroImage*. Feb.2002 15:329–344. [PubMed: 11798269]
64. Tao, X. PhD dissertation. Johns Hopkins University; Baltimore, MD, 21218, USA: January 2005. Statistical geodesics and shape models: Finding features for registering human cortical surface.
65. Song SM, Leahy RM. Computation of 3-D velocity fields from 3-D cine CT images of a human heart. *IEEE Trans Medical Imaging*. 1991; 10(3):295–306.
66. Bertalmio M, Cheng LT, Osher S, Sapiro G. Variational problems and partial differential equations on implicit surfaces: The framework and examples in image processing and pattern formation. *J Computational Physics*. 2001; 174(2):759–780.
67. Christensen GE, Rabbitt RD, Miller MI. Deformable anatomical templates using large deformation kinematics. *IEEE Trans Medical Imaging*. 1996; 5(10):1435–1447.
68. Joshi SC, Miller MI. Landmark matching via large deformation diffeomorphisms. *IEEE Trans Image Processing*. Aug.2000 9:1357–1370.
69. Foskey M, Davis B, Goyal L, Chang S, Chaney E, Strehl N, Tomei S, Rosenman J, Joshi S. Large deformation three-dimensional image registration in image-guided radiation therapy. *Phys Med Biol*. 2005:5869–5892. [PubMed: 16333161]
70. Black MJ, Sapiro G, Marimont DH, Heeger D. Robust anisotropic diffusion. *IEEE Trans Image Processing*. 1998; 7(3):421–432.
71. Rettmann, ME. PhD dissertation. Johns Hopkins University; Baltimore, MD, 21218, USA: March 2003. Analysis of regional cortical geometry using automated sulcal segmentation from a surface model of the human cerebral cortex.
72. Beason-Held LL, Golski S, Kraut MA, Esposito G, Resnick SM. Brain activation during encoding and recognition of verbal and figural information in older adults. *Neurobiol Aging*. 2005; 26(2): 237–250. [PubMed: 15582751]
73. Wells W, Viola P, Atsumi H, Nakajima S, Kikinis R. Multimodal volume registration by maximization of mutual information. *IEEE Trans Medical Imaging*. 1996; 1:35–51.
74. Maes F, Collignon A, Vandermeulen D, Marchal G, Suetens P. Multimodality image registration by maximization of mutual information. *IEEE Trans Medical Imaging*. 1997; 16:187–198.
75. Fischl B, van der Kouwe A, Destrieux C, Halgren E, Segonne F, Salat DH, Busa E, Seidman LJ, Goldstein j, Kennedy D, Caviness V, Makris N, Rosen B, Dale AM. Automatically parcellating the human cerebral cortex. *Cerebral Cortex*. 2004; 14:11–22. [PubMed: 14654453]
76. Makris N, Schlerf JE, Hodge SM, Haselgrove C, Albaugh MD, Seidman LJ, Rauch SL, Harris G, Biederman J, Caviness VS, Kennedy DN, Schmahrman JD. MRI-based surface-assited parcellation of human cerebellar cortex: an automatically specified method with estimate of reliability. *NeuroImage*. 2005; 25(4):1146–1160. [PubMed: 15850732]
77. Blatter D, Bigler E, Gale S, Johnson S, Anderson C, Burnett B, Parker N, Kurth S, Horn S. Quantitative volumetric analysis of brain MR: normative database spanning 5 decades of life. *Am J Neuroradiol*. 1995; 16:241–251. [PubMed: 7726068]
78. Walters NB, Egan GF, Kril JJ, Kean M, Jenkinson WPM, Watson JD. In vivo identification of human cortical areas using high-resolution MRI: An approach to cerebral structure-function correlation. *Physiology*. 2003; 100(5):2981–2986.
79. Haier RJ, Jung RE, Yeo RA, Head K, Alkire MT. Structural brain variation and general intelligence. *NeuroImage*. 2004; 23:425–433. [PubMed: 15325390]

Fig. 1.

An axial cross-section of (a) the MRI volume and (b) the gyral labels of atlas brain with the central cortical surface superposed; and (c) the gyral labels on the atlas's cortical surface. After volumetric normalization using the HAMMER registration algorithm [17], the gyral labels on (d) the subject's image space and on (e) the subject's cortical surface; and (f) the gyral labels on the subject's cortical surface after the surface-based spatial normalization presented in this paper.

Fig. 2. Cortical Surface Reconstruction

Axial cross-section of (a) T1-weighted MR image, (b) resulting cerebral volume, (c) WM membership after editing for the ventricles and subcortical GM structures, (d) enhanced GM membership; top view of (e) WM/GM cortical surface and (f) the central cortical surface.

Fig. 3. Cortical Unfolding

(a) Hemispherical cut path colored by red on the central cortical surface with the north pole point marked by yellow (left cortical hemisphere in blue and right cortical hemisphere in green), (b) the initial conformal flattening onto the complex plane, (c) flat map of right cortex after the area distortion minimization, and (d) the right hemispherical map.

Fig. 4. Block diagram of the described spatial normalization algorithm: Geometry-driven optical flow warping.

Fig. 5.

Geometry-driven feature matching: Find the best coordinate system transformation $\mathbf{u}(\cdot): \mathbb{R}^3 \rightarrow \mathbb{R}^3$ that associates point $\mathbf{x} \in \mathbb{S}^2$ of $\mathcal{S}$ to a corresponding point $\mathbf{x} + \mathbf{u}(\mathbf{x}) \in \mathbb{S}^2$ on $\mathcal{R}$ so that the subject's and reference's geometric features match each other.

Fig. 6. Shape index and curvedness measures complement each other in defining local surface shape and size. The (a) SI and (b) C measures of three similar objects show that correct homology can be established using these measures.

Fig. 7.

(a) A sample central cortical surface and its partially flattened representations at levels (b) $\gamma = 30$, (c) $\gamma = 20$, and (d) $\gamma = 10$.

Fig. 8.
 (a) Segmented sulcal regions versus the shape index measure. (b) Sulcal fundal tracks versus the curvedness measure.

Fig. 9.

Eulerian framework to solve a PDE on the sphere: (a) A sample 2-D slice from the 3-D implicit representation of the sphere surface with the surface contour at Ω_0 (b) The shape index measure map on $\mathbb{S}^2$ extended to the entire 3-D Euclidean space; (c) A novel multi-resolution scheme by increasing the radius (R) of sphere.

Fig. 10.

GDOF field vectors (down-sampled for display purposes) at different levels of multi-resolution scheme — i.e., left-to-right: $R = 5$, $R = 20$, and $R = 35$. Contours: The boundary of the central sulcus region of the reference brain (in magenta) and of the subject brain initially and after the warping at the current level (in yellow and cyan, respectively).

Fig. 11.
The location of the sulcal regions labeled on the lateral surface and the medial surface illustrated on a sample cortex.

Fig. 12. Probabilistic maps of four sulcal regions on the right cortical hemisphere (a)–(b) before and (c)–(d) after the GDOF-warping.

Fig. 13.

The surface area ratio measure after each level of multi-resolution scheme. (S1, S2, S3, and S4 single-scale case with $\gamma_1 = 30$, $\gamma_1 = 25$, $\gamma_1 = 20$, and $\gamma_1 = 15$, respectively; All4S multi-scale case.)

Fig. 14. Cross-sectional views for a sample brain showing volumetric sulcal labels superimposed to its skull-stripped MR image.

Fig. 15.
Volumetric probabilistic maps of four sulcal regions on the right cortical hemisphere after HAMMER warping.

Fig. 16. PET-rCBF during the rest state (a) a sample cross-section aligned with the MRI data; Smoothed PET-rCBF mapped to (b) central cortical surface and (c) the right hemispherical map.

Fig. 17.
Joint probability distribution of PET-CBF activation before and after the GDOF-warping.

TABLE I

GDOF-Warping Algorithm Parameters

Parameter	Section	Value	Multi-resolution update
γ Global shape measure	III.B	$\gamma_1 = 30, \gamma_2 = 25, \gamma_3 = 20, \gamma_4 = 15$	
S Number of shape scales	III.B	4	Constant
w_i Weight of the i^{th} shape measure	III.C	Dynamically updated	(11) and (12)
α Smoothness constraint coefficient (5)	III.C	Function of E and ν (14)	Linearly decrease
β Incompressibility constraint coefficient (5)	III.C	Function of E and ν (13)	Linearly decrease
ρ A robust error measure	III.C	Lorentzian measure	
M Levels in the multi-resolution scheme	III.E	7	
R Radius of the sphere	III.D	$R_1 = 5$ and $R_7 = 35$	Linearly increased
E Young's elasticity modulus	IV	$E_1 = 40$ and $E_7 = 20$	Linearly decreased
ν Poisson ratio	IV	0.2	Constant

TABLE II

Statistics on the probabilistic maps before and after the geometry-driven optical flow warping.

	P_{les}	P_{lsf}	P_{len}	P_{lpo}	P_{res}	P_{rsf}	P_{ren}	P_{rpo}
Before the geometry-driven optical flow warping								
max	1.00	0.74	0.74	0.95	0.89	0.74	0.84	0.94
surf. area ratio ($p = 0.7$)	0.30	0.09	0.12	0.23	0.26	0.11	0.12	0.24
surf. area ratio ($p = 0.5$)	0.42	0.27	0.28	0.37	0.42	0.23	0.28	0.37
After the geometry-driven optical flow warping								
max	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
surf. area ratio ($p = 0.7$)	0.58	0.25	0.19	0.42	0.58	0.22	0.23	0.31
surf. area ratio ($p = 0.5$)	0.63	0.42	0.30	0.50	0.68	0.29	0.35	0.51

TABLE III

Statistics on the volumetric probabilistic maps generated using HAMMER warping and GDOF-warping.

	P_{lcs}^v	P_{lsf}^v	P_{lcn}^v	P_{lpo}^v	P_{rcs}^v	P_{rsf}^v	P_{rcn}^v	P_{rpo}^v
Using HAMMER warping								
max	0.94	0.83	0.94	0.91	0.91	0.88	0.94	0.91
volume ratio	0.22	0.14	0.20	0.20	0.21	0.16	0.20	0.22
Using GDOF warping								
max	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
volume ratio	0.58	0.39	0.24	0.54	0.67	0.38	0.34	0.52