Published in final edited form as:

J Chem Eng Data. 2007 January 1; 52(1): 235–238. doi:10.1021/je060358w.

Solubility of the sesquiterpene alcohol patchoulol in supercritical carbon dioxide

Brooks M. Hybertson, Ph.D.

Webb-Waring Institute for Cancer, Aging, and Antioxidant Research and the University of Colorado School of Medicine, 4200 East Ninth Ave., Denver, CO 80262, USA

Abstract

The solubility of the sesquiterpene alcohol patchoulol in supercritical carbon dioxide was measured at P ranging from 10.0 MPa to 25.0 MPa and T of 40.0 and 50.0 °C using a simple microsampling type apparatus with a 100.5 μ L sample loop to remove aliquots for off-line analysis. The system was first validated using vanillin with off-line spectrophotometric analysis, then utilized for patchoulol measurements with off-line GC-MS analysis. The measured solubility of patchoulol in supercritical CO₂ ranged from mole fractions of 0.43×10^{-3} at 10.0 MPa and 50.0 °C to 9.45×10^{-3} at 25.0 MPa and 40.0 °C.

Introduction

The sesquiterpene patchoulol (patchouli alcohol, CAS Registry Number 5986-55-0) is a white, crystalline solid at room temperature that was first isolated and described in 1869.¹ The chemical structure of patchoulol is shown in Figure 1. The tricyclo[5.3.1.0]undecane carbon skeleton of patchoulol is somewhat unusual, and has made its chemical synthesis the subject of study by several groups over the years.^{1–6} Patchoulol typically represents 30 % to 40 % of the total mass of the dozens of compounds in patchouli oil, an essential oil commonly obtained by steam distillation of the leaves of *Pogostemon cablin* (Benth.) which is used extensively in the perfume and fragrance industry.⁷ In fact, *Pogostemon cablin* has been cultivated for patchouli oil production for over 100 years.

It has long been held that patchouli oil possesses favorable perfume, antifungal, antidepressant, and insect repellent properties,^{8–10} especially in Asian countries and India. For example, the essential oil has historically been used to repel moths from clothing. Patchouli oil and its individual components, including patchoulol, are contributors to traditional Chinese medicines which are currently being examined for use as fungicides and for the inhibition of fungal infections.¹¹ Recently, Zhu, et al., reported that both patchouli oil, and purified patchoulol itself, were toxic and repellent against Formosan subterranean termites, with topical patchoulol noted to cause substantial damage to the termite exoskeleton.¹² They concluded that the anti-termite effect of patchouli oil was due to the patchoulol component.

In addition to steam distillation to isolate patchouli oil, Huang, et al., recently found that supercritical carbon dioxide extraction methods could be used to collect a volatile oil from *Pogostemon cablin* which was 48.8 % patchoulol. This work indicates that supercritical fluid extraction processes might be advantageous for the isolation of purified patchoulol, either from natural products or from synthetic mixtures.^{3, 4, 13}

Processes using supercritical fluids are of great research interest for the synthesis, extraction, analysis, and comminution of materials, and some commercial application have arisen from these studies.^{14–17} This interest is due in part to the “green” nature of some supercritical fluids compared to the organic solvents they are proposed to replace, and in part to the tunable nature of the solvent properties of supercritical fluids.^{18, 19} The most widely used supercritical fluid has been carbon dioxide, due to its low cost, availability, reasonably low critical temperature and pressure, low toxicity, and adequate solvent properties for lipophilic solutes. Effective utilization of supercritical carbon dioxide for extraction or processing is facilitated by measurements of solubilities in supercritical carbon dioxide.^{14, 15, 20, 21} In the present work, a sampling loop method was used to determine the solubility of patchoulol in supercritical carbon dioxide; to the author’s knowledge, these are the only solubility data reported for patchoulol in carbon dioxide.

Experimental Section

Materials

Solid, crystalline patchoulol (CAS 5986-55-0, shown in Figure 1) was a kind gift from International Flavors and Fragrances Inc. (New York, NY). Pure carbon dioxide (Coleman grade, 99.99 %) was obtained from General Air Service & Supply (Denver, CO), vanillin (99.5 %) was obtained from Aldrich Chemical Co. (Milwaukee, WI), absolute ethanol was obtained from Aaper Alcohol and Chemical Co. (Shelbyville, KY), all other chemicals were obtained from Sigma Chemical Co. (St. Louis, MO). The reported purity levels of the vanillin and patchoulol solutes were verified by thin-layer chromatography, and the compounds were used as received.

Experimental apparatus and procedure

A schematic of the experimental apparatus is shown in Fig. 2. It is a microsampling system with a high pressure sample loop and valve system adapted from the system described by McHugh and Paulaitis,²² and is similar to the apparatus used in many previous reports in which the static sampling strategy has been used.^{14, 23} Such systems utilize a sample loop to remove small portions of a saturated supercritical fluid solution for analysis. To test the present system, it was used first to determine the solubility of vanillin in carbon dioxide for comparison to published values and validation of the system,²⁴ and then it was used to determine solubility of patchoulol in carbon dioxide. A high pressure syringe pump (Isco model 260D, Teledyne Isco, Inc., Lincoln, NE) was used to pressurize the carbon dioxide ($P = (10.0 \text{ to } 25.0 \text{ MPa})$, $\pm 0.5 \%$), which was directed through a coil of 1/16” stainless steel tubing as a preheater, contained within a recirculating, temperature-controlled water bath (VWR Scientific Model 1131, West Chester, PA), and then through a 7.5 mL stainless steel extraction vessel as a saturator (Keystone Scientific, Bellefonte, PA) packed with solute (vanillin or patchoulol) and 3 mm glass beads, with glass wool used to trap the solid solute in the center of the vessel. The pressures delivered by the syringe pump at each set point were measured using a mechanical Bourdon tube-type gauge rated at $\pm 0.25 \%$ accuracy (Helicoid Gage, ACCO, Bridgeport, CT), and the precision of the set pressures was verified to be $\pm 0.5 \%$. The fittings on the inlet and outlet of the saturator vessel contained sintered stainless steel frits to act as filters and prevent undissolved solute from being swept into the sample loop. The preheater, saturator, and sampling loop were all contained within the circulating bath and the continuously-circulating water was maintained at a constant temperature ($T = 40.0 \text{ }^{\circ}\text{C}$ or $50.0 \text{ }^{\circ}\text{C}$, calibrated with a Hg thermometer and controlled to within $\pm 0.5 \text{ }^{\circ}\text{C}$). Flow through the saturator was stopped for 1 h at each set temperature and pressure, with pressure maintained from the syringe pump, to give sufficient time to approach saturation conditions.²⁰ Effluent from the saturator was then directed for 1 min at 0.5 mL/min through a nominally $100 \text{ }\mu\text{L}$ sample loop attached to a 6-port, 2-way valve (Rheodyne Model A7000, Rohnert Park, CA, referred to here as valve A) using

an adjustable valve (fill position) and then vented to waste. When filled with saturated solution, the valve was turned to the inject position which allowed to loop to depressurize through a needle valve into a preweighed collection vial outside of the temperature-controlled bath into which 2 mL of ethanol solvent was added to trap the solute, and then the loop was flushed with additional 3 mL of ethanol into the collection vial using an HPLC pump (Waters Model 501, Milford, MA) connected to a second Rheodyne 6-port, 2-way valve (valve B, rinse position), on which only 3 of the ports were utilized. The total amount of ethanol solvent used to collect the solute was determined gravimetrically (± 0.0001 g). Before switching valve A back to the fill position for the next sample collection, valve B was switched (air flush position) and the lines and sample loop were flushed with compressed air to remove ethanol otherwise trapped within, then valve B was switched back to rinse position with flow from the HPLC pump turned off. Multiple samples were collected at each pressure and temperature combination.

Sample loop volume calibration

The volume of the sample loop (100.5 ± 2 μ L) was determined by measuring the amount of dilution of a vanillin solution of known concentration in ethanol. Briefly, the sample loop was loaded by syringe with the standard solution, then directed into a preweighed collection tube using the HPLC pump and ethanol. The amount of dilution was determined spectrophotometrically using a Beckman DU600 spectrophotometer (Fullerton, CA) at 279 nm, a relative absorption maxima for vanillin, and a 1 cm quartz cell. The final volume was determined gravimetrically. For determination of concentrations, a standard curve was prepared for absorption at 279 nm of vanillin solutions of 0.3, 1.5, 3, 15, 30, and 150 μ M in ethanol, and a linear fit was obtained with a correlation coefficient >0.99 . A wavelength scan of one of our vanillin standards in ethanol gave a relative maximum absorbance at 279 nm, in agreement with published data,^{25, 26} and a molar absorptivity on the order of 10^4 L/mol-cm at this wavelength.

Quantitation of carbon dioxide

The carbon dioxide solution densities were estimated to be the same as those for pure carbon dioxide, which has been shown to be accurate for solutions with mole fraction < 1 %.^{23, 27} To verify this approximation, we measured the gas volume of carbon dioxide (± 0.5 mL) discharged from the loop at each pressure and temperature, with and without saturation with patchoulol solute. The gas volumes (ranging from about 20 mL to 65 mL) were identical at each pressure and temperature combination for pure carbon dioxide and for carbon dioxide saturated with patchoulol, supporting the prior assertions, and indicating the validity of using pure carbon dioxide densities to quantitate the solvent. To determine the molar amount of solvent contained within the known loop volume, the carbon dioxide densities at each pressure and temperature used were determined using an equation of state;²⁸ to accomplish this, the online version of software from the US National Institute of Standards and Technology was used (<http://webbook.nist.gov/cgi/fluid.cgi?ID=C124389&Action=Page>) which allows calculations of the density, and other thermophysical properties, of carbon dioxide at specified temperatures and pressures.

Quantitation of solutes

The solute collected in ethanol was quantitated by spectrophotometry (for vanillin) or GC-MS (for patchoulol), and the values presented are the means of 3 or more repetitions. For vanillin, which was used to compare with previous solubility data and verify the currently used apparatus and method, triplicate runs were collected at $T = 45.0$ °C and $P = 10.0, 15.0,$ and 20.0 MPa, and the collected samples were first diluted 1:20 with additional ethanol and then analyzed by spectrophotometry at 279 nm with a 1 cm quartz cell, and quantitated by comparison to a standard curve made using vanillin and ethanol at dilutions of 0.3 μ M to 150 μ M as described

above. Patchoulol samples were collected at $T = 40.0\text{ }^{\circ}\text{C}$ and $50.0\text{ }^{\circ}\text{C}$ and $P = 10.0, 15.0, 20.0$, and 25.0 MPa , and the resultant ethanol solutions were analyzed by GC-MS. A wavelength scan of a patchoulol standard in ethanol gave a relative maximum absorbance at 309 nm , but the solution was nearly transparent, with a molar absorptivity of only about 1.5 L/mol cm at this wavelength. A GC-MS method was therefore adapted from previous work by Zhu, et al.¹² In the present work, the collected samples were pure patchoulol of unknown concentrations in ethanol, meaning that the quantitation of patchoulol did not require separation from a complex mixture, so the chromatography was greatly simplified compared to previous reports.^{11, 13} Briefly, patchoulol was resolved on a 30 m DB-23 column, $0.25\text{ }\mu\text{m}$ film thickness, using pulsed splitless injection of $1\text{ }\mu\text{L}$ aliquots using an Agilent 6890 GC-MS with autosampler. The inlet temperature was $250\text{ }^{\circ}\text{C}$, the pulse pressure was 32 psi for 0.5 min , then the run pressure was 19.58 psi . The column temperature started at $150\text{ }^{\circ}\text{C}$ and was increased at $30\text{ }^{\circ}\text{C/min}$ to a maximum of $250\text{ }^{\circ}\text{C}$. The retention time of patchoulol under these conditions was approximately 2.7 min , and the peak shape was narrow and symmetrical. For detection, chemical ionization (CI) mode was used, with a solvent delay of 2.05 min . The $[\text{M-OH}]^{+}$ ion was abundantly formed by CI, so this m/z value (205.1) was monitored for detection. To verify the results, the $[\text{M-H}]^{+}$ ion at $m/z = 221.1$ was also monitored. External standards of patchoulol in ethanol from $6.25\text{ }\mu\text{M}$ to 6.25 mM were used to generate a linear standard curve ($r^2 = 1.00$) which was used to quantitate the patchoulol concentrations in the samples.

Results and Discussion

To validate the solubility measurement system used for the present study, the solubilities of vanillin in supercritical CO_2 were first determined experimentally using the microsampling apparatus, and the data was compared to previously published results. As shown in Figure 3, the solubilities of vanillin at $T = 45.0\text{ }^{\circ}\text{C}$ and $P = 10.0, 15.0$, and 20.0 MPa determined using our system are in close agreement with the data from Wells, et al.²⁴ and to the data in recent work by Skerget, et al. (data not shown).²⁹ This indicates that the apparatus used in the present study is appropriate for supercritical CO_2 solubility determinations of patchoulol, which like vanillin is a lipophilic, crystalline solid.

The solubilities of patchoulol in supercritical CO_2 are presented in Table I and Figure 4. The solubility of patchoulol in supercritical CO_2 ranged from mole fractions (y) of 0.43×10^{-3} at 10.0 MPa and $50.0\text{ }^{\circ}\text{C}$ to 9.4×10^{-3} at 25.0 MPa and $40.0\text{ }^{\circ}\text{C}$. As shown in Figure 4, the mole fraction (y) of patchoulol in supercritical CO_2 increased with increasing pressure at constant temperature, and decreased with increasing temperature at constant pressure. Each point is the average of three measurements $\pm$ the standard error of the mean (SEM). The variability of the solubility data was presented as the SEM to indicate how well the determined mean solubility value represents the actual solubility at those conditions. Potential sources of experimental uncertainty in the solubility measurements include possible deposition of solid patchoulol within the decompression region between the sampling loop and the collection vial, and possible loss of post-expansion patchoulol particulates that could have blown through the ethanol solvent in the collection vial.

Conclusions

The solubilities of patchoulol in supercritical CO_2 were determined at $40.0\text{ }^{\circ}\text{C}$ and $50.0\text{ }^{\circ}\text{C}$ in the pressure range of (10.0 to 25.0) MPa . The observed solubilities ranged from mole fractions (y) of $(0.43 \times 10^{-3} \pm 0.01 \times 10^{-3})$ to $(9.4 \times 10^{-3} \pm 1.3 \times 10^{-3})$. Under these experimental conditions, the patchoulol solute was a crystalline solid and the mole fraction in supercritical CO_2 increased with increases in pressure at constant temperature, and decreased with increases in temperature at constant pressure. The results support the idea that supercritical carbon

dioxide may be useful for the processing of patchouli oil and the preparation of purified patchoulol.

Acknowledgments

Grateful acknowledgment is given for the use of the Mass Spectrometry Core Laboratory of the University of Colorado's Clinical Nutrition Research Unit and for the expert assistance of Michael Armstrong and Uwe Christians, MD, PhD.

Financial Support

This work was supported in part by grants from the NIH (CA112652, AI061722), the Cancer League of Colorado, Newborn Hope, and the Cancer Research and Prevention Foundation.

Literature Cited

1. Magee TV, Stork G, Fludzinski P. A total synthesis of rac-patchouli alcohol. *Tetrahedron Lett* 1995;36:7607–7610.
2. Buchi G, Erickson RE, Terpenes V. The structure of patchouly alcohol. *Journal of the American Chemical Society* 1956;78:1262–1263.
3. Buchi G, MacLeod W Jr. Synthesis of patchouli alcohol. *Journal of the American Chemical Society* 1962;84:3205–3206.
4. Kaliappan KP, Subba Rao GSR. Synthesis based in cyclohexadienes. Part 22. Formal syntheses of patchouli alcohol and norpatchoulol. *Journal of the Chemical Society, Perkin Transactions 1: Organic and Bio-Organic Chemistry* 1997;9:1385–1389.
5. Kraft P, Weymuth C, Nussbaumer C. Total Synthesis and Olfactory Evaluation of (1*R**,3*S**,6*S**,7*S**,8*S**)- 3-Hydroxy-6,8-dimethyltricyclo[5.3.1.0^{3,8}]undecan-2-one: A New Synthetic Route to the Patchoulol Skeleton. *European Journal of Organic Chemistry* 2006;2006(6):1403–1412.
6. Srikrishna A, Satyanarayana G. An enantiospecific total synthesis of (–)-patchouli alcohol. *Tetrahedron: Asymmetry* 2005;16:3992–3997.
7. Bruneton, J. *Pharmacognosy, Phytochemistry, Medicinal Plants*. Vol. 2nd ed. Lavoisier Publishing: Paris; 1999.
8. Aleu J, Hanson JR, Galan RH, Collado IG. Biotransformation of the fungistatic sesquiterpenoid patchoulol by *Botrytis cinerea*. *J Nat Prod* 1999;62(3):437–440. [PubMed: 10096853]
9. Aleu J, Hanson JR, Hernandez Galan R, Collado IG. Biotransformation of the fungistatic sesquiterpenoids patchoulol, ginsenosol, cedrol and globulol by *Botrytis cinerea*. *Journal of Molecular Catalysis B: Enzymatic* 2001;11(4–36):329–334.
10. Trongtokit Y, Rongsriyam Y, Komalamisra N, Apiwathnasorn C. Comparative repellency of 38 essential oils against mosquito bites. *Phytother Res* 2005;19(4):303–309. [PubMed: 16041723]
11. Wu J, Lu X, Tang W, Kong H, Zhou S, Xu G. Application of comprehensive two-dimensional gas chromatography-time-of-flight mass spectrometry in the analysis of volatile oil of traditional Chinese medicines. *Journal of Chromatography, A* 2004;1034(1–2):199–205. [PubMed: 15116931]
12. Zhu BCR, Henderson G, Yu Y, Laine RA. Toxicity and Repellency of Patchouli Oil and Patchouli Alcohol against Formosan Subterranean Termites *Coptotermes formosanus* Shiraki (Isoptera: Rhinotermitidae). *Journal of Agricultural and Food Chemistry* 2003;51(16):4585–4588. [PubMed: 14705881]
13. Bure CM, Sellier NM. Analysis of the essential oil of Indonesian patchouli (*Pogostemon cablin* Benth.) using GC/MS (EI/CI). *Journal of Essential Oil Research* 2004;16(1):17–19.
14. Lucien FP, Foster NR. Solubilities of solid mixtures in supercritical carbon dioxide: a review. *Journal of Supercritical Fluids* 2000;17(2):111–134.
15. Reverchon E. Supercritical fluid extraction and fractionation of essential oils and related products. *Journal of Supercritical Fluids* 1997;10(1):1–37.
16. Reverchon E, Caputo G. Fine particle generation techniques using supercritical fluids. *Trends in Chemical Engineering* 2003;8:183–198.

17. Clifford, AA.; Williams, JR. Introduction to supercritical fluids and their applications. In: Williams, JR.; Clifford, AA., editors. *Supercritical Fluid Methods and Protocols*. Totowa, NJ: Humana Press; 2000. p. 1-16.
18. King JW. Critical fluid technology for the processing of lipid-related natural products. *Comptes Rendus Chimie* 2004;7(6-7):647-659.
19. King JW, Williams LL. Utilization of critical fluids in processing semiconductors and their related materials. *Current Opinion in Solid State & Materials Science* 2003;7(4-5):413-424.
20. Burgos-Solorzano GI, Brennecke JF, Stadtherr MA. Solubility measurements and modeling of molecules of biological and pharmaceutical interest with supercritical CO₂. *Fluid Phase Equilibria* 2004;220(1):55-67.
21. Lang Q, Wai CM. Supercritical fluid extraction in herbal and natural product studies - a practical review. *Talanta* 2001;53(4):771-782. [PubMed: 18968166]
22. McHugh M, Paulaitis ME. Solid solubilities of naphthalene and biphenyl in supercritical carbon dioxide. *J. Chem. Eng. Data* 1980;25:326-329.
23. Dobbs JM, Wong JM, Johnston KP. Nonpolar co-solvents for solubility enhancement in supercritical fluid carbon dioxide. *Journal of Chemical and Engineering Data* 1986;31(3):303-308.
24. Wells PA, Chaplin RP, Foster NR. Solubility of phenylacetic acid and vanillin in supercritical carbon dioxide. *Journal of Supercritical Fluids* 1990;3(1):8-14.
25. Ni Y, Zhang G, Kokot S. Simultaneous spectrophotometric determination of maltol, ethyl maltol, vanillin and ethyl vanillin in foods by multivariate calibration and artificial neural networks. *Food Chemistry* 2004;89(3):465-473.
26. CRC handbook of chemistry and physics. Boca Raton, Fla: CRC Press; 1988.
27. Sane A, Taylor S, Sun Y-P, Thies MC. A semicontinuous flow apparatus for measuring the solubility of opaque solids in supercritical solutions. *Journal of Supercritical Fluids* 2004;28(2-3):277-285.
28. Lemmon, EW.; McLinden, MO.; Friend, DG. Thermophysical properties of fluid systems. In: Linstrom, PJ.; Mallard, WG., editors. *NIST Chemistry WebBook, NIST Standard Reference Database Number 69*. Gaithersburg, MD: National Institute of Standards and Technology; 2003.
29. Skerget M, Cretnik L, Knez Z, Skrinjar M. Influence of the aromatic ring substituents on phase equilibria of vanillins in binary systems with CO₂. *Fluid Phase Equilibria* 2005;231(1):11-19.

Figure 1.
Structure of patchoulol (patchouli alcohol).

Figure 2.

Schematic diagram of the apparatus used: (1) CO₂ cylinder with dip tube; (2) syringe pump; (3) thermostated water bath; (4) preheater coil; (5) saturator; (6) off-line sample collection tube; (7) waste collection flask; (8) ethanol reservoir; (9) HPLC pump; (10) pressurized air; (A) six port valve with sample loop; (B) six port valve.

Figure 3. Solubility of vanillin in carbon dioxide at 45.0 °C as mole fraction (y) to validate the microsampling apparatus used in this study against previous results from Wells, et al.²⁴

Figure 4. Solubilities of patchoulol in carbon dioxide at 40.0 and 50.0 °C presented as mole fraction (y), based on the mean of 3 measurements with standard error of the mean shown.

Table 1

Solubility of patchoulol in supercritical CO₂ : temperature T , pressure P , supercritical CO₂ density^a ρ , mole fraction y , and concentration C

$T/^{\circ}\text{C}$	P/MPa	$\rho\text{CO}_2/\text{mol}\cdot\text{L}^{-1}$	$y (\cdot 10^3) \pm \text{SEM}$	$C/\text{g}\cdot\text{L}^{-1} \pm \text{SEM}$
40.0	10.0	14.28	1.8 ± 0.3	5.7 ± 0.9
40.0	15.0	17.73	4.0 ± 0.9	16 ± 4
40.0	20.0	19.08	6.0 ± 1.2	25 ± 5
40.0	25.0	19.98	9.4 ± 1.3	42 ± 6
50.0	10.0	8.73	0.43 ± 0.01	0.84 ± 0.03
50.0	15.0	15.9	3.1 ± 0.1	10.8 ± 0.3
50.0	20.0	17.82	4.8 ± 0.2	18.8 ± 0.7
50.0	25.0	18.96	7.7 ± 0.7	33 ± 3

^aSupercritical carbon dioxide density from NIST Webbook calculation reference.²⁸