Implementation of Medical Information Exchange System Based on EHR Standard

Soon Hwa Han, MS¹, Min Ho Lee, BS¹, Sang Guk Kim, BS¹, Jun Yong Jeong, BS¹, Bi Na Lee, MS¹,
Myeong Seon Choi, MS², Il Kon Kim, PhD³, Woo Sung Park, MD, PhD⁴, Kyooseob Ha, MD, PhD⁵, Eunyoung
Cho, MS⁶, Yoon Kim, MD, PhD⁷, Jae Bong Bae, PhD⁷

¹R&D Center, ezCare Tech Co. Ltd., Seoul; ²R&D Center, UBcare, Seoul; ³IHIS System Development Center, Kyungpook National University, Daegu; ⁴Department of Pediatrics, Dankook University Hospital, Cheonan; ⁵Department of Psychiatry, Seoul National University Bundang Hospital, Seoul National University College of Medicine, Seongnam; ⁶Department of Medical Information Center, Seoul National University Bundang Hospital, Seongnam; ⁷R&D Center for Interoperable EHR, Seoul, Korea

Objectives: To develop effective ways of sharing patients' medical information, we developed a new medical information exchange system (MIES) based on a registry server, which enabled us to exchange different types of data generated by various systems. **Methods:** To assure that patient's medical information can be effectively exchanged under different system environments, we adopted the standardized data transfer methods and terminologies suggested by the Center for Interoperable Electronic Healthcare Record (CIEHR) of Korea in order to guarantee interoperability. Regarding information security, MIES followed the security guidelines suggested by the CIEHR of Korea. This study aimed to develop essential security systems for the implementation of online services, such as encryption of communication, server security, database security, protection against hacking, contents, and network security. **Results:** The registry server managed information exchange as well as the registration information of the clinical document architecture (CDA) documents, and the CDA Transfer Server was used to locate and transmit the proper CDA document from the relevant repository. The CDA viewer showed the CDA documents via connection with the information systems of related hospitals. **Conclusions:** This research chooses transfer items and defines document standards that follow CDA standards, such that exchange of CDA documents between different systems became possible through ebXML. The proposed MIES was designed as an independent central registry server model in order to guarantee the essential security of patients' medical information.

Keywords: Electronic Health Record, VPN, Web Service Security Enhanced, Health Level 7 Standard, CDA R2

Received for review: August 3, 2010

Accepted for publication: December 15, 2010

Corresponding Author

Min Ho Lee, BS
ezCaretech Co. Ltd R&D Center, 125-1 Kwansoo-dong, Jongno-gu,
Seoul 100-420, Korea. Tel: +82-70-7410-4309, Fax: +82-2-3672-
0356, E-mail: jkgroove@gmail.com

1. Introduction

Since now, when a patient is transferred to another hospital, the patient needs to bring his/her own records and submits to the newly assigned doctors [1]. To lessen this inconvenience, data transferring, or data exchanging techniques have been developed. The biggest limitation on this issue is that the records are in various forms by each doctor or each institution. To overcome this barrier, some web-based information sharing systems have been developed in some General Hospitals to communicate with their affiliated clinics to eliminate manual procedures recently. However, these kind of systems are not proper for the nation-wide standard

model but for their affiliated medical facilities [2]. The electronic healthcare record (EHR) is an information system that integrates electronic medical record (EMR) maintained by individual hospitals to effectively exchange histories of patient's treatment record scattered around medical facilities [3].

In terms of improved medical service quality, better accessibility and enhanced safety for patients, EHR provides various benefits. Based on the electronic treatment information and clinical decision support system, EHR can check drug interactions to reduce prescription errors and constantly monitor pharmaceutical side-effects of safe medical services. Moreover, by making individual treatment information available regardless of time and location, EHR can increase patient's right to know, improve the ability to manage diseases, and alleviate the asymmetry between the medical staff and the patient [3]. EHR can also intensify personal information protection by implementing managerial, technical and physical measures against misuse and abuse of patient's treatment information [4].

The primary aim of this research was to build a medical information exchange system (MIES) which made it possible to exchange medical information between various medical information systems of hospitals and also guarantees the interoperability between medical information systems of the participating institutions.

II. Methods

To enhance the reliability and effectiveness of the medical information exchange between different medical institutions, the following factors is considered importantly: well screened items, data transmission methods, standardized

terminologies and security of data and system.

Considering the above issues, this study adopted ebXML as data transmission standard suggested by Center for Interoperable Electronic Healthcare Record (CIEHR) of Korea in order to transmit messages between various systems. Furthermore, in this study, the Web Service technique was adopted to connect EMR systems of each hospital. In addition, the international standard of the clinical document architecture (CDA) R2 was used to enable nationwide transfer of medical records for the information exchange. We implemented the centralized EHR Registry Server which contains information to share. As a result, it enabled users to retrieve and distribute the CDA document from CDA Repository by patient's index.

The EHR Registry Server is the center to store and manage information on hospitals, patient's medical information and their consent to release of their medical records.

1. System Process and Architecture

The MIES developed through this study have been tested by Seoul National University Bundang Hospital (SNUBH) as a general hospital and 33 nearby physician's clinics. Figure 1 shows the delivery process model of referral from a physician's clinic to a general hospital. The physician's clinic sends a referral message to the Registry Server when referring the patient and it will store the CDA document at its CDA Repository. Then it sends referral message to a requested hospital. The requested hospital sends the patient's information to the Registry Server and retrieves the CDA document after checking the registry information. Also referral reply and Information for Request are delivered as reverse way. Figure 1 focuses on system architecture and technical approach of the MIES for medical information exchange process.

Figure 1. Referral process from physician's clinic to general hospital through medical information exchange system (MIES). CDA: clinical document architecture.

Figure 2. Medical information exchange system architecture. EMR: electronic medical record, CDA: clinical document architecture, EHR: electronic health record.

The MIES was designed to exchange CDA documents between designated medical facilities through the CDA Transfer Server with helping of Central Registry Server. The main function of this server is to manage the index information of patients subject to information exchange and facilitate the exchange of CDA documents via the CDA Transfer Server with this index information [5].

The MIES has two servers and needs to be connected to an adaptor. This adaptor plays a role of intermediary to transmit the CDA document and messages. The Registry Server stores the patient's information according to predefined schema and generates the index of patient, and it is used for searching CDA documents. Using the produced index of the patient, the CDA Transfer Server extracts the relevant CDA documents from the CDA Repository of the physician's clinic for transmission. Then, the transmitted data is stored at the repository of the requested hospital (Figure 2).

The MIES is composed of three categories of services: The registry server manages information exchange and the registration information of the CDA documents, and the CDA Transfer Server is used for the registration information,

Figure 3. Service architecture of cal information exchange system (MIES). CDA: clinical document architecture.

locates the proper CDA document from the relevant repository and transmits it [6]. The CDA viewer shows the CDA documents through connection with information systems of hospitals related (Figure 3).

2. Application Methodology of CDA

To share medical information between medical institutions, it is necessary to determine items to be exchanged. The items are defined in 'HL7 CDA' format which is the standard for XML-based CDA exchange. The used version is release 2 version.

As a result, three templates can be generated: Referral Form, Referral Reply, and Information Release Request. In this study, lab test result, medication order and health summary are summed up into an integrated template, and reproduced into a standardized XML format.

A CDA document basically consists of two parts: Header and Body [7]. The former contains patient's personal information and the latter contains medical information.

In this study, the CDA Body was constructed in the Struc-

tured Body type and was written out in the XML format. The Body encompassed items regarding lab test results, medication orders and treatment summaries and was constructed in accordance with the CDA standard, as shown in Figure 4.

We structuralized diagnosis, injection history, and test results. In addition, we adopted 'entry' concept to achieve interoperability between different terms that have same meanings, so that the loss of information is reduced, and the value of information is raised [8]. More details are mentioned in 4.

```

- <component>
- <structuredBody>
+ <component>
- <component>
- <section>
  <templateId root="2.16.410.1.11111.2.3" />
  <code code="11348-0" displayName="History of Past Illness" codeSystem="2.16.840.1.113883.6.1" codeSystemName="LOINC" />
  <title>History of Past Illness</title>
- <text>
- <paragraph>
  <![CDATA[ * Reservation 2008-10-31 AM 10:00  ]]>
  </paragraph>
</text>
</section>
</component>
- <component>
- <section>
  <templateId root="2.16.410.1.11111.2.3" />
  <code code="29545-1" displayName="Physical findings" codeSystem="2.16.840.1.113883.6.1" codeSystemName="LOINC" />
  <title>Physical findings</title>
- <text>
- <paragraph>
  <![CDATA[
    #1. AR + AC , pale mucosa (o/s SFT mite)
    SPT : Dp 8.2 Df 11 Tp 3 TSM 3 multiple mold Dog
    #2. snoring T2A0
    #3. B) Thyroid enlargement
    R/O Rt thyroid nodule
    R/O Hyperthyroidism
    TFT : TSH 0.05 TG 124.3
    #4. Exophthalmosis
    #5. weight gain 10kg : increase
    f/u : thyroid sono & FNA
  ]]>
  </paragraph>
</text>
</section>
</component>

```

Figure 4. Clinical document extensible markup language (XML) format for diagnosis applying clinical document architecture (CDA) standard.

Figure 5. Document registry framework (DRF). CDA: clinical document architecture.

Application of Standard Terminology.

3. Application Methodology of Data Transfer

The Document Registry Framework (DRF) suggested by CIEHR of Korea is used to connect the Registry Server, which registers and manages information categories subject to exchange, and the Repository, which stores and manages the CDA documents (Figure 5).

A CDA document is stored at the Repository upon creation, and registration information is stored at the Registry in the form of a message. To retrieve the generated CDA document, the Document Consumer obtains the CDA ID and information on the location of the Repository from the Registry, and finally gets the CDA document through ebXML.

The DRF was provided in the format of Web service definition language (WSDL) along with the API of a transmitting

module in order to be applied to various platforms easily. The system in this study was developed on ".NET" platform, and the API was applied by using the "Visual studio .net."

4. Application of Standard Terminology

Since a standardized terminology needs to be employed to transfer information of a diagnosis and medication from different systems, the code for the standardized terminology was adopted. The description of the standard code was made into CDA Entry level. To notate the diagnosis of a patient, ICD-10 codes were used and marked into the Entry in a CDA document. The medication was represented in the Entry level of CDA document by using the main ingredient electronic data interchange (EDI) codes.

For diagnosis code ICD-10, the codeSystem sets 2.16.840.1.113883.6.3 at the Entry Observation (Figure 6).

```
- <component>
- <section>
  <templateId root="2.16.410.1.11111.2.2" />
  <code code="29548-5" displayName="Diagnosiss" codeSystem="2.16.840.1.113883.6.1" codeSystemName="LOINC" />
  <title>Desease Name(Diagnosis)</title>
- <text>
- <list>
- <item>
  <![CDATA[ Allergic rhinitis, persistent, moderate/severe ]]>
  </item>
</list>
</text>
- <entry>
- <observation classCode="COND" moodCode="EVN">
  <templateId root="2.16.410.1.11111.3.2" />
  <code code="J303" displayName="Allergic rhinitis, persistent, moderate/severe" codeSystem="2.16.840.1.113883.6.3"
  codeSystemName="ICD 10" />
  <statusCode code="completed" />
  <effectiveTime value="20061219" />
</observation>
</entry>
+ <entry>
</section>
</component>
```

Figure 6. Example of applying standard terminology to diagnosis.

```
- <consumable>
- <manufacturedProduct>
- <manufacturedLabeledDrug>
  <code codeSystem="2.16.410.1.10000.4" codeSystemName="EDI Code" code="E01860051" displayName="Ensure Liquid" />
  <code codeSystem="2.16.410.1.10000.4" codeSystemName="EDI Cheif Integration" code="304700ALQ" displayName="Ensure Liquid" />
- <originalText>
  <reference value="#m1" />
</originalText>
</manufacturedLabeledDrug>
- <manufacturerOrganization>
  <name>MEIJI</name>
</manufacturerOrganization>
</manufacturedProduct>
</consumable>
```

Figure 7. Example of applying standard terminology to medication.

The EDI code for medication is employed without alternation and the codeSystem is set for 2.16.410.1.10000.4, along with the information on ingredients, dosages and manufacturers of the drugs in use (Figure 7).

5. Application of Security

The security guidelines proposed by the CIEHR of Korea was used to ensure the information security. In this study, we aimed at building essential security systems for implementation of online services, such as encryption in the communication section, server security, and database security, protection against hacking, contents and network security.

For this purpose, the VPN was implemented to encode packet in each middleware section. To protect the database and the server, an encryption solution was applied. A web firewall was installed to protect hacking. Especially, to secure the data, all the transmitted data were sent out after encoding and decoded after receiving by using public-key cryptography.

The communication through the Web Service mounted on the middleware is conducted by managing the certification codes for the middleware of each hospital so the access to the service is blocked if certification failed.

When sending a message, each packet is encoded for transmission within VPN-controlled section. As the message calls the Web Service on the Registry Server; the paging call is verified against the Web Service Security Enhanced (WSE) for passage. Also, the Token in SOAP-type is checked for verification. Specifically, the ID and the password are checked. The password is encoded and stored in the database for verification. Finally, after certification, the encoded message is decoded and delivered to the final recipient.

Furthermore, access control was accomplished by monitoring user's IP and Mac address on internal network in the security policy.

III. Results

1. Registry Server

The Registry Server stores meta-information for exchanging the patient's medical information to referral. It provides two types of services: messaging service which facilitates sending and receiving the meta-information, and the registry service which registers and manages information on exchange.

1) Messaging service

The messaging service is composed of the services of storing and inquiring the transmitted message. When transmitted, each message is made in the XML format.

The meta-information contains data of the sending and receiving medical institutions, medical staff in charge, reservations, diagnosis and meta ID. Especially, the meta ID is transmitted as a message produced by the OID rules. This OID is unique to each message, and serves as an index to search the relevant CDA document [9,10].

When receiving a message, it is delivered via the Web Service which known as the CDAREgService. This web service uses the message decryption for decoding, and uses the message parser for interpretation, and stores the meta data to the database.

2) Information exchange registry service

For patient or hospital to subscribe this service, it needs to sign up for the service at the MIES Server for certification. The registration procedure is provided by Web Service at the EHR Registry Server. The procedure is tailored for the each stage of information exchange, and contains information on Referral, Reply, and Request. In addition, two other services are provided: one that verifies the consent to the release of the medical information, and the other that stores the registry information. The fields managed by Registry Server are shown in Table 1.

A certification message in a XML format is sent out, which activates the Registry Service from the MIES Server. The

Table 1. Registry information type & description

Field name	Field description
REG_HOS_ID	Electronic health record agree institution code
REG_ID	Patient identifier
REG_PT_NM	Patient name
REG_PT_SSNID	Patient social number
SND_HOS_CODE	'Refer in' hospital code
SND_DEPT_CODE	'Refer in' hospital department code
SND_DEPT_NM	'Refer in' hospital department name
SND_DR_NM	'Refer in' doctor name
RCV_HOS_CODE	'Refer out' hospital code
RCV_DEPT_CODE	'Refer out' hospital department code
RCV_DEPT_NM	'Refer out' hospital department name
RCV_DR_NM	'Refer out' doctor name
RSV_HOPE_DATE	Reservation date
META_ID	Clinical document architecture document identifier
DIAGNOSIS_CODE	Diagnosis code
DIAGNOSIS_NM	Diagnosis name

final authentication undergoes the processes such as verification of consent, certification and EHR registration. The certification message conveys the information on the ID code of the medical institution and the patient's social security number. These two pieces of information are used to check whether the EHR registration has been done or not. During transmission, the certification information is encrypted.

When the consent information is absent, the Registry Web Service sends an "Authentication Fail" message to the original sender. Upon receiving it, the sender sends back the registry information. When the registry information arrives at the MIES Server, its Registry Service activates and registers the information. Once the information on the patient and the hospital are registered, the Registry Service sends an "Authentication Success" message to the original sender, and the sender is now able to access the information exchange service and start the medical information exchange process.

2. CDA Transfer Server

When a hospital transfers patient to another institution, the requesting institutions send a referral message to the Reg-

istry Server and the CDA document is stored at the CDA Repository. To transmit the stored CDA document, the Transfer Server searches the CDA documents produced at the requesting institution or the receiving institution, and sends the relevant information to the requesting institutions.

To search a document stored at the CDA Repository of the hospital, the unique index of the document is required to facilitate this process. Thus, a unique ID is assigned to each CDA document, and the unique ID is transferred as the meta ID upon message transmission.

When requesting for transfer of a CDA document, the requesting hospital sends to the requested hospital, the OID generated from the messaging Web Service. The link service, which searches the CDA record, is registered at the registry through the CDA Search Service, and the CDA Document is stored at the CDA Repository.

The requested hospital finds out the location in the Registry in reference to the meta ID of the received message. Upon receipt of the request, the DRF Server searches the indexed document stored at the CDA Repository by the meta ID and transfers to the requested hospital.

진료의뢰서				
[보내는 곳]		[받는 곳]		
기관명: 전세정소아과		기관명: 분당서울대병원		
보낸명: 권 해정		받는사람: 최		
연락처: 031-7		연락처: 031-7		
▲ 환자정보				
환자이름: 최		환자번호: 14936		
성별: 남		생일: 2004년 8월 19일		
▲ 상병명(전단명)				
날짜	병명			
20080625	상세불명의 급성 상기도 감염 (Acute upper respiratory infection, unspecified)			
20080625	상세불명의 천식 (Asthma, unspecified)			
20080625	상세불명의 기관지염 (Bronchopneumonia, unspecified)			
20080625	상세불명의 알레르기성 비염 (Allergic rhinitis, unspecified)			
20080625	상세불명의 결막염 (Conjunctivitis, unspecified)			
20080625	급성 후두기관염 (Acute laryngotracheitis)			
20080623	상세불명의 급성 상기도 감염 (Acute upper respiratory infection, unspecified)			
20080623	상세불명의 천식 (Asthma, unspecified)			
20080623	상세불명의 기관지염 (Bronchopneumonia, unspecified)			
20080623	상세불명의 알레르기성 비염 (Allergic rhinitis, unspecified)			
20080623	상세불명의 결막염 (Conjunctivitis, unspecified)			
▲ 약 처방				
처방날짜	약종명	용량	일회수	일수
20080623	코데날정 (내복)	1.25	3	4
20080623	소아용아스피린서방정 (내복)	1.25	3	4
20080623	푸로스타틴정 (내복)	7.5	3	4
20080623	변토린내복 2.5mg (외용)	2	2	6
20080623	폴리코트레스를 분무용현탁액0.5mg/2ml (외용)	2	2	6
20080620	코데날정 (내복)	1.34	3	3
20080620	소아용아스피린서방정 (내복)	1.34	3	3
20080620	푸로스타틴정 (내복)	7.5	3	3
20080620	변토린내복 2.5mg (외용)	3	3	3
20080620	폴리코트레스를 분무용현탁액0.5mg/2ml (외용)	3	3	3

진료의뢰서																				
의뢰기관: 분당서울대학교병원 주소: 경기도 성남시 분당구 구미동 300 전화번호: 031-797-2000		의뢰인: 이만호의원/박노기과 주소: 경기도 용인시 용인읍 1000-9 하나로초2차 전화번호: 031-250-8875																		
어원호적부번호: 가 어원호: 상병명 제하 상병명에서 의학계주인 환자의 진료결과를 다음과 같이 알려드리오니 향후 진료에 참고하시기 바랍니다. 최환의 무궁한 발전을 기원합니다.																				
수신자	성명	성명	성명	성명																
연락번호	연락번호	연락번호	연락번호	연락번호																
상병명(전단명) acute epiglottitis 주요검사결과 치료(수술) 및 경과 진료에 대한 최초 확인서입니다. 57기 환자 testicular pain을 주소로 의뢰되어 2008년 9월 8일에 비뇨기과 방치 수 10수일 진료를 받았으나 급성 상기도 감염 및 no dysuria로 acute epiglottitis (최근 치아교정 수술 후 제대로 먹지 못해 불 섭취가 증가)로 인한 것으로 추정. 2008년 9월 8일, 9월 9일, 9월 10일 후 비뇨기과 방치 수 10수일 치료 후 상기도 감염 및 P.O medication 처방되었습니다. 추후 진료 경과에 대해 통지하시기 바랍니다.																				
항우치료명령 환자 의뢰자에 주신 것 같습니다.																				
주요약제 <table border="1"> <thead> <tr> <th>모태일</th> <th>제명/내용</th> <th>용량</th> <th>회수</th> <th>일수</th> </tr> </thead> <tbody> <tr> <td>2008-09-08</td> <td>Asac 100mg tab(Acetofenac)</td> <td>Tab</td> <td>2</td> <td>14일</td> </tr> </tbody> </table>					모태일	제명/내용	용량	회수	일수	2008-09-08	Asac 100mg tab(Acetofenac)	Tab	2	14일						
모태일	제명/내용	용량	회수	일수																
2008-09-08	Asac 100mg tab(Acetofenac)	Tab	2	14일																
검체검사 <table border="1"> <thead> <tr> <th>일자</th> <th>항목명</th> <th>검사명</th> <th>검사결과</th> </tr> </thead> <tbody> <tr> <td>2008-09-08</td> <td>[일반혈액] [EDTA BLD]</td> <td>WBC</td> <td>8.01 x 10⁹/ul</td> </tr> <tr> <td>2008-09-08</td> <td>[일반혈액] [EDTA BLD]</td> <td>RBC</td> <td>4.72 x 10¹²/ul</td> </tr> <tr> <td>2008-09-08</td> <td>[일반혈액] [EDTA BLD]</td> <td>Hb</td> <td>14.4g/dL</td> </tr> </tbody> </table>					일자	항목명	검사명	검사결과	2008-09-08	[일반혈액] [EDTA BLD]	WBC	8.01 x 10 ⁹ /ul	2008-09-08	[일반혈액] [EDTA BLD]	RBC	4.72 x 10 ¹² /ul	2008-09-08	[일반혈액] [EDTA BLD]	Hb	14.4g/dL
일자	항목명	검사명	검사결과																	
2008-09-08	[일반혈액] [EDTA BLD]	WBC	8.01 x 10 ⁹ /ul																	
2008-09-08	[일반혈액] [EDTA BLD]	RBC	4.72 x 10 ¹² /ul																	
2008-09-08	[일반혈액] [EDTA BLD]	Hb	14.4g/dL																	
수술기록 <table border="1"> <thead> <tr> <th>수술일</th> <th>수술명</th> <th>수술한 전단명</th> <th>수술한 전단명 코드</th> <th>비고</th> </tr> </thead> <tbody> <tr> <td>2008-09-08</td> <td>Other facial bone repair and orthognathic surgery</td> <td>malocclusion</td> <td>malocclusion</td> <td>치교 전</td> </tr> </tbody> </table>					수술일	수술명	수술한 전단명	수술한 전단명 코드	비고	2008-09-08	Other facial bone repair and orthognathic surgery	malocclusion	malocclusion	치교 전						
수술일	수술명	수술한 전단명	수술한 전단명 코드	비고																
2008-09-08	Other facial bone repair and orthognathic surgery	malocclusion	malocclusion	치교 전																
당초 의뢰에서 자료를 계속하실 계획이 있으시거나 더 궁금하신 사항은 전화(031-797-2000 또는 FAX031-797-8090)로 연락주시면 곧 회답하여 드리겠습니다.																				
2008년 9월 8일 진료과: 비뇨기과 분당서울대학교병원 진료협력센터 담당자: 김																				
이 기록은 의무기록에 근거하여 작성하였습니다. 문의전화: 797-2000 (분당서울대학교병원 진료협력센터)																				

Figure 8. Clinical document architecture (CDA) Viewer.

Table 2. Comparison of the prototype of the information exchange system and the MIES

Subject	Prototype of information exchange system	MIES (System based on EHR standard)
Subject institution	Clinics, secondary hospitals (SNUBH)	Clinics, secondary hospitals (SNUBH)
No. of affiliated clinics	9	33
No. of cases	Appr. 1250 (2007.07.19 - 2008.6.20)	Appr. 5100 (2008.06.21 - 2009.03.20)
Information exchanged	Diagnosis, medication orders, lab test result	Diagnosis, medication orders, lab test result, surgery history, and medical images
Documents exchanged	Medical referral and reply form	Lab, medication, health summary medical referral and reply form, request for release of medical information
CDA level	CDA R2 without entry	CDA R2 with entry
Standard terminology	No applicable codes	- Diagnosis: ICD-10 - Medication: EDIcode - Item definition: LOINC
Parties of exchange	One-to-one exchange via gateway between hospitals	One-to-many exchange via EHR registry server
Transmission method	Web service	Web service (message) & ebXML (CDA)
Encryption	Secret key cryptography	Public-key cryptography
Platform	.NET	.NET & JAVA
Security	SSL, server vaccine, and firewall	Encryption in the communication section, server security, database security, protection against web attacks, content security and network security, SSL implementation of VPN

MIES: medical information exchange system, EHR: electronic health record, SNUBH: Seoul National University Bundang Hospital, CDA: clinical document architecture, SSL: secure socket layer, VPN: virtual private network.

3. CDA Viewer

When a hospital or a clinic refers or replies to another institution, including medication information, LAB test results and the patient profiles the CDA document is generated.

The requesting hospital needs a program to make the CDA document, CDA generator. Also, to see the CDA document, you need the CDA viewer which changes the CDA document into the document applied XML Style Sheet (XSLT) (Figure 8).

IV. Discussion

We developed a CDA standard-based medical information exchange system which electronically exchanges the medical information items defined in accordance with the CDA document standard, adopting the standard transmission method and security devices. The security and standardization approaches covered all processes.

To provide the better protection and security of the patient's information, the MIES established a Registry Server and a

CDA Transfer Server separately in order to divide patient information and medical information. The Registry Server contains the patient profile and the indexes of the medical information only. Therefore it is possible to reduce the burden arising from management of the entire medical data. Each CDA document is maintained in the CDA Repository of each medical institution.

The interaction between heterogeneous systems became possible by using middleware. Since MIES was constructed based on the exchange standard suggested by CIEHR of Korea, any system can be accessed.

Table 2 shows comparison of the old "Prototype of the Information Exchange System" and the new "MIES" developed in this study. The "Prototype of Information Exchange System" was implemented to check possibility of medical information exchange between nearby several clinics and SNUBH.

Currently, there's a lot of Hospital's demand to adopt this instant system for effective information exchange in Korea. To meet these demands, following study must be pursued to build an advanced system enabling information exchange

between multiple Hospitals and clinics.

By applying international standards to exchange of information between different medical information systems, this study will expectedly contribute to medical information exchange not only between domestic medical institutions, but also international medical institutions.

Conflict of Interest

No potential conflict of interest to this article was reported.

Acknowledgements

This study was sponsored by the Ministry of Health & Welfare of Korea (Assignment No.: A050909).

References

1. Kim NH, Kim HR, Nah JY, Choi HJ, Lee HR, Jung HJ, Choi MR. Designing electronic medical record using health level 7 development framework. *J Korean Soc Med Inform* 2005; 11: 273-278.
2. Park SH, Bom HS. A web-based medical information exchange system using HL7 protocols. *J Korean Soc Med Inform* 2002; 8: 11-16.
3. Center for Interoperable EHR. EHR. Seoul: Center for Interoperable EHR; c2008- [cited at 2010 Dec 15]. Available from: <http://www.ehrkorea.org/>.
4. Kim Y, Cho IS, Seo JW, Kim IK, Kim HG, Choi Y. Research and development efforts aimed at implementing electronic health record systems with interoperability and patient safety. *J Korean Soc Med Inform* 2006; 12: 115-132.
5. Sartipi K, Yarmand MH. Standard-based data and service interoperability in eHealth systems. This paper presented at IEEE International Conference on Software Maintenance 2008; 2008 Sep 28 - Oct 4; Beijing, China.
6. Haomin L, Huilong D, Xudong L, Zhengxing H. A clinical document repository for CDA documents. In: Proceedings of ICBBE 2007: Bioinformatics and Biomedical Engineering; 2007 July 6-8; Wuhan, China. p1084-1087.
7. Health Level Seven International. Clinical Document Architecture [Internet]. Ann Arbor, MI: Health Level Seven International; c2007-2010 [cited at 2010 Aug 3]. Available from: <http://www.hl7.org>.
8. Yun JH. Generation and processing of CDA documents based on entry level supporting templates [dissertation]. Daegu: Kyungbuk National University; 2008. p116.
9. Health Level Seven International. Object identifier (OID) registry [Internet]. Ann Arbor, MI: Health Level Seven International; c2007-2010 [cited at 2010 Aug 3]. Available from: <http://www.hl7.org/oid/index.cfm>.
10. France telecom. Object identifier(OID) repository [Internet]. Paris: France telecom; c2010 [cited at 2010 Aug 3]. Available from: <http://www.oid-info.com>.