Figure 2 Catheter exchange; use of 5mm port as exit site

Figure 3 Confirmation of catheter position

DISCUSSION

The technique described allows the PDC to be inserted and tunnelled out through the well planned, working 5mm port site, keeping incisions to a minimum. In addition, the working ports can be used to deal with possible problems encountered in previous surgery such as an extensive laparoscopy (especially with previous peritonitis), assessing the feasibility of peritoneal dialysis, performing a biopsy of the peritoneum for encapsulating peritoneal sclerosis, dealing with adhesions and replacing/exchanging displaced PDCs into the pelvic sump (Figs 1–3).

References

- Schmidt SC, Pohle C, Langrehr JM *et al.* Laparoscopic-assisted placement of peritoneal dialysis catheters: implantation technique and results. *J Laparoendosc Adv Surg Tech A* 2007; **17**: 596–599.
- Lu CT, Watson DI, Elias TJ *et al.* Laparoscopic placement of peritoneal dialysis catheters: 7 years' experience. *ANZ J Surg* 2003; **73**: 109–111.
- Wilkie M, Wild J. Peritoneal dialysis access – results from a UK survey. *Perit Dial Int* 2009; **29**: 355–357.
- Ko J, Ra W, Bae T *et al.* Two-port laparoscopic placement of a peritoneal dialysis catheter with abdominal wall fixation. *Surg Today* 2009; **39**: 356–358.
- Regoczi T, Jósavay J, Bálint A *et al.* Experiences with Tenckhoff peritoneal dialysis catheter. *Orv Hetil* 2009; **150**: 2,110–2,114.

An innovative technique for removal of a broken intramedullary hip screw

F Runau, B Bloch, T Green

Department of Trauma and Orthopaedics, Leicester Royal Infirmary, Leicester, UK

CORRESPONDENCE TO

Franscois Runau, E: franscois_gerald@yahoo.com

Figure 1 Guidewire with distal hook and broken intramedullary hip screw nail

Figure 2 Guidewire hooked into distal intramedullary hip screw hole

BACKGROUND

Intramedullary hip screw breakage is an uncommon occurrence, with a reported incidence ranging from 0.2% to 5.7%.¹ Removal of a broken intramedullary nail is difficult, particularly the distal fragment.^{2–4} We describe a cheap, simple and novel technique using readily available instruments on a single patient.

TECHNIQUE

First, the proximal part of the nail, the lag screw in the femoral head and the distal locking screws are removed, leaving the distal fragment of the intramedullary nail. Next, using a heavy pair of forceps and wire cutters, a 1.0mm x 1,000mm guidewire is bent twice and the tip shaped into a hook (Fig 1). This is inserted into the nail. The double bend on the shaft against the lumen of the nail acts as a spring mechanism to allow the tip to engage positively into the distal oval screw hole (Figs 2 and 3);

Figure 3 Radiograph of guidewire hooked into screw hole

a simple analogy would be to the spring loaded locking mechanism on adjustable crutches. Finally, a T-handle Jacobs chuck is applied to the proximal end of the guidewire and pulled.

DISCUSSION

We believe this to be a simple and effective solution for what could be a difficult situation intraoperatively by using cheap universally available equipment without causing any unnecessary delays for the patient.

References

1. Wee JL, Sathappan SS, Yeo MS, Low YP. Management of gamma nail breakage with bipolar hemi-arthroplasty. *Singapore Med J* 2009; **50**: e44–47.
2. Blake SM. A technique for the removal of the distal part of a broken intramedullary nail. *Ann R Coll Surg Engl* 2009; **91**: 169–170.
3. Deakin DE, Cooper JP. Use of a cork-screw femoral head extractor for removal of a stuck intramedullary nail. *Ann R Coll Surg Engl* 2008; **90**: 163.
4. Riansuwan K, Carter C, Nercessian O. Removal of broken long gamma nail: a modified guide wires technique. *J Trauma* 2008; **64**: 517–519.

A simple and cost-effective technique to prevent turbulence and improve visualisation during shoulder arthroscopy

K Theivendran, MM Shah

Department of Orthopaedics, Walsall Manor Hospital, Walsall, UK

CORRESPONDENCE TO

Kanthan Theivendran, E: kanthan@hotmail.co.uk

BACKGROUND

During arthroscopic shoulder surgery, subacromial space bleeding can obscure and frustrate attempts to obtain effective visualisation during such procedures as acromioclavicular joint (ACJ) excision or rotator cuff repair. In many cases this is due to fluid leakage from non-cannulated portals. Fluid flow from these portals creates a suction effect by virtue of Bernoulli's principle and draws blood into the subacromial space. Digital

Figure 1 A 20-gauge needle and sheath

Figure 2 Right shoulder arthroscopy with standard posterior subacromial camera portal with sheath placed into the lateral portal to prevent excessive fluid escape and turbulence. Anterior acromioclavicular joint (ACJ) portal is used to perform joint excision with clear visualisation.

pressure over these portals can prevent this; however, an assistant will be required during the procedure.¹ We describe an independent, simple and cost-effective way of controlling turbulence within this closed system.

TECHNIQUE

Using the standard posterior subacromial portal, the subacromial space can be visualised. A lateral portal is created by a stab incision using a No 15 blade and a subacromial decompression can be performed. When more than two portals are required, such as the anterior portal for an ACJ excision, a sterile 20-gauge needle sheath (Fig 1) can be inserted into the lateral portal to prevent fluid leakage and turbulence (Fig 2). The needle can be used to localise the anterior portal for the arthroscopic ACJ excision.

DISCUSSION

This technique has not been described previously and allows the surgeon to operate independently without the use of an assistant to apply digital