Published in final edited form as:

Soft Matter. 2013 ; 9(16): 4284–4296. doi:10.1039/C3SM27683J.

Deformation of an elastic capsule in a rectangular microfluidic channel

S. Kuriakose and P. Dimitrakopoulos*

Department of Chemical and Biomolecular Engineering, University of Maryland, College Park, Maryland 20742, USA

Abstract

In the present study we investigate computationally the deformation of an elastic capsule in a rectangular microfluidic channel and compare it with that of a droplet. In contrast to the bullet or parachute shape in a square or cylindrical channel where the capsule extends along the flow direction, in a rectangular channel the capsule extends mainly along the less-confined lateral direction of the channel cross-section (i.e. the channel width), obtaining a pebble-like shape. The different shape evolution in these two types of solid channels results from the different tension development on the capsule membrane required for interfacial stability. Furthermore, in asymmetric channel flows, capsules show a different deformation compared to droplets with constant surface tension (which extend mainly along the flow direction) and to vesicles which extend along the more-confined channel height. Therefore, our study highlights the different stability dynamics associated with these three types of interfaces. Our findings suggest that the erythrocyte deformation in asymmetric vessels (which is similar to that of capsules) results from the erythrocyte's inner spectrin skeleton rather than from its outer lipid bilayer.

1. INTRODUCTION

The study of the interfacial dynamics of artificial or physiological capsules (i.e. membrane-enclosed fluid volumes) in Stokes flows has seen an increased interest during the last few decades due to their numerous engineering and biomedical applications. Artificial capsules have wide applications in the pharmaceutical, food and cosmetic industries [23]. In pharmaceutical processes, for example, capsules are commonly used for the transport of medical agents. In addition, the motion of red blood cells through vascular microvessels has long been recognized as a fundamental problem in physiology and biomechanics, since the main function of these cells, to exchange oxygen and carbon dioxide with the tissues, occurs in capillaries [22].

In the area of interest of the present paper, the study of the motion and deformation of capsules and biological cells in microfluidic channels is motivated by a wide range of applications including drug delivery, cell sorting and cell characterization devices [1–3, 5, 7, 15, 27], fabrication of microcapsules with desirable properties [8, 17, 21, 26], determination of membrane properties [19, 24], microreactors with better mixing properties [4, 32], and of course its similarity to blood flow in vascular capillaries [22, 23].

Studying the shape of soft particles in confined solid ducts, such as microfluidic channels and blood microvessels, provides useful information on the utilization of these particles in chemical, pharmaceutical and physiological processes. For example, understanding the stability of soft particle shapes provides helpful insight on the hydrodynamic aggregation

*dimitrak@umd.edu.

and the effective viscosity of suspensions [6]. The deformation of artificial capsules in microchannels is directly associated with drug delivery, cell sorting and cell characterization [1, 2]. Furthermore, the deformability of red blood cells plays a pivotal role in the oxygen and carbon dioxide exchange between the microcirculation and the body tissues [22], and helps identifying the effects of blood disorders and diseases [3, 14, 27].

The shape of capsules and biological cells in solid ducts, is determined by the nonlinear coupling of the deforming hydrodynamic forces with the restoring interfacial forces of the particle membrane. Since the latter forces depend on the type of the soft-particle interface, this suggests that different soft particles (such as droplets, capsules, vesicles and erythrocytes) may obtain quite different shapes as they travel in a solid vessel.

In axisymmetric-like solid ducts, such as cylindrical and square channels, soft particles commonly obtain steady-state bullet-like and parachute-like shapes, elongated along the flow direction [6, 18, 25, 28, 35]. The recent investigation of Couplier *et al.* [6] showed that in rectangular microfluidic channels, vesicles obtain an unexpected croissant shape (relatively wider in the narrowest direction of the channel) owing to the development of a four-vortex pattern on the fluid-incompressible vesicle membrane.

In this paper, we show that the capsule shape in a rectangular microfluidic channel is quite different than that in a square or cylindrical channel. In the latter channels, the capsule extends along the flow direction only obtaining a bullet or parachute shape while in a rectangular channel it extends mainly in the less-confined lateral direction of the channel cross-section, i.e. the channel width, acquiring a pebble-like shape. The different shape evolution in these two types of solid channels is associated with the deformation of elastic capsules only and results from the different tension development on the capsule membrane needed for interfacial stability. Thus, in asymmetric channel flows, capsules show a different deformation compared to droplets with constant surface tension (which extend mainly along the flow direction) and to vesicles which extend along the more-confined channel height. [6]. Our findings also provide physical insight on the deformation of erythrocytes in rectangular microfluidic channels (which also extend more along the less-confined channel width) [33], and suggest that the particular shape results from the inner cytoskeleton of the erythrocytes rather than from their outer lipid bilayer.

2. PROBLEM DESCRIPTION

We consider a three-dimensional capsule (with a spherical undisturbed shape and an elastic interface) flowing along the centerline of a straight microchannel with a (constant) rectangular cross-section as illustrated in figure 1. The capsule's interior and exterior are Newtonian fluids, with viscosities $\lambda\mu$ and μ , and the same density. The capsule size a is specified by its volume $V = 4\pi a^3/3$. The height of the channel's rectangular cross-section is ℓ_z and its width $\ell_y > \ell_z$.

Far from the capsule, the flow approaches the undisturbed flow $\mathbf{u}^\infty$ in a channel characterized by an average velocity U . (The exact form of the channel's velocity field $\mathbf{u}^\infty$ and its average velocity U are given in section 2 of our recent paper on capsule motion in a square microchannel [18].) We assume that the Reynolds number is small for both the surrounding and the inner flows, and thus the capsule deformation occurs in the Stokes regime.

In addition, we consider a slightly over-inflated capsule made of a strain-hardening membrane following the Skalak *et al.* constitutive law [29] (and thus called Skalak capsule in this paper) with comparable shearing and area-dilatation resistance. This capsule description represents well bioartificial capsules such as the capsules made of covalently

linked human serum albumin (HSA) and alginate used in the experimental study of Risso, Collé-Pailot and Zagzoule [25].

For a membrane with shearing and area-dilatation resistance considered in this work, the surface stress is determined by the in-plane stresses, i.e. $\Delta \mathbf{f} = -\nabla_s \cdot \boldsymbol{\tau}$ which in contravariant form gives

$$\Delta \mathbf{f} = -(\tau^{\alpha\beta} |_{\alpha} \mathbf{t}_{\beta} + b_{\alpha\beta} \tau^{\alpha\beta} \mathbf{n}) \quad (1)$$

where the Greek indices range over 1 and 2, while Einstein notation is employed for (every two) repeated indices. In this equation, the $\tau^{\alpha\beta} |_{\alpha}$ notation denotes covariant differentiation, $\mathbf{t}_{\beta} = \mathbf{x} / \boldsymbol{\theta}^{\beta}$ are the tangent vectors on the capsule surface described with arbitrary curvilinear coordinates $\boldsymbol{\theta}^{\beta}$, and $b_{\alpha\beta}$ is the surface curvature tensor [12, 23].

The in-plane stress tensor $\boldsymbol{\tau}$ is described by constitutive laws that depend on the material composition of the membrane. In this work, we employ the Skalak *et al.* law [29] which relates $\boldsymbol{\tau}$'s eigenvalues (or principal elastic tensions τ_{β}^P , $\beta = 1, 2$) with the principal stretch ratios λ_{β} by

$$\tau_1^P = \frac{G_s \lambda_1}{\lambda_2} \{ \lambda_1^2 - 1 + C \lambda_2^2 [(\lambda_1 \lambda_2)^2 - 1] \} \quad (2)$$

Note that the reference shape of the elastic tensions is the spherical quiescent shape of the capsule while to calculate τ_2^P reverse the λ_{β} subscripts. In Eq. (2), G_s is the membrane's shearing modulus while the dimensionless parameter C is associated with the area-dilatation modulus G_a of the membrane (scaled with its shearing modulus) [23, 29].

We further consider that the capsule is subjected to a positive osmotic pressure difference between the interior and exterior fluids, i.e. the capsule is (slightly) over-inflated and thus prestressed. For this, we define the prestress parameter α_p such that all lengths in the undeformed capsule would be scaled by $(1 + \alpha_p)$, relative to the reference shape [18]. Since the capsule is initially spherical, its membrane is initially prestressed by an isotropic elastic tension $\tau_0 = \tau_{\beta}^P(t=0)$ which depends on the employed constitutive law and its parameters but not on the capsule size. For example, for a Skalak capsule with $C = 1$ and $\alpha_p = 0.05$, the undisturbed capsule size a is 5% higher than that of the reference shape and the initial membrane tension owing to prestress is $\tau_0 / G_s \approx 0.3401$. It is of interest to note that a (small) prestress also acts as a bending resistance and thus removes the buckling instability at the capsule's lateral cross-section [18].

The numerical solution of the interfacial problem is achieved through our interfacial spectral boundary element method for membranes, and the interested reader is referred to our earlier papers for more details on our spectral algorithm and our recent investigation on the capsule dynamics in a square microchannel [12, 18]. To verify the accuracy of our results, we performed convergence runs covering the entire interfacial evolution (i.e. well past steady state) with different spacial grids for several capsules and flow rates. Our convergence runs showed that our results for the interfacial shape, the capsule velocity, the additional pressure difference and the shear stress on the solid walls (including the channel corners) were determined with an accuracy of at least 3 significant digits.

In our work we assume that the flow rate Q (or the average undisturbed velocity U) inside the channel is fixed. In addition, in sections 3 and 4 we consider a Skalak capsule with

prestress $\alpha_p = 0.05$ and membrane hardness $C = 1$, moving in a rectangular channel with aspect ratio $\ell_y/\ell_z = 2$. The effects of membrane hardness C , capsule prestress α_p and channel's aspect ratio ℓ_y/ℓ_z are investigated in section 5. The present problem depends on two additional dimensionless parameters: the capsule size (relatively to the channel height) a/ℓ_z and the capillary number Ca defined as

$$Ca = \frac{\mu \mathcal{U}}{G_s} \quad (3)$$

It is of interest to note that the capillary number, as defined by Eq.(3), does not contain any length scale, and thus it may be considered as a dimensionless flow rate. In this study, if no scale is present, the channel's half-height ℓ_z is used as the length scale, the velocity is scaled with the average undisturbed velocity $\mathcal{U}$, and thus time is scaled with $\ell_z/\mathcal{U}$, while the membrane tensions are scaled with G_s .

The range of dimensionless parameters employed in our computational work (shown in table 1) can readily be used in experimental microfluidic systems. As an example, Leclerc *et al.* [19] investigated ovalbumin microcapsules with shear modulus $G_s = 0.07\text{N/m}$ in microfluidic channels with a typical height $\ell_z = 50\text{ }\mu\text{m}$. Using as external fluid glycerin with viscosity $\mu \approx 1\text{ Pa s}$ and average velocities $\mathcal{U} = 1\text{--}4\text{ cm/s}$, the authors achieved capillary numbers in the range $Ca \approx 0.1\text{--}0.5$. Considering erythrocytes with shear modulus $G_s = 2.5\text{ }\mu\text{N/m}$ [10, 16] in microfluidic channels with height $\ell_z = \mathcal{O}(10)\text{ }\mu\text{m}$ and an external liquid with a viscosity similar to that of water, $\mu \approx 1\text{ mPa s}$, the same range of capillary numbers can be achieved with average velocities $\mathcal{U} = \mathcal{O}(1)\text{ mm/s}$.

To facilitate our results description, we imagine that the channel is horizontal, as illustrated in figure 1. Thus, the flow direction (i.e. the x -axis) corresponds to the channel's or capsule's length, the z -direction will be referred as height while the y -direction will be referred as width (of the channel or the capsule). Seeing the capsule from the negative y -axis, positive z -axis or negative x -axis represents a front view, a top view or an upstream view, respectively. In addition, we adopt the standard definition of geometric shapes (e.g. polygons). Thus we call the capsule's rear edge as convex when the radius of curvature at the middle of the rear edge points inside the capsule (i.e. the local curvature is positive); in the opposite case the edge shape is concave.

3. EFFECTS OF FLOW RATE

In this section, we collect our steady-state results as a function of the flow rate Ca , for capsule motion in a rectangular microchannel with aspect ratio $\ell_y = 2\ell_z$ and capsule sizes comparable to the channel's height ℓ_z . In particular, we consider Skalak capsules with size $a = 0.8, 0.9, 1.1$ and for small-to-moderate capillary number Ca in the range $[0, 0.2]$. To obtain these steady-state results we initiate our computations from a spherical capsule (for $a < 1$) or an ellipsoidal capsule (for $a > 1$) at the channel centerline using viscosity ratio $\lambda = 1$ and compute the capsule dynamics until times $t = 10\text{--}20$, i.e. well-past steady state which usually is achieved around time $t = 2\text{--}4$.

Owing to the specific symmetry of the channel flow and the material interface (i.e. the elastic-solid membrane) of the capsule, at steady state there is no flow inside the capsule (in agreement with our computational results), and thus the steady-state capsule properties are independent of the inner viscosity or the viscosity ratio λ [18, 23]. For the same reason, the membrane viscosity (if any), which is not accounted in our computations, does not affect the capsule's steady-state properties.

Figure 2 shows different views of the steady-state capsule shape for capillary number $Ca = 0.05$. Note that the three-dimensional capsule views presented in this paper were derived from the actual spectral grid by spectrally interpolating to a denser grid (with $N_B = 25$ spectral points along each direction of each spectral element) and using orthographic projection in plotting.

At this low flow rate, the capsule appears like a bullet if seen from the front as in figure 2(a), i.e. the capsule downstream edge has become more pointed while its upstream edge has become flatter but remains convex. Thus, this capsule view resembles the bullet-like shape observed in square and circular solid ducts at low flow rates [18, 25]. The explanation for the common behavior is straightforward if we consider the balance of the deforming hydrodynamic forces with the restoring membrane tension forces. That is, to balance the deforming hydrodynamic forces, the capsule tries to increase its downstream curvature and decrease its upstream curvature so that the total restoring tension force on the membrane is increased. In essence, this capsule deformation results from the curvature term in the membrane traction, Eq.(1), as we identified in our earlier studies on capsule dynamics in planar extensional flows or in square channels [11, 12, 18].

The effects of the channel's cross-section asymmetry is seen from the other two directions, i.e. in figure 2(b, c). Owing to the channel's rectangular cross-section, the capsule is extended along the less-confined width direction, and from the top, its shape appears like a pebble as seen in figure 2(b). The capsule's width extension is also shown from the upstream direction where its shape appears like a flattened ellipse, i.e. rectangular-like with rounded corners. A lateral dimple with negative curvature has also been developed at the capsule's upstream portion where the membrane is in proximity with the channel's top and bottom walls (owing to the strong local normal lubrication forces), as shown at the right of figure 2(b). We emphasize that in the present study, the membrane tensions at steady state are always positive owing to prestress and thus negative curvature or dimples on the capsule interface cannot result from local negative tensions, i.e. interfacial dimples are pure hydrodynamic effects.

Clearly, the non-axisymmetric channel's cross-section has resulted in a highly non-axisymmetric, fully three-dimensional capsule shape which cannot be described from single-view observations as commonly happens in microfluidic channels or based on axisymmetric or two-dimensional computations.

By increasing the flow rate to $Ca = 0.2$, the capsule appears like a parachute from a front view as seen in figure 3(a). The stronger hydrodynamic forces cause the capsule to obtain a more pointed downstream edge and a concave upstream edge (with a negative curvature). This shape increases the membrane interfacial forces required to balance the increased hydrodynamic forces as also happens in square and circular ducts [18, 25].

However the capsule appears quite different if seen from top; the capsule shape seems circular-like as shown at the left of figure 3(b). In essence, the capsule has obtained now a pebble shape flattened along the channel width with two wide upstream tails. Seeing the capsule from the upstream direction in figure 3(c) reveals a greater width extension (compared to that for $Ca = 0.05$); however this view does not provide information on the sign of the rear curvature, i.e. if the capsule rear is convex or concave.

The effects of the flow rate on the capsule shape is clearly shown in figure 4 where we plot the capsule profiles (i.e. the cross-section of the capsule surface with the planes $y = 0$, $z = 0$ and $x = 0$) for capillary number $Ca = 0.05, 0.1, 0.2$. As the flow rate increases, the thickness h of the lubrication film between the capsule surface and the solid walls in the more confined channel's height is increased as seen in figure 4(a). This helps in the steady-state

equilibrium by reducing the strong local lubrication forces in the flow direction which (per volume) scale as

$$F_f^x \sim \mu \frac{d^2 u_x}{dz^2} \sim \mu \frac{U_x}{h^2} \quad (4)$$

where U_x is the capsule velocity. (See also section 5 in Ref.[18] and section 3 in Ref.[31].) For the highest flow rate studied, i.e. $Ca = 0.2$, the capsule's concave upstream edge is accompanied with two pointed rear tails (close to the solid walls) as shown in figure 4(a), and thus with the development of small local length scales.

It is of interest to note that the capsule shape is flattened along the channel's top or bottom walls in the capsule's upstream portion (i.e. from its centroid to its rear end) as seen in figure 4(c). On the other hand, the capsule's downstream portion is ellipsoidal-like especially close to its front edge. Thus the capsule shape is fully three-dimensional mainly in its upstream portion.

We conclude this section by stating that the flow rate effects we have identified for the capsule size $a = 1.1$ (i.e. slightly higher than the channel height ℓ_c) are identical to those for moderate-size capsules (e.g. size $a = 0.8, 0.9$) and thus these results are omitted.

A. Comparison with droplet dynamics

Owing to the rather unexpected effect of the flow rate on the capsule shape in a rectangular microchannel (i.e. to increase the capsule extension in the less-confined lateral direction), we proceed now by investigating the corresponding effects on the droplet deformation. A droplet is also a deformable object but, in contrast to a capsule, its surface tension γ remains constant. Thus, our goal here is to clarify the similarities and differences of droplet and capsule dynamics in rectangular microchannels.

To determine the droplet dynamics, we utilized both our explicit and the fully-implicit time-integration spectral algorithms for droplets [9, 34]. Our convergence runs showed that our droplet dynamics results were determined with at least 3 significant-digit accuracy. We emphasize that our spectral boundary element method has also been used to study droplet motion in solid channels of different cross-sections and we have made successful comparisons with published experimental and computational results [20].

For droplet motion, the capillary number is defined as $Ca = \mu U / \gamma$ where γ is the droplet's surface tension. In addition, the viscosity ratio λ does affect the droplet shape even at steady state owing to the non-zero inner circulation. As the viscosity ratio λ increases, the droplet deformation increases owing to the higher inner hydrodynamic forces. Since our droplet results for $\lambda = 1, 5$ are qualitatively similar, we only present our results for $\lambda = 1$ droplets.

As seen in figure 5(a) the droplet's $y = 0$ profile changes from bullet-like to parachute-like as the flow rate increases, similarly to what happens for a capsule shown earlier in figure 4(a). Thus at high enough Ca , the droplet's rear edge also becomes concave with a negative curvature. However, the droplet does not develop very pointed tails at its upstream section in proximity to the solid walls. Furthermore, the flow rate increase causes a significant droplet extension along the flow direction which results in a different $z = 0$ profile (compared to that for a capsule) as shown in figure 5(b). Even the droplet's $x = 0$ profile along the channel cross-section is not so flattened but it is more elliptical as seen in figure 5(c).

The significant differences in the shape of capsules and droplets are clearly shown in figure 6 where we plot three-dimensional views of the droplet shape for capillary number $Ca = 0.3$. This flow rate causes the same rear concavity (i.e. the same negative curvature at the rear edge) as for the capsule with $Ca = 0.2$ shown earlier in figure 3.

Our capsule-vs-droplet conclusions are quantified in figures 7 and 8 where we plot the steady-state lengths and the tail curvature as a function of the capillary number Ca for these two deformable particles.

Figure 7 shows that as the flow rate increases, both deformable particles are restricted similarly along the channel's more confined height direction, i.e. their height L_z is reduced similarly. However, to accommodate the higher hydrodynamic forces, the droplet extends mainly along the flow direction (i.e. higher length L_x) while the capsule extends rather unexpectedly along the channel's less confined width direction (i.e. higher width L_y).

Figure 8 shows the steady-state maximum curvature $\mathcal{C}_{xz}^{max}$ as a function of the flow rate for the two soft particles. Observe that $\mathcal{C}_{xz}^{max}$ is a line curvature, determined along the interfacial cross-section with the $y = 0$ plane, and takes on positive values for the spherical quiescent shape where $\mathcal{C}_{xz}^{max} = a^{-1}$. Thus, for the problem studied in this paper, this curvature represents the local curvature at the interfacial tail developed in the particle upstream portion near the channel walls, as seen in figures 4(a) and 5(a). Clearly, the tail curvature is much higher for a capsule than for a droplet, and thus at their rear tails capsules develop pointed local areas characterized by a local length scale (or radius of curvature) which is of $O(30)$ smaller than the capsule size.

B. Reasoning for the capsule deformation

The explanation for the different shape development between a droplet and a capsule in a rectangular channel lies on the tension development on the capsule membrane. Excluding the prestress tension τ_0 , a capsule does not have membrane tensions at the quiescent spherical condition. Membrane tensions develop as the capsule deforms due to the external flow; they may grow locally under extension dynamics or decay under local compression.

In a rectangular channel, a soft particle (with a size comparable to the channel's height) causes a significant flow blocking along the channel height; however its blocking is much smaller along the channel width. As the flow rate increases, the particle height L_z is decreased owing to the stronger normal hydrodynamic forces in the small gap between the particle surface and the channel's top and bottom walls.

For a droplet with constant surface tension γ , the increased flow rate and the height reduction L_z cause a significant extension L_x along the flow direction, i.e. both the particle's height reduction and length extension are pure hydrodynamic effects. However, the droplet's constant surface tension creates strong lateral interfacial forces which are able to balance the lateral flow forces; thus the droplet is not extended much along its width.

For the case of a capsule, the increased flow rate and the height reduction cause also the capsule to extend along the flow direction. Thus, along its lateral cross-section, the membrane develops stabilizing tensions pointing in the flow direction. At the same time, the flow forces also extend the capsule along the less-confined width direction owing to the initial weak lateral tensions. This lateral extension results in tensions development (pointing in the lateral direction) while the width extension ceases when the lateral membrane tensions grow strong enough to withstand the deforming hydrodynamic forces.

Therefore, both the capsule's length and width extensions contribute to increased membrane tensions and thus to the interfacial stability. The greater width extension compared to the length extension reveals the membrane preference in developing strong lateral tensions and clearly shows that the capsule dynamics is a three-dimensional phenomenon. In essence, the capsule's width extension resembles the lateral extension of capsules in planar extensional flows which also builds strong lateral tensions [11, 12].

To support our reasoning, in figure 9(a) we plot the steady-state distribution of the two principal tensions, τ_F^P and τ_L^P , on the membrane cross-section with the plane $x = x_\zeta$ i.e. the x -coordinate of the capsule centroid. Observe that the tensions τ_F^P point mainly towards the flow direction while the tensions τ_L^P point mainly in the lateral direction. Owing to the capsule's flow extension, the associated tensions τ_F^P have been increased significantly with respect to the prestress tension τ_0 of the spherical shape. However, the capsule's width extension also creates local extension on the membrane in the lateral direction. Thus the lateral tensions τ_L^P are also increased everywhere along the capsule lateral cross-section and especially at the locations of the highest width extension, as seen in figure 9(a).

Even though the flow-oriented tensions τ_F^P are higher than the laterally-oriented tensions τ_L^P , both of them contribute significantly to the capsule stability since the membrane forces also include the associated interfacial curvatures. That is, as suggested by the curvature term in Eq.(1), the restoring membrane normal stress f_m^n along the capsule's lateral cross-section can be approximated by

$$f_m^n \sim \tau_F^P \mathcal{C}_F + \tau_L^P \mathcal{C}_L \quad (5)$$

where $\mathcal{C}_F$ and $\mathcal{C}_L$ are the interfacial curvatures along the flow and lateral directions, respectively. In general, $\mathcal{C}_L > \mathcal{C}_F$ and thus both normal stress components contribute to the capsule stability along its cross-section.

It is of interest to note that in a square or cylindrical channel, the required tensions development results only from the capsule extension along the flow direction, i.e. the only direction which is not confined by the solid walls. In particular, the lateral membrane tensions are decreased owing to the compression dynamics associated with the reduction of the capsule's lateral dimensions in these solid ducts. Both effects on the cross-section principal tensions are shown in figure 9(b) based on the results of our earlier work for capsule motion in a square channel [18]. This constitutes a major difference in the membrane stability for a capsule moving in an asymmetric or symmetric solid duct.

Note that in figure 9, the sinusoidal-like variation of the membrane principal tensions, τ_F^P and τ_L^P , with the azimuthal angle ϕ results from the fact that, in a square or rectangular channel, the local flow stresses near the middle of the channel walls are different than those at the channel corners. This creates varying local extension on the capsule membrane and thus varying tensions with the azimuthal angle ϕ . Owing to the cross-section asymmetry, the period of this variation in a rectangular channel is obviously twice that in a square channel.

The membrane's tension evolution also explains the much more pointed tails developed at the upstream portion of the capsule compared to the droplet tails. For both soft particles, the restoring tension forces (which are required to balance the deforming flow forces) result from both the local tension and the local curvature, e.g. the curvature term in Eq.(1) or Eq. (5). Our computations show that at the capsule tail, local compression occurs and thus there

the membrane tensions become weaker as the flow rate increases. Therefore, the capsule needs to increase significantly the tail curvature to produce a strong enough local interfacial force. On the other hand, on the droplet interface, the surface tension γ remains constant and thus a sufficiently strong local surface tension force results from a smaller local curvature.

4. EFFECTS OF CAPSULE SIZE

In this section, we collect our steady-state results as a function of the capsule size a , for capsule motion in a rectangular microchannel with aspect ratio $\ell_y = 2\ell_z$ and capillary number $Ca = 0.2$. In particular, we consider Skalak capsules with $C = 1$ and $\alpha_p = 0.05$, for size $a = 0.1, 0.2, \dots, 1.1$, i.e. much smaller up to slightly higher than the channel height ℓ_z .

The effects of the capsule size a on the the steady-state capsule dimensions and profiles are shown in figures 10 and 11, respectively. For small capsule sizes $a \lesssim 0.4$, the hydrodynamic forces associated with the flow rate $Ca = 0.2$ are weak and cause minimal deformation. Thus the capsule remains nearly spherical with $L_x \approx L_y \approx L_z \approx 2a$ and circular profiles. For moderate capsule sizes $0.5 \lesssim a \lesssim 0.7$, the length L_x and the height L_z of the capsule are practically equal to their undisturbed value $2a$. However, now the hydrodynamic forces are stronger owing to the smaller gap between the capsule interface and the solid walls, and cause the capsule to deform into a bullet-like shape with a pointed downstream edge and a flattened, convex rear as shown in figure 11(a). Most important, the capsule extends in the less-confined channel width and thus the capsule width L_y becomes larger than its other two dimensions as seen in figure 10. For higher capsule sizes $a \gtrsim 0.8$, the capsule surface is in proximity to the channel's top and bottom walls. Thus, the capsule height L_z is restricted owing to the strong normal lubrication forces in the narrow gap between the capsule surface and the solid walls. For these capsules, the capsule length L_x starts to increase in order to accommodate the capsule's larger volume; however it always remains smaller than the capsule width L_y as seen in figure 10.

Looking at the $x = 0$ profile of the different capsules included in figure 11(c), we observe that the capsule remains axisymmetric until $a \approx 0.4$. At higher sizes, the increase of the capsule width L_y causes the capsule's $x = 0$ profile to become rectangular-like with rounded corners, especially for the larger capsules we studied where the capsule interface becomes parallel to the channel's top and bottom walls, as seen in figure 11(c). Therefore, for moderate and especially for large sizes, the capsule deformation is highly affected by the duct's rectangular cross-section and thus the capsule shape deviates significantly from that in a square or cylindrical channel [18, 25].

As the capsule size increases, the smaller gap between the capsule and the channel's top and bottom walls creates stronger hydrodynamic forces. To increase the downstream membrane forces needed for interfacial balance, the capsule front becomes more pointed along the $y = 0$ profile and thus the downstream edge curvature $\mathcal{C}_{xz}^d$ is increased, as shown in figure 11(a) and 12(a). However, the edge curvature $\mathcal{C}_{xy}^d$ along the $z = 0$ profile remains practically unchanged as seen in figure 12(a) since the capsule front does not cause significant flow blocking along the (wider) channel width.

The three deformation regimes identified based on the capsule dimensions result in three distinct regimes with respect to the shape of the capsule rear. For small capsule sizes $a \lesssim 0.4$, the capsule rear is spherical-like as shown in figure 11(a, b). For moderate capsule sizes $0.5 \lesssim a \lesssim 0.7$, the increased hydrodynamic forces make the capsule rear flatter but still convex in both the front and top view, i.e. the $y = 0$ and $z = 0$ profiles, as seen in figure 11(a, b).

Therefore, both rear curvatures $\mathcal{C}_{xz}^u$ and $\mathcal{C}_{xy}^u$ decrease but remain positive; see figure 12(a). This increases the net membrane forces on the capsule by reducing the adverse upstream

membrane force. In essence, the capsule shape is a flattened bullet, extended along the channel width.

For higher capsule sizes $a \gtrsim 0.8$, to account for the stronger lubrication forces in the narrow gap along the channel height, the capsule obtains a parachute-like front view (or $y = 0$ profile) with a concave upstream shape which produces a positive upstream membrane force. (See figures 11(a) and 12(a).) However, along the less-confined channel width, the capsule rear still appears like a bullet, with a convex shape and positive curvature $\mathcal{C}_{xy}^u$, owing to the smaller deforming hydrodynamic forces along this direction. Therefore for these sizes, the capsule has obtained a flattened pebble shape with two pointed upstream tails.

For the larger capsules studied in this work, the strong lubrication forces in the narrow gap between the capsule surface and the channel's top and bottom walls, cause the development of upstream pointed tails (in proximity to the solid walls) as shown in the profiles included in figure 11(a). Thus the tail curvature, represented by the curvature $\mathcal{C}_{xz}^{max}$ in figure 12(b), increases significantly with the capsule size. As explained in section 3B, these pointed tails result from the decrease of the local membrane tensions, and thus the need for the capsule to increase the tail curvature significantly to produce strong enough local interfacial forces.

5. EFFECTS OF MEMBRANE HARDNESS, PRESTRESS AND CHANNEL ASYMMETRY

In the section we consider briefly the effects of the membrane hardness, capsule prestress and channel's aspect ratio on the deformation of the elastic capsule. The goal of this section is to investigate the effects of these parameters on the main conclusion of this work, i.e. the fact that a capsule in a rectangular channel extends mainly along the less-confined channel width.

Figure 13 focuses on the deformation of strain-hardening Skalak capsules with increasing membrane hardness (i.e. $C = 0.5, 1, 2, 5$) and the same initial prestress tension $\tau_0/G_s \approx 0.3401$. As the membrane hardness increases, its increased area-dilatation modulus creates stronger locally-isotropic tensions and thus tries to make the deformed capsule shape more axisymmetric-like. (See the isotropic term containing the membrane hardness C at the right-hand-side of the Skalak *et al.* law in Eq.(2).) Thus, as seen in figure 13(b), at steady state both the reduction of the capsule height L_z and the increase of its width L_y are decreased with C , and thus the capsule length L_x is increased to accommodate the same capsule volume. Nevertheless, even the most strain-hardening Skalak capsule we studied shows mainly an extension along the less-confined channel width and thus an increased width L_y .

As the capsule prestress parameter α_p increases, the increased prestress tension τ_0 acts as a additional restoring interfacial force and thus it reduces the deformation of the capsule for a given flow rate Ca , as shown in figure 14. However, the capsule asymmetry along the two channel's lateral directions is preserved while the capsule is mainly extended along the less-confined channel width. It is of interest to note that the reduction (or complete elimination) of the capsule prestress increases significantly the capsule's asymmetric deformation and thus the growth of the capsule width L_y (relatively to its height L_z). Via this lateral extension, the capsule builds strong lateral membrane tensions necessary for interfacial stability, as discussed in session 3B.

We conclude this session by stating that the capsule's lateral extension is also present in rectangular channels with varying aspect ratio ℓ_y/ℓ_z , as shown in figure 15. Therefore, this property represents a general feature of the deformation of elastic strain-hardening capsules in rectangular channels with comparable sizes, a and ℓ_z . In essence, in these duct flows,

capsules show a different deformation compared to droplets with constant surface tension (which extend mainly along the flow direction) and the vesicles which extend along the more-confined channel height [6].

6. CONCLUSIONS

In this paper we have investigated computationally the deformation of an elastic capsule in a rectangular microfluidic channel and compared it with that of a droplet. In particular, we have considered an elastic capsule made of a strain-hardening membrane (following the Skalak *et al.* constitutive law) with comparable shearing and area-dilatation resistance. Our investigation involves low-to-moderate flow rates with capillary number $Ca = O(0.1)$ and capsule sizes a comparable or smaller to the channel's narrowest direction (height). This study is motivated by a wide range of applications including drug delivery, cell sorting and cell characterization devices, microcapsule fabrication, determination of membrane properties, and of course its similarity to blood flow in vascular capillaries.

Our investigation shows that the capsule shape in a rectangular microfluidic channel is quite different than that in a square or cylindrical channel where the capsule extends along the flow direction obtaining a bullet-like or parachute-like shape [18, 25]. By contrast, in a rectangular channel the capsule extends mainly along the less-confined lateral direction of the channel cross-section (i.e. its width) obtaining a pebble-like shape. The different shape evolution in these two types of solid channels results from the different tension development on the capsule membrane required for interfacial stability. In a square or cylindrical channel, the required tensions development results only from the capsule extension along the flow direction, i.e. the only direction which is not confined by the solid walls. However, in a rectangular microchannel, the capsule lateral extension also results in tensions development, and thus both the capsule's flow and lateral extensions contribute to the interfacial stability. The greater width-to-length extension of the capsule in a rectangular channel reveals the membrane preference in developing strong lateral tensions and clearly shows that the capsule dynamics is a three-dimensional phenomenon [12].

Therefore, the channel's cross-section asymmetry results in a highly non-axisymmetric, fully three-dimensional capsule shape (as shown in figures 2 and 3), which cannot be described from single-view observations as commonly happens in microfluidic experiments or based on axisymmetric or two-dimensional computations. It is of interest to note that seeing the capsule only from the channel height (as it may happen in a microfluidic experiment) provides misleading information since from this view the capsule still resembles a bullet or a parachute. To overcome this issue, experimental studies may work with two sets of rectangular microfluidic channels so that they are able to observe the soft particles from both the channel's width and height.

In addition, our work shows that the capsule deformation in a rectangular microchannel is different from that of droplets with constant surface tension (which extend mainly along the flow direction) and of vesicles which extend along the more confined channel height owing to the development of a four-vortex pattern on the fluid-incompressible vesicle membrane [6]. In essence, our study highlights the different stability dynamics associated with these three types of interfaces, i.e. constant tension interface of a droplet, capsule membrane (with comparable shearing and area-dilatation resistance), and the local-incompressible vesicle membrane with no shearing resistance.

It is of interest to note that our conclusions are not restricted to artificial capsules but should also represent physiological capsules, such as erythrocytes, for the same physical reasons. For example, in their experimental study on the viscoelasticity of the erythrocyte's membrane, Tomaiuolo *et al.* [33] reported that in PDMS rectangular microfluidic channels,

erythrocytes obtain a more flattened shape elongated along the less-confined channel's width. (See also the experimental photos in figure 6(a) of the earlier study.) We note that the erythrocyte membrane consists of an outer lipid bilayer (which is essentially a two-dimensional incompressible fluid with no shearing resistance as in vesicles) and an underlying spectrin skeleton (which exhibits shearing and area-dilatation resistance like the elastic membrane of common artificial capsules) [13, 16, 30]. Therefore, our findings suggest that the similar erythrocyte deformation in rectangular microchannels (and more general in asymmetric vessels) results from the erythrocyte's inner spectrin skeleton rather than from its outer lipid bilayer.

Acknowledgments

This work was supported in part by the National Science Foundation and the National Institutes of Health. Most computations were performed on multiprocessor computers provided by the Extreme Science and Engineering Discovery Environment (XSEDE) which is supported by the National Science Foundation.

References

1. Abkarian M, Faivre M, Horton R, Smistrup K, Best-Popescu CA, Stone HA. Cellular-scale hydrodynamics. *Biomed Mater*. 2008; 3 034011(1–13).
2. Alexeev A, Balazs AC. Designing smart systems to selectively entrap and burst microcapsules. *Soft Matter*. 2007; 3:1500–1505.
3. Antia M, Herricks T, Rathod PK. Microfluidic modeling of cell-cell interactions in malaria pathogenesis. *PLoS Pathog*. 2007; 3:0939–0948.
4. Baroud CN, Gallaire F, Dangla R. Dynamics of microfluidic droplets. *Lap Chip*. 2010; 10:2032–2045.
5. Chabert M, Viovy J-L. Microfluidic high-throughput encapsulation and hydrodynamic self-sorting of single cells. *Proc Natl Acad Sci*. 2008; 105:3191–3196. [PubMed: 18316742]
6. Coupier G, Farutin A, Minetti C, Podgorski T, Misbah C. Shape Diagram of Vesicles in Poiseuille Flow. *Phys Rev Lett*. 2012; 108:178106. [PubMed: 22680911]
7. Cranston HA, Boylan CW, Carroll GL, Suter SP, Williamson JR, Gluzman IY, Krogstad DJ. *Plasmodium falciparum* maturation abolishes physiologic red cell deformability. *Science*. 1984; 223:400–403. [PubMed: 6362007]
8. Dendukuri D, Hatton TA, Doyle PS. Synthesis and self-assembly of amphiphilic polymeric microparticles. *Langmuir*. 2007; 23:4669–4674. [PubMed: 17402702]
9. Dimitrakopoulos P. Interfacial dynamics in Stokes flow via a three-dimensional fully-implicit interfacial spectral boundary element algorithm. *J Comp Phys*. 2007; 225:408–426.
10. Dimitrakopoulos P. Analysis of the variation in the determination of the shear modulus of the erythrocyte membrane: Effects of the constitutive law and membrane modeling. *Phys Rev E*. 2012; 85:041917.
11. Dodson WR III, Dimitrakopoulos P. Spindles, cusps and bifurcation for capsules in Stokes flow. *Phys Rev Lett*. 2008; 101:208102. [PubMed: 19113382]
12. Dodson WR III, Dimitrakopoulos P. Dynamics of strain-hardening and strain-softening capsules in strong planar extensional flows via an interfacial spectral boundary element algorithm for elastic membranes. *J Fluid Mech*. 2009; 641:263–296.
13. Dodson WR III, Dimitrakopoulos P. Tank-treading of erythrocytes in strong shear flows via a non-stiff cytoskeleton-based continuum computational modeling. *Biophys J*. 2010; 99:2906–2916. [PubMed: 21044588]
14. Fedosov DA, Lei H, Caswell B, Suresh S, Karniadakis GE. Multiscale modeling of red blood cell mechanics and blood flow in malaria. *PLoS Comput Biol*. 2011; 7:e1002270. [PubMed: 22144878]
15. Fiddes LK, Young EWK, Kumacheva E, Wheeler AR. Flow of microgel capsules through topographically patterned microchannels. *Lab Chip*. 2007; 7:863–867. [PubMed: 17594005]

16. Hnon S, Lenormand G, Richert A, Gallet F. A new determination of the shear modulus of the human erythrocyte membrane using optical tweezers. *Biophys J*. 1999; 76:1145–1151. [PubMed: 9916046]
17. Jiang K, Xue C, Arya C, Shao C, George EO, DeVoe DL, Raghavan SR. A new approach to in-situ “micromanufacturing”: microfluidic fabrication of magnetic and fluorescent chains using chitosan microparticles as building blocks. *Small*. 2011; 7:2470–2476.
18. Kuriakose S, Dimitrakopoulos P. Motion of an elastic capsule in a square microfluidic channel. *Phys Rev E*. 2011; 84:011906.
19. Leclerc E, Kinoshita H, Fujii T, Barths-Biesel D. Transient flow of microcapsules through convergent-divergent microchannels. *Microfluid Nanofluid*. 2012; 12:761– 770.
20. Lee, MS. MS thesis. University of Maryland; 2010. Computational studies of droplet motion and deformation in a microfluidic channel with a constriction.
21. Lensen D, Breukelen KV, Vriezema DM, Hest JCMV. Preparation of biodegradable liquid core PLLA microcapsules and hollow PLLA microcapsules using microfluidics. *Macromol Biosci*. 2010; 10:475–480. [PubMed: 20336699]
22. Popel AS, Johnson PC. Microcirculation and Hemorheology. *Annu Rev Fluid Mech*. 2005; 37:43–69. [PubMed: 21151769]
23. Pozrikidis, C., editor. Modeling and Simulation of Capsules and Biological Cells. Chapman and Hall; London: 2003.
24. Prevot M, Cordeiro AL, Sukhorukov GB, Lvov Y, Besser RS, Mhwald H. Design of a microfluidic system to investigate the mechanical properties of layer-by-layer fabricated capsules. *Macromol Mater Eng*. 2003; 288:915–919.
25. Risso F, Coll-Pailot F, Zagzoule M. Experimental investigation of a bioartificial capsule flowing in a narrow tube. *J Fluid Mech*. 2006; 547:149–173.
26. Seiffert S, Thiele J, Abate AR, Weitz DA. Smart microgel capsules from macromolecular precursors. *J Am Chem Soc*. 2010; 132:6606–6609. [PubMed: 20397695]
27. Shelby JP, White J, Ganesan K, Rathod PK, Chiu DT. A microfluidic model for single-cell capillary obstruction by *Plasmodium falciparum* infected erythrocytes. *Proc Natl Acad Sci USA*. 2003; 100:14618–14622. [PubMed: 14638939]
28. Skalak R, Branemark P-I. Deformation of red blood cells in capillaries. *Science*. 1969; 164:717–719. [PubMed: 5778020]
29. Skalak R, Tozeren A, Zarda RP, Chien S. Strain energy function of red blood cell membranes. *Biophys J*. 1973; 13:245–264. [PubMed: 4697236]
30. Skalak R, zkaya N, Skalak TC. Biofluid Mechanics. *Annu Rev Fluid Mech*. 1989; 21:167–204.
31. Stone HA. Interfaces: in fluid mechanics and across disciplines. *J Fluid Mech*. 2010; 645:1–25.
32. Teh SY, Lin R, Hung LH, Lee AP. Droplet microfluidics. *Lab Chip*. 2008; 8:198–220. [PubMed: 18231657]
33. Tomaiuolo G, Barra M, Preziosi V, Cassinese A, Rotolid B, Guido S. Microfluidics analysis of red blood cell membrane viscoelasticity. *Lab Chip*. 2011; 11:449–454. [PubMed: 21076756]
34. Wang Y, Dimitrakopoulos P. A three-dimensional spectral boundary element algorithm for interfacial dynamics in Stokes flow. *Phys Fluids*. 2006; 18 082106(1–16).
35. Wang Y, Dimitrakopoulos P. Low-Reynolds-number droplet motion in a square microfluidic channel. *Theor Comput Fluid Dyn*. 2012; 26:361–379.

FIG. 1.
An elastic capsule flowing at the centerline of a rectangular microchannel.

FIG. 2. Steady-state shape of a Skalak capsule with $C = 1$, $\alpha_p = 0.05$ and size $a = 1.1$ in a rectangular microchannel, for capillary number $Ca = 0.05$. The capsule shape is plotted as seen from (a) the negative y -axis, (b) the positive z -axis and slightly askew from it, and (c) the negative x -axis.

FIG. 3. Steady-state shape of a Skalak capsule with $C = 1$, $\alpha_p = 0.05$ and size $a = 1.1$ in a rectangular microchannel, for capillary number $Ca = 0.2$. The capsule shape is plotted as seen from (a) the negative y -axis, (b) the positive z -axis and slightly askew from it, and (c) the negative x -axis.

FIG. 4.

Steady-state profile for a Skalak capsule with $C=1$, $\alpha_p=0.05$ and size $a=1.1$ in a rectangular microchannel, for capillary number $Ca=0.05, 0.1, 0.2$. Capsule profile, i.e. interface intersection with the plane (a) $y=0$, (b) $z=0$, and (c) $x=0$. All profiles are shown with centroid $\mathbf{x}_c = \mathbf{0}$.

FIG. 5. Steady-state profile for a droplet with viscosity ratio $\lambda = 1$ and size $a = 1.1$ in a rectangular microchannel, for capillary number $Ca = 0.05, 0.1, 0.2, 0.3$. Droplet profile, i.e. interface intersection with the plane (a) $y = 0$, (b) $z = 0$, and (c) $x = 0$. All profiles are shown with centroid $\mathbf{x}_c = \mathbf{0}$.

FIG. 6. Steady-state shape of a droplet with viscosity ratio $\lambda = 1$ and size $a = 1.1$ in a rectangular microchannel, for capillary number $Ca = 0.3$. The droplet shape is plotted as seen from (a) the negative y -axis, and (b) the positive z -axis and slightly askew from it.

FIG. 7.

Steady-state projection lengths, L_x , L_y and L_z , (scaled with the length $2a$ of the undisturbed spherical shape), of (a) a Skalak capsule with $C=1$ and $\alpha_p=0.05$, and (b) a droplet with viscosity ratio $\lambda=1$, as a function of the capillary number Ca for size $a=1.1$ in a rectangular microchannel. These lengths are determined as the maximum distance of the deformable interface in the x , y and z directions.

FIG. 8.

Steady-state maximum curvature $\mathcal{C}_{xz}^{max}$ along the $y=0$ profile, for a Skalak capsule with $C=1$ and $\alpha_p=0.05$, and for a droplet with viscosity ratio $\lambda=1$, as a function of the capillary number Ca for size $a=1.1$ in a rectangular microchannel. The curvatures are scaled with the curvature of the undisturbed spherical shape.

FIG. 9.

Steady-state distribution of the two principal tensions, τ_F^P and τ_L^P , among the spectral discretization points, on the membrane cross-section with the plane $x = x_0$, as a function of the azimuthal angle ϕ (measured in degrees), with respect to the positive y -direction. For a Skalak capsule with $C = 1$, $\alpha_p = 0.05$ and size $a = 1.1$ moving in (a) a rectangular channel with aspect ratio $\ell_y/\ell_z = 2$ and $Ca = 0.2$, and (b) a square channel with $Ca = 0.1$. Also included as a horizontal line is the (constant) tension distribution τ_0 due to prestress.

FIG. 10. Steady-state capsule lengths, L_x , L_y and L_z , as a function of the capsule's size a for a Skalak capsule with $C = 1$, $\alpha_p = 0.05$ and capillary number $Ca = 0.2$, in a rectangular microchannel. The lengths are scaled with the length $2a$ of the undisturbed spherical shape.

FIG. 11. Steady-state profile for a Skalak capsule with $C = 1$, $\alpha_p = 0.05$ and capillary number $Ca = 0.2$, in a rectangular microchannel, for capsule size $a = 0.4, 0.6, 0.7, 0.8, 0.9, 1, 1.1$. Capsule profile, i.e. interface intersection with the plane (a) $y = 0$, (b) $z = 0$, and (c) $x = 0$. All profiles are shown with centroid $\mathbf{x}_c = \mathbf{0}$.

FIG. 12.

Steady-state curvatures as a function of the capsule size a for a Skalak capsule with $C=1$, $a_p=0.05$ and capillary number $Ca=0.2$, in a rectangular microchannel. (a) Edge curvature along the $y=0$ and $z=0$ profile. Downstream edge: $\mathcal{C}_{xz}^d$ and $\mathcal{C}_{xy}^d$; upstream edge: $\mathcal{C}_{xz}^u$ and $\mathcal{C}_{xy}^u$. (b) Maximum curvature $\mathcal{C}_{xz}^{max}$ along the $y=0$ profile. The curvatures are scaled with the curvature of the undisturbed spherical shape.

FIG. 13.

Transient evolution of the lengths, L_x , L_y and L_z for a Skalak capsule with size $a = 0.8$ and capillary number $Ca = 0.1$ in a rectangular microchannel. The membrane hardness is $C = 0.5, 1, 2, 5$ and the prestress $\alpha_p = 0.0732, 0.05, 0.0311, 0.0147$, respectively, so that all capsules have the same initial prestress tension $\tau_0/G_s \approx 0.3401$. Capsule lengths: (a) L_x , and (b) L_y and L_z .

FIG. 14.

Transient evolution of the lengths, L_x , L_y and L_z for a Skalak capsule with $C = 1$, size $a = 0.8$ and capillary number $Ca = 0.1$ in a rectangular microchannel. The capsule prestress is $\alpha_p = 0.025, 0.03, 0.05, 0.1$ and thus the initial prestress tension is $\tau_0/G_s \approx 0.1597, 0.1941, 0.3401, 0.7716$. Capsule lengths: (a) L_x , and (b) L_y and L_z . For $\alpha_p = 0.025$ our computations cover up to time $t = 15$ where the steady state is well established.

FIG. 15. Transient evolution of the lengths, L_x , L_y and L_z for a Skalak capsule with $C = 1$, $\alpha_p = 0.05$ and size $a = 0.8$, for capillary number $Ca = 0.1$ in a rectangular microchannel with aspect ratio $\ell_y/\ell_z = 1.1, 1.25, 1.5, 2$. Capsule lengths: (a) L_x , and (b) L_y and L_z .

TABLE 1

Range of parameters studied in this work. The length scale is the channel's half-height ℓ_z , while if the channel's aspect ratio ℓ_y/ℓ_z is not specified, then our results are valid for $\ell_y/\ell_z = 2$.

Varying parameter	Fixed parameters
$Ca = 0.05-0.2$	$a = 0.6-1.1, C = 1, \alpha_p = 0.05$
$a = 0.1-1.1$	$Ca = 0.1, 0.2, C = 1, \alpha_p = 0.05$
$C = 0.5-5$	$a = 0.8, Ca = 0.1, \tau_0/G_s = 0.3401$
$\alpha_p = 0.025-0.1$	$a = 0.8, Ca = 0.1, C = 1$
$\ell_y/\ell_z = 1-6$	$a = 0.8, Ca = 0.1, C = 1, \alpha_p = 0.05$