Published in final edited form as:

Int J Consum Stud. 2013 July 1; 37(4): 433–441. doi:10.1111/ijcs.12012.

The Environmental Cost of Misinformation: Why the Recommendation to Use Elevated Temperatures for Handwashing is Problematic

Amanda R. Carrico¹, Micajah Spoden², Kenneth A. Wallston³, and Michael P. Vandenbergh⁴

Micajah Spoden: mspoden@mail.nur.utexas.edu; Kenneth A. Wallston: ken.wallston@vanderbilt.edu; Michael P. Vandenbergh: Michael.vandenbergh@vanderbilt.edu

¹Research Assistant Professor, Vanderbilt Institute for Energy and Environment, Climate Change Research Network

²Project Director, Youth Health Research Office, School of Nursing, University of Texas at Austin, NUR 3.422, 1700 Red River, Austin, TX 78701-1499, phone: 615-513-1404, fax: 512-232-7595

³Professor of Psychology in Nursing, Vanderbilt School of Nursing, Vanderbilt University. 461 21stAvenue South, Nashville, TN 37240, phone: 615-343-3317, fax: 615-343-2661

⁴Carlton Tarkington Professor of Law, Co-Director, Regulatory Program and Director, Climate Change Research Network, Vanderbilt University Law School. 131 21stAvenue South, Nashville, TN 37203. Phone: 615-322-6763, Fax: 615-322-6631

Abstract

Multiple government and health organizations recommend the use of warm or hot water in publications designed to educate the public on best practices for washing one's hands. This is despite research suggesting that the use of an elevated water temperature does not improve handwashing efficacy, but can cause hand irritation. There is reason to believe that the perception that warm or hot water is more effective at cleaning one's hands is pervasive, and may be one factor that is driving up unnecessary energy consumption and greenhouse gas emissions. We examine handwashing practices and beliefs about water temperature using a survey of 510 adults in the United States. The survey included measures of handwashing frequency, duration, the proportion of time an elevated temperature was used, and beliefs about water temperature and handwashing efficacy. We also estimate the energy consumed and resultant carbon dioxide equivalent emissions (CO₂eq) in the U.S. due to the use of elevated temperatures during handwashing. Participants used an elevated temperature 64% of the time, causing 6.3 million metric tons (MMt) of CO₂eq which is 0.1% of total annual emissions and 0.3% of commercial and residential sector emissions. Roughly 69% of the sample believed that elevated temperatures improve handwashing efficacy. Updating these beliefs could prevent 1 MMt of CO₂eq annually, exceeding the total emissions from many industrial sources in the U.S. including the Lead and Zinc industries. In addition to causing skin irritation, the recommendation to use an elevated temperature during handwashing contributes to another major threat to public health—climate change. Health and consumer protection organizations should consider advocating for the use of a “comfortable” temperature rather than warm or hot water.

Correspondence can be sent to Vanderbilt University, PMB 407702, 2301 Vanderbilt Place, Nashville, TN 37240-7702, phone: 615-322-9690, fax: 615-322-7012, amanda.carrico@vanderbilt.edu.

⁸We use the ISO conversion factor of 0.9478 British thermal units (Btu) per kilojoule.

Due to the growing cost of energy and increasing concerns over the environmental impact of energy production, energy conservation has become an increasing focus of businesses, consumers and consumer advocates around the world. Of particular concern is the growing body of work documenting the enormous economic and health threats posed by climate change (Intergovernmental Panel on Climate Change, 2007). To lessen these impacts, greenhouse gas (GHG) emissions must be quickly stabilized and drastically reduced over the coming decades. A recent report from a panel of the U.S. National Research Council of the National Academies (2010) recommended a 50–80% decrease of U.S. GHG emissions below 1990 levels by 2050 (America's Climate Choices Panel on Limiting the Magnitude of Climate Change, 2010). A more ambitious target of an 80 – 95% reduction by 2050 has been proposed in the European Union (European Commission, 2012). Efforts to improve conservation and efficiency within the household and commercial sectors will be critical to meeting these targets, and may represent one of the most cost-effective options available for achieving near-term emissions reductions (Bressand et al., 2007; Dietz et al., 2009; Gardner and Stern, 2008; Vandenbergh et al., 2008). As such, a challenge for researchers is to identify sources of emissions that can reduce consumer energy costs and contribute to the necessary level of reductions in GHG emissions.

A number of researchers and conservationists have turned to water use as one opportunity for reducing emissions (Biermayer, 2005; Clarke et al., 2009; Somner et al., 2008). The provision of clean water alone requires a substantial amount of energy to remove pathogens and to deliver water to the user's tap. The additional energy required to heat water accounts for approximately 15% of residential energy use in both the U.S. and European Union, second only to space heating and cooling (U.S. Environmental Protection Agency, n.d.; European Environment Agency, 2011). There are significant opportunities for reducing household energy use by reducing hot water consumption during routine activities such as laundry (e.g., Laitala, Boks and Kless, 2011; Laitala, Klepp and Boks, 2012). For example, Laitella et al. (2011) found that laundry done at 30° C cleans as effectively as laundry done at the more commonly used 40°C, uses nearly 30% less energy, and reduces wear and tear on clothing. Researchers at the University of Bonn have found that consumers who followed ten "Best Practice Tips" during manual dishwashing reduced their energy use during this activity by 70% (Fuss, Bornkessel, Mattern and Stamminger, 2011).

Relatively little attention has been given to handwashing as an opportunity for reducing energy consumption (for an exception, see Somner, et al. 2008). Although the amount of energy used for handwashing is relatively small in comparison to other water using behaviors, there is reason to believe that the amount of energy is inflated due to the misperception that warm or hot water improves the efficacy of washing ones hands. This is particularly true in North America and Western Europe, where there is a strong cognitive connection between water temperature and hygiene relative to other countries, such as Japan, where warm or hot water is used primarily for comfort (Wilhite, et al., 1996). Although the perception that hot water is more hygienic is based in some factual evidence, the literature reviewed below suggests that there are few, if any, hygienic benefits of using warm or hot water to wash ones hands. Despite this, well-intentioned public health advocates have perpetuated this perception by recommending to consumers that they wash their hands in warm or hot water, potentially driving up unnecessary energy consumption without providing health benefits to the consumer. In this study we examine Americans' perceptions of water temperature and handwashing efficacy, as well as self-reported handwashing practices. The potential reductions in energy use and GHG emissions that could be saved in the United States by updating these beliefs are estimated below. We conclude with recommendations for consumer advocates and health agencies.

Water Temperature and Handwashing

Washing one's hands may be the single most important means of preventing the spread of infectious disease and protecting families from illness. Multiple government and health organizations offer instructions for how to most effectively wash hands to eliminate pathogens. This typically includes the application of soap, vigorous rubbing for 15–20 seconds, rinsing, and drying with a towel or air dryer (Department of Health, England, 2007; European Centre for Disease Prevention and Control, n.d., U.S. Department of Health and Human Services, 2008). Although many prominent health organizations such as the World Health Organization, the US Centers for Disease Control, and Department of Health, England do not specify a water temperature in their instructions for handwashing, numerous other well-known organizations specifically recommend the use of “warm” or “hot” water. For example, on websites and pamphlets aimed at the general public, the US Food and Drug Administration (FDA), the American Society for Microbiology and Health Canada all recommend the use of an elevated water temperature¹. Not surprisingly, these recommendations have been cited by smaller public health departments and advocacy groups and have become the standard for acceptable or, in some cases, required handwashing practice. The 2005 U.S. FDA Food Code not only requires the use of warm water, but also requires handwashing sinks to reach a temperature of no less than 38°C (100°F) (U.S. Food and Drug Administration, 2005). Failure to meet these standards can result in the accumulation of violations and eventual closure of food establishments.

Despite what is commonly advocated, there are no known data to support the claim that water temperature is associated with handwashing efficacy. It is true that heat kills bacteria; however, the level of heat required to neutralize pathogens is beyond what is considered safe for prolonged human contact. Water considered “hot” for the purposes of handwashing has been estimated to be within the range of 40 to 55°C (104 – 131°F) (Herrmann et al., 1994; Michaels et al., 2001; Rothenborg et al., 1977). Although the high end of this estimate is sufficiently hot to neutralize some pathogens, it could not be sustained for a long enough period without causing serious harm. Common pathogens such as *Escherichia coli*, *Salmonella typhimurium* and *Klebsiella pneumoniae* stay alive at temperatures up to 55°C (131°F) for over ten minutes and *Staphylococcus aureus* would require at least 50 minutes of exposure at a temperature of 60°C (140°F) to be reduced to an immeasurable level (Angelotti et al., 1961; Spinks et al., 2006). By comparison, just 30 seconds of skin exposure to water heated to 55°C would cause deep second-degree burns, and water heated to 60°C could be tolerated for less than six seconds before causing serious harm.

It has also been claimed that higher water temperatures are more effective at removing bacteria-containing oil and dirt (U.S. Food and Drug Administration, n.d.). Price (1938) examined microbial counts after hand scrubbing at various water temperatures between

¹For example, the U.S. Department of Agriculture on its “Teamnutrition” website recommends washing hands under “warm running water” (http://teamnutrition.usda.gov/Resources/how_to_washhands.pdf), as does the American Society for Microbiology (http://www.microbeworld.org/images/stories/washup/downloads/2008handhygienedontgetcaught_000.pdf). Health Canada on its website “The Benefits of Hand Washing” recommends wetting and rinsing hands with “warm water” <http://www.hc-sc.gc.ca/hl-vs/iyh-vsv/diseases-maladies/hands-mains-eng.php#how>. The Iowa Department of Public Health recommends using soap and “warm or hot running water,” and states that “cold water and a quick rub” is not effective and that “you need to use warm water and soap to get the oil and germs off your skin” (www.idph.state.ia.us/adper/common/pdf/abx/tab2_handwashing.pdf). The US FDA recommends the use of “hot, soapy water” for adults and “warm, soapy water” for kids (http://www.fda.gov/ForConsumers/ByAudience/ForWomen/ucm118524.htm?utm_campaign=http://www.fda.gov/Food/ResourcesForYou/StudentsTeachers/ScienceandTheFoodSupply/ucm215837.htm). Similarly, multiple local- and state-level organizations including the New York State Department of Health (<http://www.health.ny.gov/publications/7096.pdf>), the Wisconsin Department of Health Services (<http://www.dhs.wisconsin.gov/communicable/resources/foodsafety/food.htm>), the City of Albuquerque (<http://www.cabq.gov/envhealth/foodsafety.html>) and the University of Arizona (extension.arizona.edu/sites/...edu/.../Proper%20Handwashing2.pdf) also recommend using hot water. Interestingly, the University of Arizona suggests a water temperature “as hot as you can stand it” and specifies a range of “100°F – 110°F” (38°C – 43°C).

24°C (75°F) and 56°C (133°F) and found no difference in the rate of germ removal. More recent studies using updated methods support Price's findings (Larson et al., 1980; Michaels et al., 2001; Michaels et al., 2002). Although some soap may emulsify better with warmer water, these gains appear to be overwhelmed by the process of scrubbing, rinsing and drying the hands. Michaels et al. conducted a series of studies in which soiled hands were washed with a common non-antibacterial soap under various temperature conditions between 4.4°C and 50°C (Michaels et al., 2001; Michaels et al., 2002). They found no significant differences in levels of bacterial reduction as a function of temperature. This procedure was repeated using four antibacterial soaps with different active ingredient and, although the level of bacterial reduction was slightly higher in the high temperature condition, no significant differences were found. These findings have led to the conclusion that warm water should not be advocated for its antimicrobial properties (Laestadius and Dimberg, 2005; World Health Organization, 2009).

Although there appear to be no direct health benefits associated with the use of elevated temperatures, indirect benefits may exist among those who find warmer temperatures more comfortable and may, therefore, wash their hands more frequently or for longer durations. However, advocating for the use of warm or hot water, rather than a "comfortable" temperature, may lead to the misperception that proper hygiene can only be achieved by using elevated temperatures. Perceptions of comfort may shift according to consumer preference and ambient temperature, and some consumers may be willing to sacrifice comfort in order to save money or reduce their environmental "footprint." There may also be negative health impacts of this recommendation. Advocating the use of elevated temperatures, particularly "hot" water, may lead some to choose temperatures that are higher than what is comfortable, potentially leading to scalding. Furthermore, elevated temperatures, even within a range that most would consider comfortable (i.e. 37°C vs. 40°C) can lead to skin irritation when paired with many common hand soaps (Clarys et al., 1997; Emilson et al., 1993; Ohlenschlaeger et al., 1996; Rothenborg et al., 1977). In addition to causing pain, the damage to the protective barrier of the skin that results can cause the skin to be less resistant to bacterial colonization. For example, nurses with irritated hands were significantly more likely to be colonized with a number of potentially harmful bacteria, including *Staphylococcus aureus* (Cook et al., 2007; Larson et al., 1998). Hand irritation is also a commonly cited reason among nurses for not washing their hands as often as recommended (Larson and Killien, 1982; Pittet et al., 1999).

Research Objectives and Study Overview

Previous research has found that, in some cases, well-intentioned behaviors based on misperceptions or outdated beliefs can lead to outcomes that are against the consumer's own economic interests and unnecessary environmental impacts (Carrico *et al.*, 2009). We examine beliefs regarding water temperature and hand hygiene using a survey of American adults. Perceptions of the cleaning benefits of various water temperatures are measured, and we examine how they relate to self-reported handwashing behavior. These measurements serve as the basis of an estimate of energy use and GHG emissions that result from the use of warm or hot water for handwashing in the United States.

Methods

Participants

Participants were adults (18 and over) living in the U.S. recruited during the spring of 2009 from an online research panel.² Of the 515 individuals who logged in to complete the survey, 510 provided usable data. Table 1 presents the demographic profile of this sample as compared to population estimates. The sample was representative with the exception of age.

Previous studies suggest there are few, if any, age differences in handwashing practices among adults (American Society for Microbiology, 2005, 2007); therefore, this sampling bias is considered trivial. In addition, food service workers were slightly under-represented and health care workers were slightly over-represented. However, the two groups combined (both are required to wash their hands more frequently than the general population) made up 11% of the sample as compared to 13% of the population.

Procedure

Prospective participants were invited via e-mail to participate in a study about handwashing. Those who agreed were directed to a website where they completed a survey regarding their typical handwashing practices, beliefs about the efficacy of various handwashing techniques, and attitudes towards handwashing. The survey took roughly 5 to 10 minutes to complete.

Measures

Demographic information—Information about the participant's age, sex, education and income were collected. Respondents reported their annual household income before taxes using one of six categories, "less than \$15,000," "\$15,000 – \$24,999," "\$25,000 – \$34,999," "\$35,000 – \$49,999," "\$50,000 – \$74,999" and "\$75,000 and above." Participants also indicated the highest level of education they had completed on a six-item response scale including, "less than high school degree," "high school degree," "some college/associate's degree," "college degree," "some post-graduate work," or "post-graduate degree."

Handwashing behavior—Participants indicated how many times during the previous 24 hours that they washed their hands (frequency) and the average time spent during each handwash (duration). The use of an elevated temperature during handwashing was classified as any time an individual selected the "warm" or "hot" option at the faucet. To measure this, participants were asked to indicate the proportion of time that they used "warm or hot water" at the faucet to wash their hands (proportion elevated).

Handwashing beliefs—Participants were asked to rate the effectiveness of five different water temperatures at cleaning one's hands, including cold water (12.8°C – 18.3 °C/55°F – 65 °F), cool water (18.3 °C – 23.9 °C/65 °F – 75 °F), room temperature water (23.9 °C – 29.4 °C/75 °F – 85 °F), warm water (29.4 °C – 35°C/85 °F – 95 °F), and hot water (35 °C – 40.6 °C/95 °F – 105 °F). Responses were made on a 5-point scale ranging from 1 ('not at all effective') to 5 ('highly effective').

Handwashing motivations—Five items assessed the reasons for which individuals chose a particular handwashing temperature. First, participants were asked to indicate to what extent they "make a conscious decision or choice about water temperature." Response options ranged from 1 ('almost never') to 5 ('almost always'). Next, participants were asked to indicate to what extent they would attribute their choice of water temperature to: cleanliness, comfort, habit, and availability. Responses ranged from 1 ('not at all') to 5 ('very much').

²All participants were recruited from eLab, an online research panel managed by Vanderbilt University's Owen Graduate School of Management. This panel includes over 50,000 users worldwide who have volunteered to participate in online research studies. More Information about this research panel can be found at <http://elab.vanderbilt.edu/>.

Results

Preliminary Analysis

Calculations for determining the amount of energy and GHG emissions required to heat water for handwashing are provided in the appendix. These estimates suggest that, considering fuel sources and efficiency (see section 3 of the appendix) each liter of heated water requires roughly 244 kilojoules (kJ) of energy and results in 0.02 kilograms (kg) of carbon dioxide equivalent (CO₂eq; or 0.08 kg/gallon).³ Calculations based on faucet flow rate and use find that 0.11 liters of water are used for each second of a handwash.

To calculate the average time an individual uses an elevated temperature, the frequency, duration and proportion elevated were estimated. Due to the tendency for individuals to over-report handwashing (American Society for Microbiology, 2005, 2007), these data were aggressively screened for outliers. Values that were clearly out of range were first excluded, including those who reported washing their hands more than 30 times a day ($n = 5$) or for an average duration of one minute or more ($n = 80$). Next, values that fell beyond two standard deviations above the mean were excluded.⁴ This includes individuals who reported washing their hands more than 25 times a day ($n = 19$) or for an average duration of 46 seconds or longer ($n = 6$). These estimates resulted in an average frequency of eight handwashes per day, an average duration of 21 seconds, and the use of an elevated temperature 75% of the time.

It is likely that our estimates are inflated due to social desirability bias. We are aware of only two studies that have measured handwashing duration within the general population. One took place in shopping malls in Japan and found an average duration of 14 seconds (Toshima et al., 2001). In a second, individuals were observed in public restrooms at a large university in the U.S. and found that the average person washed their hands for four to six seconds (Monk-Turner et al., 2005). To be conservative, and because cultural differences may partially account for the discrepancy between these estimates, it is assumed that the population observed in this latter study better reflects the behavior of the average American. Because this estimate is drastically lower than estimates collected in other settings (Taylor, 1978; Toshima et al., 2001), the high end of this range (6 seconds) was substituted as the estimated average duration.

No known studies that have measured handwashing frequency or the use of elevated water temperatures. Surveys commissioned by the ASM used both self-report and behavioral observation to assess the proportion of time Americans wash their hands in various situations (American Society for Microbiology, 2005, 2007). Between 91 and 95% of Americans reported “always” washing their hands after using a public restroom. Observations conducted in public restrooms throughout the U.S. (e.g., airports, train stations) found that only 77 to 82% of those observed actually washed their hands, indicating that the general public tends to overestimate this behavior by roughly 15%. To account for the tendency to over-report, self-reported frequency and the proportion elevated were adjusted downward by 15%. Therefore, we assume the typical American washes his or her hands seven times a day and uses warm or hot water 64% of the time.

³We estimate carbon dioxide, methane and nitrous oxide emissions, which are the three primary anthropogenic greenhouse gasses associated with the fuel sources used to provide hot water. The global warming impact of methane and nitrous oxide emissions are expressed in terms of carbon dioxide equivalents using IPCC standards for global warming potential as described in the Appendix.

⁴Because our primary concern was over-reporting of handwashing behavior due to social desirability bias, scores that fell below two standard deviations from the mean were left in the sample. This allowed for a more conservative estimate of handwashing behavior.

Energy Use and Greenhouse Gas Emissions

To calculate the average minutes per day an individual uses warm or hot water during handwashing, the estimated number of handwashes per day (7) was multiplied by the estimated proportion of time individuals used an elevated temperature (64%) and the estimated average duration per handwash (6 seconds). This resulted in 27 seconds per person per day. Multiplying this figure by 365 days in the year and the roughly 304 million people currently living in the U.S. (U.S. Census Bureau, 2009b) indicates that, each year, the use of elevated temperatures for handwashing accounts for roughly 276 billion liters of water (73 billion gallons), 68 trillion kilojoules (kJ) of energy (65 trillion British thermal units; Btu), and roughly 6.3 MMt of CO₂eq. The parameters and calculations used to estimate water, energy use and greenhouse gas emissions are provided in the Appendix.

Beliefs about Water Temperature

The means and standard deviations for the perceived effectiveness of various water temperatures are provided in Table 2. In all cases, warmer temperatures were rated as more effective, with hot water rated as the most effective and cold water as the least. Based on the average ratings, hot water was believed to be over two times as effective as cold water. Paired *t*-tests revealed that the rated effectiveness of each temperature was significantly different from the one above or below it,⁵ suggesting a linear relation between water temperature and perceived cleaning ability. A direct comparison of the perceived effectiveness of room temperature vs. warm water showed that 69% of the sample ($n = 351$) believed warm water to be more effective and 28% ($n = 140$) believed it to be equally as effective as room temperature water. Only two percent ($n = 11$) thought that warm water was less effective than room temperature water.

Next, the proportion of time participants used warm or hot water during handwashing was compared between those who held accurate and inaccurate beliefs. Those who believed warm water was less effective were excluded from the analysis. A one-way analysis of variance (ANOVA) was used to compare the remaining two groups. On average, those who held accurate beliefs reported using warm or hot water 55% of the time, compared to 68% among those who held inaccurate beliefs, $F(1, 489) = 33.74$, $p < .01$ (means are adjusted downward by 15%).

Although these data suggest that misperceptions are related to the use of elevated handwashing temperatures, the use of elevated temperatures was relatively high even among those who held accurate beliefs (55% of handwashes). This suggests that factors beyond cleaning effectiveness play an important role in an individual's decisions to use warm or hot water. When asked, the majority of respondents (70%, $n = 354$) reported that they do make a conscious decision about water temperature "most of the time" (34%) or "all of the time" (36%). Interestingly, participants ranked cleanliness as equally important ($M = 3.96$, $SD = 1.24$) as comfort ($M = 4.07$, $SD = 1.03$), habit ($M = 4.06$, $SD = 1.02$) and availability ($M = 3.88$, $SD = 1.18$).⁶ Thus, the perceived importance of all four of these factors is equivalently high.

Conclusions

These data suggest that the use of elevated temperatures for handwashing is common practice. The average respondent reported using warm or hot water 64% of the time.

⁵One-tailed paired *t*-tests were used for this analysis using a *Bonferroni* adjustment to control for family-wise error. The alpha level was set at $p < .013$.

⁶All responses were made on a scale ranging from 1 (not at all) to 5 (very much). Paired *t*-tests indicated that the importance of cleanliness was not statistically different from comfort, habit or availability.

Although the choice of water temperature during a single handwash may appear trivial, when multiplied by the nearly 8 billion handwashes performed by Americans each year, this practice results in over 6 MMt of CO₂eq annually. To put this figure in perspective, 6 MMt is roughly 0.1% of annual GHG emissions in the U.S. and around 0.3% of the total annual emissions attributable to the commercial and residential sectors combined.⁷ This value is roughly equivalent to the emissions of two coal-fired power plants, which emit around 3.8 MMt of CO₂eq a year (U.S. Environmental Protection Agency, 2009a). Not surprisingly, a large majority of the sample (69%) endorsed the belief that handwashing with warm water is more effective than room temperature water. Those who held this misperception indicated that they use warm water significantly more often than those who believed that water temperature does not affect handwashing efficacy. If updating beliefs would induce these individuals to use warm or hot water at the same level as those who hold accurate beliefs, U.S. emissions could be reduced by nearly 1 MMt annually. These savings would be equivalent to eliminating total annual emissions from the Zinc or Lead industries in the U.S. or the total emissions of any number of small countries including Malawi or Barbados (U.S. Environmental Protection Agency, 2009b; World Resources Institute, 2008).

Although 0.1% of annual GHG emissions may seem insignificant, even a seemingly trivial proportion of GHG emissions can be important given the ambitious emissions targets that have been set and the improbability that these can be achieved by only focusing on large sources (Stack and Vandenbergh, 2011). Researchers and policymakers often prioritize actions based on their technical potential for saving energy. However, multiple scholars have argued for the need to consider both technical potential as well as behavioral plasticity—the likelihood that an action will be adopted by the consumer (e.g., Vandenbergh, Barkenbus and Gilligan, 2008; Dietz et al. 2009). The latter depends, in part, on barriers to adoption such as up-front costs and the ease of engaging in an action. In line with these concerns, researchers have identified a number of actions that have the potential to deliver smaller yet non-trivial reductions in emissions that could be achieved rapidly and often with little economic or lifestyle sacrifices (e.g., Gardner and Stern, 2008; Dietz et al. 2009; Carrico et al. 2009). For this reason behaviors such as handwashing, which are strongly influenced by inaccurate information or misperceptions, may be good candidates for public information campaigns designed to update beliefs. The prevalence with which respondents reported using warm or hot water is not surprising considering the frequency with which it is advocated. Multiple high profile organization examined for the purpose of this research, including the FDA, ASM, and state public health agencies recommend using elevated water temperatures and, in some cases, cite its superior cleaning ability as the rationale (U.S. Department of Health and Human Services, 2008; U.S. Food and Drug Administration, n.d.). There is no doubt that the intention of these organizations is to promote a behavior that is vital to protecting public health; however, the preponderance of evidence reviewed here suggests this recommendation provides no health benefit and may, in fact, negatively impact health. Climate scientists have warned that a rise in the average global temperature could result in a number of threats to human health, including increases in flooding, drought, and infectious disease in some regions (Intergovernmental Panel on Climate Change, 2007). In addition to the impacts of climate change, elevated water temperatures are associated with skin damage and may contribute to bacterial colonization and reduced handwashing compliance. It is possible that the use of elevated temperatures may induce some individuals to wash their hands more frequently or for longer durations, therefore decreasing the spread of pathogens. For this reason, we suggest the public be encouraged to choose a “comfortable” water temperature, so as not to imply that warm or hot water is somehow

⁷According to the EPA’s greenhouse gas inventory, in 2007 the United States emitted 6088 MMt of CO₂eq. It has been estimated that direct behavior of individuals and households accounts for approximately 38% of total US emissions, or roughly 2,313 MMt annually (Gardner & Stern, 2008).

superior in its cleaning ability. Some individuals may prefer the use of warm or hot water, while others may decide that less elevated temperatures in the “tepid” to “warm” range are sufficiently comfortable. Although the degree of temperature was not measured in the current study, these data suggest that those who hold accurate beliefs do choose against selecting warm or hot water at the faucet on many occasions.

Given the importance of handwashing in preventing the spread of disease, we encourage consumer advocates and those in the field of public health to examine this issue more deeply. It is possible that there may be some situations in which the use of an elevated temperature is preferable, such as when the hands are visibly soiled, when certain contaminants are involved, or when the individual has Raynaud’s phenomenon. However, currently available data suggest that no such benefits exist except, perhaps, in cases of Raynaud’s. Additional efforts should be made to more accurately measure and quantify the impact of this behavior. Although precautions were taken to reduce the effects of social desirability bias on these data, self-report is inherently flawed and behavioral observations would allow for a more accurate estimate of actual handwashing practices. Additional factors, such as the time that water is run to reach the desired temperature, the actual temperature that was reached and throttling of hot vs. cold water could also improve accuracy. Similarly, estimates of the level of emissions reductions that could be realistically achieved through updating inaccurate beliefs assume that beliefs about water temperature are causally related to handwashing behavior. Because the current data are correlational and cross-sectional, causality cannot be established. More research is needed to accurately estimate the level of behavior change that can be expected by addressing this and other similar behaviors, as well as the most effective methods for educating the public on this issue.

Finally, these estimates are limited to the US, where this study was conducted; however, they have international importance. Parallel studies in other countries would be useful in determining the extent to which consumers associate water temperature with hygiene, as well as the role this perception plays in resource use and resultant GHG emissions. As discussed above, it is clear that this perception varies strongly across cultures. For example, ethnographic research has shown that, while cleanliness and hygiene are strongly valued in Japan, hot water is not cognitively connected to cleanliness as it is in western cultures, and is almost exclusively used for comfort (Wilhite, et al. 1996). Although this study focused specifically on the issue of water temperature in handwashing behavior, underlying perceptions of hygiene and water temperature drive a host of related behaviors, including the washing of clothes and dishes. Thus, the role of perceptions and cultural norms surrounding hygiene and water and energy use worldwide has great import for conserving resources and mitigating climate change.

Acknowledgments

Support for this project was provided by the Vanderbilt Climate Change Research Network and the Vanderbilt Institute for Energy and Environment. The research described was also supported by CTSA award No. **UL1TR000445** from the National Center for Advancing Translational Sciences. Its contents are solely the responsibility of the authors and do not necessarily represent official views of the National Center for Advancing Translational Sciences or the National Institutes of Health.

We would like to thank Paul Padgett for his assistance on the emissions quantification and Vanderbilt’s eLab for their programming efforts and assistance in data collection. We would also like to thank Dr. Thomas Talbot and the anonymous reviewers for their valuable comments on this manuscript.

References

- American Society for Microbiology. [accessed on May 17, 2012] A survey of handwashing behavior: 2005 findings. 2005. [WWW document] URL <http://www.washup.org/page04.html>
- American Society for Microbiology. [accessed on May 17, 2012] A survey of handwashing behavior (trended): 2007 Findings. 2007. [WWW document] URL <http://www.washup.org/page04.html>
- The National Research Council of the National Academies, America's Climate Choices Panel on Limiting the Magnitude of Climate Change. Limiting the Magnitude of Future Climate Change. The National Academies Press; Washington, D.C: 2010.
- Angelotti R, Foter MJ, Lewis KH. Time-temperature effects on Salmonellae and Staphylococci in foods. III. Thermal death time studies. *Applied Microbiology*. 1961; 9:308–315. [PubMed: 13683564]
- Biermayer, PJ. Potential water and energy savings from showerheads. Ernest Orlando Lawrence Berkeley National Laboratory; 2005. [WWW document] URL <http://escholarship.org/uc/item/79f5g8ds> [accessed on May 17, 2012]
- Bressand, F.; Farrell, D.; Haas, P.; Morin, F.; Nyquist, S.; Remes, J.; Roemer, S.; Rogers, M.; Rosenfeld, J.; Woetzel, J. Curbing global energy demand growth: The energy productivity opportunity. McKinsey Global Institute; 2007. [WWW document] URL http://www.mckinsey.com/mgi/publications/Curbing_Global_Energy/index.asp [accessed on May 17, 2012]
- Brown; Caldwell. Department of Housing and Urban Development. Residential Water Conservation Projects: Summary Report. Washington, D.C: The Division, Washington, D.C; 1984.
- Carrico AR, Padgett P, Vandenbergh MP, Gilligan J, Wallston KA. Costly myths: An analysis of idling beliefs and behavior in personal motor vehicles. *Energy Policy*. 2009; 37:2881–2888.
- Clarke, A.; Grant, N.; Thornton, J. Quantifying the energy and carbon effects of water saving: Full technical report. Environment Agency and Energy Saving Trust; 2009.
- Clarys P, Manou I, Barel AO. Influence of temperature on irritation in the hand/forearm immersion test. *Contact Dermatitis*. 1997; 36:240–243. [PubMed: 9197957]
- Cook HA, Cimiotti JP, Della-Latta P, Saiman L, Larson EL. Antimicrobial resistance patterns of colonizing flora on nurses' hands in the neonatal intensive care unit. *American Journal of Infection Control*. 2007; 35:231–236. [PubMed: 17482994]
- Dietz T, Gardner GT, Gilligan J, Stern PC, Vandenbergh MP. Household actions can provide a behavioral wedge to rapidly reduce US carbon emissions. *Proceedings of the National Academy of Sciences of the United States of America*. 2009; 106:18452–18456. [PubMed: 19858494]
- Emilson A, Lindberg M, Forslind B. The Temperature Effect on in-Vitro Penetration of Sodium Lauryl Sulfate and Nickel Chloride through Human Skin. *Acta Dermato-Venereologica*. 1993; 73:203–207. [PubMed: 8105620]
- European Commission. Climate Change. European Union; 2012. from: http://ec.europa.eu/clima/publications/docs/factsheet_climate_change_2012_en.pdf [Accessed July 26, 2012]
- European Environment Agency. [Accessed July 27, 2012] Households energy consumption by end use. 2011. from <http://www.eea.europa.eu/data-and-maps/figures/households-energy-consumption-by-end-uses-2>
- Fuss N, Bornkessel S, Mattern T, Stamminger R. Are resource savings in manual dishwashing possible? Consumers applying best practice tips. *International Journal of Consumer Studies*. 2011; 35:194–200.
- Gardner GT, Stern PC. The short list - The most effective actions US households can take to curb climate change. *Environment*. 2008; 50:12–24.
- Herrmann C, Candas V, Hoeft A, Gerreaud I. Humans under showers: Thermal sensitivity, thermoneutral sensations, and comfort estimates. *Physiology and Behavior*. 1994; 56:1003–1008. [PubMed: 7824563]
- Intergovernmental Panel on Climate Change. Climate Change 2007: The Physical Science Basis. 2007.
- Laestadius JG, Dimberg L. Hot water for handwashing - where is the proof? *Journal of Occupational and Environmental Medicine*. 2005; 47:434–435. [PubMed: 15824636]
- Laitala K, Boks C, Klepp IG. Potential for environmental improvements in laundering. *International Journal of Consumer Studies*. 2011; 35:254–264.

- Laitala KC, Klepp IG, Boks C. Changing laundry habits in Norway. *International Journal of Consumer Studies*. 2012; 36:228–237.
- Larson E, Killien M. Factors influencing handwashing behavior of patient care personnel. *American Journal of Infection Control*. 1982; 10:93–99. [PubMed: 6922685]
- Larson EL, Hughes CA, Pyrek JD, Sparks SM, Cagatay EU, Bartkus JM. Changes in bacterial flora associated with skin damage on hands of health care personnel. *American Journal of Infection Control*. 1998; 26:513–521. [PubMed: 9795681]
- Larson EL, Strom MS, Evans CA. Analysis of three variables in sampling solutions used to assay bacteria of hands: type of solution, use of antiseptic neutralizers, and solution temperature. *Journal of Infectious Disease*. 1980; 63:301–318.
- Mayer, P.; DeOreo, W.; Opitz, E.; Kiefer, J.; Davis, W.; Dziegielewski, B.; Nelson, JO. Residential End Uses of Water. Water Research Foundation; 1999. [WWW document] URL <http://www.waterresearchfoundation.org/research/topicsandprojects/execSum/241.aspx> [accessed May 12, 2012]
- Michaels B, Gangar V, Schultz A, Arenas M, Curiale M, Ayers T, Paulson D. Handwashing temperature effects on the reduction of resident and transient (*Serratia marcescens*) flora when using bland soap. *Dairy, Food and Environmental Sanitation*. 2001; 121:12–21.
- Michaels B, Gangar V, Shultz A, Arenas M, Curiale M, Ayers T, Paulson D. Water temperature as a factor in handwashing efficacy. *Food Service Technology*. 2002; 2:139–149.
- Monk-Turner E, Edwards D, Broadstone J, Hummel R, Lewis S, Wilson D. Another look at hand-washing behavior. *Social Behavior and Personality*. 2005; 33:629–634.
- Ohlenschlaeger J, Friberg J, Ramsing D, Agner T. Temperature dependency of skin susceptibility to water and detergents. *Acta Dermato Venereologica*. 1996; 76:274–276. [PubMed: 8869682]
- Pittet D, Mourouga P, Perneger TV. Compliance with handwashing in a teaching hospital. *Infection Control Program. Annals of Internal Medicine*. 1999; 130:126–130. [PubMed: 10068358]
- Price PB. The bacteriology of normal skin; a new quantitative test applied to a study of the bacterial flora and the disinfectant action of mechanical cleansing. *Journal of Infectious Disease*. 1938; 63:301–318.
- Rothenborg HW, Menne T, Sjolín KE. Temperature dependent primary irritant dermatitis from lemon perfume. *Contact Dermatitis*. 1977; 3:37–48. [PubMed: 139284]
- Somner JEA, Stone N, Koukkoulli A, Scott KM, Field AR, Zygmunt J. Surgical scrubbing: can we clean up our carbon footprints by washing our hands? *Journal of Hospital Infection*. 2008; 70:212–215. [PubMed: 18701193]
- Sharp GB, Carter MA. Prevalence of smoke detectors and safe tap-water temperatures among welfare recipients in Memphis, TN. *Journal of Community Health*. 1992; 17:351–365. [PubMed: 1293141]
- Spinks AT, Dunstan RH, Harrison T, Coombes P, Kuczera G. Thermal inactivation of water-borne pathogenic and indicator bacteria at sub-boiling temperatures. *Water Research*. 2006; 40:1326–1332. [PubMed: 16524613]
- Stack KM, Vandenbergh MP. The one percent problem. *Columbia Law Review*. 2011; 111:1385–1443.
- Taylor LJ. An evaluation of handwashing techniques-2. *Nursing Times*. 1978; 74:108–110. [PubMed: 622335]
- Toshima Y, Ojima M, Yamada H, Mori H, Tonomura M, Hioki Y, Koya E. Observation of everyday hand-washing behavior of Japanese, and effects of antibacterial soap. *International Journal of Food Microbiology*. 2001; 68:83–91. [PubMed: 11545224]
- U.S. Census Bureau. Table 1: Annual Estimates of Housing Units for the United States and States: April 1, 2000 to July 1, 2008. US Census Bureau, Population Division; 2009a. [WWW document] URL <http://www.census.gov/popest/housing/HU-EST2008.html> [Accessed Dec. 11, 2010]
- U.S. Census Bureau. [Accessed Dec. 11, 2010] Table 1: Annual Estimates of the Resident Population for the United States, Regions, States, and Puerto Rico: April 1, 2000 to July 1, 2008. 2009b. [WWW document] <http://www.census.gov/popest/states/NST-ann-est.html>
- U.S. Department of Energy, Office of Energy Efficiency and Renewable Energy. Energy Conservation Program for Consumer Products: Test Procedures and Certification and Enforcement

- Requirements for Plumbing Products; and Certification and Enforcement Requirements for Residential Appliances; Final Rule. 1998. p. 13309
- U.S. Department of Energy. [Accessed May 18, 2012] Technical Support Document: Energy Efficiency Standards for Consumer Products: Residential Water Heaters; Appendix D-2. Water Heater Analysis model (WHAM). 2000. [WWW document] http://www1.eere.energy.gov/buildings/appliance_standards/residential/waterheat_0300_r.html
- U.S. Department of Health and Human Services. [accessed May 12, 2012] Clean Hands Save Lives. 2008. [WWW document] URL <http://www.cdc.gov/handwashing/>
- U.S. Energy Information Administration; U.S. Department of Energy, editor. [Accessed May 18, 2012] Table HC2.8 Water Heating Characteristics by Type of Housing Unit, 2005: Million U.S. Housing Units. 2005. [WWW document] http://www.eia.doe.gov/emeu/recs/recs2005/hc2005_tables/hc8waterheating/pdf/alltables.pdf
- U.S. Energy Information Administration. [accessed May 12, 2012] Voluntary Reporting of Greenhouse Gases, Appendix F. Electricity Emission Factors, F1. Domestic Electricity Emission Factors, 1999–2002. 2007. [WWW document] URL http://www.eia.doe.gov/oiaf/1605/pdf/Appendix%20F_r071023.pdf
- U.S. Environmental Protection Agency. Energy Star. US Environmental Protection Agency; n.d. High Efficiency Water Heaters. [WWW document] URL www.energystar.gov/ia/new_homes/features/WaterHtrs_062906.pdf [Accessed May 18, 2012]
- U.S. Environmental Protection Agency. [Accessed May 18, 2010] Greenhouse Gas Equivalencies Calculator. 2009a. [WWW document] URL <http://www.epa.gov/cleanenergy/energy-resources/calculator.html>
- U.S. Environmental Protection Agency. [Accessed May 18, 2012] Inventory of Greenhouse Gas Emissions and Sinks: 1990 – 2012. 2009b. [WWW document] <http://www.epa.gov/climatechange/emissions/downloads12/US-GHG-Inventory-2012-Main-Text.pdf>
- U.S. Food and Drug Administration. [Accessed July 26, 2012] Handwashing. n.d. from: <http://www.fda.gov/Food/ResourcesForYou/StudentsTeachers/ScienceandTheFoodSupply/ucm215837.htm>
- U.S. Food and Drug Administration. [Accessed May 18, 2012] Food Code 2005, Section 5-202.12 Handwashing Sink, Installation. 2005. [WWW document] URL <http://www.fda.gov/Food/FoodSafety/RetailFoodProtection/FoodCode/FoodCode2005/default.htm>
- Vandenbergh MP, Barkenbus J, Gilligan J. Individual carbon emissions: The low-hanging fruit. *UCLA Law Review*. 2008; 55:1701–1758.
- Wilhite H, Nakagami H, Masuda T, Yamaga Y, Haneda H. A cross-cultural analysis of household energy use behaviour in Japan and Norway. *Energy Policy*. 1996; 24:795–803.
- World Health Organization. WHO Guidelines on Hand Hygiene in Health Care. Geneva, Switzerland: 2009. [WWW document] URL whqlibdoc.who.int/publications/2009/9789241597906_eng.pdf [Accessed May 18, 2012]
- World Resources Institute. [Accessed May 18, 2012] GHG Protocol tool for stationary combustion (Version 4.0). 2008. [WWW document] URL <http://www.ghgprotocol.org/calculation-tools/all-tools>

Appendix

1. Water consumption

To determine the volume of water used for handwashing, the average maximum flow rate of faucets in the U.S. was multiplied by the throttling factor. This figure was then divided by 60 to provide the number of gallons of water used per second of a handwash.

$$\begin{aligned}
 \text{Liters/second} &= (\text{Flow Rate}) \times (\text{Throttle}) / 60 \\
 &= 8.3 \text{ lpm} \times (.67) / 60 \\
 &= \mathbf{0.09 \text{ liters/second (0.03 gallons/second)}}
 \end{aligned}
 \tag{1}$$

2. Energy required to heat one liter of water

The energy required to provide a liter of hot water for handwashing was calculated by multiplying the mass of water to be heated in kg (1 liter = 1 kg of water) by the change in water temperature that occurs (*Setpoint – Inlet*) and the specific heat of water (*Q*).

$$\begin{aligned}\text{Required energy (kJ)} &= (\text{Water Mass}) \times (\text{Setpoint} - \text{Inlet Temp.}) \times Q \\ &= (57^{\circ}\text{C} - 15^{\circ}\text{C}) \times 4.186 \text{ kJ/kg}^{\circ}\text{C} \\ &= \mathbf{176 \text{ kJ (166.6 Btu}^8)}\end{aligned}\quad [2]$$

3. Fuel required to heat one liter of water

Actual fuel consumption and GHG emissions were calculated separately for each fuel source. In each equation, the energy required to heat one liter of water (176 kJ) was multiplied by the proportion of water heaters in the U.S. heated by that specific energy source. This value was then divided by the DOE's 2004 efficiency standard for water heaters powered by that particular fuel source. [3] Fuel Consumption = $[(\text{Required Energy}) \times (\text{Proportion of Fuel Source})] / (\text{Efficiency})$

$$\text{Fuel consumption} = [(\text{Required Energy}) \times (\text{Proportion of Fuel Source})] / (\text{Efficiency}) \quad [3]$$

$$\begin{aligned}\text{Electricity} &= (176 \text{ kJ} \times 39\%) / 93\% \\ &= \mathbf{74 \text{ kJ (70 Btu/0.02 kWh)}}\end{aligned}\quad [3a]$$

$$\begin{aligned}\text{Natural Gas} &= (176 \text{ kJ} \times 54\%) / 62\% \\ &= \mathbf{153 \text{ kJ (145 Btu)}}\end{aligned}\quad [3b]$$

$$\begin{aligned}\text{Fuel Oil} &= (176 \text{ kJ} \times 4\%) / 59\% \\ &= \mathbf{12 \text{ kJ (11 Btu)}}\end{aligned}\quad [3c]$$

$$\begin{aligned}\text{Propane} &= (176 \text{ kJ} \times 3\%) / 100\% \\ &= \mathbf{5 \text{ kJ (5 Btu)}} \\ \text{Total} &= \mathbf{244 \text{ kJ (21 Btu)}}\end{aligned}\quad [3d]$$

4. GHG Emissions

The emissions factors used to estimate carbon dioxide (CO₂), methane (CH₄) and nitrous oxide (N₂O) are provided in Table 4. These values were then converted to carbon dioxide equivalents (CO₂eq) based on IPCC estimates for global warming potential (GWP) over a 100-year time horizon. Based on these calculations the energy used to heat one liter of hot water results in 0.02 kg of CO₂eq, on average.

Table 1

Demographic profile of sample and population

	Sample	Population ^
Sex (% female)	46%	51%
Age (median)	44	37
Education (median)	some college	some college
Income (median)	\$50,000 – \$74,999	\$50,000
Food Service Industry	3%	8%
Health Care Industry	8%	5%

^ Population estimates for sex, age, education and income are based on 2008 data from the U.S. Census Bureau (U.S. Census Bureau 2009a,b). The proportion of food service and health care employees are based Bureau for Labor statistics (2009).

Table 2

Means and standard deviations for perceived effectiveness of water temperatures.

	M	SD
Cold	2.18	1.13
Cool	2.46	1.09
Room Temp.	3.09	1.03
Warm	4.01	0.85
Hot	4.44	0.96

M = Mean; *SD* = Standard Deviation

Note. Responses were made on a 5-point scale ranging from “not at all effective” to “highly effective.”

Table 3

Explanation of parameters used to calculate water and energy consumption.

Parameter	Description	Value	Comment/Source
<i>Flow Rate</i>	Faucet flow rate (liters per minute)	8.3 lpm/2.2 gpm	There are no data on the average maximum flow rate of sink faucets. In 1998 the U.S. Department of Energy (1998) adopted 2.2 gallons per minute (gpm) at 60 pounds per square inch (psi) as the maximum flow rate for all faucets. It is likely that many households and businesses have installed low-flow faucets; however, it is also likely that many faucets exceed this standard. Mayer et al. (1999) found that nearly a quarter of showerheads exceeded the maximum flow rate. To be conservative, we adopt the national standard of 2.2 gpm or 8.3 liters per minute (lpm)
<i>Throttle</i>	Degree that faucet that is opened during use.	2/3	On most occasions, faucets are used at only a portion of the maximum flow rate. A report prepared for the Department of Housing and Urban Development estimated that, when used for purposes other than filling a container, faucets are throttled at 2/3 of maximum capacity (Brown and Caldwell, 1984).
<i>Inlet Temp.</i>	Inlet water temperature	15° C (58°F)	The U.S. Department of Energy (2000) Energy Efficiency Standards for Consumer Products estimates that the nationwide average inlet temperature for water heaters is 58°F or 15°C.
<i>Setpoint</i>	Water heater setpoint	57°C (135°F)	They use 135°F (57°C) as the standard setpoint of a hot water heater when determining energy demand. It is likely that many homes and businesses have followed Department of Energy suggestions to set back their water heaters to 120°F; however, many also exceed the 135°F setpoint. A 1992 study visited a non-representative sample of over 100 homes and found that in 73% of homes, faucet temperatures exceeded 130°F (Sharp and Carter, 1992). To be conservative, and due to a lack of recent data, we adopt the Department of Energy standard setpoint of 135°F (57°C), which is equivalent to 57°C.
<i>Q</i>	Heat capacity of water (specific heat)	4.186 kJ/kg°C	The kilojoules (kJ) of energy required to raise 1 kilogram (kg) of water 1°C.
<i>Proportion of Fuel Source</i>	Proportion of water heated by energy source	electric: 39% nat. gas: 54% fuel oil: 4% propane: 3%	Based on data provided by the U.S. Energy Information Administration (2005).
<i>Efficiency</i>	Mechanical Efficiency	electric: 93% nat. gas: 62% fuel oil: 59% propane: 100%	To account for energy lost due to mechanical inefficiency, Department of Energy standards for water heater efficiency were included in the analysis. No efficiency standards have been adopted for propane-heated water heaters, therefore, complete efficiency is assumed (U.S. Department of Energy, 1998).

Table 4

Emissions factors and Global Warming Potential

	Electricity ⁱ (kg/MWh)	Natural Gas ⁱⁱ (kg/MMBtu)	Fuel Oil ⁱⁱ (kg/MMBtu)	Propane ⁱⁱ (lbs/MMBtu)	GWP ⁱⁱⁱ
Carbon Dioxide (CO ₂)	676	53	79	63	1
Methane (CH ₄)	0.02	4.75E-03	1.00E-02	4.75E-03	25
Nitrous Oxide (N ₂ O)	0.01	9.50E-05	6.01E-04	9.50E-05	298

ⁱ Emissions factors for electricity production are based on EIA estimates, which include losses incurred in delivering electricity to the point of use. The U.S. average estimate is 0.68 metric tons per megawatt hour (MWh) or 1,490 lbs/MWh (Energy Information Administration, 2007).

ⁱⁱ CO₂ emissions are based on EIA estimates (Energy Information Administration, 2007), CH₄ and N₂O estimates are based on calculations from the World Resources Institute (World Resources Institute, 2008).

ⁱⁱⁱ Provided by the IPCC (2007) report.