Video Article

Automated Analysis of Dynamic Ca^{2+} Signals in Image Sequences

Michael Francis¹, Josh Waldrup², Xun Qian², Mark S. Taylor²

¹Department of Pharmacology, University of South Alabama

²Department of Physiology, University of South Alabama

Correspondence to: Mark S. Taylor at mtaylor@southalabama.edu

URL: <http://www.jove.com/video/51560>

DOI: [doi:10.3791/51560](https://doi.org/10.3791/51560)

Keywords: Basic Protocol, Issue 88, signaling, ImageJ, detection, microscopy, algorithm, calcium

Date Published: 6/16/2014

Citation: Francis, M., Waldrup, J., Qian, X., Taylor, M.S. Automated Analysis of Dynamic Ca^{2+} Signals in Image Sequences. *J. Vis. Exp.* (88), e51560, doi:10.3791/51560 (2014).

Abstract

Intracellular Ca^{2+} signals are commonly studied with fluorescent Ca^{2+} indicator dyes and microscopy techniques. However, quantitative analysis of Ca^{2+} imaging data is time consuming and subject to bias. Automated signal analysis algorithms based on region of interest (ROI) detection have been implemented for one-dimensional line scan measurements, but there is no current algorithm which integrates optimized identification and analysis of ROIs in two-dimensional image sequences. Here an algorithm for rapid acquisition and analysis of ROIs in image sequences is described. It utilizes ellipses fit to noise filtered signals in order to determine optimal ROI placement, and computes Ca^{2+} signal parameters of amplitude, duration and spatial spread. This algorithm was implemented as a freely available plugin for ImageJ (NIH) software. Together with analysis scripts written for the open source statistical processing software R, this approach provides a high-capacity pipeline for performing quick statistical analysis of experimental output. The authors suggest that use of this analysis protocol will lead to a more complete and unbiased characterization of physiologic Ca^{2+} signaling.

Video Link

The video component of this article can be found at <http://www.jove.com/video/51560/>

Introduction

Ca^{2+} is a ubiquitous second messenger signaling molecule and cytosolic Ca^{2+} levels are highly regulated. Intracellular Ca^{2+} signals are complex and include isolated transients, oscillations, and propagating waves¹⁻⁴. Spatial and temporal control of Ca^{2+} is thought to underlie physiological signal specificity, and therefore the analysis of Ca^{2+} signal patterns is of considerable interest to investigators in multiple fields⁵.

Ca^{2+} indicator dyes such as Fluo-4 and Fura-2 are commonly employed to measure intracellular Ca^{2+} signals with fluorescence microscopy⁵⁻¹². Typically, temporal Ca^{2+} signals are evaluated as time-dependent changes in mean fluorescence within a user-defined area, or region of interest (ROI)^{5,6,13-16}. Currently, manual ROI analysis is both time consuming and labor intensive because it requires users to identify many ROIs and perform repetitive computations¹⁷⁻¹⁹. These techniques may also be subject to considerable user error, including introduction of artificial signal modes and exclusion of low amplitude or diffuse signals^{18,20}.

Automated ROI detection algorithms have previously been implemented using a variety of statistical approaches to determine optimal ROI placement, but they have generally been limited to analysis of line scan or pseudo-line scan images, which restricts analysis to a single spatial dimension in time^{17,19-22}. Additionally, many existing algorithms are not adequate to encompass the diversity of Ca^{2+} release events which range from periodic, localized transients to propagating waves^{23,24}. Comprehensive evaluation of physiological Ca^{2+} signals is often further complicated by the presence of significant image artifact that confounds signal to noise discrimination in many experimental systems.

Previously, an automated ROI detection algorithm solution to Ca^{2+} signal transient detection, implemented as a plugin for NIH ImageJ software (National Institutes of Health, Bethesda, MD), was developed and validated^{25,26}. This algorithm, called LC_Pro, was designed to identify and analyze ROIs encompassing Ca^{2+} signal transients in two-dimensional time lapse image sequences. Here a practical experimental protocol and representative demonstration of an application of the algorithm in porcine coronary artery endothelium is provided, with additional postprocessing using the open source statistical processing software R to generate usable graphical output.

Protocol

1. Vessel Dissection and Imaging

1. Harvest tissue from domestic juvenile pigs as described in Martens *et al*²⁷. Place harvested swine right ventricles into a polydimethylsiloxane (PDMS) bottom dissection dish containing HEPES buffered physiological saline solution (PSS).

1. With the aid of a stereomicroscope, dissect and remove a segment of the left anterior descending coronary artery (~8 mm length, 0.5 mm diameter) from surrounding tissue using forceps and spring scissors by removing the vessel segment from the surrounding cardiac tissue layers. NOTE: Take care to not puncture the vessel wall.
2. Place a PDMS block (1 x 0.5 x 0.5 cm) into the dissection dish, and use a needle to pin it to the bottom. Cut an approximately 40 μ m diameter tungsten wire into twelve ~0.3 cm length segments, forming micropins, and place these in the dish. Using forceps, secure one end of the vessel segment to the block with a micropin.
3. Carefully insert small spring scissors into the vessel lumen, and cut longitudinally down one side of the vessel to open it completely. Orient the opened vessel segment with the endothelium up.
4. Use the remaining micropins to secure the borders of the opened vessel segment to block such that the vessel forms a flat rectangle. NOTE: Micropin tops should be bent to 90° and inserted until flush with the block surface. Care should be taken to stretch the vessel preparation without overstretching; final width should be ~1.5x the starting unstretched width.
5. Prepare a small volume (~1 ml) of Fluo-4 AM loading solution by mixing Fluo-4 AM (10 μ M) dissolved in DMSO with pluronic (0.03 %) in a HEPES buffered PSS (containing in mM: 134 NaCl, 6 KCl, 1 MgCl, 10 HEPES, 10 glucose), and insert the entire block into the loading solution for approximately 40 min at room temperature in the dark.
6. After loading, wash the block in HEPES buffered PSS for 5-10 min.
7. Mount the block onto 50-100 μ m thick spacers in a coverglass bottom chamber containing HEPES buffered PSS. NOTE: Metal pins can be used as spacers and ensure the vessel segment is facing down and not touching the spacers.
8. Place the chamber on the stage of an inverted microscope equipped for confocal imaging, and focus on the endothelial cell layer.
9. Capture time lapse image sequences of basal relative fluorescence for ~3 min at 20X magnification and a frame rate of ~8 frames per sec using confocal image sequence acquisition software.
10. After ~3 min of recording basal fluorescence, replace HEPES buffered PSS solution with the same volume (~1 ml) of Substance P (100 pM) dissolved in HEPES buffered PSS, and record for an additional 3 min.

2. Automated Analysis

1. Render image sequence(s) of fluorescent calcium activity from confocal acquisition software as 8 bit, grayscale '.tif' format files with no scale information.
2. Open ImageJ, click 'open' in the file menu, and select the appropriate image sequence in the explorer window to view the image sequence(s) in ImageJ.
3. Determine an appropriate ROI diameter by using the rectangular ROI tool to estimate the upper and lower boundaries of the spatial spread of activity within the image sequence(s). NOTE: The mean rectangular diameter is a suitable choice for ROI diameter.
4. Create a new folder on the computer hard drive, and add the image sequence(s) into the folder directory.
5. In ImageJ, click the 'plugins' window, then click 'LC_Pro' to start the analysis.
6. Enter the ROI diameter value and select the filter threshold value (either 0.05 or 0.01).
7. Click the 'drug treatment' checkbox and enter the time point values immediately before and after the drug was added (in seconds).
8. Click 'ok', and enter the image sequence directory into the file explorer window.

3. Graphical Output

1. Download R version 3.0.2 from <http://www.r-project.org/>.
2. Open the 32 bit version of R.
3. Click "file", then 'open script' and select the 'traceplot.R' R script for generating graphical experimental reports.
4. Install the calibrate, and gplots packages by selecting 'packages', 'install packages', and selecting the appropriate packages.
5. Click 'file', then 'change directory' command, and use the explorer window to select the directory that corresponds to the LC_Pro analysis output.
6. Click on the script window and then the 'run all' command to run the script.

Representative Results

A custom algorithm, LC_Pro, was developed and implemented in order to perform automated analysis of Ca^{2+} dynamics on confocal image sequences. As depicted in **Figure 1**, the algorithm utilizes sequential processing modules that A) detect and track sites of dynamic Ca^{2+} change above statistical ($p < 0.01$) noise, B) define regions of interest (ROI) automatically at active site centers, and C) calculate average fluorescence intensities at ROIs to determine specific event parameters. A graphical overview of the algorithm is shown using computer generated Gaussian pulses of known intensity and location (**Figure 2**). Signal pulses (**Figures 2A and B**) were converted to binary using the z-score for a standard normal distribution, and best-fit ellipses were assigned to pixel loci above signal threshold (**Figure 2C**). An ellipse sorting algorithm was used to determine optimal ROI placement (**Figure 2D**). ROI mean intensity versus time was then measured and signal parameters of amplitude, duration and spatial spread were computed (**Figure 2E**). This analysis approach was applied to assess cellular Ca^{2+} dynamics in intact vascular endothelium. Specifically, confocal imaging was performed in opened swine coronary arteries as described in **Figure 3**, and the algorithm was employed offline to quantify distinct Ca^{2+} parameters. For these experiments, continuous recordings were made before and after addition of the endothelial stimulus, substance P (SP; 100 pM), and LC_Pro analysis was subsequently performed. For scaling signal within each ROI, baselines were derived as linear regressions of ROI intensity over the experimental time course (**Figure 4**). Mean signal intensity values were computed for each ROI (**Figure 4A**), and values above the mean were truncated to the mean and a linear regression was performed to approximate signal baseline (**Figure 4B**). Finally, raw intensity values were divided by the value of the regression line to convert values to fold change over baseline (**Figure 4C**). **Figure 5** shows a representative experiment, including images of Ca^{2+} dependent fluorescence in the endothelium (**Figure 5A**), accumulate binary masks of total Ca^{2+} signal detected within the sampled field (**Figure 5B**), and recordings of

average fluorescence at each ROI (**Figure 5C**) before and after SP treatment. Subsequent parameter analysis was performed using R software. Resulting histograms show the amplifying effect of SP on event amplitude, duration, and spatial spread (**Figure 6**).

Figure 1. Signal flow charts of algorithm processes (this figure was obtained with permission from Francis *et al.*)²⁴. The algorithm was organized into three sections: Image processing, event processing, and region of interest (ROI) processing. Image sequences are input into the flow chain, and event statistics are generated as final output. The image processing (**A**) subroutine of the algorithm converts the input image sequence into a list of best-fit ellipses by thresholding, using the z-score for a standard normal distribution and ImageJ particle analysis. Event processing (**B**) is a sorting subroutine used to determine optimum ROI position by organizing ellipse locations into event “sites” by time. After mean intensity measurements are taken at each ROI, statistical parameters for each event and site are calculated by the ROI processing subroutine (**C**) to generate the final output. BKGD, background; AVG, average. [Please click here to view a larger version of this figure.](#)

Figure 2. Demonstration of automated ROI acquisition and signal detection using a computer-generated Gaussian pulse (this figure was adapted with permission from Francis *et al.*)²⁴. A single computer-generated signal pulse (A) was embedded in random background noise. The gray scale image sequence was filtered to remove static background pixel values (B) and converted to binary using threshold pixel intensity values of $P < 0.05$ calculated by the standard score (C). ImageJ particle analysis algorithms were then applied to the image sequence to assign best-fit ellipses to pixel loci within each frame. A novel algorithm was used to group ellipses into discrete temporal “events” and determine the optimal position for each ROI based on the mean ellipse center (D). An ROI of user defined radius is then placed at each position (dotted circle). Mean intensity values within an ROI are calculated for each frame and scaled using a linear baseline approximation. Peak amplitude is identified as local maxima above $P < 0.05$ as defined by the standard score for a corresponding ROI tracing (E). [Please click here to view a larger version of this figure.](#)

Figure 3. Porcine coronary artery dissection protocol. Approximately 0.5 mm diameter x 8 mm length branches of the left anterior descending coronary artery (1st image, dotted circle) were dissected from the surrounding myocardium. Vessel segments were trimmed of surrounding adventitial tissue and cut lengthwise with small scissors (2nd image). Next, the opened vessels were pinned flat to a PDMS block using fine tungsten wires (3rd image). Mounted vessel segments were loaded with Fluo-4 Ca^{2+} indicator dye, washed, and then placed in a coverglass-bottomed imaging chamber. Images were collected at 20X magnification (488 ex., 510 em.) at 8.0 frames per sec using an inverted confocal microscope. [Please click here to view a larger version of this figure.](#)

Figure 4. ROI mean intensity baseline approximation. Following mean intensity versus time measurements (solid lines) for each ROI, the raw intensity values are scaled to F/F_0 using the following baseline approximation method. The mean signal intensity (dashed line) during the control period is computed from user defined control and treatment interval values (**A**). The time-dependent signal intensity curve is then truncated above the mean control intensity to the mean control intensity to filter activity from baseline approximation, and a linear regression is performed on the resultant curve (dotted lines) (**B**). Finally, the raw intensity values are scaled to the computed linear baseline (**C**). [Please click here to view a larger version of this figure.](#)

Figure 5. Representative results from LC_Pro analysis of basal and stimulated Ca^{2+} dynamics. Time lapse images of an input image sequence of a basal sampling interval (A, left panel) followed by a Substance P-stimulated sampling interval (A, right panel) are shown in grayscale. Time lapse image sequences of best fit ellipses for basal and stimulated intervals (B) were rendered by LC_pro. Finally, time-dependent scaled intensity curves from each automatically positioned region of interest (ROI) are shown (C).

Figure 6. Histograms of parameter distributions from a representative experiment (Figure 4). Histograms from parameters of peak amplitude (F/F_0), duration at $\frac{1}{2}$ max (sec), and maximum spatial spread (μm^2) for both control (left column) and Substance P-stimulated (right column) events from a representative experiment were rendered using R to graphically process the output from LC_pro. Notably, Substance P stimulation expanded the number of events, and caused a significant right shift in the median amplitude and duration by Mann-Whitney U test ($p < 0.01$).

Discussion

Decoding complex Ca^{2+} signals at the cellular and multicellular level will require rigorous experimental and analytical approaches. Here, an approach is described in which time resolved confocal image sequences of Ca^{2+} dependent fluorescence are subjected to an automated analysis that identifies and quantifies statistically relevant Ca^{2+} signals within intact cellular fields. In the specific case presented, an artery segment was isolated from pig heart, pinned opened to expose the endothelium, loaded with the Ca^{2+} indicator Fluo-4 AM, subjected to confocal imaging, and evaluated with the custom algorithm LC_Pro. This algorithm is designed to 1) detect and track sites of dynamic Ca^{2+} change above statistical ($p < 0.01$) noise, 2) define regions of interest (ROI) automatically at active site centers, and 3) analyze average fluorescence intensities at ROIs to determine specific event parameters. The approach overcomes major limitations of biological signaling research by reducing user error and bias, greatly reducing offline analysis time, and providing a complete index of signals across a field to discern representative profiles or patterns. Output from LC_Pro is further processed through R scripts, providing full parameter reports for individual experiments, including high quality graphical output.

Several steps are important for proper performance of the described technique. The tissue dissection procedure (step 1.1.1) must be performed carefully in order to avoid denudation or damage of the endothelial cell layer. Additionally, image sequences must be in the proper format (step 2.1) for the automated region of interest algorithm to work correctly. For example, if there is scale information associated with the file, regions of interest will be incorrectly placed according to the pixel locations, rather than the scaled unit locations. Also, choosing a suitable region of interest diameter is critical to correctly performing automated analysis of the fluorescent activity within an image sequence. Too small a diameter value may result in redundant measurements, whereas too large a diameter will result in exclusion of subtle signals.

Potential pitfalls of this technique primarily relate to sensitivity of the automated analysis to x-y shifts in recorded image sequences and to signal saturation and/or bleaching, which may result in false positive or false negative results. Dimensional drifts or shifts may be addressed

directly through use of stack registration software and accurate designation of intervals where perturbations are introduced. Gray levels and ROI diameter parameters may also be optimized for a given preparation in advance of data collection in order to standardize raw data sets.

Because it serves as a standard approach for any dynamic fluorescence signal, the analysis described here is suitable for a diverse body of applications. In the vasculature, this method is being employed to define characteristic physiological and pathophysiological signal modalities in multiple vascular beds under basal and stimulated conditions^{25,26}. It is also being applied in the automated tracking of Ca^{2+} waves. Ultimately, such global automated analysis will be a crucial linchpin in deciphering spatially and temporally complex bio-signals and in establishing new cell and multi-cell models.

Disclosures

The authors have nothing to disclose.

Acknowledgements

This work was supported in part by National Institutes of Health Grants HL-085887, HL-092992, S10RR027535, and MOP-93676.

References

- Berridge, M. J. Inositol trisphosphate and calcium signalling. *Nature*. **361**(6410), 315-325, 10.1038/361315a0, (1993).
- Berridge, M. J. *et al.* The versatility and universality of calcium signalling. *Nat Rev Mol Cell Biol*. **1**(1), 11-21, 10.1038/35036035, (2000).
- Delisle, S. The four dimensions of calcium signalling in *Xenopus* oocytes. *Cell Calcium*. **12**(2-3), 217-227, 16/0143-4160(91)90022-7, (1991).
- Dupont, G. *et al.* Calcium dynamics: spatio-temporal organization from the subcellular to the organ level. *Int Rev Cytol*. **261**, 193-245, S0074-7696(07)61005-5, (2007).
- Hayashi, H. and Miyata, H. Fluorescence imaging of intracellular Ca^{2+} . *J Pharmacol Toxicol Methods*. **31**(1), 1-10, (1994).
- Barreto-Chang, O. L. and Dolmetsch, R. E. Calcium imaging of cortical neurons using Fura-2 AM *J Vis Exp*. (23), e1067, 10.3791/1067, (2009).
- Hong, J. H. *et al.* Intracellular calcium spikes in rat suprachiasmatic nucleus neurons induced by BAPTA-based calcium dyes. *PLoS One*. **5**(3), e9634, 10.1371/journal.pone.0009634, (2010).
- Kuga, N. *et al.* Large-scale calcium waves traveling through astrocytic networks *in vivo*. *J Neurosci*. **31**(7), 2607-2614, 10.1523/JNEUROSCI.5319-10.2011, (2011).
- Mumtaz, S. *et al.* The mechanism of agonist induced Ca^{2+} signalling in intact endothelial cells studied confocally in situ arteries. *Cell Calcium*. **49**(1), 66-77, 10.1016/j.ceca.2010.11.010, (2011).
- Paredes, R. M. *et al.* Chemical calcium indicators. *Methods*. **46**(3), 143-151, 10.1016/j.ymeth.2008.09.025, (2008).
- Silei, V. *et al.* Measurement of intracellular calcium levels by the fluorescent Ca^{2+} indicator Calcium-Green. *Brain Res Brain Res Protoc*. **5**(2), 132-134, 16/S1385-299X(00)00003-9, (2000).
- Simpson, A. M. Fluorescent measurement of $[\text{Ca}^{2+}]_i$: basic practical considerations. *Methods Mol Biol*. **937**, 3-36, 10.1007/978-1-62703-086-1_1, (2006).
- Gaspers, L. D. and Thomas AP. Calcium signaling in liver. *Cell Calcium*. **38**(3-4), 329-342, 10.1016/j.ceca.2005.06.009, (2005).
- Hellman, B. *et al.* Cytoplasmic Ca^{2+} oscillations in pancreatic β -cells. *Biochem Biophys Acta*. **1113**(3-4), 295-305, 16/0304-4157(92)90003-S, (1992).
- Kansui, Y. *et al.* Enhanced spontaneous Ca^{2+} events in endothelial cells reflect signalling through myoendothelial gap junctions in pressurized mesenteric arteries. *Cell Calcium*. **44**(2), 135-146, 10.1016/j.ceca.2007.11.012, (2008).
- Tatsumi, H. *et al.* Measurement of the intracellular calcium concentration in guinea-pig myenteric neurons by using fura-2. *Brain res*. **451**(1-2), 371-375, 16/0006-8993(88)90787-1, (1988).
- Lorenz, J. J. *et al.* Pixel-based criteria-oriented analysis of time-lapse Ca^{2+} -fluorescence images. *J Neurosci Meth*. **127**(2), 157-166, 16/S0165-0270(03)00124-9, (2003).
- Mukamel, E. A. *et al.* Automated analysis of cellular signals from large-scale calcium imaging data. *Neuron*. **63**(6), 747-760, 10.1016/j.neuron.2009.08.009, (2009).
- Reidl, J. *et al.* Independent component analysis of high-resolution imaging data identifies distinct functional domains. *Neuroimage*. **34**(1), 94-108, 10.1016/j.neuroimage.2006.08.031, (2007).
- Wegner, F. *et al.* Automated detection of elementary calcium release events using the $\acute{a}$ trous wavelet transform. *Biophys J*. **90**(6), 2151-2163, 10.1529/biophysj.105.069930, (2006).
- Cheng, H. *et al.* Amplitude distribution of calcium sparks in confocal images: theory and studies with an automatic detection method. *Biophys J*. **76**(2), 606-617, 10.1016/S0006-3495(99)77229-2, (1999).
- Picht, E. *et al.* SparkMaster: automated calcium spark analysis with ImageJ. *Am J Physiol Cell Physiol*. **293**(3), C1073-C1081, 10.1152/ajpcell.00586.2006, (2007).
- Abramoff, M. D. *et al.* Image processing with ImageJ. *Biophoton Int*. **11**, 36-42, (2004).
- Francis, M. *et al.* Automated region of interest analysis of dynamic Ca^{2+} signals in image sequences. *Am J Physiol Cell Physiol*. **303**(3), C236-243, 10.1152/ajpcell.00016.2012, (2012).
- Qian, X. *et al.* Recruitment of dynamic endothelial Ca^{2+} signals by the TRPA1 channel activator AITC in rat cerebral arteries. *Microcirculation*. **20**(2), 138-148, 10.1111/micc.12004, (2013).
- Taylor, M. S. *et al.* Dynamic Ca^{2+} signal modalities in the vascular endothelium. *Microcirculation*. **19**(5), 423-429, 10.1111/j.1549-8719.2012.00180.x, (2012).
- Martens, C. J. *et al.* Mucous solids and liquid secretion by airways: studies with normal pig, cystic fibrosis human, and non-cystic fibrosis human bronchi. *Am J Physiol Lung Cell Mol Physiol*. **301**(2), L236-246, 10.1152/ajplung.00388.2010, (2011).