Published in final edited form as:

J Vis Impair Blind. 2011 October ; 105(10): 648–661.

Nonvisual Cues for Aligning to Cross Streets

Alan C. Scott¹, Janet M. Barlow², David A. Guth³, Billie Louise Bentzen⁴, Christopher M. Cunningham⁵, and Richard Long³

¹Elon University, Elon, North Carolina USA

²Accessible Design for the Blind, Asheville, North Carolina USA

³Western Michigan University, Kalamazoo, Michigan USA

⁴Boston College, Boston, Massachusetts USA

⁵Institute for Transportation Research and Education, Raleigh, North Carolina USA

Abstract

Accurately aligning to the crosswalk is an important component of safe street crossing for pedestrians who are blind. Six alignment cues were evaluated in a simulated crosswalk environment in which crosswalk angle was not always in line with ramp slope. The effectiveness of each cue is reported and implications are discussed.

Introduction

For individuals who are blind, the tasks required to cross a street include detecting the street, locating the crosswalk or crossing location, aligning (determining the appropriate initial heading), determining an appropriate time to cross, and traveling on an appropriate heading until the crossing is completed (Guth, Rieser, & Ashmead, 2010; Tauchi, Sawai, Takato, Yoshiura, & Takeuchi, 1998). The study reported here is the first of a series evaluating the effectiveness of various treatments as aids for alignment and for maintaining the correct heading while crossing streets without vision.

Orientation and mobility (O&M) specialists teach various strategies for aligning one's facing direction with the direction of a crosswalk before initiating a street crossing. It is assumed that an appropriate facing direction leads to an appropriate initial heading once the pedestrian begins to cross. If individuals who are blind are misaligned, traffic sounds may be misinterpreted (e.g., thinking turning traffic is traveling straight through the intersection), dog guides may aim for an incorrect corner or island, and an individual's first step may be toward moving traffic. Some alignment strategies involve the use of physical cues such as grasslines and returned curbs (curbs along the edges of curb ramps) that are perpendicular to the street that is about to be crossed (Hill & Ponder, 1976; Whipple, 2004). Others involve acoustic cues, such as the sounds of traffic moving parallel or perpendicular to the crosswalk (Barlow, Bentzen, Sauerburger, & Franck, 2010; Guth et al., 2010; Stollof, 2005a). At

modern intersections, however, such cues may be unavailable. For example, at curb ramps, grasslines at the sides of the ramp, if present, are rarely aligned with the crosswalk. Parallel and perpendicular patterns of traffic movement often do not occur at some crosswalks, such as crosswalks at roundabouts and channelized turn lanes, and they may be unreliable at other crosswalks, such as those where traffic volume is low during parts of the day.

The installation of curb ramps at many intersections has further complicated the alignment task. In the United States, curb ramps often slope toward the center of the intersection rather than in the direction of the crosswalk (see Figure 1), which sometimes results in pedestrians who are blind crossing toward the center of the intersection (Hauger, Rigby, Safewright, & McAuley, 1996).

Even when separate curb ramps serve the two crosswalks on a corner, the large radius of many corners results in curb ramps at which the slope is out of line with the crosswalk, in order to be perpendicular to the street edge and gutter. Curb ramp slopes are required to be perpendicular to the gutter to minimize the tipping hazard for wheelchair users. Although some curb ramps are aligned with the crosswalks they serve, it is not known whether ramp slope actually provides a useful alignment cue to pedestrians who are blind. In areas where sidewalks are narrow, parallel ramps are often used, in which the sidewalk itself slopes down to an area that is level with the street (see Figure 2). At a parallel ramp, the sidewalk often curves, and this curvature can affect the direction the pedestrian is facing upon arrival at the street.

Previous research evaluated alignment based on traffic sounds, tactile arrows, and bar tiles. Chew (1986) and Guth, Hill, and Rieser (1989) assessed the skill with which experienced blind pedestrians aligned themselves parallel to and perpendicular to traffic that ranged from a single car to heavy traffic. Their findings suggest that under geometrically ideal conditions, traffic sounds can be used to align to within about 10 degrees of the desired direction. At complex intersections without special alignment cues, blind pedestrians have been found to be misaligned prior to crossing between 24% and 50% of the time (Barlow, Bentzen, & Bond, 2005; Scott, Barlow, Bentzen, Bond, & Gubbe, 2008; Crandall, Brabyn, Bentzen, & Myers, 1999).

Tactile arrows are incorporated into Accessible Pedestrian Signal (APS) pushbuttons to enable users to confirm which crosswalk is controlled by the pushbutton. Individuals at a workshop on curb ramp alignment suggested that tactile arrows may also aid pedestrians in aligning to cross (Stoloff, 2005a). However, Poulsen (1982) found that the presence of an “arrow” (a 2.5 inch long rod mounted atop an APS) did not improve alignment accuracy. Tauchi, Takeda, Nakamura, and Takato (2007) found that when participants aligned with tactile arrows as long as 8 inches, they were able to stay within a 10 foot (3 m) wide by 30 foot (9 m) long path on only 75% of trials; shorter arrows resulted in poorer accuracy.

Takeda, Watanabe, Takahashi, and Tauchi (2006) investigated the ability of blind participants to walk in a straight line for approximately 30 feet when they used a standardized Japanese guiding surface of bar tiles to establish their initial heading.

Participants deviated from the intended heading the least when the bars were oriented perpendicular to the intended direction of travel.

In this study, we assessed the precision of alignment under six cue conditions, including ramp slope alone and ramp slope in combination with each of five other cues. The cues were ones that have been suggested in the literature as alignment cues, are used as alignment cues in other countries, or are advertised/sold as an alignment cue. In the combination conditions, the ramp slope and the other cues were sometimes aligned in the same direction and sometimes in conflicting directions. Because of the variety of curb ramp configurations in the United States and the difficulty of installing any configuration consistently (Kirschbaum et al., 2001), we assumed that any alignment cue would need to be installed either on curb ramps or on the flares (the sloping sides) of curb ramps and would often be on a surface which did not slope in the direction indicated by the cue. If a cue provides good alignment information even when misaligned to the slope, we speculate that it should work as well or better on a level surface such as the landing of a parallel curb ramp.

Methods

Alignment Cues and Apparatus

The alignment cues evaluated in this study are shown in Figure 3 and described below.

- A. **Slope Only:** The slope only condition (i.e. the running slope of the ramp), was included because it has been assumed to provide useful information for alignment, although this has never been documented. For example, draft PROWAG Advisory R303.1 advises aligning ramp slope with the direction of pedestrian travel at crosswalks to provide wayfinding information for visually impaired pedestrians (U.S. Access Board, 2005).
- B. **Bar Tile Perpendicular:** This cue comprises two parallel raised bars arranged perpendicular to the intended direction of travel. It was included because bar tiles arranged in this way have been found by Tauchi et al. (2007) to promote more accurate initial heading than bar tiles arranged parallel to the intended direction of travel.
- C. **Bar Tile Parallel:** This cue was the same tile configuration used in the perpendicular condition but with the raised bars arranged parallel to the intended direction of travel. It was included because it is commonly used internationally as a guidance surface.
- D. **Detectable Warning with Bar Tile:** The cue was a modification to the truncated dome detectable warnings that are required at curb ramps in the United States (U.S. Access Board, 2005) and in many other countries. In the United States, detectable warnings indicate the edge of the street, and are not intended to indicate a direction of travel. However, installation standards in Australia, New Zealand, and the United Kingdom require that truncated dome surfaces be installed perpendicular to the direction of travel on a crosswalk (Standards Australia/Standards New Zealand, 2002; Department of Transport, 2002).

In an unpublished pilot study that also focused on alignment, Long, Barlow, and Bentzen assessed cues that included an unmodified detectable warning. Blind participants were unsuccessful at aligning with the detectable warning, so this cue was not included in the present study.

Because establishing a heading from raised bars perpendicular to the intended direction of travel had been found by Tauchi et al. (2007) to result in relatively accurate travel, it was hypothesized that substituting a single raised bar, perpendicular to the direction of travel, for the bottom two rows of truncated domes on a detectable warning pattern might enable relatively accurate alignment. If this proved to be the case, a single cue (detectable warning with bar) might be used to provide both edge of street information and a cue for alignment. The raised bar on this prototype surface was 18 inches long, so users of most wheelchairs could avoid traversing the bar by placing it between their wheels.

- E. Arrow: This cue consisted of a tactile arrow on a pedestrian pushbutton mounted 42 inches (107 cm) above the surface of the ramp. For half of the participants the pushbutton was on the left, and for the other half of the pushbutton was on the right. This condition was included because a tactile arrow aligned with the direction of travel on the associated crosswalk is required on accessible pedestrian signal pushbuttons in the United States (U.S. Department of Transportation, FHWA, 2009). The arrow is intended primarily to indicate which crossing is actuated by pressing the button. However, if the tactile arrow enables accurate alignment, the use of the arrow for alignment could be encouraged.
- F. Returned Curb: This cue consisted of a simulated curb mounted on one side of a ramp. A returned curb has been assumed to provide alignment information to pedestrians who are blind. For example, Stollof (2005b) suggests “The returned curbs give good cues to crosswalk direction.” This assumption that has not been tested.

Each cue was attached to a ramp structure. Figure 4 shows the profile of the structure which was constructed of plywood and positioned on a level area in a quiet, paved parking lot. The 16 foot (4.9 m) by 24 foot (7.3 m) structure had a landing (representing the sidewalk at the top of a ramp) with four 4 foot (1.2 m) wide by 8 foot (2.4 m) long ramps, at a slope of 1:12, secured to the landing on each side, with the ramps also secured to each other. The directional cues being evaluated were mounted on the two inside ramps on each side of the landing, with the outside ramps being used to provide a safety zone so that participants did not step off the side of the raised structure.

As shown in Figure 3, some of the ramps were outfitted with inlaid rotating circles to which various underfoot tactile directional cues were attached. The circles were locked in place on each trial so the orientation of the cue could be positioned in one of the following seven positions: 0 degrees (in line with ramp slope) and 15, 30 and 45 degrees to the right and left of ramp slope (Figure 3D shows a cue oriented at 45 degrees left). Other cues were mounted atop the ramps and could likewise be rotated to each of the seven positions (Figures 3E and F).

Alignment Measurement

Alignment measurement has traditionally involved measuring the facing direction of the body. For example, Guth et al. (1989) used a shoulder mounted compass in studies of the use of traffic sounds for alignment. There are several practical problems with this approach, the greatest of which is the calibration of the compass such that its orientation relative to the body is known. This and other practical problems involved in the use of a compass are detailed by Guth (1986). There is also the conceptual problem of assuming that the facing direction of one's trunk reflects one's future heading. In other words, one's facing direction is interpreted as predicting one's initial walking direction.

The present study took a more direct approach by measuring a participant's heading over the first 10 feet (3 m) of walking. Once participants decided they were aligned, they walked forward and, while doing so, they crossed over arcs at two distances from the alignment cue. The first arc was near the starting location, and can be seen along the outside edge of the circles shown in Figures 3B–D. Similar arcs were drawn for the conditions that did not use an inlaid circle (Figures 3A, E and F) but these cannot be seen in the photographs. In the same manner, arcs with radii of 10 feet (3 m) were drawn on the asphalt using chalk (see Figures 3B and D). The location at which the left side of the participant's left heel crossed these arcs was recorded. The two recorded locations for a given test surface and trial allowed the calculation of the participant's initial heading.

Participants and Procedure

There were twenty blind participants, none of whom had more vision than light perception. All participants were experienced long cane users, although some customarily used a dog guide. The study was approved by the Boston College Institutional Review Board and all participants gave their informed consent prior to participating.

Before the first experimental condition, participants were oriented to the ramp structure, and before each cue condition, participants were shown the cue (including exploring the underfoot cues with their hands) and they were shown how the orientation of the cues would be changed between trials. The exception was the slope-only condition, before which the participants were instructed that they would be approaching the slope from an angle and should try to align themselves so they were walking straight down the slope of the ramp. Before each cue condition, the method for using the cue was first explained in general terms (e.g., align your feet in the same direction as the underfoot bars) and then a variety of strategies for using the cue were suggested, with participants adopting whatever method they preferred, including methods not mentioned. For example, in the condition shown in Figure 3C, participants were told that they could put one foot to the side of one of the bars, put a foot between the bars, put one or both feet atop the bars, straddle the bars, or use any other strategy that they felt would be effective. For each cue condition, participants practiced for as many trials as they wished until they felt confident in their use of the cue.

For each trial, participants were guided to the level landing by an O&M specialist and positioned facing one of the ramps at randomly varied distances. Participants then walked forward onto the ramp using their long canes, located the alignment cue, used the cue to

establish a heading, and then walked down the ramp and continued beyond the 10 foot (3 m) arc. Several feet after passing the arc, participants were asked to stop walking and were guided back to the landing for the next trial.

Participants completed eight trials per alignment cue, including two trials in which the cue was aligned with the ramp's running slope (0 degrees), and one trial each with the cue positioned 15, 30, and 45 degrees to the right and to the left of the running slope. As described earlier, for the slope only condition, the participants approached the slope from different angles.

Trials were blocked such that participants completed all eight trials with a given cue before moving on to the next cue. The order of the six cue conditions, as well as the order of the alignment orientations was completely randomized for each participant. At the completion of the experimental trials, participants were debriefed to obtain subjective information about which cue conditions they preferred and why.

Results

Overview

For each trial, the orientation of the alignment cue indicated the desired heading. Angular errors were computed as the absolute difference between the desired heading and the actual heading. Thus the average angular error represents how far out of alignment participants tended to be from perfect alignment. Smaller values represent better alignment than larger values.

Effect of Alignment Cue on Average Angular Error

A one-way repeated-measures ANOVA revealed a significant effect of alignment cue on average angular alignment error [$F(5, 80) = 3.68, p < .01, \eta_p^2 = .187$] (Means are presented in Table 1). The step-down Holm-Bonferroni procedure was used to evaluate single-degree-of-freedom planned comparisons between the slope-only condition and each other condition. Both the detectable warning with a perpendicular bar and the perpendicular bar tile resulted in significantly smaller initial alignment errors as compared to the slope-only condition [detectable warning, $F(1, 17) = 11.66, p < .01$; bar tile, $F(1, 17) = 7.90, p < .0125$]. No other comparisons were significant. Consistent with previous research, these results suggest an advantage for underfoot cues that can be oriented perpendicular to the desired direction of alignment.

Effect of Cue-Slope Misalignment

With the exception of the slope-only condition, participants' task was to base their heading on the alignment cue, not the ramp's running slope. We hypothesized that the greater the discrepancy between the two, the more heading error would occur. A one-way repeated-measures ANOVA reveals a significant effect of cue-slope misalignment on average angular error [$F(3, 57) = 2.96, p < .05, \eta_p^2 = .135$], the result of a linear trend of larger errors with greater angles of misalignment between the running slope of the ramp and the cue [$F(1, 19) = 4.81, p < .05$] (Means are presented in Table 2).

This general pattern of results suggests that although slope alone is not a particularly useful alignment cue (as shown in Table 1), a running slope that is discrepant with an alignment cue by 30 degrees or more may have a deleterious effect on the usefulness of that cue. Furthermore, the data suggest that when the cue-slope misalignment was 30 or 45 degrees, the slope exerted a directional “pull” on participants’ paths of travel. On average, participants veered in the direction of the ramp’s running slope (e.g., in 45-degree left conditions, average error was to the right of the direction indicated by the cue).

Subject Survey Responses Compared to Objective Findings on Alignment Cues

After completing all experimental trials, participants were asked to indicate their preferred cue and the cue they found least useful. Interestingly, the tactile arrow received the most first-place votes with seven (out of 20), despite the fact that alignment errors were largest in that condition. Overall, there was not a clear consensus with regard to subjective preference with each of the five cues receiving between three and seven first-place votes. There was far greater consensus regarding the least useful cue; 11 of 20 participants indicated the detectable warning with bar was least useful and an additional 4 selected the slope-only condition. Once again, the subjective preference data is counter to the objective behavioral measures, as the detectable warning with bar resulted in the most accurate alignment performance. Eight of the 11 participants who selected the detectable warning as least useful commented that the surface was “too busy,” that it was difficult to distinguish between the bumps and the bar, and/or that it was difficult to detect the bar.

General Discussion

To relate the alignment errors obtained in this study to an actual street crossing, consider the crossing of a four-lane road where a crosswalk is approximately 50 feet (15 m) long. Assuming that pedestrians begin walking in the center of a 6 foot wide crosswalk and maintain their initial heading for the full distance, and assuming that there is neither veering from nor correction to the initial heading, with 4, 6, 8, and 10.5 degrees of initial misalignment, they would deviate 3.5 feet (1 m), 5.25 feet (1.6 m), 7 feet (2.1 m) and 9.25 feet (2.8 m), respectively, from the center line of the crosswalk. Given these assumptions, the pedestrian would not finish crossing within the crosswalk with even 4 degrees of initial misalignment. If the assumed crosswalk is 10 feet (3.0 m) wide, the pedestrian would complete the crossing within the crosswalk only under the condition of 4 degrees of initial misalignment. Average angles of initial misalignment measured in this study ranged between 6.3 and 10.9 degrees. Accommodating a 10.5 degree initial misalignment would require a crosswalk that is at least 18.5 feet (5.6 m) wide. Because many crosswalks are longer than 50 feet and because veering from one’s initial heading can reasonably be assumed (Rouse & Worchel, 1955; Cratty, 1967; Guth & LaDuke, 1994), even 4 degrees of misalignment could be a serious problem in the absence of information with which to adjust one’s heading, such as the sound of parallel traffic (Guth et al., 1989). In contrast, substantially greater misalignment may be tolerable at shorter crosswalks, such as the typical 12 foot (3.7 m) crosswalk at a single lane roundabout. Using the same assumptions given above for a 50 foot crosswalk, it would require 14.5 degrees of initial misalignment for a pedestrian at a 12 foot crosswalk to leave the crosswalk before completing the crossing.

Not only was the running slope of the ramp found to be an inaccurate alignment cue, but it also was found to interfere with the usefulness of the other cues when it was misaligned with those cues by 30 and 45 degrees. The good news is that there was little effect of this misalignment at 15 degrees, which suggests that minor discrepancies of alignment cues with a ramp's running slope may not be of much consequence. This pattern of findings supports attempting to align the slope of the curb ramp as closely as possible with the direction of travel on the crosswalk in order to maximize the usefulness of other sources of alignment information. This would be a benefit for wheelchair users as well, since turning near the curb to align with the crosswalk or ramp adds time and difficulty to their crossings (Kirschbaum et al., 2001).

In principle, alignment based on the perception of running-slope requires discriminating differences between the downward angle and the lateral forces on the body when walking or standing facing various directions relative to the running slope of the ramp. When oriented in line with the running slope, the downward angle of the foot (i.e., the drop or heel-to-toe-angle) is at its maximum, and there is no lateral force on the body. As the foot/body is rotated relative to the ramp slope, the downward angle decreases and the amount of lateral force increases (e.g., the foot rolls to the side). Although many parts of the body would likely be involved in detecting these differences, it may be an extremely difficult perceptual task. Consider, for example, that relative to standing in line with the 1:12 slope, a 15 degree rotation changes the downward heel-to-toe angle by only 0.16 degrees.

Although several participants subjectively preferred the tactile arrows as an alignment cue, this cue resulted in the least accurate performance. One possible explanation of this finding is that adjusting the alignment of the body with the pointing direction of the hand or arm is a difficult challenge of perceptual-motor coordination (Guth et al., 2010). That is, it may be that the participants were pointing accurately, but they were unable to face and/or walk in the direction they were pointing. Also, a number of participants independently decided to use a strategy of placing their upper arms, held in a relatively vertical position, against the arrow, a strategy that may have felt comfortable or natural to participants, but which had little possibility of providing accurate directional information. Although it remains possible that a strategy exists which would result in good alignment from the arrow, such a strategy was not intuitively obvious to participants, an important consideration in selecting an alignment cue.

Participants were also relatively poor at using the returned curb and using the bar tile when it was aligned parallel to the desired direction of travel. In these conditions, we observed that participants often adopted strategies that involved aligning one foot with the cue. The other foot was commonly observed to point away from the cue, apparently reflecting the normal 5–10 degree V-like out-toeing (“angle of gait”) of the feet that occurs when standing or walking (Rigas, 1984). When participants began walking, they tended to bisect the angle of gait; that is, they walked in the direction of the center of the “V.” When the aligned foot was the right foot, veering was often observed to be to the left of the direction indicated by the cue, and vice versa. Unfortunately, we did not collect the data necessary to make a strong claim in this regard.

However, alignment was most accurate when participants aligned with a bar perpendicular to their feet, either the bar tiles or the detectable warnings with a bar. Individuals used different strategies, with some putting their toes or heels on the bar, while others centered the bar on the balls of their feet, and at least one person lined up the back of the heels against the bar. This is consistent with the findings of Takeda et al. (2006) that perpendicular bars resulted in more accurate alignment than parallel bars. While our participants were most accurate when using the detectable warning with a bar, they subjectively judged it to be the least useful cue. Participants had difficulty finding the bar on the detectable warning surface, often exploring the surface with their feet and canes for several minutes, or even bending down to touch the surface with their hand to confirm the location of the bar. This would clearly be unacceptable in an actual street crossing environment.

Conclusions

For the cues evaluated in this study, performance was best in the two conditions involving underfoot bars mounted perpendicular to the desired walking direction; performance was intermediate for underfoot bars and a simulated curb oriented parallel to the desired direction of travel; and performance was worst for tactile arrows and the running slope of a curb ramp. Better performance may have been observed had the participants received more instruction and practice and been required to use a strategy from which it was possible to obtain good directional information. When the running slope of a curb ramp was misaligned with another alignment cue by 30 or 45 degrees, it tended to exert a directional pull on the participant's heading, which exacerbated alignment error. Even the best alignment cues resulted in an average error of approximately 6 degrees, which at many--but not all--crosswalks would be sufficient to result in walking outside the crosswalk unless additional guidance cues were available *during* the crossing. At many intersections, additional cues may be available from traffic and other intersection features; however, there are also many intersections where such cues are either not available or are intermittent.

While establishing an initial heading is important, blind pedestrians must also *maintain* a proper heading in order to remain within the crosswalk. Accurate initial alignment may not be sufficient to enable blind pedestrians to maintain an accurate heading, particularly for long crossings or those where there is little or no vehicular traffic parallel to the crosswalk. In the second study in this series (Scott et al., in press), we evaluated the usefulness of cues for maintaining a proper heading over simulated street crossings of a one, three, and six-lane street (approx. 12, 36, and 72 feet).

Acknowledgements

This project was supported by Grant #5 R01 EY12894-07 from the National Eye Institute, National Institutes of Health. Its contents are solely the responsibility of the authors and do not necessarily represent the official views of the National Eye Institute.

We thank Bastian Schroeder and Nagui Rouphail of the Institute for Transportation Research and Education at North Carolina State University for technical advice and assistance, Greg Lucier, Johnathan McEntire and Sami Rizkalla of the Constructed Facilities Lab at North Carolina State University for ramp structure design and construction, Daniel Ashmead of Vanderbilt University and Robert Wall Emerson and Dae Kim of Western Michigan University for methodological assistance, Hunter Brown for assistance in moving cues during data collection, and Alison Joy Walker of the North Carolina Rehabilitation Center for recruiting participants. Thanks especially to the individuals who are blind from the Raleigh, North Carolina area who participated in this research.

References

- Barlow, JM.; Bentzen, BL.; Sauerburger, D.; Franck, L. Teaching travel at complex intersections. In: Wiener, W.; Welsh, R.; Blasch, B., editors. Foundations of orientation and mobility. 3rd ed.. Vol. Volume 2. New York, NY: American Foundation for the Blind; 2010.
- Barlow J, Bentzen BL, Bond T. Blind pedestrians and the changing technology and geometry of signalized intersections: Safety, orientation, and independence. *Journal of Visual Impairment and Blindness*. 2005; 99:587–598.
- Chew, SL. Unpublished doctoral dissertation. Minneapolis, MN: University of Minnesota; 1986. The use of traffic sounds by blind pedestrians.
- Crandall W, Brabyn J, Bentzen B, Myers L. Remote infrared signage evaluation for transit stations and intersections. *Journal of Rehabilitation Research and Development*. 1999; 36:341–355. [PubMed: 10678457]
- Cratty BJ. The perception of gradient and the veering tendency while walking without vision. *American Foundation for the Blind Research Bulletin*. 1967; 14:31–51.
- Department of Transport. Guidance on the use of tactile paving surfaces. London, UK: The Scottish Office; 2002. (Publication No. UK 99MU0024) Retrieved from <http://www.dft.gov.uk/adobe/pdf/259428/tactilepavement>
- Guth, DA. Unpublished doctoral dissertation. Nashville, TN: Vanderbilt University; 1986. Preparing to cross a street without vision: Blind and blindfolded pedestrians' use of traffic sounds for spatial orientation.
- Guth DA, Hill EW, Rieser JJ. Tests of blind pedestrians' use of traffic sounds for street-crossing alignment. *Journal of Visual Impairment and Blindness*. 1989; 83:461–468.
- Guth DA, LaDuke RO. The veering tendency of blind pedestrians: An analysis of the problem and literature review. *Journal of Visual Impairment and Blindness*. 1994; 88:391–400.
- Guth, DA.; Rieser, JJ.; Ashmead, DH. Perceiving to move and moving to perceive: Control of locomotion by students with vision loss. In: Wiener, W.; Welsh, R.; Blasch, B., editors. Foundations of orientation and mobility. 3rd ed.. Vol. Volume 1. New York, NY: American Foundation for the Blind; 2010.
- Hauger JS, Rigby JC, Safewright M, McAuley WJ. Detectable warning surfaces at curb ramps. *Journal of Visual Impairment and Blindness*. 1996; 90:512–525.
- Hill, E.; Ponder, P. Orientation and mobility techniques: A guide for the practitioner. New York, NY: American Foundation for the Blind; 1976.
- Kirschbaum, J.; Axelson, P.; Longmuir, P.; Mispagel, K.; Stein, J.; Yamada, D. Designing sidewalks and trails for access, Part II of II: Best practices design guide. Washington, DC: Federal Highway Administration; 2001.
- Poulsen T. Acoustic traffic signal for blind pedestrians. *Applied Acoustics*. 1982; 15:363–376.
- Rouse D, Worchel D. Veering tendency in the blind. *New Outlook for the Blind*. 1955; 55:115–119.
- Rigas C. Spatial parameters of gait related to the position of the foot on the ground. *Prosthetics and Orthotics International*. 1984; 8:130–134. [PubMed: 6522253]
- Scott AC, Barlow JM, Bentzen BL, Bond TLY, Gubbe D. Accessible pedestrian signals at complex intersections: Effects on blind pedestrians. *Transportation Research Record: Journal of the Transportation Research Board*. 2008; 2073:94–103.
- Standards Australia/Standards New Zealand. Australian/New Zealand Standard: Design for access and mobility, Part 4: Tactile indicators. Sydney, Australia: Standards Australia; 2002. (Publication No. AS/NZS 1428.4:2002)
- Stollof E. Wayfinding at intersections: Efforts toward standardization—A joint workshop of the Institute of Transportation Engineers and the U.S. Access Board. *ITE Journal*. 2005a; 75(4):20–25.
- Stollof E. Developing curb ramp designs based on curb radius. *ITE Journal*. 2005b; 75(4):26–32.
- Takeda M, Watanabe Y, Takahashi R, Tauchi M. A study for directionality of bar-shaped, tactile walking surface indicator examined by vision impaired persons. *The Japanese Journal of Ergonomics*. 2006; 42:190–199.

- Tauchi, M.; Sawai, H.; Takato, J.; Yoshiura, T.; Takeuchi, K. Development and evaluation of a novel type of audible traffic signal for the blind pedestrians. Proceedings of the 9th International Mobility Conference; Atlanta, GA. 1998. p. 108-111.
- Tauchi, M.; Takeda, M.; Nakamura, T.; Takato, J. Evaluation of the tactile arrows indicating a direction for vision impaired to cross intersections. Proceedings of the 11th International Conference on Mobility and Transport for Elderly and Disabled Persons; Montreal, Canada. 2007.
- U.S. Access Board. Revised draft guidelines for accessible public rights-of-way. 2005. Retrieved from <http://www.access-board.gov/prowac/draft.pdf>
- U.S. Department of Transportation, Federal Highway Administration. Manual on uniform traffic control devices for streets and highways. 2009. Retrieved from <http://mutcd.fhwa.dot.gov/pdfs/2009/mutcd2009edition.pdf>
- Whipple, M. Proceedings of the Wayfinding at Intersections Workshop. Washington, DC: Institute of Transportation Engineers/U.S. Access Board; 2004. Curb ramp design by elements and planter strip curb ramp.

Figure 1.

Intersections with perpendicular curb ramps in which (A) the ramp slopes in the direction of travel on the crosswalk, and (B) the ramp slopes toward the center of the intersection.

Figure 2.
Intersection with parallel ramps used in the sidewalk.

Figure 3.
Alignment cues and apparatus (details in the text).

Figure 4.
Experimental platform with landing and ramps.

Table 1

Average angular errors by alignment cue condition.

Alignment Cue	Average Angular Error (in degrees)
Slope only	10.2
Arrow	10.9
Returned Curb	8.5
Bar Tile, Parallel	7.7
Bar Tile, Perpendicular	6.4 [†]
Detectable Warning w/ Perpendicular Bar	6.3 [*]

^{*} $p < .01$,

[†] $p < .0125$ (when compared to the slope-only condition using the step-down Holm–Bonferroni procedure for alpha correction)

Table 2

Average angular errors by cue-slope misalignment angle.

Cue-Slope Misalignment Angle (in degrees)	Average Angular Error (in degrees)
0 (aligned with slope)	7.6
15	7.7
30	9.4
45	9.7