Published in final edited form as:

Fire Saf J. 2015 November ; 78: 180–187.

Enforcing realizability in explicit multi-component species transport

Randall J. McDermott^{1,*} and Jason E. Floyd²

¹National Institute of Standards and Technology, Gaithersburg, Maryland ²Jensen Hughes, Baltimore, Maryland

Abstract

We propose a strategy to guarantee realizability of species mass fractions in explicit time integration of the partial differential equations governing fire dynamics, which is a multi-component transport problem (realizability requires all mass fractions are greater than or equal to zero and that the sum equals unity). For a mixture of n species, the conventional strategy is to solve for $n - 1$ species mass fractions and to obtain the n th (or “background”) species mass fraction from one minus the sum of the others. The numerical difficulties inherent in the background species approach are discussed and the potential for realizability violations is illustrated. The new strategy solves all n species transport equations and obtains density from the sum of the species mass densities. To guarantee realizability the species mass densities must remain positive (semidefinite). A scalar boundedness correction is proposed that is based on a minimal diffusion operator. The overall scheme is implemented in a publicly available large-eddy simulation code called the Fire Dynamics Simulator. A set of test cases is presented to verify that the new strategy enforces realizability, does not generate spurious mass, and maintains second-order accuracy for transport.

1 Introduction

This paper deals with a potential flaw in the thermochemical state which feeds the combustion model in the Fire Dynamics Simulator (FDS) for versions prior to and including FDS 6.1.2. It was recently observed that the chemical species mass fractions may sum to be greater than unity [16], a clear violation of realizability. While the impact of this error is deemed to be minor, it is prudent to correct the flaw. In this work, we describe the root causes of the problem and a new solution method, which is implemented in FDS 6.2.0.

A numerical solution is *realizable* if it can physically exist. For example, positive mass densities are realizable, negative mass densities are not. Species mass fractions also have realizability constraints: mass fractions for a mixture of n species must all be greater than or equal to zero and sum to unity. Stated mathematically, the mass fractions obey $Y_\alpha \geq 0$ for all α and $\sum_\alpha Y_\alpha = 1$. In this paper, we discuss a method to enforce this constraint for an *explicit* update of the species transport equations for a multi-component mixture. The scheme is

*randall.mcdermott@nist.gov.

implemented in a publicly available large-eddy simulation (LES) code called the Fire Dynamics Simulator (FDS) [1, 9].

FDS is a fully explicit finite-volume code used to model low-speed flows, with an emphasis on smoke and heat transport from fires. FDS employs block structured Cartesian cells on a staggered grid [4]. Details of the solver, including a complete description of the system of equations governing low-Mach turbulent reacting flows, may be found in [9]. The reader should bear in mind that it is very difficult to estimate time step constraints for our system of equations that are not overly conservative. FDS evaluates stability criteria and makes time step adjustments *after* an explicit predictor step, which is the first stage in a second-order Runge-Kutta scheme. If the time step requires adjustment (based on the predicted velocity fields), the predictor stage is repeated. Within the “adjusttime-step loop”, it is critical that FDS exits the mass transport predictor stage with a realizable mass density field regardless of the chosen time step. Otherwise, the subsequent calculation of the velocity field may result in a run-time error (in other words, the code crashes, often due to unallowable values in a thermochemistry lookup table). Hence, decreasing our time step *a priori* (the usual approach to addressing such problems with explicit methods) is not a viable solution to the problems we will discuss here.

We are concerned with the explicit time integration of the species transport equation and the resulting numerical effects on the species mass fraction field. The species transport equation is (summation over repeated suffixes is implied)

$$\frac{\partial(\rho Y)_\alpha}{\partial t} + \frac{\partial(\rho Y)_\alpha u_i}{\partial x_i} = - \frac{\partial J_{\alpha,i}}{\partial x_i} + \dot{m}_\alpha''' \quad (1)$$

where ρ is the mass density, u_i is the velocity component in direction i , and the diffusive fluxes and chemical source term, respectively, obey the constraints $\sum_\alpha J_{\alpha,i} = 0$ and

$\sum_\alpha \dot{m}_\alpha''' = 0$. Summation of (1) from $\alpha = 1$ to n yields the continuity equation,

$$\frac{\partial \rho}{\partial t} + \frac{\partial \rho u_i}{\partial x_i} = 0. \quad (2)$$

Clearly, between (1) and (2), only n of the $n + 1$ equations are independent.

It is important to appreciate that the transported mass per unit volume of species α in (1) is given by the quantity $(\rho Y)_\alpha$. Numerically, we should distinguish between this and the product $(\rho)(Y_\alpha)$. To avoid confusion, in this paper whenever we write $(\rho Y)_\alpha$ we mean the transported dependent variable in (1). We will use $(\rho)(Y_\alpha)$ to indicate the product of the density and the mass fraction of α . Of course, our goal is to make these consistent. Below we will discuss the numerical challenges this presents.

The species transport equation (1) may be cast as an ordinary difference equation [7] of the

form $\frac{d\phi}{dt} = f_\phi$. Our goal is to update the unknown ϕ from t^k to $t^{k+1} = t^k + \Delta t$. By definition, in an *explicit* scheme, all terms in f_ϕ are evaluated at time t^k or earlier. For example, an explicit Euler update is given by

$$\phi^{k+1} = \phi^k + \Delta t f_{\phi}^k. \quad (3)$$

The second-order time marching scheme used in FDS is known as a strong-stability-preserving (SSP) Runge-Kutta (RK) method [3]. SSP methods inherit the total variation diminishing (TVD) properties of their individual explicit steps. Hence, within this paper we may focus on the properties of the Euler update, as in (3).

The right-hand-side of the ordinary difference equation, f_{ϕ}^k , contains both advective and diffusive transport terms. Chemistry is time split from transport and does not contribute to any realizability violation. The diffusive flux terms are modeled using Fick's law with mixture-averaged diffusivities (this is discussed further in the next section). In FDS, the advective flux terms are based on flux limiters, which essentially interpolate the cell-centered scalar values to the cell faces in such a way as to limit oscillations in the scalar solution. FDS employs both Superbee [14] and CHARM [19] limiters for LES and DNS, respectively. But other options are available. For example, the bounded QUICK or BQUICK scheme of Herrmann et al. [5] enforces global bounds on the scalar by automatically switching to first-order upwinding (Godunov) (see, e.g., [18]) if the scalar were to go out of bounds for the chosen time step (note, however, that BQUICK is not locally TVD). Regardless of the chosen limiter, for an explicit update the time step must be small enough to maintain boundedness (even Godunov is not unconditionally stable). To ensure a robust code, the method proposed in this paper is designed to handle all degenerate cases that we may encounter in practice.

The remainder of this paper is organized as follows. In the next section, we describe options for solving the system of equations governing variable-density, low-Mach reacting flows. In Sec. 3, we identify the sources of realizability violations in common solver strategies. To overcome these issues, we adopt the strategy of solving transport equations for *all* mixture species. The problem of scalar boundedness, which is shared by all strategies, is addressed in Sec. 4. In Sec. 5, we present a range of verification cases to illustrate the improvements in the solver while maintaining second-order transport accuracy. Finally, conclusions are given in Sec. 6.

2 Methods for Low-Mach Reacting Flows

If we add temperature to our list of dependent variables and energy to our list of equations, we can understand the approaches for solving the system of equations for typical combustion problems. The methods may be categorized by how they compute density and how they compute diffusive fluxes. The density is obtained either from the equation of state (EOS) or from solving the continuity equation (actually this variant is most common in compressible Euler schemes). To our knowledge, obtaining the total mass density by explicit summation of ρY_{α} , as we propose below, is a novel approach.

The level of sophistication needed in computing the diffusive fluxes depends greatly on the application. For large-eddy simulations it is uncommon to employ detailed multi-component transport (see, e.g., [17]). Instead, it is common to employ mixture-averaged Fickian

diffusion. To guarantee the diffusive fluxes sum to zero, there are basically two options. The first is to use a “background” species to absorb the error into a single species concentration (see, e.g., [13]). The second is to apply a correction velocity to all species (see, e.g., [12, 13]). The background error method, which we have adopted in FDS, is the simplest and cheapest computationally and is completely adequate for handling diffusive transport for practical fire applications.

Below we provide a more detailed account of selected methods for solving our system of equations in order to provide a basis for comparison with the proposed new algorithm.

Method 1 (Typical)

The most common approach to solving our system of equations is to obtain the temperature from the energy equation, the density from the EOS, and to solve only $n - 1$ of the species equations. The mass fraction of the n th species is obtained from $Y_n = 1 - \sum_{\alpha=1}^{n-1} Y_\alpha$. This method is iterative because to obtain any individual mass fraction requires $Y_\alpha = (\rho Y)_\alpha / \rho$ where ρ is from the EOS. But the EOS requires Y_α . Note that the n th species is usually taken to be the most abundant (prescribed *a priori*) and is often referred to as the “background”. For this method, no constraint on the diffusive fluxes is enforced, as all errors in diffusive transport are absorbed by the background species.

Method 2 (current FDS approach)

Historically the strategy employed by FDS has been to solve the continuity equation (2) directly for ρ and then to solve $n - 1$ of the species equations. Individual mass fractions are obtained from $Y_\alpha = (\rho Y)_\alpha / \rho$, as in Method 1, but here ρ does not require iteration. Again, the remaining species mass fraction is obtained from $Y_n = 1 - \sum_{\alpha=1}^{n-1} Y_\alpha$. The temperature is then obtained from the EOS. The energy equation is still used to form a flow divergence constraint that tightly couples mass, momentum, and energy [8]. It should be noted that both the EOS and transport equation for density are consistent by construction. As we will see, the strategy used in Methods 1 and 2 to obtain Y_n is dangerous in terms of realizability. These approaches may also generate spurious mass.

Method 3 (present proposal)

If $(\rho Y)_\alpha$ obeys boundedness, $(\rho Y)_\alpha \geq 0$, and we solve n species equations obtaining the density via $\rho = \sum_{\alpha=1}^n (\rho Y)_\alpha$, then mass fractions obtained by $Y_\alpha = (\rho Y)_\alpha / \rho$ are *guaranteed to be realizable* (for $\rho > 0$). Thus, we have reduced the realizability problem to the “easier” problem of boundedness for $(\rho Y)_\alpha$ (of course, the other two methods must also address boundedness for an explicit scheme). Details of the scalar boundedness correction are discussed in Sec. 4.

With this approach we must take care to ensure $\sum_\alpha J_{\alpha,i} = 0$. Our strategy is to absorb any errors in diffusive transport into the most abundant species *locally*. That is, for a given cell face we set $J_{m,i} = - \sum_{\alpha \neq m} J_{\alpha,i}$, where m is the most abundant species adjacent to that face. (In practice, because of the way fluxes and cell-centered scalars are stored in FDS, it is most

convenient to look at the concentration on the minus side of the face normal to direction i .) Note that, since FDS is typically used as an LES code, mass transport by molecular diffusion may be two or three orders of magnitude less than turbulent transport, which uses the same turbulent diffusion coefficient for all species (hence, no errors in summation of the diffusive fluxes).

In the FDS algorithm, integration of the mean chemical source term, $\dot{m}_\alpha'''$, is time split from transport (refer to [9] for details) and therefore does not directly create a realizability problem in the transport step, which is the focus of this paper. To be clear, *the chemistry submodel does not violate realizability*—all violations occur upon exit of the transport step. It is apparent, however, that the steep gradients created by the chemistry substep exacerbate the boundedness and realizability problems faced by the transport scheme.

3 Potential Problems with Solver Strategies

Below we list the potential problems that may arise for explicit time updates using the methods discussed above. The problem of enforcing boundedness is shared by all three methods. If boundedness is satisfied, Methods 1 and 2 also have the potential for unrealizable mass fractions and spurious mass creation.

Boundedness

In any of the approaches, the possibility exists that an *explicit* update of the species transport equation will result in $(\rho Y)_\alpha < 0$. Obviously, this result must be corrected. But how it should be corrected is not so obvious. Suppose the floating-point result (the representation of the real number on a digital computer) is $(\rho Y)_\alpha = -1.0 \times 10^{-10}$? Are we justified in “clipping” this value to zero? Generally, no. Repeated application of such clipping, when applied millions of times in a simulation, can produce significant mass conservation errors. It is better to apply a correction. Our correction strategy is outlined in Sec. 4.

Spurious mass creation

Spurious mass is created when the background species should be absent and one minus the sum of the other species gives a small positive number, $Y_n = 1 - \sum_{\alpha=1}^{n-1} Y_\alpha = +\epsilon$. One can make the argument that a different background species should be chosen. But in practice this is not always possible. The net result is that species n magically appears without being introduced through a boundary or created by a reaction.

Sum of tracked species greater than unity

This is the problem that initiated the present work. It is possible to end up with the condition $\sum_{\alpha=1}^{n-1} Y_\alpha > 1$ while the individual Y_α are all bounded between 0 and 1. Of course, the result would then give $Y_n < 0$. But, as alluded to above, the temptation is to simply clip (hopefully small) negative values of mass fraction. Currently, FDS first applies a filter to the mass fraction field to correct any boundedness violations and then clips any values that are not caught by the filter (the filter is not perfect—but a major shortcoming of the old correction scheme is addressed here in Sec. 4). The filter corrects for boundedness and it was

previously assumed that $Y_n = 1 - \sum_{\alpha=1}^{n-1} Y_\alpha$ enforced realizability. But, in fact, this last step does *not* enforce realizability if we must resort to clipping Y_n .

To illustrate the resulting problem, Fig. 1 (Left) shows a methane fire (500 kW) simulated using Method 2 above. We use a “mixed is burnt” model for combustion chemistry, Fuel + Air $\rightarrow$ Products. Hence, there are three “lumped species”, Fuel, Air, and Products, in this simulation (a lumped species is a grouping of primitive species that transport and react together, implying equal diffusivities for all primitive species within a given lumped species [9]). Note that in Method 2 only two of the three lumped species are tracked. In this case, we track Fuel and Products. Air is the background species. A virtual concentration measurement device is placed in the center near the base of the fire. On the right in the figure is a plot of the mass fractions of Fuel, Air, and Products along with the sum (dashed line). As can be seen, there are several excursions of the sum above one, a clear violation of realizability. We determined that the root cause of the realizability violation was not integration of the mean chemical source term. The problem originates in the explicit transport step, though it seems to be the case that chemical reaction exacerbates the underlying transport problems (we speculate that this is due to steep scalar gradients that appear after the time splitting of the chemical source term).

4 Scalar Boundedness Correction

In this section, we work in terms of the mass density ρ , but species mass densities $(\rho Y)_\alpha$ are treated analogously. Our goals are, first, to illustrate why boundedness violations may occur, and second, to outline a scheme to correct these violations.

Consider the explicit time update of (2) in one dimension (1D). We assume a constant wind speed u moving from left to right and we use first-order upwinding (Godunov’s scheme) (see, e.g., [6, 18]) for the scalar face value. The forward Euler update for cell j is then

$$\rho_j^{k+1} = \rho_j^k - \frac{\Delta t u}{\Delta x} (\rho_j^k - \rho_{j-1}^k). \quad (4)$$

For arbitrarily small values of ρ_{j-1}^k , positivity of ρ_j^{k+1} requires $\frac{\Delta t u}{\Delta x} \leq 1$. This is the well-known CFL (Courant-Friedrichs-Lewy) time step constraint (see, e.g., [6, 18]).

In general, FDS employs second-order flux limiters (Superbee [14] or CHARM [19]), which are total variation diminishing (TVD) under certain CFL limitations. Unfortunately, it is impossible to predict the precise CFL stability limit for an arbitrary, nonlinear 3D flow field [18]. So, we are faced with a choice: (1) be overly conservative and pay the price of increased simulation times (perhaps by a factor of 2 or more) or (2) live with the fact that we may, on occasion, overstep the local CFL limit and be forced to correct the violation. In practice, the latter approach must be considered, which we discuss next.

1D example

We start by considering a minimum boundedness violation for density in 1D. Let ρ_i^* denote the resulting density from the explicit transport step for cell i with volume V_i . Our goal is to find a correction $\delta\rho_i$ that

- a. satisfies boundedness, $\rho_i = \rho_i^* + \delta\rho_i \geq \rho_{\min}$ for all i
- b. conserves mass, $\sum_i \delta\rho_i V_i = 0$
- c. minimizes data variation, $\sum_i |\delta\rho_i|$ (i.e., we change the field as little as possible)

The basic idea is to apply a linear smoothing operator, $\mathcal{L}$, to the density field in regions where boundedness violations have occurred. So, the correction may be viewed as an explicit diffusion step applied to the uncorrected field with diffusion coefficient c ,

$$\rho = \rho^* + c\mathcal{L}(\rho^*). \quad (5)$$

Let us envision that the density in cell i is negative but that the densities in cells $i-1$ and $i+1$ are both in bounds (this actually is what happens most of the time with dispersion error). We therefore want a correction that takes mass away from $i-1$ and $i+1$ and moves it to i to make up the deficit. We know that for cell i the minimum change in mass and therefore the minimum correction that will satisfy boundedness is $\delta\rho_i = \rho_{\min} - \rho_i^*$. We take the operator $\mathcal{L}$ as the standard discrete Laplacian. The correction for cell i is then

$$\rho_i = \rho_i^* + \delta\rho_i, \quad \rho_i = \rho_i^* + \rho_{\min} - \rho_i^*, \quad \rho_i = \rho_i^* + c_i(\rho_{i-1}^* - 2\rho_i^* + \rho_{i+1}^*). \quad (6)$$

Comparing the second and third lines, we find that the diffusion coefficient is given by

$$c_i = \frac{\rho_{\min} - \rho_i^*}{\rho_{i-1}^* - 2\rho_i^* + \rho_{i+1}^*}. \quad (7)$$

It may be noted that (6) and (7) are similar to the corrections derived for BQUICK [5]. Based on the third line of (6), the correction for cell i may be thought of as the sum of the two mass fluxes from its neighboring cells. The change in mass of cell i is $\delta m_i = \delta\rho_i V_i$ and is balanced by changes in mass for cells $i-1$ and $i+1$:

$$\delta m_{i-1} = -c_i(\rho_{i-1}^* - \rho_i^*)V_i,$$

$$\delta m_{i+1} = -c_i(\rho_{i+1}^* - \rho_i^*)V_i.$$

In this case the sum of the mass corrections is zero, as desired:

$$\sum_{j=i-1}^{i+1} \delta m_j = \delta\rho_{i-1}V_{i-1} + \delta\rho_i V_i + \delta\rho_{i+1}V_{i+1}, \quad = -c_i(\rho_{i-1}^* - \rho_i^*)V_i + c_i(\rho_{i-1}^* - 2\rho_i^* + \rho_{i+1}^*)V_i - c_i(\rho_{i+1}^* - \rho_i^*)V_i, \quad = 0.$$

Realistic cases

The discussion above is meant to provide a simple case for understanding the basic idea behind the correction method. In a realistic case we must account for multi-dimensional aspects of the problem (standard 3D discrete Laplacian is used for $\mathcal{L}$) and for the possibility that neighboring cells may both be out of bounds. Details of the full correction scheme may be found in [9].

Degenerate cases

With the correction scheme discussed above there are two situations that require special attention (remember, we are considering arbitrarily large time steps for an explicit time update). The first is that a single diffusion step may not be sufficient to alleviate all boundedness errors. And the second is that it is possible—in a multi-component flow—that all the species mass densities get corrected to zero to machine precision. Of course, this results in a zero mass density, $\rho = \sum_{\alpha} (\rho Y)_{\alpha} = 0$, and then the calculation of $Y_{\alpha} = (\rho Y)_{\alpha} / \rho$ produces a floating-point overflow.

The solution to both these problems is to compute $\rho = \sum_{\alpha} (\rho Y)_{\alpha}$ *before* the species correction. We then correct this density via the same procedure outlined above with $\rho_{\min} > 0$. We also apply the correction to the mass density for each species with $(\rho Y)_{\alpha, \min} = 0$. The error in species mass density is, again, absorbed in the most abundant species locally,

$$(\rho Y)_m = \rho - \sum_{\alpha, \alpha \neq m} \max[0, (\rho Y)_{\alpha}], \quad (8)$$

where m corresponds to the maximum value of $(\rho Y)_{\alpha}$ *after correction*. Notice that after one round of correction we do—as a last resort—clip the species mass densities to be positive within the summation in (8). As we will see in the test cases below, this is a robust procedure that should be invoked rarely in practice and does not adversely affect the final results.

5 Verification Test Cases

The following test cases illustrate that the new scheme yields realizable mass fractions (Sec. 5.1), does not generate spurious mass (Sec. 5.2), and is second-order accurate (Sec. 5.3). All the input files for cases presented below are archived in the FDS verification suite [1, 10]. All cases were run with a pre-release of FDS 6.2.0 (Subversion 21586).

5.1 Realizability

As shown in Fig. 2, when the new scheme is applied to the methane burner problem discussed above in Sec. 3 the resulting mass fraction time history is realizable. No qualitative differences in the flame dynamics are observed (compare with the mean temperature map image in Fig. 1). The integrated heat release rate curves for the old scheme and the new scheme are shown in Fig. 3. The curves follow each other closely at the initial transient and oscillate around the prescribed 500 kW later in the simulation. This indicates that, while the realizability violations are undesirable, previous FDS results should be valid within the uncertainties established in the FDS Validation Guide [11].

5.2 Mass conservation

In this case, several species are introduced into the domain via a solid phase chemical reaction. The domain is a sealed box. The added species, which enter the calculation through a mass flux boundary condition, are CO_2 , NO , NO_2 , and Cl_2 . The interesting aspect of this problem is that we track two additional species that are neither created nor destroyed via chemical reaction. One of these species is nitrogen, initialized to have zero concentration. The other species is argon, initialized to a mass fraction of unity throughout the domain. Ideally, we should see no spurious creation of N_2 mass and no spurious destruction of Ar mass. This is a nontrivial exercise because the issues discussed in Sec. 3 can lead to spurious creation of the background (in this case N_2) and spurious destruction of a species whose total mass should remain constant to machine precision (in this case Ar).

The results for the new scheme are shown in Fig. 4. The image on the left shows the Ar mass fraction field at some later time in the simulation. The point of this plot is to impress upon the reader that the mass fraction field is nontrivial. Therefore, discrete conservation of total mass is challenging. The plot on the right is a time history of the mass of each species in the box. Note that the symbols for the injected species all overlap; they each rise slightly up to a value of 0.1 kg by the end of the run. From the plot, it is apparent that the masses of Ar and N_2 are reasonably constant. What cannot be discerned from the plot is that the mass is constant to eight significant figures. The argon mass is maintained at 1.6605509E+000 kg. And the nitrogen mass is maintained at 0.0000000E+000 kg. This is a noteworthy achievement given that the total mass is always reconstructed from a volume integral of $(\rho)(Y_\alpha)$.

Figure 5 shows the change in mass for nitrogen and argon for Method 2 (old scheme, left) and Method 3 (new scheme, right). As can be seen, the background species approach used in the old scheme causes spurious creation of background species (N_2 in this case), while the transported species (argon) remains reasonably constant. As shown on the right, the new scheme solves the spurious mass creation problem (by construction).

5.3 Accuracy

To demonstrate second-order accuracy of the new species transport algorithm, here we present numerical results for the manufactured solution proposed by Shunn et al. [15]. The parameters for this problem are given in Table 1. In the 2D sinusoidal solution given below, Z is the mixture fraction, ρ is the density, u and v are velocity components, and p is the hydrodynamic pressure. The solution translates diagonally across the domain with velocity $[u_f, v_f]$. The translated positions are defined by $\hat{x} \equiv x - u_f t$ and $\hat{y} \equiv y - v_f t$. The solution is spatially periodic on a square domain extending from -1 m to 1 m ($L = 2$ m) on each side and has a time period of 1 s.

$$Z(x, y, t) = \frac{1 + \sin(\pi k \hat{x}) \sin(\pi k \hat{y}) \cos(\pi \omega t)}{(1 + \frac{\rho_0}{\rho_1}) + (1 - \frac{\rho_0}{\rho_1}) \sin(\pi k \hat{x}) \sin(\pi k \hat{y}) \cos(\pi \omega t)} \quad (9)$$

$$\rho(x, y, t) = \left(\frac{Z(x, y, t)}{\rho_1} + \frac{1 - Z(x, y, t)}{\rho_0} \right)^{-1} \quad (10)$$

$$u(x, y, t) = u_f + \frac{\rho_1 - \rho_0}{\rho(x, y, t)} \left(\frac{-\omega}{4k} \right) \cos(\pi k \hat{x}) \sin(\pi k \hat{y}) \sin(\pi \omega t) \quad (11)$$

$$v(x, y, t) = v_f + \frac{\rho_1 - \rho_0}{\rho(x, y, t)} \left(\frac{-\omega}{4k} \right) \sin(\pi k \hat{x}) \cos(\pi k \hat{y}) \sin(\pi \omega t) \quad (12)$$

$$\tilde{p}(x, y, t) = \frac{1}{2} \rho(x, y, t) u(x, y, t) v(x, y, t) \quad (13)$$

The source terms for the manufactured solution, $\dot{Q}_\rho$, etc., are defined as the residuals of the conservative form of the transport equations:

$$\frac{\partial \rho}{\partial t} + \nabla \cdot (\rho \mathbf{u}) = \dot{Q}_\rho, \quad (14)$$

$$\frac{\partial(\rho Z)}{\partial t} + \nabla \cdot (\rho Z \mathbf{u}) - \nabla \cdot (\rho D \nabla Z) = \dot{Q}_Z, \quad (15)$$

$$\frac{\partial(\rho \mathbf{u})}{\partial t} + \nabla \cdot (\rho \mathbf{u} \mathbf{u}) + \nabla \tilde{p} - \nabla \cdot \mathbb{T} = \dot{Q}_\mathbf{u}, \quad (16)$$

where the components of the deviatoric stress tensor, $\mathbb{T}$, are given by

$$T_{ij} = 2\mu \left(S_{ij} - \frac{1}{3} S_{kk} \delta_{ij} \right); S_{ij} \equiv \frac{1}{2} \left(\frac{\partial u_i}{\partial x_j} + \frac{\partial u_j}{\partial x_i} \right). \quad (17)$$

The source terms (which are complex sinusoidal functions) may be obtained from [15]. A feature of this particular solution is that the mass source is zero, $\dot{Q}_\rho = 0$, which provides a more realistic test case and simplifies the manufactured solution implementation.

Manufactured Solution Procedure—Two species transport equations are solved. The mixture fraction in the manufactured solution is set as component 2:

$$\frac{\partial(\rho Z_1)}{\partial t} + \nabla \cdot (\rho Z_1 \mathbf{u}) - \nabla \cdot (\rho D \nabla Z_1) = -\dot{Q}_Z, \quad (18)$$

$$\frac{\partial(\rho Z_2)}{\partial t} + \nabla \cdot (\rho Z_2 \mathbf{u}) - \nabla \cdot (\rho D \nabla Z_2) = -\dot{Q}_Z. \quad (19)$$

The density is obtained via $\rho = (\rho Z)_1 + (\rho Z)_2$.

Define the Bernoulli integral $H \equiv \tilde{p}/\rho + \frac{1}{2}|\mathbf{u}|^2$. The RHS of the momentum equation is rearranged into Stokes' form and written as follows:

$$\frac{\partial \mathbf{u}}{\partial t} = -(\mathbf{F} + \nabla H) + \dot{\mathbf{Q}}_{\mathbf{u}}/\rho. \quad (20)$$

The Poisson equation for H becomes

$$\nabla^2 H = - \left[\nabla \cdot (\mathbf{F} - \dot{\mathbf{Q}}_{\mathbf{u}}/\rho) + \frac{\partial}{\partial t}(\nabla \cdot \mathbf{u}) \right]. \quad (21)$$

The thermodynamic divergence, $\nabla \cdot \mathbf{u}$, is factored out of the discrete conservative form of the sensible enthalpy equation. Details are provided in [8, 9]. The continuous form of the divergence expression is shown here for reference:

$$\nabla \cdot \mathbf{u} = \frac{1}{\rho h_s} \left[\frac{D}{Dt}(\bar{p} - \rho h_s) + \dot{q}''' - \nabla \cdot \dot{\mathbf{q}}'' \right]. \quad (22)$$

Here, h_s is the sensible enthalpy, $\bar{p}$ is the thermodynamic pressure (constant in this case), $\dot{q}'''$ is the heat release rate (zero in this case), and $\dot{\mathbf{q}}''$ is the heat flux vector (including radiation). Of course, for this particular problem the divergence could be obtained analytically from the velocity field solution. But in general this is not possible. For the purposes of verification of the algorithm all terms are retained in the solution procedure.

Simulations are performed for $N = \{32, 64, 128, 256, 512\}$, where N is the number of cells in each direction, using an adaptive time step satisfying both convective and diffusive CFL numbers of 0.5. The time step criterion and the simulation parameters in Table 1 are chosen to match Shunn et al. [15]. The density equation (14) is solved using the CHARM flux limiter. Qualitative results for the 256^2 case are shown in Fig. 6. These images may be compared to the images presented in [15]. In Fig. 7, we plot the L2 error at time $t = 1$ s as a function of grid spacing, $\Delta x = L/N$, confirming second-order accuracy of the solutions for density, mixture fraction, and velocity. As shown in Fig. 7, schemes such as ours, where the pressure is set to zero at the beginning of each stage of the integration (in other words, no pressure gradient term shows up in the source term for the Poisson equation), are known to be first-order accurate for pressure [2]. This is not a severe limitation of the algorithm since the hydrodynamic pressure does not factor into the equation of state for low-Mach flows.

6 Conclusions

In this paper we have identified shortcomings in the strategy of solving only $n - 1$ of the species transport equations in explicit fire dynamics simulations. Floating-point truncation errors can lead to spurious mass creation or destruction and, worse, unrealizable mass fractions if clipping is required of the n th species. While boundedness corrections were applied in previous versions of FDS, clipping of the background species led to the possibility of realizability violations (see Fig. 1). This problem is illustrated for a simple methane fire where we observe occasional excursions of the mass fraction sum above unity, up to values near 1.2. It should be noted that this did not adversely affect the heat release

rate since fuel mass is unlikely to be clipped (see Fig. 3). The most likely scenarios to feel the ill effects of the realizability violations would be cases using Arrhenius chemistry or cases that rely heavily on the thermal extinction model. The validity of current and older versions of FDS still may be traced to the uncertainties published in the FDS Validation Guides [11].

To solve the realizability problem we have adopted the strategy of solving n species transport equations and obtaining the density via $\rho = \sum_{\alpha} (\rho Y)_{\alpha}$. Mass fractions are then obtained via $Y_{\alpha} = (\rho Y)_{\alpha} / \rho$. This composition is guaranteed to be realizable provided $(\rho Y)_{\alpha} \geq 0$. An improved boundedness correction procedure is provided, which highlights degenerate cases and solves these problems by absorbing any errors in the most abundant *local* species. Note that the present strategy eliminates the possibility of both overshoots ($\sum_{\alpha} Y_{\alpha} > 1$) and undershoots ($\sum_{\alpha} Y_{\alpha} < 1$) in the composition field.

To verify the claims made in this paper we present several test cases. First, we rework the methane fire case (which originally exposed the realizability violations) and show that species mass fractions are indeed realizable with the new method (compare Figs. 1 and 2). This is the key result of the paper. The second test case illustrates that the new scheme does not generate or destroy mass spuriously (see Fig. 4). The final test case confirms that the new scheme maintains second-order accuracy for density and species mass fractions (see Fig. 7).

Acknowledgments

The authors wish to thank Dan Swenson of Thunderhead Engineering for identifying the realizability issue [16].

References

1. <http://firemodels.github.io/fds-smv>.
2. Armfield S, Street R. An analysis and comparison of the time accuracy of fractional-step methods for Navier-Stokes equations on staggered grids. *Int. J. Num. Meth. Fluids*. 2001; 38:255–282.
3. Gottlieb S, Shu C-W, Tadmor E. Strong Stability-Preserving High-Order Time Discretization Methods. *SIAM Review*. 2001; 43(1):89–112.
4. Harlow FH, Welch JE. Numerical calculation of time-dependent viscous incompressible flow of fluid with a free surface. *Phys. Fluids*. 1965; 8:2182.
5. Herrmann M, Blanquart G, Raman V. Flux Corrected Finite Volume Scheme for Preserving Scalar Boundedness in Reacting Large-Eddy Simulations. *AIAA Journal*. 2006; 44(12):2879–2886.
6. LeVeque, RJ. *Numerical Methods for Conservation Laws*. 2nd edition. Springer Basel AG; 1992.
7. Lomax, H.; Pulliam, TH.; Zingg, DW. *Fundamentals of Computational Fluid Dynamics*. 2nd edition. Springer; 1999.
8. McDermott RJ. A velocity divergence constraint for large-eddy simulation of low-Mach flows. *J. Comput. Phys*. 2014; 274:413–431.
9. McGrattan, K.; Hostikka, S.; McDermott, R.; Floyd, J.; Weinschenk, C.; Overholt, K. *Fire Dynamics Simulator, Technical Reference Guide, Volume 1: Mathematical Model*. sixth edition. National Institute of Standards and Technology, Gaithersburg, Maryland, USA, and VTT Technical Research Centre of Finland, Espoo, Finland; 2013 Sep.
10. McGrattan, K.; Hostikka, S.; McDermott, R.; Floyd, J.; Weinschenk, C.; Overholt, K. *Fire Dynamics Simulator, Technical Reference Guide, Volume 2: Verification*. sixth edition. National Institute of Standards and Technology, Gaithersburg, Maryland, USA, and VTT Technical Research Centre of Finland, Espoo, Finland; 2013 Sep.

11. McGrattan, K.; Hostikka, S.; McDermott, R.; Floyd, J.; Weinschenk, C.; Overholt, K. Fire Dynamics Simulator, Technical Reference Guide, Volume 3: Validation. sixth edition. National Institute of Standards and Technology, Gaithersburg, Maryland, USA, and VTT Technical Research Centre of Finland, Espoo, Finland; 2013 Sep.
12. Oran ES, Boris JP. Detailed Modeling of Combustion Systems. Progress in Energy and Combustion Science. 1981; 7:1–72.
13. Poinso, T.; Veynante, D. Theoretical and Numerical Combustion. 2nd edition. Philadelphia, Pennsylvania: R.T. Edwards, Inc.; 2005.
14. Roe PL. Characteristics-based schemes for the Euler equations. Ann. Rev. Fluid Mech. 1986; 18:337.
15. Shunn L, Ham F, Moin P. Verification of variable-density flow solvers using manufactured solutions. J. Comput. Phys. 2012; 231:3801–3827.
16. Swenson D. <https://github.com/firemodels/fds-smv/issues/2261>.
17. Taylor, R.; Krishna, R. Multicomponent Mass Transfer. Wiley-Interscience; 1993.
18. Toro, EF. Riemann Solvers and Numerical Methods for Fluid Dynamics: A Practical Introduction. 2nd edition. Springer; 1999.
19. Zhou, G. PhD thesis. Chalmers Univ. of Tech.; Goteborg, Sweden: 1995. Numerical simulations of physical discontinuities in single and multi-fluid flows for arbitrary Mach numbers.

Figure 1.

(Left) Mean temperature contours (°C) for a 500 kW methane fire. (Right) Mass fraction time history. A virtual measurement device records the species mass fractions at a point near the flame base ($x = 0$ m, $z = 0.2$ m). The plot shows the Fuel, Air, and Product fractions.

While all mass fractions are bounded ($0 \leq Y_\alpha \leq 1$), there are significant jumps in $\sum_{\alpha=1}^n Y_\alpha$ above unity.

Figure 2.

(Left) Mean temperature contours ($^{\circ}\text{C}$) for a 500 kW methane fire (comparable to Fig. 1 (Left)). (Right) Mass fraction time history from a single point near the base of the fire ($x = 0$ m, $z = 0.2$ m) using the new transport algorithm with the updated correction scheme (with proper handling of degenerate cases). Note that the mass fraction sum remains unity with all three tracked species maintaining positive concentrations.

Figure 3.

Time history of integrated heat release rate from the methane fire (Figs. 1 and 2) for the old scheme (open circles) and new scheme (+). The mean heat release rate is the prescribed 500 kW for both simulations.

Figure 4.

(Left) Mass fraction contours of argon at $t = 50$ s in a plane through the center of the domain. (Right) Time history of total mass of Ar and N_2 and other species (symbols overlap) in a sealed box. Even though the density field is changing and the Ar mass fraction field is nontrivial, the total mass of Ar in the domain is perfectly constant. Also, the nitrogen field remains perfectly zero, even though N_2 is a tracked species.

Figure 5. Change in mass for N₂ and Ar for the Mass Conservation problem (same as Fig. 4). (Left) Old scheme, Method 2 in Sec. 2, with N₂ set as the background species. (Right) New scheme, Method 3 in Sec. 2. Notice that spurious creation of N₂ (background) occurs with the old scheme (left), i.e., the background species approach.

Figure 6. Evolution of the variable-density manufactured solution. From top to bottom, the images show density, ρ , mixture fraction, Z , and the u -velocity component from the 256^2 simulation at the times shown at the top of the columns. These results may be compared to [15] to confirm the validity of the numerical solution.

Figure 7.

Convergence for the manufactured solution. The L2 error at time $t = 1$ s is plotted as a function of grid spacing for $N = \{32, 64, 128, 256, 512\}$ points in each direction. The grid spacing is $\Delta x = L/N$, where $L = 2$ m. Calculations were performed with an adaptive time step satisfying both convective and diffusive CFL (Von Neumann) limits of 0.5. These results confirm second-order accuracy of the flow solver for density, mixture fraction, and velocity. As is known for projection schemes like ours, the pressure solution (represented by H) is first-order accurate [2].

Table 1

Parameters for Shunn et al. [15] manufactured solution.

Parameter	Value	Units
ρ_0	5	kg/m ³
ρ_1	1	kg/m ³
$k = \omega$	2	1/m, 1/s
$u_f = v_f$	0.5	m/s
$\rho D = \mu$	0.001	kg/(m · s)