A dual-core double emulsion platform for osmolarity-controlled microreactor triggered by coalescence of encapsulated droplets

Xuwei Guan,^{1,a)} Likai Hou,^{1,a)} Yukun Ren,^{1,2,b)} Xiaokang Deng,¹ Qi Lang,¹ Yankai Jia,¹ Qingming Hu,¹ Ye Tao,¹ Jiangwei Liu,¹ and Hongyuan Jiang^{1,2,b)}

¹*School of Mechatronics Engineering, Harbin Institute of Technology, West Da-zhi Street 92, Harbin, Heilongjiang 150001, People's Republic of China*

²*State Key Laboratory of Robotics and System, Harbin Institute of Technology, West Da-zhi Street 92, Harbin, Heilongjiang 150001, People's Republic of China*

(Received 11 April 2016; accepted 13 May 2016; published online 24 May 2016)

Droplet-based microfluidics has provided a means to generate multi-core double emulsions, which are versatile platforms for microreactors in materials science, synthetic biology, and chemical engineering. To provide new opportunities for double emulsion platforms, here, we report a glass capillary microfluidic approach to first fabricate osmolarity-responsive Water-in-Oil-in-Water (W/O/W) double emulsion containing two different inner droplets/cores and to then trigger the coalescence between the encapsulated droplets precisely. To achieve this, we independently control the swelling speed and size of each droplet in the dual-core double emulsion by controlling the osmotic pressure between the inner droplets and the collection solutions. When the inner two droplets in one W/O/W double emulsion swell to the same size and reach the instability of the oil film interface between the inner droplets, core-coalescence happens and this coalescence process can be controlled precisely. This microfluidic methodology enables the generation of highly monodisperse dual-core double emulsions and the osmolarity-controlled swelling behavior provides new stimuli to trigger the coalescence between the encapsulated droplets. Such swelling-caused core-coalescence behavior in dual-core double emulsion establishes a novel microreactor for nanoliter-scale reactions, which can protect reaction materials and products from being contaminated or released. *Published by AIP Publishing.* [<http://dx.doi.org/10.1063/1.4952572>]

I. INTRODUCTION

Advancement in the droplet microfluidic technologies provides new means for droplet-based microreactors, which enable two or more miscible fluids to mix and react upon contact and coalescence.^{1–5} Because of the controllability, high reaction efficiency, and low reagent consumption, droplet microreactors have widely been used in a variety of applications, such as the synthesis of functional particles, drug discovery for therapeutic applications, protein expression in the biological field, and components for cosmetics and food additives.^{6–14} A key step for achieving the above applications is that two or more single droplets containing different chemical compositions are triggered to coalesce through extra stimuli, such as heating, electric/magnetic fields, or channel structure, and achieve desirable reactions during this coalescence process.^{13–25} However, there are always undesirable multiple coalescences using the single emulsions coalescence method.^{14,18}

An innovative approach for addressing this limitation is to encapsulate the target reaction droplets in a bigger droplet, forming a multi-core double emulsion microreactor, which supplies

^{a)}X. Guan and L. Hou contributed equally to this work.

^{b)}Authors to whom correspondence should be addressed. Electronic addresses: rykhit@hit.edu.cn and jhy_hit@hit.edu.cn.

a separate reaction room for target droplets to avoid undesirable multiple coalescence.^{1,26,27} For instance, a double emulsion containing two different inner droplets is used as a microreactor to fabricate high viscosity particles and demonstrate the dissolution of cell membranes, where the flow rate ratios act as stimuli to trigger inner droplets to coalesce together.¹ Furthermore, the double emulsion enables the microreactor to separate the target droplets from the outer environment and protect reaction materials, as well as products, from being contaminated or released. Although droplet microfluidic technology successfully realizes the encapsulation of different droplets inside one bigger double emulsion droplet,^{1,28,29} no more efficient stimuli have ever been reported to trigger the core-coalescence in these double emulsion microreactors. Thus, more active stimuli should be designed to make the coalescence process more feasible and accurate, thereby extending the range of applications in various areas.

In this work, we demonstrate that osmolarity-controlled swelling behavior of double emulsions can be a novel stimulus to trigger the coalescence between encapsulated droplets. Motivated by recent successes in the fabrication of multi-core double emulsions, we generate osmolarity-responsive double emulsion with two different inner droplets, which have precisely osmolarity-controlled swelling behaviors. The middle phase of the double emulsion is Polydimethylsiloxane (PDMS), which allows the diffusion of only low-molecular weight molecules such as water, antibiotics, and signaling molecules. Moreover, its excellent bioinertness and biocompatibility make it suitable for encapsulating important actives in the inner droplets.³⁰ Here, the swelling behavior of the inner droplets in the PDMS double emulsion is performed by controlling the osmotic pressure between the inner droplets and outer environment.^{31–33} We show that the inner droplets can be triggered to coalesce through this osmolarity-controlled swelling behavior, and the coalescence process can be controlled precisely. In order to validate this osmolarity-controlled core-coalescence microreactor, we also demonstrate the synthesis of calcium carbonate particles through triggering the coalescence of two droplets containing calcium chloride and sodium carbonate, respectively. The simplicity and accuracy of our method should permit other active ingredients such as drugs, microbes, living cells, and functional materials to be reacted in this double emulsion microreactor. Such a microreactor triggered by osmolarity-controlled swelling behavior in double emulsion would be useful in a variety of applications including drug development, synthesis of functional materials, and protein expression in the biological field.

II. EXPERIMENT SETUP

A. Fabrication of the glass capillary microfluidic device

The schematic in Fig. 1(b) illustrates the generation of the Water-in-Oil-in-Water (W/O/W) dual-core double emulsions utilizing a glass capillary microfluidic device (Fig. 1(a)), which consists of four inlets, two inner phase inlets (core 1 and core 2), and two inlets for middle phase and outer phase. The middle phase channel and the collection channel are fitted into the two ends of the square capillary tube (AIT Glass, Inc., 810-9917). They are made of circular capillaries (World Precision Instruments, Inc., 1B100–6) with an inner diameter of 580 μm and an outer diameter of 1.03 mm, of which the tips are tapered using a micropipette puller (P-97, Sutter Instrument) into diameters of 85 μm and 250 μm for the middle phase channel and the collection channel, respectively. The two inner phase channels, which are fitted into the interior of the middle phase channel, are composed of two smaller diameter capillaries (170 μm in outer diameter, Vitro, Inc., CV1017), and the tips are pulled into a conical structure (25 μm in diameter). In addition, the outer surface of the inner phase channels and the inner wall of the middle phase channel are treated with octadecyltrichlorosilane (OTS, Sigma-Aldrich) to make them hydrophobic.

B. Materials used for double emulsions generation

The outer phase is 5 wt. % aqueous solution of polyvinyl alcohol (PVA, 87%–89% hydrolyzed, average $M_w = 13\,000$ – $23\,000$, Sigma-Aldrich). The middle oil phase consists of silicone oil (50cSt, PMX-200, Dow Corning) and polydimethylsiloxane (PDMS, Sylgard 184, Dow

FIG. 1. (a) The glass capillary microfluidic device designed to generate double emulsions with different inner cores. (b) The schematic illustration shows the double emulsion generation process. Two core phases first break into droplets, which are arranged in the middle phase channel, and then double emulsions are formed by the shearing force of outer phase. (c) Microscopic optical image of double emulsion containing two inner droplets, cores 1 and 2.

Corning) mixed in accordance with the volume ratio of 7:3. Different inorganic salts (purchased from Tianjin Hengxing Chemical Reagent Co. Ltd.), such as potassium chloride, calcium chloride, and sodium carbonate, are prepared for the inner phase solutions. In the experiment of investigating the relationship between the osmotic pressure and core-coalescence, we, respectively, formulate 0.5 mol/l, 1.0 mol/l, and 2 mol/l potassium chloride (KCl) solutions with 8 vol. % glycerol as inner phase. Moreover, in the experiment to demonstrate the feasibility of this osmolarity-controlled core-coalescence in dual-core double emulsion droplet as a micro-reactor, we formulate 0.75 mol/l calcium chloride and 0.75 mol/l sodium carbonate solutions as the different inner active ingredients, respectively. Unless otherwise noted, all water used to prepare solutions is deionized water.

C. Generation of double emulsions with different inner cores

The glass capillary microfluidic device (Fig. 1(a)) is mounted on an inverted optical microscope (CKX41, Olympus), while the emulsion generation process is monitored by a high speed camera (DP27, Olympus) attached to the microscope. To generate double emulsions with different inner cores, four fluid phases are injected into the glass capillary device by four syringe pumps (Harvard Apparatus, PHD 2000 Series). First, droplets with two different components (core 1 and core 2) are separately emulsified at the end of inner capillaries, as illustrated in Fig. 1(b). By fine adjustment of the flow rates, the size and frequency of these inner droplets can be controlled precisely and independently, and these droplets can be maintained in a linear array in the middle phase channel. Then, the middle phase is further emulsified by the shearing force of the outermost phase, forming double emulsions with two different inner cores (Fig. 1(c)). Here, a small amount of rhodamine B is added into one of the inner phases to distinguish the two inner cores during the double emulsion generation process. Finally, these double emulsions are collected from the outlet in 1 wt. % PVA solution to prevent the coalescence of them and induce the osmotic pressure between the inner phases and the collection solution.

III. RESULTS AND DISCUSSION

In order to study the effect of osmolarity-controlled swelling behavior on core-coalescence of double emulsions, first, the swelling and coalescence phenomena of double emulsion with same inner cores are investigated. Dual-core double emulsions with a given concentration of salt as the inner aqueous cores are produced using our devices. Both core 1 and core 2 are

0.5 mol/l KCl solutions containing 8 vol. % glycerol, and approximately equal in size. Here, the concentration of KCl induces the osmotic pressure between inner cores and collection solution (1 wt. % aqueous solution of PVA). As the electrolyte concentration of the inner cores is higher than the collection solution, water in the cores has a lower chemical potential than that of the collection solution; therefore, water molecules penetrate through the PDMS shell into the cores, leading to the swelling behaviors of inner cores, as shown in Figs. 2(a) and 2(b). Along with the swell of inner cores, the double emulsion droplet becomes a dumbbell-shaped structure, while the interfacial oil film between the two inner cores gets sufficiently thinner and thinner. After a specific period of time, the interfacial film cannot maintain its structure for a long time and ruptures to trigger the core-coalescence of these two inner cores.

FIG. 2. (a) Schematic and (b) optical microscope images displaying the swelling and core-coalescence behaviors of osmolarity-responsive double emulsion, respectively. (c) A set of optical microscope images displaying the coalescence process of two inner cores. The PDMS shell recovers uniformly with time shown in the images. (d) and (e) Optical microscope images of osmolarity-responsive double emulsions (d) before and (e) after core-coalescence. The scale bar on each image is 200 μm . (Multimedia view) [URL: <http://dx.doi.org/10.1063/1.4952572.1>]

Optical microscope images of the core-coalescence behavior in a double emulsion droplet are presented in Fig. 2(c). When the double emulsion droplet swells to this dumbbell-shaped structure, there forms two ultra-thin oil films. One is the “shell film” between the inner cores and the outer fluid, and the other one is the “dissepiment film” between the two inner cores. The non-spherical envelope of these oil films exerts a strong capillary force on the inner cores, resulting in slow but continuous drainage of the oil phase from the thinnest parts of the films. The reason why the two inner cores coalesce together rather than rupture toward the outer fluid is that the lubrication resistance in the shell film is stronger than the dissepiment film.³⁴ As shown in Figure 2(d), the shell film between the inner cores and outer fluid has almost the same curvature with the inner cores, which leads to a strong lubrication resistance; however, the dissepiment film between the two inner cores has opposite curvature with the inner cores, which leads to a relatively weaker lubrication resistance. As the inner cores keep swelling, therefore, the film with the relatively weaker lubrication resistance has greater drainage velocity and ruptures more easily than the stronger one, resulting in the final core-coalescence in the dual-core double emulsion. As soon as the cores coalesce, a fresh droplet is born in 0.1 s and the PDMS shell recovers it uniformly in several minutes, forming a new spherical double emulsion droplet with an ultrathin PDMS shell, as shown in Fig. 2(c). Although the shell is ultrathin after core-coalescence, the droplet is very stable and the coalesced core can be firmly encapsulated by the shell. The swelled dumbbell-shaped double emulsion droplets and coalesced thin shell double emulsion droplets are shown in Figs. 2(d) and 2(e), respectively, in which the volume of encapsulated droplets ranges from 20 to 40 nl. This osmolarity-controlled core-coalescence behavior in dual-core double emulsion establishes a novel microreactor for nanoliter-scale reactions. For example, functional particles synthesized from two different special delicate ingredients can be easily encapsulated and reacted using this approach.

Furthermore, the process of the core-coalescence can be precisely controlled by adjusting the electrolyte concentrations between the inner cores and the collection solution. We generate three groups of dual-core double emulsions containing different concentrations of salt in the inner cores, i.e., 0.5 mol/l, 1.0 mol/l, and 2.0 mol/l KCl solutions. The osmotic pressure between the inner cores and the collection solution increases along with the increase of the KCl concentration. To eliminate the interference caused by the droplet size and structure, we make the three groups of double emulsions with the same initial dimensions, which can be achieved easily by tuning the fluid properties in the glass capillary microfluidic system during all the experiments. As shown in Fig. 3, each of the curves demonstrates the swelling speed, and the end

FIG. 3. Comparison of double emulsions swelling and the core-coalescence process with different inner cores concentration of salt. The salt concentration of the two inner cores in one double emulsion droplet is equal, and the end pentacle of each curve represents the core-coalescence.

FIG. 4. Synthesis of calcium carbonate particles using the core-coalescence method in double emulsion as a microreactor. (a) Optical microscope images of core-coalescence and generation of calcium carbonate particles. (b) Histogram of calcium carbonate content varying with time.

pentacle of each curve represents the occurrence of core-coalescence in the double emulsion droplets. It is obvious that as the salt concentration increases, both the swelling process and the core-coalescence are accelerated. When the inner concentration of KCl is 2 mol/l, the inner droplets coalesce together within 60 min of the osmotic swelling (blue curve), which is approximately twice faster than 0.5 mol/l (black curve). Moreover, there is a significant difference within the size of the dumbbell-shaped double emulsions when the inner cores coalesce (the pentacles in Fig. 3). We attribute this difference in size during a core-coalescence process to the difference of osmotic pressure between the inner cores and the outer fluid in these three groups of double emulsion droplets. Higher osmotic pressure induces faster swelling speed of the inner cores, which interferes with the stability of dissepiment film. Therefore, the core-coalescence process happens at different dimensions with the rise of the swelling speed.

To explore the feasibility of this osmolarity-controlled core-coalescence microreactor for nanoliter-scale reactions, we demonstrate the synthesis of calcium carbonate particles through triggering the core-coalescence using the same design in Fig. 1. Here, each double emulsion droplet encapsulates two groups of nanoliter cores: core 1 is 0.75 mol/l calcium chloride solution and core 2 is 0.75 mol/l sodium carbonate solution. Both of the two inner solutions contain 8 vol.% glycerol to calibrate the viscosity. The double emulsion droplets are also collected in 1 wt.% aqueous solution of PVA, which supplies the osmotic pressure between the inner cores and the collection solution and protects the big double emulsion droplets from being coalesced during the swelling process. When the inner cores in the emulsion droplet swell to critical size, which makes the oil film interface between the inner cores reach instability, core-coalescence happens. The fluid flow caused by the core-coalescence brings a full mixing of the two inner solutions in several minutes. Fig. 4(a) represents the optical microscope images of a double emulsion droplet before and after the inner cores coalesce. Chemical reaction happens immediately once the cores coalesce, and calcium carbonate particles are produced inside the shell. We also measure the content of calcium carbonate varying with time as illustrated in Fig. 4(b). The concentration of calcium carbonate remains unchanged after about 3 min, which indicates that the inner cores can be fully mixed in a short time after the core-coalescence. We believe that the core-coalescence method is useful for nanoliter-scale reactions because it is purely controlled by osmotic pressure without other stimuli being applied, such as UV light, electrical fields, or heat treatment.

IV. CONCLUSION

In this work, we have developed an osmolarity-responsive PDMS double emulsion platform for the construction of a nanoliter-scale microreactor using the core-coalescence method. By adding different concentrations of KCl inside the encapsulated cores and in the outer

environment, the osmotic swelling and coalescence processes of this double emulsion can be exclusively controlled by osmotic pressure. As the KCl concentration in the inner cores increases from 0.5 mol/l to 2 mol/l, the swelling speed is almost doubled, resulting in the significant promotion of the core-coalescence process. Furthermore, to explore the feasibility of this method as a microreactor, we provide a demonstration of the synthesis of calcium carbonate particles, which can be generated quickly upon the core-coalescence process and firmly encapsulated by the PDMS shell. Using this method, the encapsulated materials in the droplets for reaction can be less than tens of nanoliters. This double emulsion microreactor not only provides a safe and controlled way of mixing and synthesizing delicate and harmful materials but also protects the subsequent products from being contaminated or released, which has great significance for some nanoscale reactions and corresponding applications. Current efforts in our group are focusing on the fabrication of functional materials using this method, such as proteins and gas sensitive particles, which are typically contaminated by the outer environment.

ACKNOWLEDGMENTS

This work was supported by the National Natural Science Foundation of China (Grant Nos. 51305106 and 11372093), the Self-Planned Task (Grant Nos. 201510B and SKLRS201606C) of State Key Laboratory of Robotics and System (HIT), the Programme of Introducing Talents of Discipline to Universities (Grant No. B07018), and the Research Fund for the Doctoral Program of Higher Education of China (RFDP, Grant No. 20122302120040). The authors wish to acknowledge Professor Lei Lei's group (Harbin Medical University) for their assistance with the Micropipette Puller.

- ¹H. Chen, Y. Zhao, J. Li, M. Guo, J. Wan, D. A. Weitz, and H. A. Stone, *Lab Chip* **11**(14), 2312 (2011).
- ²H. Song, D. L. Chen, and R. F. Ismagilov, *Angew. Chem.* **45**(44), 7336 (2006).
- ³M. T. Guo, A. Rotem, J. A. Heyman, and D. A. Weitz, *Lab Chip* **12**(12), 2146 (2012).
- ⁴S. Y. Teh, R. Lin, L. H. Hung, and A. P. Lee, *Lab Chip* **8**(2), 198 (2008).
- ⁵J. H. Kim, T. Y. Jeon, T. M. Choi, T. S. Shim, S. H. Kim, and S. M. Yang, *Langmuir* **30**(6), 1473 (2014).
- ⁶Y. Tao, A. Rotem, H. Zhang, C. B. Chang, A. Basu, A. O. Kolawole, S. A. Koehler, Y. Ren, J. S. Lin, J. M. Pipas, A. B. Feldman, C. E. Wobus, and D. A. Weitz, *Lab Chip* **15**(19), 3934 (2015).
- ⁷L. Mazutis, J. C. Baret, P. Treacy, Y. Skhiri, A. F. Araghi, M. Ryckelynck, V. Taly, and A. D. Griffiths, *Lab Chip* **9**(20), 2902 (2009).
- ⁸P. W. Ren, X. J. Ju, R. Xie, and L. Y. Chu, *J. Colloid Interface Sci.* **343**(1), 392 (2010).
- ⁹H. Zhang, E. Tumarkin, R. Peerani, Z. Nie, R. M. Sullan, G. C. Walker, and E. Kumacheva, *J. Am. Chem. Soc.* **128**(37), 12205 (2006).
- ¹⁰H. Song and R. F. Ismagilov, *J. Am. Chem. Soc.* **125**(47), 14613 (2003).
- ¹¹Y. Jang, W.-S. Jang, C. Gao, T. Soup Shim, J. C. Crocker, D. A. Hammer, and D. Lee, *ACS Macro Lett.* **5**(3), 371 (2016).
- ¹²S. Okushima, T. Nisisako, T. Torii, and T. Higuchi, *Langmuir* **20**(23), 9905 (2004).
- ¹³E. Brouzes, M. Medkova, N. Savenelli, D. Marran, M. Twardowski, J. B. Hutchison, J. M. Rothberg, D. R. Link, N. Perrimon, and M. L. Samuels, *Proc. Natl. Acad. Sci. U. S. A.* **106**(34), 14195 (2009).
- ¹⁴H. Shintaku, T. Kuwabara, S. Kawano, T. Suzuki, I. Kanno, and H. Kotera, *Microsyst. Technol.* **13**(8–10), 951 (2007).
- ¹⁵L. Mazutis, J. C. Baret, and A. D. Griffiths, *Lab Chip* **9**(18), 2665 (2009).
- ¹⁶A. N. N. Lai, N. Bremond, and H. A. Stone, *J. Fluid Mech.* **632**, 97 (2009).
- ¹⁷N. Bremond, A. Thiam, and J. Bibette, *Phys. Rev. Lett.* **100**(2), 024501 (2008).
- ¹⁸K. Liu, H. J. Ding, J. Liu, Y. Chen, and X. Z. Zhao, *Langmuir* **22**(22), 9453 (2006).
- ¹⁹D. R. Link, E. Grasland-Mongrain, A. Duri, F. Sarrazin, Z. Cheng, G. Cristobal, M. Marquez, and D. A. Weitz, *Angew. Chem.* **45**(16), 2556 (2006).
- ²⁰D. De Bruyker, M. I. Recht, A. A. Bhagat, F. E. Torres, A. G. Bell, and R. H. Bruce, *Lab Chip* **11**(19), 3313 (2011).
- ²¹F. Sarrazin, L. Prat, N. Di Miceli, G. Cristobal, D. R. Link, and D. A. Weitz, *Chem. Eng. Sci.* **62**(4), 1042 (2007).
- ²²P. Paik, V. K. Pamula, and R. B. Fair, *Lab Chip* **3**(4), 253 (2003).
- ²³X. Niu, S. Gulati, J. B. Edel, and A. J. deMello, *Lab Chip* **8**(11), 1837 (2008).
- ²⁴M. Zagnoni, C. N. Baroud, and J. M. Cooper, *Phys. Rev. E* **80**(4 Pt 2), 046303 (2009).
- ²⁵Z. Liu, R. Cao, Y. Pang, and F. Shen, *Exp. Fluids* **56**, 24 (2015).
- ²⁶R. Shah, H. Shum, A. Rowat, D. Lee, J. Agresti, A. Utada, L. Chu, J. Kim, A. Fernandeznieves, and C. Martinez, *Mater. Today* **11**(4), 18 (2008).
- ²⁷A. S. Utada, E. Lorenceau, D. R. Link, P. D. Kaplan, H. A. Stone, and D. A. Weitz, *Science* **308**(5721), 537 (2005).
- ²⁸Y. Zhao, Z. Xie, H. Gu, L. Jin, X. Zhao, B. Wang, and Z. Gu, *NPG Asia Mater.* **4**(9), e25 (2012).
- ²⁹W. Wang, R. Xie, X. J. Ju, T. Luo, L. Liu, D. A. Weitz, and L. Y. Chu, *Lab Chip* **11**(9), 1587 (2011).
- ³⁰M. J. Oh, T. K. Ryu, and S. W. Choi, *Macromol. Rapid Commun.* **34**(21), 1728 (2013).
- ³¹F. Tu and D. Lee, *Langmuir* **28**(26), 9944 (2012).
- ³²G. Jiang, B. C. Thanoo, and P. P. DeLuca, *Pharm. Dev. Technol.* **7**(4), 391 (2002).
- ³³K. F. Pistel and T. Kissel, *J. Microencapsulation* **17**(4), 467 (2000).
- ³⁴S. S. Lee, A. Abbaspourrad, and S. H. Kim, *ACS Appl. Mater. Interfaces* **6**(2), 1294 (2014).