has a number of advantages. It is simple, applicable to all headed screw types and does not require either an assistant or the use of additional instrumentation.

References

1. Dattani R, Patel VR. Arthroscopic assisted removal of screws from proximal humeral locking plates. *Int J Shoulder Surg* 2013; **7**: 125–126.
2. Maqdes A, Levy B, Klouche S, Hardy P. The feasibility and results of an arthroscopic removal of humeral locking plates and glenohumeral arthrolysis after proximal humeral fractures. *Knee Surg Sports Traumatol Arthrosc* 2014; **22**: 456–461.
3. Veselko M, Senekovic V, Tonin M. Simple and safe arthroscopic placement and removal of cannulated screw and washer for fixation of tibial avulsion fracture of the anterior cruciate ligament. *Arthroscopy* 1996; **12**: 259–262.
4. Zhang Q, Huang XL, Zhang S, Cao XC. Removal of the cannulated screw used for fixation of fractures of the tibial eminence under arthroscopy. *Ann R Coll Surg Engl* 2014; **96**: 548–549.
5. Parikh SN. Arthroscopic removal of a cannulated screw and washer from the knee joint. *Orthopedics* 2010; **33**: 675.

'Rain chain' for ankle arthroscopy

AL Ramavath¹, N Geary²

¹Mersey Deanery, UK

²Arrowe Park Hospital, UK

CORRESPONDENCE TO

AL Ramavath, E: alramavath@gmail.com

During ankle arthroscopy, water leakage from the portals (particularly from the lateral portal) flows onto the camera head and steams-up the lens. A swab opened and tied around the endoscope ahead of the camera diverts water to drip-off the swab, thereby avoiding wetting of the lens (Fig 1). A clear view is maintained without drying the lens repeatedly. The idea was conceived by observing 'chain down pipes' used in cold countries to convey water from gutters when a normal, hollow-down pipe would freeze.

Figure 1 The rain chain for ankle arthroscopy

Technical tip in the use of obstetric forceps to remove high rectal foreign bodies

L Sparks, A Lazzaro, S Badvie

Royal Free London NHS Foundation Trust, UK

CORRESPONDENCE TO

Laura Sparks, E: laura.sparks@nhs.net

Obstetric forceps may be used transanally to remove rectal foreign bodies under general anaesthesia¹ but using both blades risks further damage on extraction to an already disrupted sphincter complex. We recommend using just one lubricated blade of Wrigley's forceps as a simulated surgeon's extended hand, particularly for high spherical items that are difficult to reach and grip. The blade is passed laterally alongside the foreign body and carefully rotated 90° to allow the item to lie in its concavity. The curved upper lip of the blade prevents the item moving cephalad and guides its smooth removal.

References

1. MacDonald AP. Foreign body in the rectum removed by obstetric forceps. *Practitioner* 1961; **186**: 370–371.

Figure 1 Positioning of left blade of Wrigley's forceps to remove high rectal foreign bodies