Technical Section [TECHNICAL NOTES AND TIPS

A novel way to augment a tibial prosthesis for significant bone loss

M Ricks, N Flynn

Portsmouth Hospitals NHS Trust, UK

CORRESPONDENCE TO

Matthew Ricks, E: matthewrichardricks@doctors.net.uk

During joint replacement, when faced with significant unilateral bone loss of the tibia, impaction bone grafting has been shown to be effective in small defects.¹ We propose a technique for augmenting a prosthesis to fill a large defect. Using tibial augments of decreasing size provides a tapered effect. A stepped cut of the tibia is performed and the size of the defect is measured. Each block is cemented on top of the other up to the desired size (Fig 1) and can then be implanted into the tibia (Fig 2).

Figure 1 Intraoperative photograph of the augmentation technique

Figure 2 Postoperative radiography of the augmentation technique

Reference

1. Kharbada Y, Sharma M. Autograft reconstructions for bone defects in primary total knee replacement in severe varus knees. *Indian J Orthop* 2014; **48**: 313–318.

A novel technique to assist arthroscopic screw removal

L Stroud, TD Tennent

St George's University Hospitals NHS Foundation Trust, UK

CORRESPONDENCE TO

Duncan Tennent, E: duncan@tennent.net

A video demonstration of this technique is available to view at:

<http://publishing.rcseng.ac.uk>

BACKGROUND

Arthroscopic removal of screws has advantages although it can be technically challenging. It can be difficult to withdraw the screw and there is a risk of dropping it, resulting in a loose body. Several techniques to lessen this risk have been described. However, they require a skilled assistant, a washer or a cannulated screw. None help with the difficulty of withdrawing the screwdriver while remaining engaged in the screw head.

TECHNIQUE

A few turns of the screwdriver are made to back the screw out and expose the shaft. Via an accessory portal, a loop of suture is placed around the neck of the screw. A simple sliding knot is tied and pulled tight. A knot pusher can be used to make the knot more secure. The suture limbs are withdrawn via the original portal and the screwdriver is re-engaged. As the screwdriver is turned, traction is applied to the suture limbs. This reproduces the 'negative traction' effect and ensures that as the screw comes free of the bone, it is not lost in either the joint or soft tissues.

DISCUSSION

Various techniques for the arthroscopic removal of screws have been described. Forceps can be used when all but the last few threads have been disengaged¹ or an assistant can stabilise the screw via an accessory portal.² If the screw is cannulated, a guidewire³ or bent K-wire⁴ can be placed in the cannulated shaft of the screw.

When removing a screw and washer, a suture may be looped through the washer to prevent loss.⁵

All of these techniques either risk losing the screw or are applicable only to certain screw types. None provides the 'negative traction' required when removing a screw. The technique we describe

has a number of advantages. It is simple, applicable to all headed screw types and does not require either an assistant or the use of additional instrumentation.

References

1. Dattani R, Patel VR. Arthroscopic assisted removal of screws from proximal humeral locking plates. *Int J Shoulder Surg* 2013; **7**: 125–126.
2. Maqdes A, Levy B, Klouche S, Hardy P. The feasibility and results of an arthroscopic removal of humeral locking plates and glenohumeral arthrolysis after proximal humeral fractures. *Knee Surg Sports Traumatol Arthrosc* 2014; **22**: 456–461.
3. Veselko M, Senekovic V, Tonin M. Simple and safe arthroscopic placement and removal of cannulated screw and washer for fixation of tibial avulsion fracture of the anterior cruciate ligament. *Arthroscopy* 1996; **12**: 259–262.
4. Zhang Q, Huang XL, Zhang S, Cao XC. Removal of the cannulated screw used for fixation of fractures of the tibial eminence under arthroscopy. *Ann R Coll Surg Engl* 2014; **96**: 548–549.
5. Parikh SN. Arthroscopic removal of a cannulated screw and washer from the knee joint. *Orthopedics* 2010; **33**: 675.

'Rain chain' for ankle arthroscopy

AL Ramavath¹, N Geary²

¹Mersey Deanery, UK

²Arrowe Park Hospital, UK

CORRESPONDENCE TO

AL Ramavath, E: alramavath@gmail.com

During ankle arthroscopy, water leakage from the portals (particularly from the lateral portal) flows onto the camera head and steams-up the lens. A swab opened and tied around the endoscope ahead of the camera diverts water to drip-off the swab, thereby avoiding wetting of the lens (Fig 1). A clear view is maintained without drying the lens repeatedly. The idea was conceived by observing 'chain down pipes' used in cold countries to convey water from gutters when a normal, hollow-down pipe would freeze.

Figure 1 The rain chain for ankle arthroscopy

Technical tip in the use of obstetric forceps to remove high rectal foreign bodies

L Sparks, A Lazzaro, S Badvie

Royal Free London NHS Foundation Trust, UK

CORRESPONDENCE TO

Laura Sparks, E: laura.sparks@nhs.net

Obstetric forceps may be used transanally to remove rectal foreign bodies under general anaesthesia¹ but using both blades risks further damage on extraction to an already disrupted sphincter complex. We recommend using just one lubricated blade of Wrigley's forceps as a simulated surgeon's extended hand, particularly for high spherical items that are difficult to reach and grip. The blade is passed laterally alongside the foreign body and carefully rotated 90° to allow the item to lie in its concavity. The curved upper lip of the blade prevents the item moving cephalad and guides its smooth removal.

References

1. MacDonald AP. Foreign body in the rectum removed by obstetric forceps. *Practitioner* 1961; **186**: 370–371.

Figure 1 Positioning of left blade of Wrigley's forceps to remove high rectal foreign bodies