Figure 1 Suzuki frame

Figure 2 Metal cannula passed over K-wire

Figure 3 Metal stilette of suction cannula

DISCUSSION

The metal suction cannula thus simplifies the procedure, saving time and preventing needlestick injuries. The metal stilette of the suction cannula (Fig 3) can also be used as an intraoperative aid in hand surgery.

Evgeniou *et al* have described a rectangular metal frame to identify the bone graft harvest position on the distal radius using a straight 0.9mm K-wire bent to the desired size.² The advantage of the suction stilette is that it is preformed; the ends are blunt and smooth, with no risk of sustaining a sharps injury.

References

1. Suzuki Y, Matsunaga T, Sato S, Yokoi T. The pins and rubbers traction system for treatment of comminuted intraarticular fractures and fracture-dislocations in the hand. *J Hand Surg Br* 1994; **19**: 98–107.
2. Evgeniou E, Dimitriadis PA, Kulkarni M. Metal frame for identification of bone graft harvest position. *Ann R Coll Surg Engl* 2014; **96**: 315.

Syringe barrels as radiolucent drill sleeves during fixation of intramedullary nails for long-bone fractures

ERB Stirling, MS Patel, SC Williams

University Hospitals of Leicester NHS Trust, Leicester, UK

CORRESPONDENCE TO

Mohammed Patel, E: shaqs@doctors.org.uk
doi 10.1308/rcsann.2016.0121

BACKGROUND

Drill sleeves used for insertion of free-hand locking screws of intramedullary nails or external fixator pins are radiopaque, thereby making visualisation of trajectory challenging.

Figure 1 A 1ml syringe

Figure 2 A reamer within the barrel of a 10ml syringe

TECHNIQUE

After removal of the tip with a sharp blade, the barrel of a 1ml syringe can be used as a radiolucent sleeve (Fig 1). Similarly, a 10ml syringe (Fig 2) permits passage of a size-15 reamer in place of a metallic sleeve for reaming of long bones. Sleeves can be customised as needed by cutting the barrel to the required length.

DISCUSSION

The strategy described here provides an inexpensive, sterile method to assist in correct placement of metalwork while protecting the soft-tissue envelope.

Figure 3 An external fixator pin within the barrel of a 1ml syringe