Elasto-inertial migration of deformable capsules in a microchannel

Amir Hossein Raffiee,¹ Sadegh Dabiri,^{1,2} and Arezoo M. Ardekani¹

¹*School of Mechanical Engineering, Purdue University, West Lafayette, Indiana 47907, USA*

²*Department of Agricultural and Biological Engineering, Purdue University, West Lafayette, Indiana 47907, USA*

(Received 13 September 2017; accepted 6 December 2017; published online 27 December 2017)

In this paper, we study the dynamics of deformable cells in a channel flow of Newtonian and polymeric fluids and unravel the effects of deformability, elasticity, inertia, and size on the cell motion. We investigate the role of polymeric fluids on the cell migration behavior and the performance of inertial microfluidic devices. Our results show that the equilibrium position of the cell is on the channel diagonal, in contrast to that of rigid particles, which is on the center of the channel faces for the same range of Reynolds number. A constant-viscosity polymeric fluid, modeled using an Oldroyd-B constitutive equation, drives the cells toward the channel centerline, while a shear-thinning polymeric fluid, modeled using a Giesekus constitutive equation, pushes the cells toward the channel wall. The findings of this paper suggest that the addition of polymers in microfluidic devices can be used to enhance the throughput of cell focusing and separation devices at a low cost. This study provides an insight on the role of rheological properties of the fluid and the ways that they can be tuned to control the focal position of the cells.

Published by AIP Publishing. <https://doi.org/10.1063/1.5004572>

I. INTRODUCTION

Separation and focusing of cells are critical processes in biomedical applications.^{1–4} In these applications, the samples of interest are mostly composed of various populations of cells with different sizes, shapes, and properties needed to be isolated, filtered, or sorted. These operations are mostly used for diagnostic, therapeutic, or biological purposes.⁵ For instance, fractionated blood components are used for several diagnostic tests, such as leukocytes (white blood cells) required for hematologic tests,⁵ isolated reticulocytes and mononucleated red blood cells (RBCs) used for diagnosis of diseases concerned with RBC turnover,⁶ and purified plasma used for cancer detection.^{7,8} In addition to these components, blood may contain extremely rare cells which their identification is a vital step for the diagnosis of lethal diseases. The identification of circulating tumor cells (CTC),⁹ malaria,¹⁰ and fetal cells¹¹ that are present in a limited quantity in blood are of significant importance. Cell isolation is also used for therapeutics such as platelet transfusion,¹² CTC filtration, and blood cleansing.⁵ Furthermore, providing highly concentrated suspension of homogeneous cells enables biologists to study the biological and physical properties of cells¹³ which points out the significance of cell isolation techniques. There are several techniques that use biochemical markers for separation of cells in a heterogeneous population such as Fluorescence-activated cell sorting (FACS)¹⁴ and Magnetic-activated cell sorting (MACS).¹⁵ These methods are robust, but the complexity of the process and costly procedures required in these techniques prevent them from being widely used in clinical applications. The use of biochemical markers may also affect the natural biological process of cells in targeted samples. Hence, researchers focus on the development of label-free strategies which rely on the intrinsic properties of the cells including size,¹⁶ shape,¹⁷ and electrical polarizability.¹⁸ One of the main advantages of these techniques is the fact that they are not costly and the users do not

need to be highly skilled to work with them. In this paper, we focus on a label-free technique which works based on the hydrodynamic interaction between cells and the surrounding fluid.

Cross-stream migration of particles in moderate Reynolds numbers was first observed by Segre and Silberberg.¹⁹ In their experiment, the millimeter-sized particles were distributed randomly in a circular tube and they noticed that these particles assembled in an annulus with the radius 0.6 times the tube radius. A similar behavior was also observed for tubes with rectangular and square cross-sections.^{20–23} Drag and lift forces, acting on the particle surface, drive the particle to a steady equilibrium position. The lift force is the results of two counteractive forces: (i) the inertial lift force that pushes the particle toward the wall²⁴ and (ii) the repulsive wall-induced force²⁵ that drives the particle toward the channel centerline. The interplay between these two opposing forces determines the final position of the particle in a channel filled with a Newtonian fluid. Several analytical investigations were conducted to explain the dynamics of particles in the flow. These studies used a matched asymptotic expansion technique to obtain a scaling for the lift force.^{24,26–29} Findings of these studies suggest that a particle with diameter a moving in a channel with dimension H experiences a lift force in the form of $F_L = f_L(Re, \frac{a}{H})\rho U^2 a^4 / H^2$. In other words, this model predicts that the lift force is a function of particle position and Reynolds number. Although this model is accurate enough to explain the observed particle behavior in Segre and Silberberg experiment, it is only valid for small particle Reynolds numbers and size ratios $\frac{a}{H}$ that significantly restricts its range of applicability.²³ This restriction motivated researchers to conduct numerical and experimental investigations to study various aspects of this phenomenon.^{29–33} The suspensions in biomedical and industrial applications mostly contain particles with deformable membranes. These particles have different dynamics compared with rigid particles because of the additional deformability-induced lift force acting on the deformable particles.³⁴ The interplay among the three indicated lift forces determines the transient motion and final position of particles. The underlying physics of migration of deformable particles has been numerically^{35,36} and experimentally³⁷ investigated. Recently, there has been a growing interest in developing techniques that take advantage of cell deformability to enhance the efficiency of microfluidic devices working with biological fluids.^{37,38} Thus, it is necessary to study the motion of deformable particles, i.e., capsules, vesicles, and red blood cells, in a microchannel, but most of the studies in this field have been conducted for rigid particles in a poiseuille flow. The findings of the present study provide an insight into the performance of the inertia-based separation techniques and effective parameters that improve the efficiency of these devices.

The current sorting strategies based on inertial migration suffer from a serious restriction which is low flow throughput. The volume flow rate of the samples is limited by two factors: (i) hydrodynamic transition from laminar to turbulent flow in straight microchannels³⁹ and (ii) the ratio of the Dean drag force to inertial lift that restricts the throughput in curved channels.⁴⁰ One of the promising approach to solve this problem is the addition of polymers to the fluid. Lim *et al.*⁴¹ showed that their microfluidic device for cell sorting and classification successfully works at $Re \sim 10\,000$ by adding polymers to the suspending fluid. They added micromolar concentration of hyaluronic acid (HA) to the solution and were able to significantly increase the sample volume flow rate and particle velocity. In this system, the migration behavior of the cells is significantly influenced by the interaction between viscoelastic and inertial lift forces.^{41,42} Del Giudice *et al.*^{43,44} also investigated the effect of fluid rheology on the alignment of rigid particles in a microchannel. They showed that the particle focusing in a viscoelastic fluid is enhanced for high flow rates and they quantified the effect of fluid rheological properties on the focusing length of particles. The rheological properties of polymeric fluids can be tuned such that the resulting migration behavior changes in a desired manner for high throughput conditions.⁴² Furthermore, the system gives us the ability to control the focal position of cells that enhances the efficiency of the current methods in cell sorting and classification at a low cost.

In this paper, we study the viscoelastic effects of the suspending fluid and its interaction with inertial forces on the migration behavior of deformable cells. We study the focal position of the cells in inertial-based microfluidic devices in polymeric and Newtonian fluids. The role

of various fluid rheological parameters is investigated to provide an insight into an efficient design of microfluidic sorting and separation devices.

II. METHODOLOGY

A. Governing equations

The system of equations governing the flow and the motion of an elastic capsule in a Newtonian fluid is presented in this section. The inner and outer fluids are assumed to be incompressible. Hence, we have

$$\nabla \cdot \mathbf{u} = 0, \quad (1)$$

$$\frac{\partial(\rho \mathbf{u})}{\partial t} + \nabla \cdot (\rho \mathbf{u} \mathbf{u}) = -\nabla p + \nabla \cdot \boldsymbol{\tau} + \mathbf{F}, \quad (2)$$

where ρ is the density of the inner and outer fluids, $\mathbf{u}$ is the velocity vector, t represents the time, and p and $\boldsymbol{\tau}$ denote the pressure and the total stress tensor, respectively. The total stress tensor in a Newtonian fluid is calculated by $\boldsymbol{\tau} = \mu \mathbf{D}$, where μ is the viscosity and $\mathbf{D} = \nabla \mathbf{u} + (\nabla \mathbf{u})^T$ is the strain rate tensor. In Eq. (2), $\mathbf{F}$ represents the smoothed elastic force exerted by the capsule membrane which is calculated as

$$\mathbf{F}(x, t) = \int_{\partial B} \mathbf{f}(x_i, t) \delta(x - x_i) dV. \quad (3)$$

This force represents the membrane response to the surrounding fluid which is zero everywhere except on the membrane. In this equation, x and x_i denote arbitrary points in the computational domain and on the membrane surface and δ and V are the Dirac delta function and volume, respectively. In order to distribute the membrane force over a few Eulerian grid points surrounding the membrane interface, we use the smooth representation of delta function defined as

$$\delta(x) = \tilde{D}(x) \tilde{D}(y) \tilde{D}(z), \quad (4)$$

$$\tilde{D}(x) = \frac{1}{4\Delta} \left(1 + \cos \left(\frac{\pi}{2\Delta}(x) \right) \right), \quad |x| \leq 2\Delta, \quad (5)$$

where Δ is the grid size. This method allows us to solve a single set of equations over the entire computational domain and capture the change in fluid properties across the membrane. The details of this method are explained in our previous work.⁴⁵ In Eq. (3), $\mathbf{f}$ is the response force due to the shear deformation and area dilatation resistance of the capsule membrane. We use the Shalak model⁴⁶ to include the resistive force of the membrane. In this model, the following strain energy function is assigned to the membrane:

$$W = \frac{E_s}{12} \left((\epsilon_1^2 + \epsilon_2^2 - 2)^2 + 2(\epsilon_1^2 + \epsilon_2^2 - 2) - 2(\epsilon_1^2 \epsilon_2^2 - 1) \right) + \frac{E_a}{12} (\epsilon_1^2 \epsilon_2^2 - 1)^2, \quad (6)$$

where ϵ_1 and ϵ_2 are principal strains and E_s and E_a represent the shear and area dilatation moduli, respectively. Following Krüger *et al.*,⁴⁷ we assume a fixed ratio for $\frac{E_a}{E_s} = 2$. We use a finite element method⁴⁸ to obtain the interfacial force $\mathbf{f}$. We have validated this model in our previous work.⁴⁵

In this study, we used a finite volume method to discretize the Navier Stokes equations. Time discretization is conducted using an Explicit Euler scheme and convective and diffusive terms are discretized using a third order Quadratic Upstream Interpolation for Convective Kinematics (QUICK)⁴⁹ and central difference schemes, respectively. Furthermore, the velocity-pressure coupling is conducted using a projection method.⁵⁰ A front-tracking⁵¹ method is used in this study to model the membrane. In this technique, the computational domain and the

membrane surface are discretized with fixed Eulerian and moving Lagrangian grids, respectively, which allows accurate interface tracking.

Biological fluids are often complex fluids due to the presence of polymers, proteins, and DNA molecules. In order to model viscoelastic complex fluids, the total stress tensor in (2) is split into solvent stress tensor (τ_s) and polymeric stress tensor (τ_p) as follows:

$$\tau = \tau_s + \tau_p, \quad (7)$$

where the solvent stress tensor τ_s is

$$\tau_s = \mu_s \mathbf{D}, \quad (8)$$

where μ_s is the solvent viscosity. The nonlinear elastic properties of complex fluids can be modeled using the Giesekus constitutive equation,⁵² which captures both effects of fluid elasticity and shear-thinning behavior. The Giesekus constitutive equation is written as

$$\lambda \overset{\nabla}{\tau_p} + \tau_p + \frac{\alpha \lambda}{\mu_p} \tau_p \cdot \tau_p = \mu_p \mathbf{D}. \quad (9)$$

In this equation, μ_p is the polymeric viscosity and α denotes the mobility factor, which is in the range of $0 < \alpha < 0.5$.⁵³ If α is set to zero, the polymeric fluid follows an Oldroyd-B model, which behaves like a constant-viscosity elastic fluid. Furthermore, λ is the relaxation time of polymeric fluid and $\overset{\nabla}{\tau_p}$ denotes the upper convected time derivative defined as

$$\overset{\nabla}{\tau_p} = \frac{\partial \tau_p}{\partial t} + \mathbf{u} \cdot \nabla \tau_p - \nabla \mathbf{u} \tau_p - \tau_p \nabla \mathbf{u}^T. \quad (10)$$

The first and second normal stress differences in a viscoelastic polymeric fluid, defined below, can lead to flow phenomena in contrast with their counterpart in Newtonian fluids

$$N_1 = \tau_{xx} - \tau_{yy}, \quad (11)$$

$$N_2 = \tau_{zz} - \tau_{yy}, \quad (12)$$

where τ_{xx} , τ_{yy} , and τ_{zz} represent the normal stresses along the x , y and z directions, respectively. In order to solve the Giesekus constitutive equation, we use an explicit Euler scheme for time discretization. The details of the numerical scheme is explained in Ref. 45.

B. Problem set-up

We consider the motion of a deformable capsule in a straight square channel with the edge length of $2W$ and the channel length of $4W$ illustrated in Fig. 1. A constant pressure gradient is applied in the x direction, leading to a parabolic Poiseuille flow. The periodic boundary condition is applied in the x direction and the no-slip boundary condition is applied in the y and z directions. In this study, we consider W and U_0 (the centerline velocity of the channel filled with a Newtonian fluid) as the length and velocity scales, respectively. The dynamics of motion of the capsule is governed by the following dimensionless parameters: (i) Reynolds number $Re = \frac{\rho U_0 2W}{\mu}$, representing the ratio of the inertial to the viscous force (ii) Laplace number $La = \frac{2\rho E_s a}{\mu^2}$, denoting the deformability of the cell (iii) Weissenberg number $Wi = \frac{\lambda U_0}{W}$, which is defined as a function of polymer relaxation time, length, and velocity scales, (iv) $\beta = \frac{\mu_p}{\mu}$ represents the ratio of the polymeric viscosity to the total viscosity. The total viscosity is defined as $\mu = \mu_s + \mu_p$. (v) Aspect ratio $AR = \frac{a}{W}$ represents the blockage of the channel by the capsule. Unless otherwise stated $Re = 37.8$. The blockage ratio is set to 0.2 and 0.3 to study the effect of the capsule size on its cross-streamline motion. The fluid inside the cell is assumed to be Newtonian, and its viscosity

and density are equal to the total viscosity and density of the outer fluid ($(\mu_s + \mu_p)_{outer} = (\mu_s)_{inner}$ and $\rho_{inner} = \rho_{outer}$). Unless otherwise stated, β is set to 0.9 in polymeric fluids. The initial viscoelastic stress in the domain is zero in all simulations. The cells are assumed to have spherical initial shape and they are released at $\frac{y}{W} = 1.5$ and $\frac{z}{W} = 1.3$. Furthermore, in the case of polymeric fluid, the initial viscoelastic stress is zero. The computational domain is discretized using two sets of uniformly distributed Eulerian grids. For the cases corresponding to $Re = 37.8$, we use $128 \times 76 \times 76$ grid points and for higher Reynolds numbers, we use $200 \times 128 \times 128$ grid points. The mesh independency tests are included in the [Appendix](#). The capsule surface is discretized using 21632 triangular elements to accurately track the location of the membrane. Furthermore, since an explicit Euler method is used for time discretization, the time step is restricted by the CFL number, which is set to 0.9.

III. RESULTS AND DISCUSSION

A. Cell focusing in a Newtonian fluid

In this section, we study the dynamics of a cell moving in a Newtonian fluid. The blockage ratio is set to $\frac{a}{W} = 0.2$ and 0.3 and the Laplace number varies between 1 and 500. The trajectories and the time history of distance from the channel centerline are illustrated in Fig. 2 for various Laplace numbers. All the cells are released from the same location in the channel. The motion of cells can be described by two phases. In the first phase, cells migrate toward the diagonal until they reach it and then they move slowly along the diagonal until they reach their equilibrium position represented with symbols in Fig. 2(b). One of the main differences between the solid particles and deformable cells in the microchannel is the equilibrium position. According to Fig. 2(b), the equilibrium position for deformable cells lies on the diagonal, which is in agreement with a previous study.³⁸ On the other hand, experimental and numerical investigations⁵⁴ show that solid particles, for the same range of Re number, focus onto four off-center points on the main axes near the channel edges. This difference in the final equilibrium position can be used for sorting cells with different deformabilities. Figure 2(a) shows that the cells with $La = 1$ and 10 migrate to the channel center. The final position of less deformable cells approaches the channel wall and their distance from the center increases. A similar behavior is observed for the cells with $\frac{a}{W} = 0.2$ in which only the very soft cells with $La = 1$ move to the center and the equilibrium position for the rest of particles lies on the diagonal as shown in Fig. 5(a). The reason for this phenomenon is the dependence of the inertial lift force and deformability-induced lift force on the Laplace number. For low La , the deformability-induced force dominates the inertial force and the cells tend to focus on the centerline. As the Laplace number increases, the strength of the inertial force increases, while that of the deformability-induced force reduces and the inertial force becomes the dominant driving force. Under this

FIG. 1. Schematic of the microchannel.

FIG. 2. (a) The distance of cells from the channel centerline and (b) the trajectories of cells. The blockage ratio is $\frac{a}{W} = 0.3$ and $Re = 37.8$.

condition, the final position is pushed further away from the centerline and closer to that of solid particles, which is in agreement with previous studies.^{35,38}

We have also investigated the effect of Re number on the dynamics of deformable capsules. Previous numerical simulations^{35,38} studied this effect for the range of $1 < Re < 100$, while in this work, we extended this range to $37.4 < Re < 300$. Our results show that the equilibrium position of particles is almost independent of Re in the range of $1 < Re < 100$ and merely depends on La , which is in agreement with previous observations. However, the equilibrium position of capsules is a function of Reynolds number for larger values of Reynolds number. This dependency is more significant for softer capsules. As shown in Fig. 3(a), the deformable capsules move toward the channel center as Re increases and this dependency is enhanced with increasing deformability (except for $La = 1$ at which the capsules focus in the center regardless of Re number). This behavior is also observed in Ref. 35, where they showed the change in the focal position of capsules for large Reynolds numbers ($Re = 100$). We should note that a capsule with $La = 500$ is not completely rigid as shown in Fig. 3(b), where the capsule deformation is plotted.

We calculate the Taylor deformation parameter (D) to quantify the deformation of capsules. For this purpose, we compute the moment-of-inertia tensor, which provides us with the principal major and minor axes of an equivalent ellipsoidal particle (L and B , respectively). Accordingly, the deformation parameter is defined as

$$D = \frac{L - B}{L + B}. \quad (13)$$

Figure 3(b) illustrates the deformation parameter versus Re for different La . The increase in the Laplace number leads to a decrease in the deformation, except for the cases where the

FIG. 3. (a) The distance of cells from the channel centerline for various Re and La . (b) Cell deformation for various Re and La . The blockage ratio is $\frac{a}{W} = 0.3$.

FIG. 4. Deformed shape of capsules with $\frac{a}{W} = 0.3$ and $Re = 60$ and (a) $La = 1$ (b) $La = 50$ (c) $La = 500$.

capsules focus at the centerline. The reason for this phenomenon is related to the equilibrium position of these particles. The focal position for capsules with $La = 1$ is the channel centerline where the shear rate is zero and the capsule has a parachute shape that yields to a small deformation. Furthermore, increasing Re leads to an increase in the deformation because of the increase in the viscous shear stress acting on the deformable capsules. Interestingly, for $La = 50$, the deformation rapidly falls at $Re = 300$. The final position of the capsule at this Reynolds number is at the centerline. This capsule has a parachute shape and experiences a small shear rate.

Figure 4 shows the deformed shape of capsules at their focal position. According to Fig. 3(a), soft capsules (e.g., $La = 1$) focus at the centerline and experience a symmetric deformation, leading to a parachute shape. As the Laplace number increases, the final equilibrium position moves away from the centerline and capsules asymmetrically deform. Increasing the Laplace number means that the capsule behaves more similar to a rigid particle. On the other hand, the final position of capsules with larger La is closer to the wall, which yields larger viscous stress exerted on the capsule. Therefore, the deformation of capsule does not monotonically decrease with La .

The inertial force scales with $Re\left(\frac{a^3}{W^3}\right)$.³⁸ Therefore, the cell size is another important factor that changes the motion of cells. According to Fig. 5(a), the critical La_c number at which the cell equilibrium position is away from the centerline is affected by the size such that the larger cells require larger La number to not focus on the center. This value is also sensitive to Re number.³⁸ The cell size also affects the off-center equilibrium position of the cells illustrated in Fig. 5(a). Smaller cells end up at the location more distant from the center for a given La number. This is due to the fact that d_{eq} (the equilibrium distance from the centerline) is proportional to $\frac{La}{\left(\frac{a}{W}\right)^4}$.³⁸ Figure 5(b) illustrates the temporal evolution of the cross-streamline velocity V_T^* and the role of the cell deformability. The migration velocity of softer cells is larger, although all cells are released from the same location in the microchannel. The cells reach their focal

FIG. 5. (a) Equilibrium position of cells for various deformability and sizes at $Re = 37.8$. (b) Temporal evolution of cross-streamline velocity of cells with $\frac{a}{W} = 0.3$ and $Re = 60$.

FIG. 6. (a) Focal position and (b) trajectories of cells with $\frac{a}{W} = 0.3$ and $Re = 37.8$ in an Oldroyd-B fluid.

position nearly at the same time. Hence, those cells that need to travel longer distance to reach the equilibrium position have a larger velocity.

B. Cell focusing in an Oldroyd-B fluid

In this section, we study the effect of fluid elasticity on the cell migration behavior. Our numerical results suggest that an Oldroyd-B viscoelastic fluid drives the cells toward the channel centerline. Figure 6(a) shows the final position of cells for different Laplace and Weissenberg numbers for $\frac{a}{W} = 0.3$ and $Re = 37.8$. For small Wi , the equilibrium position of the cells is on the diagonal similar to a Newtonian fluid. The equilibrium position of the cells is shifted closer to the center with increasing Wi number ($Wi = 0$ represents the Newtonian fluid). Ultimately, for $Wi = 2$, all the cells regardless of their size and deformability focus at the centerline. It should be noted that for $La = 1$ and 10 , the cells end up on the centerline even for a Newtonian fluid due to the strong deformability-induced force. Hence, increasing the Wi number does not make any change to the final position of these soft cells. The observed focusing behavior provides us with the ability to control the focal position of cells by tuning Wi number when $La > 10$. The cell migration is influenced by viscoelastic, inertial, and deformability-induced forces. The viscoelastic and deformability effects have reinforcing interaction in driving the cells to the center, while the inertial force has an opposite effect. Therefore, for low Wi numbers when the fluid elasticity is weak, the cells are significantly influenced by the inertial force and focus to an equilibrium location close to the one in a Newtonian fluid. As the Weissenberg number and consequently fluid elasticity increase, the final position of cells moves toward the centerline. Figure 6(b) shows the trajectories of cells for $La = 500$, $\frac{a}{W} = 0.3$ and $Re = 37.8$ at various Wi numbers. Cells migrate to the diagonal of the microchannel and the final position represented by symbols approaches the centerline as the fluid elasticity increases. Finally, at $Wi = 2$, the cell directly moves toward the centerline indicating the dominance of the viscoelastic stress on the cell migration. Figure 7(a) shows the flow field in the cross-section of the microchannel at the location of the cell at $Re = 37.8$ and $La = 500$. The streamlines around the cell in an Oldroyd-B fluid are directed radially inward, leading to cell focusing on the centerline.

Another important effect that influences the dynamics of the cells is the inertial effect. Figure 8 illustrates the impact of the Re number on the final position of the cells at $Wi = 2$ and $Wi = 5$ for the cells with $La = 50$ and $\frac{a}{W} = 0.3$. Increasing the Re number induces disturbances in the flow field such that at a large enough Reynolds number, the flow regime transitions from laminar to turbulence and cell focusing no longer occur.⁴¹ This is the main limitation of current microfluidic technologies leading to low throughput devices for cell classification. Hence, it is important to study the inertial effects in the presence of polymers and identify the threshold above which cell focusing is not observed. Figure 8 shows the interplay between the flow inertia and the elastic effects that determines the final position of the cell. The equilibrium position of cells moves further toward the channel wall with increasing Re . The reason for this behavior

FIG. 7. The flow field around the cell in (a) an Oldroyd-B fluid ($Wi=2$) and (b) a Giesekus fluid ($Wi=2$ and $\alpha = 0.1$). The blockage ratio is $\frac{a}{W} = 0.2$ and $Re = 37.8$.

is the dependence of the inertial lift force on the Reynolds number. The inertial lift force is correlated with the Reynolds number as $F_{inertail} \sim Re^2$.³⁸ In high Re number regimes, the inertial lift force dominates other effects, while in low Re number regimes, the viscoelastic effect is stronger and the cells focus on the centerline. On the other hand, the effect of fluid viscoelasticity is significant even at high Re numbers such that cell focusing occurs in the presence of polymers. However, the focal position is no longer at the centerline. As shown in Fig. 8, the final position of the capsule in polymeric fluid is significantly affected by the Re number. This phenomenon is also observed for solid particle migration in viscoelastic fluids.⁴² The inertial lift force acting on a solid particle²⁷ is in the form of

$$F_{inertial} = \rho U_0^2 a^2 \left(\frac{a}{W} \right)^2 C_2 \left(\frac{y}{W} \right), \quad (14)$$

where y denotes the distance from the centerline. Furthermore, the viscoelastic force on a solid particle in a second order fluid⁵⁵ is

$$F_{viscoelastic} = -\frac{40}{3} \pi \rho U_0^2 (2a)^2 \left(\frac{a}{W} \right) \left(\frac{Wi}{Re} \right) \beta \left(\frac{y}{W} \right). \quad (15)$$

FIG. 8. Focal position of the cells in an Oldroyd-B fluid. Here, $\frac{a}{W} = 0.3$ and $La = 50$.

The negative sign in Eq. (15) shows that this force is toward the centerline, leading to the cell migration toward the centerline in an Oldroyd-B fluid. The balance between these two forces determines the equilibrium position of a solid particle. Equations (14) and (15) indicate that the location where the sum of forces are zero strongly depends on the Reynolds number.

The results indicate that we still have a control on the equilibrium position of cells in high Reynolds number regimes when the fluid is viscoelastic. We note that a higher Reynolds number corresponds to a larger sample volume flow rate. The addition of polymers improves the throughput of microfluidic cell focusing devices.

At $Re = 100$, the cell is no longer at the channel center for $Wi = 2$ and increasing the Re number leads to a larger equilibrium distance from the centerline. Increasing the Wi number, on the other hand, decreases the equilibrium distance from the centerline. By changing the Weissenberg number from 2 to 5, the centerline focusing occurs even for $Re = 100$. This phenomenon suggests that for each Wi number, there is a critical Re_c number above which the final position of the cells is no longer on the centerline. In order to achieve the centerline focusing of the cells for higher Re numbers, it is required to increase the Wi number of the fluid. This change is experimentally possible by increasing the polymer molecular weight or concentration, but the resulting numerical instability limits the range of the Weissenberg number that can be explored in this paper. These results suggest that this method can be used for cleaning the particulate flows. Cells in an Oldroyd-B fluid (constant-viscosity polymeric fluid) assemble in the channel center and can be separated from the suspending fluid. For instance, bacteria or circulating tumor cells (CTC) can be separated from the suspending fluid.⁵ Furthermore, this method does not employ any complex active system for controlling the migration such as electric or magnetic field or acoustic wave application, which limit the sample throughput and often requires skilled users.

Another important advantage of using fluid elasticity is the ability of the polymer chains in maintaining the flow regime in a laminar regime even for very high Re numbers. It means that a higher sample throughput can be pumped into the microchannel without transition into a turbulent regime, and the focusing behavior is still observed for high flow rates. We note that the previous studies on particle focusing were restricted to rigid particles in a Newtonian fluid or highly viscoelastic fluid ($Wi \gg Re$) in the creeping flow limit.⁵⁶⁻⁶⁰ In these studies, the deterioration of particle focusing was observed for $Re > 1$. Lim *et al.*⁴¹ showed that the focusing behavior of rigid particles can be achieved for high Reynolds numbers ($10 < Re < 10^4$) and weakly viscoelastic fluids ($Wi \ll Re$). Here, we quantify for the first time focusing of deformable cells in viscoelastic polymeric fluids.

C. Cell focusing in a Giesekus fluid

In this section, the effects of the fluid elasticity and shear-thinning behavior on the cell migration are investigated by using a Giesekus constitutive equation. Figure 9(a) shows the final position of the cells with varying deformability for $\frac{a}{W} = 0.3$ and $Re = 37.8$. The cells in a shear-thinning viscoelastic fluid are further pushed toward the wall compared to a Newtonian fluid. This behavior is opposite to what we observed in an Oldroyd-B fluid. The reason for this complex behavior can be explained by considering the interplay between the effective forces on the cell. In this fluid, the dynamics of the cells is governed by the interplay between shear-thinning effects, secondary flow generated by second normal stress difference (nonzero for a Giesekus fluid and zero for an Oldroyd fluid), elastic force, inertial effect, and the deformability-induced force. Mobility factor α that is non-zero in a Giesekus fluid leads to a shear-thinning effect, which is absent in an Oldroyd-B fluid. The shear-thinning effect reduces the viscoelastic force (the force that drives the cell to the centerline) by reducing the viscosity. It also increases the flow velocity [Fig. 11(b)], which enhances the inertial force (the force that pushes the cells toward the wall). Furthermore, the secondary flow induced by the second normal stress difference⁴² shown in Fig. 7(b) moves the final position of cells closer to the channel walls. The deformability-induced force for the cells with low La number ($La = 1$ and $La = 10$) dominates other effects, and similar to the Newtonian fluid, the cells move to the centerline. On the other

FIG. 9. (a) Final equilibrium location of cells and (b) their corresponding trajectories in a Giesekus fluid. The blockage ratio is $\frac{a}{W} = 0.3$ and $Re = 37.8$.

hand, increasing the Laplace number leads to the cell migration to off-center locations. The difference between the equilibrium position of soft and rigid cells becomes larger in a Giesekus fluid and this effect enhances the separation of cells based on cell deformability. The stress tensor generated in the presence of the polymeric fluid depends on parameters such as α and β [see Eq. (9)]. Therefore, it is important to study the effect of these parameters on the cell migration to provide engineers with an insight to design more efficient sorting techniques. According to Fig. 9(a), as β increases from 0.1 to 0.9 for constant Wi and α , the focal position of cells is pushed toward the wall, while the distance between the equilibrium position of the cells with different La number is significantly reduced. This behavior continues with increasing β until the cells with Laplace numbers ranging from 50 to 500 assemble in the same location at $\beta = 0.9$. In this case, all cells focus onto the same off-center point in the cross-section regardless of their deformability. Figure 9(b) shows the trajectories of cells toward the equilibrium position in a Giesekus fluid $Re = 37.8$. The final location of the cells are mostly on the channel diagonal similar to the Newtonian and Oldroyd-B fluids except for the case with $Wi = 2$, $\beta = 0.9$ and $\alpha = 0.1$, where the equilibrium position is on the x-axis. Previous studies⁶¹ have shown that the stability of final position changes with Re and size ratio ($\frac{a}{W}$), while here, we show that the stability can also change with the variation of fluid rheology such as β given a constant Reynolds number and size ratio.

Mobility factor α is another parameter that plays an important role in the cell dynamics. Increasing α from 0.1 to 0.2 leads to an increase in the equilibrium distance of the cells from the centerline. The reason for this observation can be attributed to stronger secondary flows, generated in a Giesekus fluid that pushes the cells toward the wall. This phenomenon has been previously observed for a rigid sphere.⁴² Additionally, increasing α increases the shear-thinning effects, which in turn increase the inertial lift force. This effect pushes the cells toward the channel wall. The results presented in this section suggest that the efficiency of microfluidic technologies used for classification of soft and stiff cells increases in shear-thinning polymeric fluids. In this section, we also investigate the effect of fluid elasticity on the shape and deformation of cells. Figure 10 illustrates the deformed shape of capsules at their equilibrium position for various polymeric fluids at $Re = 60$ and $La = 50$. The shape of the cell in a polymeric fluid is smoother and it does not develop sharp edges compared with the cell in a Newtonian fluid. In order to quantify the effect of viscoelasticity on the cell deformation, the Taylor deformation parameter is plotted for polymeric fluids in Fig. 11(a). The capsule deformation decreases with

FIG. 10. Deformed shape of capsules with $\frac{a}{W} = 0.3$, $La = 50$, $Re = 60$ and (a) $Wi = 0$ (b) $Wi = 0.9$ and $\alpha = 0$ (c) $Wi = 2$ and $\alpha = 0$ (d) $Wi = 1$ and $\alpha = 0.2$.

FIG. 11. (a) Deformation parameter of capsules at $Re = 60$ and (b) the velocity profile at $Z^* = 1$ and $X^* = x_{center}^*$ with $Re = 60$ and $La = 1$.

increasing Wi number in an Oldroyd-B fluid. As we mentioned in Sec. III B, the cells move toward the centerline as the Weissenberg number increases in an Oldroyd-B fluid. Therefore, the cells experience less viscous shear stress leading to smaller deformations. Furthermore, as we shown in our previous work,⁴⁵ the capsule deformation decreases with increasing Wi number due to the developed normal stress around the capsule membrane. The capsule at $Wi = 2$ focuses at the centerline [Fig. 10(c)] and it recovers the parachute shape. On the other hand, the cells in a Gieseikus fluid move toward the channel wall, leading to larger viscous shear stresses and consequently larger deformations.

Figure 11(b) shows the streamwise velocity profile at $Z^* = 1$ and $X^* = x_{center}^*$, where x_{center} represents the x-component of the capsule center of mass. In this case, $Re = 60$ and $La = 1$, the capsule focuses on the center in both Newtonian and polymeric fluids. According to this figure, the velocity profiles for Newtonian and Oldroyd-B fluids are identical, while the velocity increases for a Gieseikus fluid, due to the shear-thinning effect.⁴² The uniform velocity occurs inside the deformable capsules (channel centerline). The translational velocity of the cells is smaller than the flow velocity at that location in the absence of the cells, meaning the cell lags the flow. A similar behavior is observed for rigid particles.⁴² This behavior is attributed to the dominant effect of the wall that increases the drag force acting on capsules.^{62,63}

IV. CONCLUSIONS

In this paper, we studied the dynamics of deformable cells in Newtonian and polymeric fluids flowing in a square microchannel. We investigated the effects of various parameters such as cell deformability, fluid elasticity, inertia, and size on the cell migration behavior. The numerical results show that the equilibrium position of deformable cells is different from the rigid particles. Previous studies^{54,64} showed that the focal position of rigid particles is four off-center points near the channel wall, while our results show that of deformable cells lies on the channel diagonal. The deformability has a significant role in the dynamics of cell migration such that the reduction in the Laplace number causes the final position of cells to approach the channel centerline. This behavior is attributed to the strength of deformability-induced force that increases with a decrease in La moving the cells to the center. This effect becomes dominant for very soft cells (e.g., $La = 1$), where cells focus on the centerline. The migration of cells in a Newtonian fluid is a function of size, deformability, and flow inertia. We observed a completely different behavior for the cases in which the cells flow in a polymeric fluid. The constant-viscosity viscoelastic fluid (an Oldroyd-B fluid) pushes the cells toward the centerline. The focal position of the cells approaches the centerline with increasing Wi and ultimately all the cells with various sizes and deformability end up at the centerline. The results suggest an enhanced focusing behavior in a constant-viscosity polymeric fluid that can be used in various applications aiming to separate the cells from the suspending fluid. We also investigated the effect of fluid inertia and showed that increasing the Reynolds number pushes the equilibrium

position toward the wall, which exhibits an opposite effect compared with the Weissenberg number. The stabilizing effect of the polymer molecules in the suspending fluid enhances the throughput of current microfluidic technologies, as it delays the transition from laminar to turbulent flow. This allows us to increase the sample flow rate while achieving cell focusing. The cell motion in a shear-thinning viscoelastic fluid (a Giesekus fluid) is considered in this paper. Our findings indicate that non-Newtonian effects of a Giesekus fluid drive the cells toward the wall, contrary to an Oldroyd-B fluid. The reason for this behavior can be attributed to shear-thinning effects and the secondary flow generated in a microchannel. The findings of this paper suggest that the addition of polymers in microfluidic devices can be used to enhance the throughput of cell focusing and separation at a very low cost. This study provides an insight on the role of rheological properties of the fluid and ways they can be tuned to control the focal position of the cells.

ACKNOWLEDGMENTS

This publication was made possible, in part, with the support from NSF (Grant no. CBET-1445955-CAREER).

There are no conflicts to declare.

APPENDIX A: MESH INDEPENDENCY

In this section, we show the mesh-independency of the results presented in this study. As we mentioned in Sec. II B, the computational domain for $Re = 37.8$ is discretized using $128 \times 76 \times 76$ in x , y and z directions, respectively. In order to check the mesh-independency of the numerical simulations, we used $128 \times 152 \times 152$ Eulerian mesh. The results are shown in Fig. 12 for $La = 500$. The focal positions change 1.5% as we increase the number of grid points.

The mesh-independency of the numerical simulation is also checked for $Re = 200$ and $La = 50$. Figures 13(a) and 13(b) show the distance of the capsule from the channel centerline for Newtonian ($Wi = 0$) and Oldroyd-B ($Wi = 2$) fluids, respectively. The maximum error between two different sets of grid points are 2.02% and 0.65% for Newtonian and Oldroyd-B fluids, respectively.

APPENDIX B: DOMAIN INDEPENDENCY

Here, we show the independency of the numerical results to the domain length in the X -direction, where the periodic boundary condition is applied. Figure 14 shows the distance of capsule from the channel centerline at $Re = 100$ and $La = 500$ for two cases with different lengths in the X -direction ($L = 4W$ and $L = 8W$). The maximum error between two different cases is 1.71%.

FIG. 12. Distance of the capsule from the channel centerline for $La = 500$ and $Re = 37.8$ with $128 \times 76 \times 76$ and $200 \times 128 \times 128$ Eulerian grid points.

FIG. 13. Distance of the capsule from the channel centerline at $Re=200$ and $La=50$ for (a) $Wi=0$ and (b) $Wi=2$ with $200 \times 128 \times 128$ and $256 \times 152 \times 152$ Eulerian grid points.

FIG. 14. Distance of the capsule from the channel centerline at $Re=100$ and $La=500$ for different domain lengths $L=4W$ and $L=8W$.

APPENDIX C: VALIDATION OF NUMERICAL METHOD

The viscoelastic model used in this study is validated against published results. For this purpose, we simulated the deformation of a droplet containing polymeric fluid subjected to a shear flow. Figure 15 shows the ratio of steady-state deformation to the deformation of a droplet with a Newtonian content at $Ca=0.2$ ($Ca = \frac{\mu a \dot{\gamma}}{\sigma}$, where a and σ are the droplet radius and surface tension, respectively, and $\dot{\gamma}$ denotes the imposed shear rate). The results are in good agreement with previous published results,⁶⁵ with maximum error of 0.72%.

We also compared the results of our study with published results³⁸ to show that the numerical method used in this investigation accurately captures the inertial effects. For this purpose, the equilibrium position of capsules of various La flowing in a microchannel filled with a Newtonian fluid is computed. The Reynolds number in our study is $Re=37.8$. As we know, the Reynolds number does not affect the equilibrium position of the capsule in this range.³⁵ Our results are in good agreement with Ref. 38 and the maximum error observed here is 1.15% (Fig. 16).

FIG. 15. Deformation of polymeric droplet at $Ca=0.2$ and various Deborah numbers.

FIG. 16. Equilibrium position of a deformable capsule flowing in a microchannel filled with a Newtonian fluid.

- ¹R. D. Vidic, S. L. Brantley, J. M. Vandenbossche, D. Yoxtheimer, and J. D. Abad, *Science* **340**, 1235009 (2013).
- ²M. A. Shannon, P. W. Bohn, M. Elimelech, J. G. Georgiadis, B. J. Marinas, and A. M. Mayes, *Nature* **452**, 301 (2008).
- ³J. C. Giddings, K. A. Graff, K. D. Caldwell, and M. N. Myers, "Field-Flow Fractionation: Promising approach for the Separation and Characterization of Macromolecules" (ACS Publications, 1993).
- ⁴M. Toner and D. Irimia, *Annu. Rev. Biomed. Eng.* **7**, 77 (2005).
- ⁵D. R. Gossett, W. M. Weaver, A. J. Mach, S. C. Hur, H. T. K. Tse, W. Lee, H. Amini, and D. Di Carlo, *Anal. Bioanal. Chem.* **397**, 3249 (2010).
- ⁶H. F. Bunn, *New England J. Med.* **337**, 762 (1997).
- ⁷J. Li, Z. Zhang, J. Rosenzweig, Y. Y. Wang, and D. W. Chan, *Clin. Chem.* **48**, 1296 (2002).
- ⁸J. Villanueva, D. R. Shaffer, J. Philip, C. A. Chaparro, H. Erdjument-Bromage, A. B. Olshen, M. Fleisher, H. Lilja, E. Brogi, J. Boyd *et al.*, *J. Clin. Invest.* **116**, 271 (2006).
- ⁹A. van de Stolpe, K. Pantel, S. Sleijfer, L. W. Terstappen, and J. M. Den Toonder, "Circulating tumor cell isolation and diagnostics: Toward routine clinical use," *Cancer Res.* **71**(18), 5955–5960 (2011).
- ¹⁰P. Gascoyne, J. Satayavivad, and M. Ruchirawat, *Acta Trop.* **89**, 357 (2004).
- ¹¹K. Krabchi, F. Gros-Louis, J. Yan, M. Bronsard, J. Masse, J.-C. Forest, and R. Drouin, *Clin. Gen.* **60**, 145 (2001).
- ¹²P. Sethu, A. Sin, and M. Toner, *Lab Chip* **6**, 83 (2006).
- ¹³A. Karimi, S. Yazdi, and A. Ardekani, *Biomicrofluidics* **7**, 021501 (2013).
- ¹⁴H. M. Shapiro, *Practical Flow Cytometry* (John Wiley & Sons, 2005).
- ¹⁵S. Miltenyi, W. Müller, W. Weichel, and A. Radbruch, *Cytometry* **11**, 231 (1990).
- ¹⁶S. Zheng, H. Lin, J.-Q. Liu, M. Balic, R. Datar, R. J. Cote, and Y.-C. Tai, *J. Chromatogr. A* **1162**, 154 (2007).
- ¹⁷J. Takagi, M. Yamada, M. Yasuda, and M. Seki, *Lab Chip* **5**, 778 (2005).
- ¹⁸M. D. Vahey and J. Voldman, *Anal. Chem.* **80**, 3135 (2008).
- ¹⁹G. Segre, *Nature* **189**, 209 (1961).
- ²⁰B. Chun and A. Ladd, *Phys. Fluids* **18**, 031704 (2006).
- ²¹Y. W. Kim and J. Y. Yoo, *J. Micromech. Microeng.* **18**, 065015 (2008).
- ²²X. Shao, Z. Yu, and B. Sun, *Phys. Fluids* **20**, 103307 (2008).
- ²³D. Di Carlo, *Lab Chip* **9**, 3038 (2009).
- ²⁴E. S. Asmolov, *J. Fluid Mech.* **381**, 63 (1999).
- ²⁵L. Zeng, S. Balachandar, and P. Fischer, *J. Fluid Mech.* **536**, 1 (2005).
- ²⁶R. Cox and H. Brenner, *Chem. Eng. Sci.* **23**, 147 (1968).
- ²⁷B. Ho and L. Leal, *J. Fluid Mech.* **65**, 365 (1974).
- ²⁸J. A. Schonberg and E. Hinch, *J. Fluid Mech.* **203**, 517 (1989).
- ²⁹J.-P. Matas, J. F. Morris, and E. Guazzelli, *J. Fluid Mech.* **515**, 171 (2004).
- ³⁰A. Karnis, H. Goldsmith, and S. Mason, *Can. J. Chem. Eng.* **44**, 181 (1966).
- ³¹J. Feng, H. H. Hu, and D. D. Joseph, *J. Fluid Mech.* **261**, 95 (1994).
- ³²T.-W. Pan and R. Glowinski, *C. R. Méc.* **333**, 884 (2005).
- ³³B. Yang, J. Wang, D. Joseph, H. H. Hu, T.-W. Pan, and R. Glowinski, *J. Fluid Mech.* **540**, 109 (2005).
- ³⁴B. Kaoui, G. Ristow, I. Cantat, C. Misbah, and W. Zimmermann, *Phys. Rev. E* **77**, 021903 (2008).
- ³⁵A. Kilimnik, W. Mao, and A. Alexeev, *Phys. Fluids* **23**, 123302 (2011).
- ³⁶Y.-L. Chen, *RSC Adv.* **4**, 17908 (2014).
- ³⁷S. C. Hur, N. K. Henderson-MacLennan, E. R. McCabe, and D. Di Carlo, *Lab Chip* **11**, 912 (2011).
- ³⁸C. Schaaf and H. Stark, *Soft Matter* (2017).
- ³⁹A. T. Ciftlik, M. Ettori, and M. A. Gijs, *Small* **9**, 2764 (2013).
- ⁴⁰D. Di Carlo, J. F. Edd, D. Irimia, R. G. Tompkins, and M. Toner, *Anal. Chem.* **80**, 2204 (2008).
- ⁴¹E. J. Lim, T. J. Ober, J. F. Edd, S. P. Desai, D. Neal, K. W. Bong, P. S. Doyle, G. H. McKinley, and M. Toner, *Nat. Commun.* **5**, 4120 (2014).
- ⁴²G. Li, G. McKinley, and A. Ardekani, *J. Fluid Mech.* **785**, 486 (2015).
- ⁴³F. Del Giudice, G. Romeo, G. D'Avino, F. Greco, P. A. Netti, and P. L. Maffettone, *Lab Chip* **13**, 4263 (2013).
- ⁴⁴F. Del Giudice, G. D'Avino, F. Greco, P. A. Netti, and P. L. Maffettone, *Microfluid. Nanofluid.* **19**, 95 (2015).
- ⁴⁵A. H. Raffiee, S. Dabiri, and A. M. Ardekani, *Phys. Rev. E* **96**, 032603 (2017).
- ⁴⁶R. Skalak, A. Tozeren, R. Zarda, and S. Chien, *Biophys. J.* **13**, 245 (1973).
- ⁴⁷T. Krüger, B. Kaoui, and J. Harting, *J. Fluid Mech.* **751**, 725 (2014).
- ⁴⁸J. Charrier, S. Shrivastava, and R. Wu, *J. Strain Anal. Eng. Des.* **24**, 55 (1989).
- ⁴⁹B. P. Leonard, *Comput. Methods Appl. Mech. Eng.* **19**, 59 (1979).
- ⁵⁰A. J. Chorin, *Math. Comput.* **22**, 745 (1968).
- ⁵¹S. O. Unverdi and G. Tryggvason, *J. Comput. Phys.* **100**, 25 (1992).
- ⁵²H. Giesekus, *J. Non-Newtonian Fluid Mech.* **11**, 69 (1982).

- ⁵³G. Schleiniger and R. Weinacht, *J. Rheol.* **35**, 1157 (1991).
- ⁵⁴D. Di Carlo, J. F. Edd, K. J. Humphry, H. A. Stone, and M. Toner, *Phys. Rev. Lett.* **102**, 094503 (2009).
- ⁵⁵B. Ho and L. Leal, *J. Fluid Mech.* **76**, 783 (1976).
- ⁵⁶G. D'Avino, G. Romeo, M. M. Villone, F. Greco, P. A. Netti, and P. L. Maffettone, *Lab Chip* **12**, 1638 (2012).
- ⁵⁷A. Leshansky, A. Bransky, N. Korin, and U. Dinnar, *Phys. Rev. Lett.* **98**, 234501 (2007).
- ⁵⁸R. B. Bird, R. C. Armstrong, and O. Hassager, Dynamics of polymeric liquids in *Fluid mechanics*, 2nd ed., (John Wiley and Sons Inc., New York 1987), Vol. 1.
- ⁵⁹S. Yang, J. Y. Kim, S. J. Lee, S. S. Lee, and J. M. Kim, *Lab Chip* **11**, 266 (2011).
- ⁶⁰K. Kang, S. S. Lee, K. Hyun, S. J. Lee, and J. M. Kim, *Nat. Commun.* **4**, 2567 (2013).
- ⁶¹C. Prohm and H. Stark, *Lab Chip* **14**, 2115 (2014).
- ⁶²J. Happel and H. Brenner, *Low Reynolds Number Hydrodynamics: With Special Applications to Particulate Media* (Springer Science & Business Media, 2012), Vol. 1.
- ⁶³R. P. Chhabra, *Bubbles, Drops, and Particles in Non-Newtonian Fluids* (CRC Press, 2006).
- ⁶⁴D. Di Carlo, D. Irimia, R. G. Tompkins, and M. Toner, *Proc. Natl. Acad. Sci.* **104**, 18892 (2007).
- ⁶⁵N. Aggarwal and K. Sarkar, *J. Fluid Mech.* **584**, 1 (2007).