Xiaoya Guo

Department of Mathematics,
Southeast University,
Nanjing 210096, China

Don P. Giddens

Department of Medicine,
Emory University School of Medicine,
Atlanta, GA 30307;
The Wallace H. Coulter Department
of Biomedical Engineering,
Georgia Institute of Technology,
Atlanta, GA 30332

David Molony

Department of Medicine,
Emory University School of Medicine,
Atlanta, GA 30307

Chun Yang

Mathematical Sciences Department,
Worcester Polytechnic Institute,
Worcester, MA 01609

Habib Samady

Department of Medicine,
Emory University School of Medicine,
Atlanta, GA 30307

Jie Zheng

Mallinckrodt Institute of Radiology,
Washington University,
St. Louis, MO 63110

Gary S. Mintz

The Cardiovascular Research Foundation,
Columbia University,
New York, NY 10022

Akiko Maehara

The Cardiovascular Research Foundation,
Columbia University,
New York, NY 10022

Liang Wang

Mathematical Sciences Department,
Worcester Polytechnic Institute,
Worcester, MA 01609

Xuan Pei

School of Biological Science
& Medical Engineering,
Southeast University,
Nanjing 210096, China

Zhi-Yong Li

School of Biological Science
& Medical Engineering,
Southeast University,
Nanjing 210096, China

Dalin Tang¹

Department of Mathematics,
Southeast University,
Nanjing 210096, China;
Mathematical Sciences Department,
Worcester Polytechnic Institute,
Worcester, MA 01609

Combining IVUS and Optical Coherence Tomography for More Accurate Coronary Cap Thickness Quantification and Stress/Strain Calculations: A Patient-Specific Three-Dimensional Fluid-Structure Interaction Modeling Approach

Accurate cap thickness and stress/strain quantifications are of fundamental importance for vulnerable plaque research. Virtual histology intravascular ultrasound (VH-IVUS) sets cap thickness to zero when cap is under resolution limit and IVUS does not see it. An innovative modeling approach combining IVUS and optical coherence tomography (OCT) is introduced for cap thickness quantification and more accurate cap stress/strain calculations. In vivo IVUS and OCT coronary plaque data were acquired with informed consent obtained. IVUS and OCT images were merged to form the IVUS + OCT data set, with biplane angiography providing three-dimensional (3D) vessel curvature. For components where VH-IVUS set zero cap thickness (i.e., no cap), a cap was added with minimum cap thickness set as 50 and 180 μm to generate IVUS50 and IVUS180 data sets for model construction, respectively. 3D fluid-structure interaction (FSI) models based on IVUS + OCT, IVUS50, and IVUS180 data sets were constructed to investigate cap thickness impact on stress/strain calculations. Compared to IVUS + OCT, IVUS50 underestimated mean cap thickness (27 slices) by 34.5%, overestimated mean cap stress by 45.8% (96.4 versus 66.1 kPa). IVUS50 maximum cap stress was 59.2% higher than that from IVUS + OCT model (564.2 versus 354.5 kPa). Differences between IVUS and IVUS + OCT models for cap strain and flow shear stress (FSS) were modest (cap strain <12%; FSS <6%). IVUS + OCT data and models could provide more accurate cap thickness and stress/strain calculations which will serve as basis for further plaque investigations. [DOI: 10.1115/1.4038263]

Keywords: vulnerable plaque, OCT, IVUS, cap thickness, patient-specific model, FSI

¹Corresponding author.

Manuscript received May 28, 2017; final manuscript received October 4, 2017; published online January 23, 2018. Assoc. Editor: Alison Marsden.

1 Introduction

Computational models have been used as a powerful tool to perform mechanical analysis for vulnerable plaques and identify risk factors which may be associated with plaque progression and rupture [1–4]. Modeling results and stress/strain predictions are influenced by many complex factors including plaque morphology, components, material properties, and modeling assumptions [4–5]. Since thin fibrous cap (cap thickness $< 65 \mu\text{m}$) covering a large lipid-rich necrotic core (called lipid when proper) is known as one of the characteristics for vulnerable plaques, quantifying cap thickness and its impact on stress/strain calculations has remained a great challenge for plaque research. For coronary plaques, magnetic resonance imaging (MRI) is not able to provide enough resolution due to heart motion, distance, and small vessel size. Intravascular ultrasound (IVUS) with tissue characterization is currently used in clinical practice for recognition of vulnerable plaques in vivo [6]. Virtual histology IVUS (VH-IVUS) segments the grayscale IVUS data into four tissue types [7], allowing in vivo identification of four discrete atherosclerotic plaque components: fibrotic, fibro-fatty, necrotic, and dense calcified tissue [7]. While VH-IVUS has provided unique perspectives on in vivo human atherosclerotic plaque and novel insights into plaque morphology and natural history [8,9], it still has limited resolution of $150\text{--}250 \mu\text{m}$ and is not able to detect thin plaque cap with thickness around $65 \mu\text{m}$, a threshold value determined by histopathological studies [10,11]. VH-IVUS sets cap thickness to zero when cap is under resolution limit and IVUS does not see it. In recent years, optical coherence tomography (OCT) has emerged as an imaging modality to identify vulnerable plaques from nonvulnerable plaques to enhance future risk prediction [12–17]. OCT has resolution of $15\text{--}20 \mu\text{m}$ and therefore can better measure fibrous cap thickness and can detect plaque rupture and other rupture-prone features in patients. Figure 1 gave an example where OCT shows cap thickness and plaque rupture clearly, while IVUS cannot detect the thick cap and rupture. The major limitation of OCT is its limited penetration. Because of that, OCT could “see” thin

cap thickness and near-lumen plaque components (lipid, calcification, thrombus, macrophage, etc.). But, it is, in general, not able to penetrate the entire vessel wall, therefore, could only give incomplete vessel image. By merging VH-IVUS and OCT together, we can obtain whole vessel morphology from IVUS and superior resolution from OCT and provide better accuracy for fibrous cap quantifications (see Fig. 2). Raber et al. introduced an offline fusion technique of co-registered OCT and VH-IVUS images of human atherosclerotic plaques. Nine matched OCT, IVUS, and IVUS-VH cross sections were fused in their investigation. Their results indicated that fusion of IVUS and OCT combines the strengths of both imaging modalities and has potential for improved diagnostic accuracy of plaque characterization [18]. Karanasos et al. fused computed tomography coronary angiography and IVUS, and computed tomography coronary angiography and OCT data to investigate the relationship between endothelial shear stress (ESS) and fibrous cap thickness in segments implanted with bioresorbable scaffolds. They found that higher ESS at 2-year follow-up correlated with fibrous caps at 5 years, indicating that ESS modulates the long-term vascular healing response of the vessels treated with these devices [19]. Bourantas et al. provided an extensive review of several multimodality imaging approaches including combined near infrared spectroscopy-intravascular ultrasound, IVUS-OCT, OCT-NIRS, the OCT-near infrared fluorescence molecular imaging, IVUS-NIRF, IVUS intravascular photoacoustic imaging, and combined fluorescence lifetime-IVUS imaging [20]. The medical imaging research community is making great effort to overcome limitations of current standalone imaging tools.

In this paper, we propose to develop a multimodality image-based modeling approach combining three-dimensional (3D) IVUS, OCT, angiography, and computational modeling to better quantify human coronary atherosclerotic plaque morphology (especially cap thickness) and plaque stress/strain conditions. As indicated by Raber et al. and Bourantas et al., combining IVUS and OCT has the potential to get more accurate plaque

Fig. 1 Plaque rupture: a coronary plaque sample with IVUS, OCT, and angiography showing rupture: (a) OCT slices showing plaque rupture, (b) matching grayscale IVUS, possible rupture identified site, (c) segmented OCT, (d) angiography, and (e) colors used in (c)

Fig. 2 Merging VH-IVUS and OCT for more accurate cap thickness quantification (calcification ignored in this plot): (a) VH-IVUS slice, (b) contours directly from VH-IVUS showing zero cap thickness, (c) VH-IVUS contours with a thin cap added, (d) matching OCT Slice, (e) contours from OCT showing accurate cap thickness, and (f) IVUS+OCT has entire vessel with accurate cap thickness

morphology and identify plaques with cap thickness $<65 \mu\text{m}$ and other rupture-related features. Since IVUS does not “see” plaque caps with thickness less than its resolution ($150\text{--}250 \mu\text{m}$), VH-IVUS often have “naked” plaque components such as lipid cores and calcifications sitting right on lumen. To make plaque models, a cap with guessed cap thickness has to be added to cover those components. OCT was used as the gold standard to access the accuracy of those educated guesses since plaque samples and histological data were not available. Our main goal is to quantify the impact of more accurate cap thickness measurement on plaque stress/strain calculations. This modeling approach may provide the basis leading to better plaque stress/strain calculations and progression and vulnerability predictions.

2 Data, Models, and Methods

2.1 In Vivo IVUS and OCT Data Acquisition. In vivo 3D IVUS/OCT/Angiography data were acquired from two participants (age, sex: 51M, 67F) at Emory University, Atlanta, GA. The institutional review board approved the study and each patient gave informed consent [21,22]. Both patients suffered from recurrent angina and were found to have nonobstructive lesions (fractional flow reserve >0.8) during electively indicated cardiac catheterization. Plaque burden averaged over the vessel length was 50% and 28%, respectively. Patients underwent VH-IVUS (Volcano Corp., Rancho Cordova, CA) imaging where the IVUS catheter was traversed distally through the left anterior descending artery to the region of interest and an automatic pullback was performed at 0.5 mm/s . Slice thickness for patients 1 and 2 (P1 and P2) was 0.34 mm and 0.40 mm , respectively. The flow and pressure characteristics of the vessel were recorded using a Combo-wire (Volcano Corp.) [23]. Following VH-IVUS image

acquisition, the OCT catheter (St. Jude, Minnesota, MN) was also traversed to the region of interest and an automatic pullback at 20 mm/s was performed. All pullbacks extended until the coronary ostium and pullback lengths of 73.3 and 53.2 mm for the IVUS and $54(\times 2) \text{ mm}$ for the OCT procedures were recorded. The positions of both catheters are recorded with angiography prior to pullback to aid in the 3D reconstruction.

2.2 Segmentation, IVUS and OCT Co-Registration and Merging, and 3D Reconstruction Using Biplane Angiography.

A custom-made software atherosclerotic plaque segmentation (APS), written in MATLAB, was used to segment IVUS and OCT images and further process VH-IVUS and OCT into contours for model constructions (see Fig. 3). All image slices were segmented into four plaque elements: Fibrotic, Fibrofatty, Necrotic core, and Dense Calcium. Slices with a cap covering a lipid-rich necrotic core (nine slices from patient 1; 18 slices from patient 2) were selected for IVUS and OCT fusion. Locations of the nine selected slices from patient 1 were shown in Fig. 4. As VH-IVUS and OCT images were not recorded using the same catheter, they must be registered both longitudinally and circumferentially in order to be used for modeling. Features common to both modalities (lumen area and eccentricity, lipid core, catheter position, and calcifications) were identified and used to match VH-IVUS and OCT slices. This was achieved using a validated two-step approach [24]. First, images were initially co-registered in the longitudinal direction using a dynamic time warping method. This resulted in a corresponding OCT image for each IVUS image. Second, circumferential co-registration was achieved using a dynamic programming algorithm [24,25]. Here, a cost matrix consisting of potential rotation angles between each registered IVUS/OCT image pair was created from the features. The optimum rotation angle based

Fig. 3 IVUS and OCT segmentation, merging, and 3D reconstruction process. Slice numbers are original VH-IVUS numbers (referred to as S1–S9 in the rest of the paper): (a) selected IVUS slices, (b) matching OCT slices and segmented contours, (c) IVUS and OCT combined, after smooth (IVUS + OCT model), and (d) reconstructed 3D geometry.

Fig. 4 Three-dimensional vessel curvature reconstructed from biplane angiography: (a) reconstructed 3D curvature, (b) 3D vessel geometry with nine IVUS+OCT slices marked, (c) a angiography frame showing IVUS guidewire, and (d) vessel center line. The red part is the selected 86 slices: s50–s135 (color figure displayed online).

on the derived features was then determined as the minimum cost path through the cost matrix and each OCT image is rotated by this angle. The described approach has been found to be accurate to within 18deg circumferentially and 0.64mm longitudinally

[24]. Minor adjustments by human inspection were performed to insure best registration. This was achieved through visual assessment of landmarks such as calcifications and side-branches and limited to small angle adjustments or minor frame displacement.

For each co-registered VH-IVUS and OCT slice pairs, the VH-IVUS and OCT slices were merged together to obtained the merged IVUS + OCT slice, with VH-IVUS providing whole slice (lumen and out-boundary) contours, and OCT provide more accurate cap thickness and plaque component contours. The merging is mainly taking plaque components from segmented OCT contours and placing them in the corresponding segmented VH-IVUS lumen and out-boundary, keeping cap thickness as determined by OCT. Figure 3 provided nine co-registered VH-IVUS and OCT slices, with images, segmented contours, and merged slices. It is clearly observable from VH-IVUS image slices that many plaque components were sitting right on lumen boundary line.

The reconstruction of the 3D coronary geometry was achieved via the combination of angiography images of the IVUS catheter and merged IVUS + OCT images. Biplane angiographic images were acquired (Infinix, Toshiba, Minato, Japan) with views at least 30deg apart. The 3D path of the vessel centerline was obtained from the biplane angiographic images using Medis (Leiden, The Netherlands). The IVUS image contours are stacked on the 3D path using the known distance between consecutive IVUS frames. The rotation between successive IVUS images was determined using the sequential triangulation algorithm [26]. Figure 4 shows the 3D curvature of the vessel reconstructed from biplane angiography.

2.3 The Zero Cap Thickness Issue Due to VH-IVUS Resolution Limitation. One important fact which may be hidden in most IVUS-based modeling papers is as follows: VH-IVUS sets cap thickness to zero when cap is under resolution limit and IVUS does not see it. Due to IVUS resolution limitation (150–250 μm), when cap thickness is under resolution limit, IVUS cannot detect the cap. Then, the original VH-IVUS data will have those lipid cores and calcifications exposed directly to lumen, i.e., there is no fibrous cap covering those components. This means original VH-IVUS had those lipid cores and calcifications sitting right on lumen boundary as shown by Fig. 3. A minimum cap thickness has to be added to VH-IVUS data so that the lipid cores would be covered. This is a remedy for the original VH-IVUS data and the repaired data would be more realistic (compared to no cap) and usable for model construction. In our previous publications, a minimum 50 μm cap thickness was added in our model construction where 50 μm was chosen as it is a reasonable representative thin cap number <65 μm threshold. In this paper, we tested all minimum cap thickness for the [25 μm , 250 μm] range with 25 μm increment (with 5 μm final adjustments) and 180 μm cap thickness was found to be close to OCT cap thickness. In our segmentation software which is used to generate contour plots from VH-IVUS, a minimum cap thickness value could be set. The software will then generate a contour segment line into the vessel along the lumen to create the minimum cap thickness when it detects that a component is setting on the lumen. Therefore, in this paper, we set the minimum cap thickness as 50 and 180 μm in the custom-made software and obtained two sets of segmented contours denoted as IVUS50 and IVUS180 (or I-50 and I-180) to demonstrate the differences between the two IVUS-alone sets and the IVUS + OCT set. Cap thickness from I-50 to I-180 data sets was compared with cap thickness determined by OCT to find out their differences. It should be noted that cap thickness from I-50 to I-180 are for demonstration purpose. They by nature could be modeler's educated guesses, not cap thickness provided by IVUS. However, they are better than original IVUS data, since original VH-IVUS had zero cap thickness for those components.

2.4 The 3D FSI Model, Intraplaque Pressure, and Mooney–Rivlin Model for Material Properties. The I-50, I-180, and the merged IVUS + OCT data sets for each patient were used to construct fluid-structure interaction (FSI) models following our established procedures. The assumptions, governing

equations, and boundary conditions for the full FSI model can be found in our previous publication [23]. For readers' convenience, the FSI model is given in the following:

$$\rho(\partial \mathbf{u} / \partial t + ((\mathbf{u} - \mathbf{u}_g) \cdot \nabla) \mathbf{u}) = -\nabla p + \mu \nabla^2 \mathbf{u} \quad (1)$$

$$\nabla \cdot \mathbf{u} = 0 \quad (2)$$

$$\mathbf{u}|_{\Gamma} = \partial \mathbf{x} / \partial t, \quad \partial \mathbf{u} / \partial n|_{\text{inlet, outlet}} = 0 \quad (3)$$

$$p|_{\text{inlet}} = p_{\text{in}}(t), \quad p|_{\text{outlet}} = p_{\text{out}}(t) \quad (4)$$

$$\rho v_{i,tt} = \sigma_{ij,j}, \quad i, j = 1, 2, 3; \text{ sum over } j \quad (5)$$

$$\varepsilon_{ij} = (v_{i,j} + v_{j,i} + v_{\alpha,i} v_{\alpha,j}) / 2, \quad i, j, \alpha = 1, 2, 3 \quad (6)$$

$$\sigma_{ij} \cdot n_j|_{\text{out\_wall}} = 0 \quad (7)$$

$$\sigma'_{ij} \cdot n_j|_{\text{interface}} = \sigma^s_{ij} \cdot n_j|_{\text{interface}} \quad (8)$$

where $\mathbf{u}$ and p are fluid velocity and pressure, $\mathbf{u}_g$ is mesh velocity, μ is the dynamic viscosity, ρ is density, Γ stands for vessel inner boundary, $f \cdot \bullet_j$ stands for derivative of the function f with respect to the j th variable, σ is stress tensor (superscripts indicate different materials), ε is strain tensor, $\mathbf{v}$ is solid displacement vector, and superscript letters “ r ” and “ s ” were used to indicate different materials. For simplicity, all material densities were set to 1 $\text{g} \cdot \text{cm}^{-3}$ in this paper.

For this paper, intra-plaque pressure conditions were obtained by catheter and used as $p_{\text{in}}(t)$ (P1: $P_{\text{max}} = 147 \text{ mmHg}$, $P_{\text{min}} = 82 \text{ mmHg}$; patient 2, $P_{\text{max}} = 147 \text{ mmHg}$, $P_{\text{min}} = 98 \text{ mmHg}$). $P_{\text{out}}(t)$ was set to match catheter-measure flow conditions. Axial shrinkage was set at 5% in our models, because atherosclerotic vessels were stiffer than healthy vessels. The anisotropic Mooney–Rivlin model was used for the vessel tissue. Its strain energy density function is

$$W = c_1(I_1 - 3) + c_2(I_2 - 3) + D_1[\exp(D_2(I_1 - 3)) - 1] + (K_1/K_2)\exp[K_2(I_4 - 1)^2 - 1] \quad (9)$$

$$I_1 = \sum C_{ii}, \quad I_2 = \frac{1}{2}[I_1^2 - C_{ij}C_{ij}] \quad (10)$$

where I_1 and I_2 are the first and second invariants of right Cauchy–Green deformation tensor $\mathbf{C}$ defined as $\mathbf{C} = [\mathbf{C}_{ij}] = \mathbf{X}^T \mathbf{X}$, $\mathbf{X} = [X_{ij}] = [\partial x_i / \partial a_j]$, (x_i) is current position, (a_i) is original position, $I_4 = C_{ij}(\mathbf{n}_c)_i(\mathbf{n}_c)_j$, $\mathbf{n}_c$ is the unit vector in the circumferential direction of the vessel, and c_1 , c_2 , D_1 , D_2 , K_1 and K_2 are material parameters [23,27,28], whose values were determined using in vivo IVUS data [29]: $c_1 = -262.6 \text{ kPa}$, $c_2 = 22.9$, $D_1 = 125.9 \text{ kPa}$, $D_2 = 2$, $K_1 = 7.19 \text{ kPa}$, and $K_2 = 23.5$.

Plaque components (specifically, the necrotic lipid core in this study) were assumed isotropic and the isotropic Mooney–Rivlin material model was used to describe their material properties

$$W_{\text{iso}} = c_1(I_1 - 3) + c_2(I_2 - 3) + D_1[\exp(D_2(I_1 - 3)) - 1] \quad (11)$$

The material constants from existing literature were used in this paper [23,30,31]—lipid: $c_1 = 0.5 \text{ kPa}$, $c_2 = 0$, $D_1 = 0.5 \text{ kPa}$, $D_2 = 1.5$; calcification: $c_1 = 92 \text{ kPa}$, $c_2 = 0$, $D_1 = 36 \text{ kPa}$ and $D_2 = 2$.

2.5 Models, Solution Procedures, and Model Comparisons.

For each patient, three models were constructed and solved: model 1 was the IVUS + OCT model; model 2 was based on I-50 data (called IVUS50 or I-50 model); model 3 was based on I-180 data (called IVUS180 or I-180 model). VH-IVUS pixel size was 20 μm . The models were solved by a commercial finite element

software ADINA (Adina R & D, Watertown, MA) following established procedures [23,32]. ADINA uses unstructured finite element methods for both fluid and solid models. Nonlinear incremental iterative procedures were used to handle fluid-structure interactions. Mesh analysis was performed by refining mesh density by 10% until changes of solutions became less than 2%. Three cardiac cycles were simulated in our computational models and the solution in the third period was taken as the final result (error between cycles 3 and 2 was less than 1%). Average stress, strain, and flow shear stress (FSS) on the lumen and all the cap nodes covering the lipid-rich pool were recorded for comparison. To be clear, since stress and strain are tensors, maximum principal stress, maximum principal strain, and maximum principal flow shear stress were taken as the scalar representatives of stress, strain, and flow shear stress to present our results, respectively.

2.6 Statistical Method. Slice mean cap thickness, cap stress, cap strain and flow shear stress values for *P1* and *P2* from all three models were extracted for analysis. One-sample Kolmogorov–Smirnov test was used to check data normality and the results showed that data sets did not satisfy normality requirement. Wilcoxon signed rank test (which does not require data normality) was used to compare results from IVUS + OCT model and IVUS50/IVUS180 models. A *p*-value < 5% indicates that the median difference between two samples is statistically significant.

3 Results

3.1 IVUS + OCT Data Provided More Accurate Cap Thickness Measurements. Among many morphological plaque features, cap thickness may be the most critical and most sought-after data item we would like to quantify. Accuracy of modeling stress/strain predictions is heavily dependent on cap thickness. Table 1 shows comparisons of maximum, minimum, and mean slice cap thickness of the “cap” slices (slices with a cap covering a lipid-rich necrotic core) from the three models for the two patients studied. It should be noted that only IVUS + OCT cap thickness were real measurements from OCT, while cap thickness from IVUS50 and IVUS180 were educated guesses by hypothetical modelers. *P* < 0.05 indicates that the difference was statistically significant. Figure 5 gave bar plots showing comparison of the corresponding cap thickness values. Mean cap thickness (unit: mm) from patient 1 (nine slices) was 0.353 (OCT), 0.201 (IVUS50), and 0.329 (IVUS180), respectively. While IVUS180 cap thickness was only 7% less than the OCT value, IVUS50 cap value was 43% less than OCT value. Patient 2 mean cap thickness (18 slices) was 0.320 (OCT), 0.224 (IVUS50), and 0.285 (IVUS180), respectively. IVUS50 cap value was 30% less than OCT value. Mean cap thickness combining the slices from the two patients (27 slices) was 0.331 (OCT), 0.217 (IVUS50), and 0.299 (IVUS180), respectively. IVUS50 underestimated cap

Table 1 Mean, minimum and maximum of slice cap thickness from IVUS + OCT, IVUS50, and IVUS180 data sets showing their differences: *P1*—patient 1 and *P2*—patient 2

Cap thickness (mm)	IVUS + OCT	IVUS50	<i>P</i> value	IVUS180	<i>P</i> value
Patient 1 (nine slices)					
Average of mean slice cap thickness	0.353 ± 0.08	0.201 ± 0.020	0.0039	0.329 ± 0.049	0.1641
Average of min slice cap thickness	0.252 ± 0.081	0.113 ± 0.019	0.0039	0.239 ± 0.053	0.5938
Min of min slice cap thickness	0.147	0.083	—	0.183	—
Average of max slice cap thickness	0.484 ± 0.129	0.312 ± 0.040	0.0039	0.448 ± 0.063	0.4257
Patient 2 (18 slices)					
Average of mean slice cap thickness	0.320 ± 0.092	0.224 ± 0.069	0.0018	0.285 ± 0.042	0.1701
Average of min slice cap thickness	0.231 ± 0.082	0.108 ± 0.091	0.0010	0.177 ± 0.051	0.0641
Min of min slice cap thickness	0.114	0.023	—	0.12	—
Average of max slice cap thickness	0.538 ± 0.130	0.452 ± 0.085	0.0084	0.474 ± 0.087	0.1024
Patients 1 + 2 (27 slices)					
Average of mean slice cap thickness	0.331 ±	0.217	2.6×10^{-5}	0.299	0.0625
Average of min slice cap thickness	0.238	0.110	2.4×10^{-5}	0.198	0.0593
Min of min slice cap thickness	0.114	0.023	—	0.12	—
Average of max slice cap thickness	0.520 ± 0.130	0.405 ± 0.099	0.0002	0.465 ± 0.079	0.0643

Fig. 5 Bar plots of mean, maximum and minimum slice cap thickness show differences from IVUS + OCT, IVUS50, and IVUS180 sets. Unit: mm. Mean cap thickness and max cap thickness are average of slice values. Min cap thickness is min of slice min cap thickness. 2P min average is the patient min cap thickness average: (a) patient 1 (nine slices), (b) patient 2 (18 slices), and (c) *P1* and *P2* combined (27 slices).

thickness for the 27 slices by 34.5%, compared to OCT cap values.

Minimum cap thickness is also of interest since rupture is more likely to occur at the weakest location of the cap. Minimum cap thickness for patient 1 was 0.147 (OCT), 0.083 (IVUS50), and 0.183 (IVUS180), respectively. IVUS50 minimum cap value was 43.4% less than OCT minimum cap value. Minimum cap thickness for patient 2 was 0.114 (OCT), 0.023 (IVUS50), and 0.120 (IVUS180), respectively. IVUS50 minimum cap value was 79% less than OCT minimum cap value. As 0.023 mm is below the 0.065 mm threshold value, IVUS50 is likely to cause false alarms for patients whose true cap thickness is higher than IVUS50 predicts.

It should be noted that the minimum cap thickness in Table 1 is the value at a single point (for each slice, we made 200 points to get data) which could be subjected to large random errors. So, the minimum cap thickness value should be taken with caution.

3.2 IVUS + OCT Model Predicted Lower Cap Stress Values. While cap thickness may be classified under “data” category, accurately predicting plaque cap stress values have been the focus of vulnerable plaque modeling research. From a biomechanical point view, plaque ruptures when cap stress value exceeds its mechanical ultimate strength [33]. Table 2 compares mean and maximum cap stress values from IVUS + OCT, IVUS50, and IVUS180 models for the two patients studied. The maximum of the slice maximum cap stress values (called max of max) was provided, since this was also considered one of the most critical values linked to possible plaque rupture. Figure 6 gave model comparisons using bar plots and stress distribution on lumen and cross section cuts. Mean cap stress (kPa) from patient 1 (nine slices) was 73.3 (OCT), 106.6 (IVUS50), and 78.5 (IVUS180), respectively. While IVUS180 mean cap stress was only 7% more than the OCT value, IVUS50 mean cap stress value was 45% higher than OCT value. Patient 2 mean cap stress (18 slices) was 62.5 (OCT), 91.2 (IVUS50), and 65.9 (IVUS180), respectively. IVUS50 cap stress was 46% higher than OCT value. Mean cap stress combining the slices from the two patients (27 slices) was 66.1 (OCT), 96.4 (IVUS50), and 70.1 (IVUS180), respectively. IVUS50 overestimated cap stress for the 27 slices by 45.8%, compared to OCT cap stress.

Plaque stress analysis often pays more attention to maximum cap stress values. Maximum cap stress (maximum of the slice maxima) for patient 1 was 178.2 (OCT), 254.9 (IVUS50), and 178.6 (IVUS180), respectively. IVUS50 maximum cap stress was 43% higher than OCT maximum cap value. Maximum cap stress for patient 2 was 354.5 (OCT), 564.2 (IVUS50), and 303.2 (IVUS180), respectively. IVUS50 maximum cap stress was 59.2% higher than that from IVUS + OCT model. As 564.205 kPa exceeds 300 kPa threshold value by 88%, IVUS50 is likely to

cause false mechanical prediction for patients whose true cap thickness is higher than IVUS50 predicts.

3.3 Cap Strain by IVUS + OCT Model was Modestly Lower Than That From IVUS50 Model. Table 3 summarized mean and maximum cap strain values from the three models for the two patients studied. Figure 7 gave bar plots and strain distribution on sagittal and cross section cuts showing model comparisons. Mean cap strain from patient 1 (nine slices) was 0.078 (OCT), 0.090 (IVUS50), and 0.080 (IVUS180), respectively. IVUS180 cap strain was only 2.6% higher than OCT value. IVUS50 cap strain value was 15.4% higher than OCT value. Patient 2 mean cap strain (18 slices) was 0.139 (OCT), 0.154 (IVUS50), and 0.143 (IVUS180), respectively. IVUS50 cap strain was 10.8% higher than OCT value. Mean cap strain combining the slices from the two patients (27 slices) was 0.119 (OCT), 0.133 (IVUS50), and 0.122 (IVUS180), respectively. IVUS50 overestimated cap strain for the 27 slices by 11.8%, compared to OCT cap strain.

Maximum cap strain for patient 1 was 0.141 (OCT), 0.140 (IVUS50), and 0.128 (IVUS180), respectively. IVUS50 maximum cap strain was nearly equal to OCT maximum cap value. Maximum cap strain for patient 2 was 0.293 (OCT), 0.321 (IVUS50), and 0.298 (IVUS180), respectively. IVUS50 maximum cap strain was 9.6% higher than OCT value.

3.4 Flow Shear Stress had Modest Differences From the Three Models. The mean and maximum slice mean FSS values from the cap slices for the two patients were summarized in Table 4. Bar plots and FSS distributions on lumen and two cross sections are shown by Fig. 8. Mean FSS (dyn/cm²) from patient 1 (nine slices) was 13.1 (OCT), 12.3 (IVUS50), and 12.6 (IVUS180), respectively. IVUS180 and IVUS50 cap strain were 3.8% and 5.8% less than the OCT value, respectively. Mean FSS from patient 2 (18 slices) were 37.7 (OCT), 38.2 (IVUS50), and 38.6 (IVUS180), respectively. IVUS180 and IVUS50 cap FSS were 2.5% and 1.5% higher than the OCT value, respectively. Mean FSS combining the slices from the two patients (27 slices) was 29.5 (OCT), 29.6 (IVUS50), and 29.9 (IVUS180), respectively. The Mean FSS in three models were almost the same value (<2% difference). Maximum FSS values for all 27 slices were also provided for references. Overall, FSS differences from the three models were very modest (<6%).

4 Discussion

4.1 Significance of the IVUS + OCT Approach. Imaging resolution has been a major limitation for vulnerable plaque research (and other areas in a broader sense) since the introduction of medical imaging. The research community has been tolerant

Table 2 Mean and maximum of slice cap stress values from IVUS + OCT, IVUS50, and IVUS180 models showing their differences (unit: kPa)

Cap stress (kPa)	IVUS + OCT	IVUS50	P value	IVUS180	P value
Patient 1 (nine slices)					
Average mean stress	73.3 ± 26.2	106.6 ± 32.5	0.0039	78.5 ± 27.5	0.0195
Average max stress	121.7 ± 37.4	180.4 ± 53.0	0.0039	128.3 ± 45.6	0.8203
Max of max stress	178.2	254.9	—	178.6	—
Patient 2 (18 slices)					
Average mean stress	62.5 ± 15.4	91.3 ± 36.6	0.0012	65.9 ± 14.8	0.2145
Average max stress	141.0 ± 70.0	249.1 ± 164.9	0.0005	154.2 ± 65.4	0.1119
Max of max stress	354.5	564.2	—	303.2	—
Patients 1 + 2 (27 slices)					
Average mean stress	66.1 ± 19.8	96.4 ± 35.4	1.9×10^{-5}	70.1 ± 20.3	0.0325
Average max stress	134.6 ± 61.0	226.2 ± 140.5	9.8×10^{-6}	145.5 ± 59.9	0.0880
Max of max stress	354.5	564.2	—	303.2	—

Fig. 6 Stress distribution on lumen and cross section cuts showing differences from IVUS + OCT and IVUS50 models of patient 1. Bar plots of mean, maximum, and minimum cap stress are showing differences from IVUS + OCT, IVUS50 and IVUS180 models of two patients. Mean cap stress and min cap stress are average of cap values. Max cap stress is max of max slice cap stresses: (a) P1, IVUS + OCT model, stress distribution on lumen, (b) P1, IVUS50 model, stress distribution on lumen, (c) P1, IVUS + OCT model, stress on cross sections, (d) P1, IVUS50 model, stress on cross sections, (e) P1, cap stress (kPa), and (f) P2, cap stress (kPa).

Table 3 Mean and maximum slice cap strain values from IVUS + OCT, IVUS50, and IVUS180 models showing their differences

Cap Strain	IVUS + OCT	IVUS50	<i>p</i> -value	IVUS180	<i>P</i> value
Patient 1 (nine slices)					
Average mean strain	0.078 ± 0.017	0.090 ± 0.016	0.0039	0.080 ± 0.017	0.2227
Average max strain	0.112 ± 0.021	0.122 ± 0.014	0.1250	0.110 ± 0.015	0.6133
Max of max strain	0.141	0.140	—	0.128	—
Patient 2 (18 slices)					
Average mean strain	0.139 ± 0.012	0.154 ± 0.017	0.0018	0.143 ± 0.012	0.3158
Average max strain	0.214 ± 0.043	0.222 ± 0.041	0.1445	0.212 ± 0.036	0.7937
Max of max strain	0.293	0.321	—	0.298	—
Patients 1 + 2 (27 slices)					
Average mean strain	0.119 ± 0.032	0.133 ± 0.035	0.0001	0.122 ± 0.033	0.2110
Average max strain	0.180 ± 0.061	0.189 ± 0.059	0.0502	0.178 ± 0.058	0.6650
Max of max strain	0.293	0.321	—	0.298	—

Fig. 7 Strain distribution on lumen and cross section cuts showing differences from IVUS + OCT and IVUS50 models of patient 1. Bar plots of mean, maximum and minimum cap strain showing differences from IVUS + OCT, IVUS50, and IVUS180 models of two patients. Mean cap strain and min cap strain are average of cap values. Max cap strain is max of max slice cap strain values: (a) P1, IVUS+OCT model, stress distribution on lumen, (b) P1, IVUS50 model, stress distribution on lumen, (c) P1, IVUS+OCT model, stress on cross sections, (d) P1, IVUS50 model, stress on cross sections, (e) P1, cap strain (kPa), and (f) P2, cap strain (kPa).

for research findings such as in vivo plaque cap thickness quantifications, vulnerable plaque definitions, and plaque progression mechanism research [34]. With image resolutions at 150 μm (IVUS)–300 μm (MRI) or even worse, and plaque vessel wall thickness changes were normally under 200 μm , and “vulnerable plaque” cap thickness threshold value defined as 65 μm , many published results were educated guesses by segmentation software. The gain from the IVUS + OCT approach comes from two fronts: imaging cap thickness and model prediction of stress/strain values. From the two patients (27 cap slices) studies, IVUS-50 underestimated minimum cap thickness by 43.4% and 79%, compared to IVUS + OCT values, respectively. For maximum cap stress, IVUS-50 over-estimated maximum cap stress minimum cap thickness by 43% and 59%, compared to IVUS + OCT values, respectively. IVUS-180 provided better agreement with IVUS + OCT values. It is worth noting that the observations that IVUS-180 provided better agreement with OCT data over IVUS-50 from these two patients cannot be generalized. In fact, if we had true vulnerable plaques with thin cap, IVUS-50 would have

better agreement with OCT data over IVUS-180. The uncertainty of imaging data from IVUS, MRI, and OCT should be kept in mind when interpreting our data and findings.

4.2 Establishing In Vivo Threshold Cap Thickness and Stress/Strain Levels for Vulnerable Plaques. It is desirable to have threshold values for differentiating vulnerable plaques from less vulnerable plaques. Cap thickness of 65 μm and cap stress of 300 kPa are such well-known threshold values. It is certainly nice to have such numbers in the literature and obtaining those numbers took huge effort [10,11]. However, we should be aware that those numbers were from histological or modeling studies based on ex vivo data. The cut-off numbers are also of statistical number and should be interpreted with caution. Establish similar threshold values for vulnerable plaques based on in vivo data will require large scale data and gold standard which can be used to define plaque vulnerability. It should be reasonable to expect that in vivo cap thickness and critical stress/strain threshold values may be different from those ex vivo values.

Table 4 Mean and maximum slice FSS values from IVUS + OCT, IVUS50, and IVUS180 models showing their differences. Unit: dyn/cm².

FSS (dyn/cm ²)	IVUS + OCT	IVUS50	<i>P</i> value	IVUS180	<i>P</i> value
Patient 1 (9 slices)					
Average mean FSS	13.1 ± 1.7	12.3 ± 1.8	0.0117	12.6 ± 2.0	0.0313
Average max FSS	16.5 ± 2.7	15.0 ± 2.4	0.0039	15.3 ± 2.4	0.0039
Max of max FSS	20.4	18.4	—	18.6	—
Patient 2 (18 slices)					
Average mean FSS	37.7 ± 5.5	38.2 ± 5.9	0.5860	38.6 ± 5.8	0.1404
Average max FSS	42.7 ± 6.8	43.2 ± 5.2	0.4587	43.3 ± 5.1	0.3937
Max of max FSS	58.3	51	—	51.4	—
Patient 1 + Patient 2 (27 slices)					
Average mean FSS	29.5 ± 12.7	29.6 ± 13.4	0.6053	29.9 ± 13.4	0.6376
Average max FSS	34.0 ± 13.8	33.8 ± 14.3	0.7822	34.0 ± 14.1	0.9696
Max of max FSS	58.3	51	—	51.4	—

Fig. 8 Fluid maximum shear stress (FSS) distribution on lumen and cross section cuts showing differences from IVUS + OCT and IVUS50 models of patient 1. Bar plots of mean, maximum, and minimum cap FSS showing differences from IVUS + OCT, IVUS50, and IVUS180 models of two patients. Mean cap FSS and min cap FSS are average of cap values. Max cap FSS is max of max slice cap FSS values: (a) P1, IVUS + OCT model, FSS distribution on lumen, (b) P1, IVUS50 model, FSS distribution on lumen, (c) P1, IVUS + OCT model, FSS on cross sections (dyn/cm²), (d) P1, IVUS50 model, stress on cross sections (dyn/cm²), (e) P1, FSS, and (f) P2, FSS.

4.3 Patient Number and Study Size Limitation. Having data from only two patients is a limitation. This paper is a methodology paper proposing a modeling approach and demonstrating the impact of combining IVUS and OCT on cap thickness quantification and stress/strain calculations. We are demonstrating the

usefulness of the approach and the need for large-scale studies for potential clinical applications.

4.4 Modeling Limitations. There are so many factors that can affect model stress/strain predictions: image data resolution,

lack of flow conditions, pressure conditions, patient-specific material properties, location-specific and component-specific material properties, residual stress, cardiac motion, vessel shrinkage (longitudinal shrinkage can be 30–50% for healthy vessel), and others. However, modeling results with those limitations can still be used in clinical applications, because relative differences for patients from the same models are meaningful. We should continue to improve our technology and models for more accurate results as better data and modeling techniques become available.

Acknowledgment

Consultations and guidance from Professor Roger Kamm at MIT are happily acknowledged.

Disclosure

Tang, Yang, Zheng received support from NIH Grant No. R01 EB004759. Tang and Guo received support from Jiangsu Province Science and Technology Agency Grant No. BE2016785. There is no other conflict of interest to disclose.

Funding Data

- Jiangsu Province Science and Technology Agency (Grant No. BE2016785).
- National Institute of Biomedical Imaging and Bioengineering (NIH Grant No. R01 EB004759).

References

- [1] Gijzen, F. J. H., and Migliavacca, F., 2014, "Plaque Mechanics," *J. Biomech.*, **47**(4), pp. 763–764.
- [2] Holzapfel, G. A., Mulvihill, J. J., Cunnane, E. M., and Walsh, M. T., 2014, "Computational Approaches for Analyzing the Mechanics of Atherosclerotic Plaques: A Review," *J. Biomech.*, **47**(4), pp. 859–869.
- [3] Friedman, M. H., Krams, R., and Chandran, K. B., 2010, "Flow Interactions With Cells and Tissues: Cardiovascular Flows and Fluid-Structure Interactions," *Ann. Biomed. Eng.*, **38**(3), pp. 1178–1187.
- [4] Tang, D., Kamm, R. D., Yang, C., Zheng, J., Canton, G., and Bach, R. G., 2014, "Image-Based Modeling for Better Understanding and Assessment of Atherosclerotic Plaque Progression and Vulnerability: Data, Modeling, Validation, Uncertainty and Predictions," *J. Biomech.*, **47**(4), pp. 834–846.
- [5] Cardoso, L., and Weinbaum, S., 2014, "Changing Views of the Biomechanics of Vulnerable Plaque Rupture: A Review," *Ann. Biomed. Eng.*, **42**(2), pp. 415–431.
- [6] Mintz, G. S., Nissen, S. E., Anderson, W. D., Bailey, S. R., Erbel, R., Fitzgerald, P. J., Pinto, F. J., Rosenfield, K., Siegel, R. J., Tuzcu, E. M., and Yock, P. G., 2001, "American College of Cardiology Clinical Expert Consensus Document on Standards for Acquisition, Measurement and Reporting of Intravascular Ultrasound Studies (IVUS): A Report of the American College of Cardiology Task Force on Clinical Expert Consensus Documents," *J. Am. Coll. Cardiol.*, **37**(5), pp. 1478–1492.
- [7] Nair, A., Kuban, B. D., Tuzcu, E. M., Schoenhagen, P., Nissen, S. E., and Vince, D. G., 2002, "Coronary Plaque Classification With Intravascular Ultrasound Radiofrequency Data Analysis," *Circulation*, **106**(17), pp. 2200–2206.
- [8] Stone, G. W., Maehara, A., Lansky, A. J., de Bruyne, B., Cristea, E., Mintz, G. S., Mehran, R., McPherson, J., Farhat, N., Marso, S. P., Parise, H., Templin, B., White, R., Zhang, Z., and Serruys, P. W., 2011, "A Prospective Natural-History Study of Coronary Atherosclerosis," *N. Engl. J. Med.*, **364**(3), pp. 226–235.
- [9] Stone, P. H., Saito, S., Takahashi, S., Makita, Y., Nakamura, S., Kawasaki, T., Takahashi, A., Katsuki, T., Nakamura, S., Namiki, A., Hirohata, A., Matsuura, T., Yamazaki, S., Yokoi, H., Tanaka, S., Otsuji, S., Yoshimach, F., Honye, J., Harwood, D., Reitman, M., Coskun, A. U., Papafaklis, M. I., and Feldman, C. L., 2012, "Prediction of Progression of Coronary Artery Disease and Clinical Outcomes Using Vascular Profiling of Endothelial Shear Stress and Arterial Plaque Characteristics: The Prediction Study," *Circulation*, **126**(2), pp. 172–181.
- [10] Virmani, R., Kolodgie, F. D., Burke, A. P., Farb, A., and Schwartz, S. M., 2000, "Lessons From Sudden Coronary Death: A Comprehensive Morphological Classification Scheme for Atherosclerotic Lesions," *Arterioscler. Thromb. Vasc. Biol.*, **20**(5), pp. 1262–1275.
- [11] Virmani, R., Ladich, E. R., Burke, A. P., and Kolodgie, F. D., 2006, "Histopathology of Carotid Atherosclerotic Disease," *Neurosurgery*, **59**(5), p. S3-13.
- [12] Bourantas, C. V., Garcia-Garcia, H. M., Farooq, V., Maehara, A., Xu, K., Gnreux, P., Diletti, R., Muramatsu, T., Fahy, M., Weisz, G., Stone, G. W., and Serruys, P. W., 2013, "Clinical and Angiographic Characteristics of Patients Likely to Have Vulnerable Plaques: Analysis From the Prospect Study," *JACC: Cardiovasc. Imaging*, **6**(12), pp. 1263–1272.
- [13] Brown, A. J., Obaid, D. R., Costopoulos, C., Parker, R. A., Calvert, P. A., Teng, Z., Hoole, S. P., West, N. E., Goddard, M., and Bennett, M. R., 2015, "Direct Comparison of Virtual-Histology Intravascular Ultrasound and Optical Coherence Tomography Imaging for Identification of Thin-Cap Fibroatheroma," *Circ. Cardiovasc. Imaging*, **8**(10), p. e003487.
- [14] Maehara, A., Mintz, G. S., and Stone, G. W., 2013, "OCT Versus IVUS: Accuracy Versus Clinical Utility," *JACC: Cardiovasc. Imaging*, **6**(10), pp. 1105–1107.
- [15] Mintz, G. S., 2016, "Understanding Why and When Optical Coherence Tomography Does Not Detect Vulnerable Plaques—Is it Important?," *Circ. Cardiovasc. Interventions*, **9**(7), p. e004144.
- [16] Mintz, G. S., 2016, "Vulnerable Plaque Detection: When OCT is Not Enough," *JACC: Cardiovasc. Imaging*, **9**(2), pp. 173–175.
- [17] Tearney, G. J., Regar, E., Akasaka, T., Adriaenssens, T., Barlis, P., Bezerra, H. G., Bouma, B., Bruining, N., Cho, J. M., Chowdhary, S., and Costa, M. A., 2012, "Consensus Standards for Acquisition, Measurement, and Reporting of Intravascular Optical Coherence Tomography Studies: A Report From the International Working Group for Intravascular Optical Coherence Tomography Standardization and Validation," *J. Am. Coll. Cardiol.*, **59**(12), pp. 1058–1072.
- [18] Raber, L., Heo, J. H., Radu, M. D., Garcia-Garcia, H. M., Stefanini, G. G., Moschovitis, A., Dijkstra, J., Kelbaek, H., Windecker, S., and Serruys, P. W., 2012, "Offline Fusion of Co-Registered Intravascular Ultrasound and Frequency Domain Optical Coherence Tomography Images for the Analysis of Human Atherosclerotic Plaques," *EuroIntervention*, **8**(1), pp. 98–108.
- [19] Karanasos, A., Schuurbers, J. C., Garcia-Garcia, H. M., Simsek, C., Onuma, Y., Serruys, P. W., Zijlstra, F., van Geuns, R. J., Regar, E., and Wentzel, J. J., 2015, "Association of Wall Shear Stress With Long-Term Vascular Healing Response Following Bioresorbable Vascular Scaffold Implantation," *Int. J. Cardiol.*, **191**, pp. 279–283.
- [20] Bourantas, C. V., Jaffer, F. A., Gijzen, F. J., van Soest, G., Madden, S. P., Courtney, B. K., Fard, A. M., Tenekcioglu, E., Zeng, Y., van der Steen, A. F., and Emelianov, S., 2016, "Hybrid Intravascular Imaging: Recent Advances, Technical Considerations, and Current Applications in the Study of Plaque Pathophysiology," *Eur. Heart J.*, **38**(6), pp. 400–412.
- [21] Hung, O. Y., Molony, D., Corban, M. T., Rasoul-Arzrumly, E., Maynard, C., Eshtehardi, P., Dhawan, S., Timmins, L. H., Piccinelli, M., Ahn, S. G., and Gogas, B. D., 2016, "Comprehensive Assessment of Coronary Plaque Progression With Advanced Intravascular Imaging, Physiological Measures, and Wall Shear Stress: A Pilot Double-Blinded Randomized Controlled Clinical Trial of Nebivolol Versus Atenolol in Nonobstructive Coronary Artery Disease," *J. Am. Heart Assoc.*, **5**(1), p. e002764.
- [22] Samady, H., Eshtehardi, P., McDaniel, M. C., Suo, J., Dhawan, S. S., Maynard, C., Timmins, L. H., Quyyumi, A. A., and Giddens, D. P., 2011, "Coronary Artery Wall Shear Stress is Associated With Progression and Transformation of Atherosclerotic Plaque and Arterial Remodeling in Patients With Coronary Artery Disease," *Circulation*, **124**(7), pp. 779–788.
- [23] Yang, C., Bach, R., Zheng, J., Naqa, I. E., Woodard, P. K., Teng, Z., Billiri, K. L., and Tang, D., 2009, "In Vivo IVUS-Based 3D Fluid Structure Interaction Models With Cyclic Bending and Anisotropic Vessel Properties for Human Atherosclerotic Coronary Plaque Mechanical Analysis," *IEEE Trans. Biomed. Eng.*, **56**(10), pp. 2420–2428.
- [24] Molony, D. S., Timmins, L. H., Rasoul-Arzrumly, E., Samady, H., and Giddens, D. P., 2016, "Evaluation of a Framework for the Co-Registration of Intravascular Ultrasound and Optical Coherence Tomography Coronary Artery Pullbacks," *J. Biomech.*, **49**(16), pp. 4048–4056.
- [25] Wang, Z., Chamie, D., Bezerra, H. G., Yamamoto, H., Kanovsky, J., Wilson, D. L., Costa, M. A., and Rollins, A. M., 2012, "Volumetric Quantification of Fibrous Caps Using Intravascular Optical Coherence Tomography," *Biomed. Opt. Express*, **3**(6), pp. 1413–1426.
- [26] Wahle, A., Prause, G. P., von Birgelen, C., Erbel, R., and Sonka, M., 1999, "Fusion of Angiography and Intravascular Ultrasound In Vivo: Establishing the Absolute 3-D Frame Orientation," *IEEE Trans. Biomed. Eng.*, **46**(10), pp. 1176–1180.
- [27] Holzapfel, G. A., 2000, *Nonlinear Solid Mechanics: A Continuum Approach for Engineering*, Wiley, Chichester, UK.
- [28] Holzapfel, G. A., Gasser, T. C., and Ogden, R. W., 2000, "A New Constitutive Framework for Arterial Wall Mechanics and a Comparative Study of Material Models," *J. Elasticity*, **61**(1–3), pp. 1–48.
- [29] Guo, X., Zhu, J., Maehara, A., Molony, D., Samady, H., Wang, L., Billiri, K. L., Zheng, J., Yang, C., Mintz, G. S., Giddens, D. P., and Tang, D., 2016, "Quantify Patient-Specific Coronary Material Property and Its Impact on Stress/Strain Calculations Using In Vivo IVUS Data and 3D FSI Models: A Pilot Study," *Biomech. Model. Mechanobiol.*, **16**(1), pp. 333–344.
- [30] Walsh, M. T., Cunnane, E. M., Mulvihill, J. J., Akyildiz, A. C., Gijzen, F. J., and Holzapfel, G. A., 2014, "Uniaxial Tensile Testing Approaches for Characterization of Atherosclerotic Plaques," *J. Biomech.*, **47**(4), pp. 793–804.
- [31] Teng, Z., Zhang, Y., Huang, Y., Feng, J., Yuan, J., Lu, Q., Sutcliffe, M. P., Brown, A. J., Jing, Z., and Gillard, J. H., 2014, "Material Properties of

- Components in Human Carotid Atherosclerotic Plaques: A Uniaxial Extension Study,” [Acta Biomater.](#), **10**(12), pp. 5055–5063.
- [32] Wang, L., Zheng, J., Maehara, A., Yang, C., Billiar, K. L., Wu, Z., Bach, R., Muccigrosso, D., Mintz, G. S., and Tang, D., 2015, “Morphological and Stress Vulnerability Indices for Human Coronary Plaques and Their Correlations With Cap Thickness and Lipid Percent: An IVUS-Based Fluid-Structure Interaction Multi-Patient Study,” [PLoS Comput. Biol.](#), **11**(12), p. e1004652.
- [33] Teng, Z., Tang, D., Zheng, J., Woodard, P. K., and Hoffman, A. H., 2009, “An Experimental Study on the Ultimate Strength of the Adventitia and Media of Human Atherosclerotic Carotid Arteries in Circumferential and Axial Directions,” [J. Biomech.](#), **42**(15), pp. 2535–2539.
- [34] Mintz, G. S., 2015, “Optical Coherence Tomography and Virtual-Histology Intravascular Ultrasound Strange Bedfellows?... or Not?,” [Circ. Cardiovasc. Imaging](#), **8**(10), p. e004045.