Published in final edited form as:

Neural Comput. 2017 June ; 29(6): 1441–1467. doi:10.1162/NECO_a_00955.

A unified theory of neuro-MRI data shows scale-free nature of connectivity modes

Vitaly L. Galinsky^{1,4} and Lawrence R. Frank^{1,2,3}

¹Center for Scientific Computation in Imaging, University of California at San Diego, La Jolla, CA 92093-0854, USA

²Department of Radiology, University of California at San Diego, La Jolla, CA 92093-0854, USA

³VA San Diego Healthcare System, San Diego, CA 92161, USA

⁴Electrical and Computer Engineering Department, University of California at San Diego, La Jolla, CA 92093-0407, USA

Abstract

A primary goal of many neuroimaging studies that utilize magnetic resonance imaging (MRI) is to deduce the structure-function relationships in the human brain using data from the three major neuro-MRI modalities: high resolution anatomical, diffusion tensor imaging, and functional MRI. To date, the general procedure for analyzing these data is to combine the results derived *independently* from each of these modalities.

In this paper we develop a new theoretical and computational approach for combining these different MRI modalities into powerful and versatile framework that combines our recently developed methods for morphological shape analysis and segmentation, for simultaneous local diffusion estimation and global tractography, and for non-linear and non-Gaussian spatial-temporal activation pattern classification and ranking, as well as our fast and accurate approach for non-linear registration between modalities. This joint analysis method is capable of extracting new levels of information that is not achievable from any of those single modalities along. A theoretical probabilistic framework based on a reformulation of prior information and available interdependencies between modalities through a joint coupling matrix and an efficient computational implementation allow construction of quantitative functional, structural and effective brain connectivity modes and parcellation.

This new method provides an overall increase of resolution, accuracy, level of detail and information content and has the potential to be instrumental in the clinical adaptation of neuro-MRI modalities, which when jointly analyzed provides a more comprehensive view of a subjects structure-function relations, while the currently standard wherein single modality methods are analyzed separately leaves a critical gap in an integrated view of a subjects neuropsychological state. As one example of this increased sensitivity, we demonstrate that the jointly estimated structural and functional dependencies of mode power follow the same power law decay with the same exponent.

Keywords

Magnetic Resonance Imaging; Diffusion MRI; Resting state FMRI; Brain Connectivity

1 Introduction

One of the great scientific questions that modern imaging systems are increasingly capable of addressing is the structure-function relationships in the human brain. Magnetic resonance imaging (**MRI**), in particular, provides a unique methodology for non-invasively acquiring high spatial resolution anatomical data (**HRA**) that are capable of characterizing morphological variations in exquisite detail, diffusion tensor imaging (**DTI**) that enables the construction of neural pathways, and functional MRI (**fMRI**), and in particular resting state functional MRI (**rsfMRI**), which can detect spatial-temporal changes in brain activity.

The general idea behind characterizing structure-function relationships is to relate quantitative measures of structural features of a system with the spatiotemporal patterns of parameters changes. For example, in neuroimaging using MRI (neuro-MRI) the goal is to characterize the relationship between brain morphology, neural pathways, and brain activity by combining morphological information from HRA data, structural connectivity from DTI data, and functional connectivity from rsfMRI.

The most common approach to the analysis of neuro-MRI data is to estimate morphology, connectivity, and spatio-temporal variations separately *first*, then combine them to characterize system “modes”. This is, for the most part, simply a practical matter: different methods are used for each analysis and so are applied separately. For example, in studies of structure-function relationships in the human brain Deco et al. (2009, 2011, 2014) uses an empirical structural connectivity (SC) matrix derived from diffusion spectrum imaging (DSI, an extension of DTI) (Wedeen et al., 2005) and tractography (Hagmann et al., 2008) and an empirical functional connectivity (FC) matrix based on Honey et al. (2007, 2009a). Honey et al. (2009a) constructs FC maps based on Pearson correlation between BOLD time series (a correlation analysis.) The correlation analysis is also used in Dosenbach et al. (2007). Cammoun et al. (2012) uses a similar analysis using DSI at multiple scales, while Zalesky et al. (2014) uses a time-resolved analysis using simple correlation analysis with sliding windows.

However, the great potential of these methods is compromised because of three significant limitations in current state-of-the-art analysis approaches. First, they are, for the most part, not quantitative, and, as a consequence, often are not sufficiently accurate: 1) Quantitation of morphology from HRA is typically limited to surfaces and is highly error prone; 2) Existing DTI analysis methods are incapable of accurately characterizing voxels containing multiple fibers, leading to highly inaccurate estimation of both local anisotropy and global tractography; 3) Resting state rsfMRI analysis methods are essentially ad-hoc and have no well characterized definition of a “brain mode”, much less a computational approach amenable to the ranking of modes and the assessment of error estimates. Second, the data from each method are analyzed independently of one another, ignoring the inherent constraints that couple anatomy, connectivity, and function. Third, these methods (DTI and fMRI in particular) are poorly posed inverse problems with a wide range of possible “solutions” to any single estimate, some of which are non-physical. Current analysis methods rarely incorporate constraints that require solutions to be physically realizable.

In this paper we address all three of these deficiencies by developing a general theoretical and computational framework for the analysis of neuro-MRI data based on the reformulation of the problem in terms of our recently developed entropy field decomposition (**EFD**) method (Frank & Galinsky, 2016), which combines information field theory (**IFT**) (Enßlin et al., 2009), with prior information encoded on spatial-temporal patterns using our recently introduced method of entropy spectrum pathways (**ESP**) (Frank & Galinsky, 2014). The EFD method is a probabilistic approach that provides a general framework for the integration of HRA, DTI, and fMRI analysis, including results provided by numerical simulations (Baxter & Frank, 2013; Balls & Frank, 2009) to constrain results to those that are physically realistic. We will employ our recently developed methods for each of the three modalities; 1) The spherical wave decomposition (**SWD**) method for shape analysis and segmentation (Galinsky & Frank, 2014); 2) The geometrical optics based ESP method for simultaneous estimation of local diffusion and global tractography (**GO-ESP**) (Galinsky & Frank, 2015); 3) The characterization and estimation of space-time rsfMRI brain activation patterns using EFD (Frank & Galinsky, 2016). The spatial collocation of all these different modalities is provided by using a novel non-linear registration method based on a general symplectomorphic formulation that construct flexible grid mapping between modalities regularized by ESP coupling (**SYMREG-ESP**) (Galinsky & Frank, 2016b). We then demonstrate how these three analysis methods can be fused together and be mutually informative within the overarching theory of EFD allowing us to construct more quantitative estimates of brain structural and functional modes.

With the constantly increasing quality of data from neuroimaging methods using MRI (**neuro-MRI**), such as high resolution anatomical imaging (**HRA**), diffusion tensor imaging (**DTI**), and resting state functional MRI (**rsfMRI**), there is a significant and growing interest in the development of frameworks that can perform multimodal data fusion and analysis of these different modalities. Several methods have recently developed that are based on some modification or ad-hoc augmentation of independent component analysis (ICA) approach (Bell & Sejnowski, 1995; Hyvarinen & Oja, 2000) including (Groves et al., 2011; Douaud et al., 2014; Mueller et al., 2013), or the Joint/Parallel ICA approaches (see the review of Calhoun et al. (2009)). However the performance and applicability of ICA even for a single modality (rsfMRI) analyses is predicated on a number of assumptions, such as sparsity and independence that are questionable and have been debated (Daubechies et al., 2009; Calhoun et al., 2013). More practically, and importantly, it has been shown that the ICA approach can be shown to fail in the simplest of idealized simulations (Calhoun et al., 2013; Frank & Galinsky, 2016). This motivated our development of the EFD approach which was demonstrably more accurate than ICA in its application to rsfMRI data (Frank & Galinsky, 2016).

In our original work (Frank & Galinsky, 2016) we emphasized that the EFD formulation was very general, being based on a Bayesian formulation of field theory that facilitated the incorporation of whatever prior information might be available for the problem at hand. The novel feature of the EFD approach is its use of the ESP method to derive the optimal (in the maximum entropy sense) parameter configurations when the space-time coupling structure of the data is used as that prior information. For multi-modality data, the EFD method can

be generalized by incorporating the coupling structures not only within the data, but *between* modalities. Here we demonstrate this capability using the three major neuro-MRI modalities: HRA, DTI, and rsfMRI. Our results demonstrate an increased resolution and specificity of both structural and functional networks in the brain. This analysis allows us to uncover a scale-free organization of brain structural and functional networks that follow virtually identical power laws.

2 Theory

The EFD method developed for detection and analyses of non-linear and non-Gaussian modes and patterns present in heterogeneous datasets is well suited to the problem of multi-modal connectivity estimation. The cornerstone of EFD estimation procedure is the construction of local connectivity (including spatial connectivity, temporal connectivity, or both) present in the analyzed dataset. The extension of the EFD approach to the joint processing of multi-modal datasets requires a reformulation that combines and fuses these local connectivity patterns into a common coupling matrix. The quantitative EFD procedure can then be applied to this joint intermodality coupling matrix thus allowing the detection and ranking of the connectivity present in those individual datasets, particularly emphasizing datasets with significant inter-modal similarities.

2.1 Overview of EFD

The main purpose of data analysis in general is to estimate unknown quantities s from the data d using available priors I . The data d may include complex spatiotemporal dependencies, e.g. it may be a single value (intensity) recorded for every spatial location (HRA image), a multiple value vector or tensor field data (DTI image), or a time sequence of values (fMRI image). Hence any single point in d is a spatio-temporal point, that is, a location in space-time. From Bayes theorem the posteriori distribution for any of the unknowns can be expressed as

$$\underbrace{p(s | d, I)}_{\text{Posterior}} = \frac{\overbrace{p(d, s | I)}^{\text{Joint probability}}}{\underbrace{p(d | I)}_{\text{Evidence}}} = \frac{\overbrace{p(d | s, I)}^{\text{Likelihood}} \overbrace{p(s | I)}^{\text{Prior}}}{p(d | I)} \quad (1a)$$

$$p(d | I) = \int ds p(d, s | I) \quad (1b)$$

The IFT (Enßlin et al., 2009) uses the formalism of field theory and expresses the terms in Eqn 1a using an information Hamiltonian $H(d, s)$ as

$$H(d, s) = - \ln p(d, s | I) \quad \text{Hamiltonian} \quad (2a)$$

$$p(d | I) = \int ds e^{H(d,s)} = Z(d) \quad \text{Partition function} \quad (2b)$$

so that the posterior distribution Eqn 1a becomes

$$p(s | d, I) = \frac{e^{-H(d,s)}}{Z(d)} \quad (3a)$$

The EFD approach introduces a so called coupling matrix that characterizes the relation between locations i and j in the data $Q_{ij} = \exp\{-\gamma_{ij}\}$. The coupling matrix is used to incorporate data dependencies present in the information Hamiltonian $H(d, s)$ in a convenient and concise form appropriate for the analysis of nonlinear and non-Gaussian signals. The details of the mathematical formulation of EFD that uses these expressions are summarized in Appendix A.

2.2 The coupling matrix for multiple modalities

Constructing either linear or nonlinear solutions for the unknown signal s requires an explicit generation of either the coupling matrix Q itself or the coupling coefficients γ . Using single modality datasets as a source of coupling allows the generation of powerful and effective single modality data analysis approaches, i.e. the coupling matrix obtained from the diffusion weighted imaging data produced an accurate and effective way for simultaneous estimation of local diffusion and global tractography with the geometrical optics based GO-ESP method. Similarly, the coupling matrix based on the correlation properties of time series from rsfMRI datasets resulted in accurate and effective characterization and estimation of space-time rsfMRI brain activation patterns.

However, the generality of the EFD formalism provides a natural mechanism for even more complex and comprehensive analysis by incorporating data from different modalities into the coupling matrix. Assuming that instead of a single dataset d we now have $m = 1, \dots, M$ different modalities $d^{(m)}$ with the coupling matrices $Q^{(m)}$ that all correspond to the same unknown signal s , we then can construct an intermodality coupling matrix as the product of these coupling matrices for the individual modalities expressed in the ESP basis and registered to a common reference frame, which we denote $\tilde{Q}^{(m)}$. That is, the joint coupling matrix is $\mathcal{Q}^{(m)} = \Pi_m \tilde{Q}^{(m)}$. More specifically, the joint coupling matrix $\mathcal{Q}_{ij}$ between any two space-time locations (i, j) can be written in the general (equivalent) form as

$$\ln \mathcal{Q}_{ij} = \sum_{m=1}^M \beta_{ij}^{(m)} \ln \tilde{Q}_{ij}^{(m)} \quad (4)$$

where the exponents $\beta^{(m)}$ can either be some constants or functions of data collected for different modalities

$$\beta_{ij}^{(m)} \equiv \beta^{(m)}(\tilde{d}_i, \tilde{d}_j), \quad \tilde{d}_i \equiv \{\tilde{d}_i^{(1)}, \dots, \tilde{d}_i^{(M)}\} \quad (5)$$

$\tilde{d}_i^{(m)}$ and $\tilde{Q}_{ij}^{(m)}$ represent, respectively, the data and the coupling matrix of the modality dataset m represented in the ESP basis and evaluated at locations r_i and r_j of a common reference domain R :

$$\tilde{d}_i^{(m)} = d^{(m)}(\psi^{(m)}(r_i)), \quad \tilde{Q}_{ij}^{(m)} = Q^{(m)}(\psi^{(m)}(r_i), \psi^{(m)}(r_j)) \quad (6)$$

where $\psi^{(m)}: R \rightarrow X$ denotes a diffeomorphic mapping of m -th modality from the reference domain R to an acquisition space X .

This construction of the intermodality coupling involves several simple assumptions. Two neighboring voxels i and j are considered to be highly coupled if i) their structural image intensities are similar, ii) their diffusion-weighted spin density functions (Eqn 8 in (Galinsky & Frank, 2015)) point to each other and iii) their resting state fMRI signals are maximally correlated across all frequencies. The mathematical details that incorporate and formalize these assumptions into coupling matrix expressions are given in Appendix B.

2.3 The structural, functional and effective connectivity eigenmodes

The intermodality coupling matrix $\tilde{Q}_{ij}$ facilitates the development of a unified description of brain connectivity that includes both the structural dependencies (derived from long range DWI connectivity and HRA morphology) and the functional correlations (based on activation modes buried within the functional MRI data).

One particularly informative way in which the intermodality coupling matrix $\tilde{Q}_{ij}$ can be used is to generate the effective streamlines that characterize both structural and functional dependencies present in the data by combining the correlation function for the functional signal with the structural information from the spin density function, expressing the joint functional-structural dependencies through effective transition probabilities (Eqn 13). This is the same procedure that was used to generate fiber tracts from DTI data in the original GO-ESP method and subsequently used to perform functional tractography using the EFD method but now extended and generalized to a multi-modal coupling matrix. The resulting streamlines therefore represent high-probability pathways in the joint structural-functional space.

A set $L = \{l^n\}$, $n = 1 \dots N$ of effective multi-modality streamlines can be used to generate a new coupling matrix that includes connections between distant voxels. Assuming that each streamline l^n is a vector such that

$$l_i^{(n)} = \begin{cases} 1 & \text{voxel } i \text{ belongs to the streamline } l^{(n)} \\ 0 & \text{voxel } i \text{ does not belong to the streamline } l^{(n)} \end{cases} \quad (7)$$

then we can define the *eigenmode coupling matrix*

$$\mathbf{Q}^e = \sum_{n=1}^N \mathbf{l}^{(n)T} \mathbf{l}^{(n)} - N \mathbf{1} \quad (8)$$

Finding the eigenvalues and eigenvectors of the $\mathbf{Q}^e$ matrix gives us ranked connectivity eigenmodes.

3 Implementation

The multi-modal joint estimation scheme described above is very general. Here we present one particular application of the method: a typical single subject neuro-MRI study with HRA, DWI and rsfMRI datasets acquired. We emphasize that this is but one specific instantiation of the method as additional modalities can be easily added into the processing. All elements of the processing were coded in standard C/C++ and parallelized using POSIX threads. An illustrative workflow scheme is shown in Figure 1 and can be described as follows:

- The processing workflow starts with HRA dataset. First it extracts the brain, doing skull stripping, and then generates the SWD for the brain volume to be used in volume segmentation and registration later.
- For the DWI dataset the GO-ESP procedure is used that generate a new data volume of the equilibrium probabilities (EP) data
- For the rsfMRI dataset the EFD procedure is used to generate a new data volume of the mean field data (that is a volume that contains averages of all activations), removing both temporal and spatial outliers.
- The DWI equilibrium probabilities and the rsfMRI mean field volumes are then registered with the HRA brain volume using the symplectomorphic registration SYMREG-ESP providing forward and inverse maps.
- The symplectomorphic maps together with the HRA SWD volume are then included into GO-ESP global tractography to generate high resolution very high density fiber tracts with a possibility of more than twofold improvement of the DWI spatial resolution and potentially resolving crossing fibers at below 10° angular resolution reported in Galinsky & Frank (2016a).
- The high resolution very high density fiber tracts distribution is used to generate ESP long range structural connectivity eigenmodes.

- The symplectomorphic maps together with the HRA SWD volume and the long range structural connectivity eigenmodes are used in rsfMRI EFD processing, providing a greater improvement in resolved details of rsfMRI activation modes than is possible without the information provided by the other modalities by generating high resolution effective connectivity eigenmodes. A fusion of structural and functional coupling provide an important advantage of those high resolution effective connectivity eigenmodes over single modality fMRI activation modes – the effective eigenmodes include both WM and GM regions in a way consistent with both structural and functional dependencies.

Additional modalities can easily be incorporated into this workflow.

4 Results

4.1 Data

To test our approach we used one of the publicly accessible datasets available from the open source Human Connectome Project (Van Essen et al., 2013, 2012; Sotiropoulos et al., 2013), as well as several diffusion imaging datasets collected locally at the UCSD Center for Functional MRI (CFMRI).

The HCP dataset was collected on the customized Siemens 3T Connectom scanner, which is a modified 3T Skyra system (MAGNETOM Skyra Siemens Healthcare), housed at the MGH/HST Athinoula A. Martinos Center for Biomedical Imaging (see Setsompop et al. (2013) for details of the scanner design and implementation). A 64-channel, tight-fitting brain array coil (Keil et al., 2013) was used for data acquisition. The dataset contains 96 slices of 140×140 matrix (1.5 mm linear voxel size) at four levels of diffusion sensitizations (b-values b=1k, 3k, 5k and 10k s/mm²) distributed over 552 total q-vectors.

The CFMRI data were acquired with a 3T GE Discovery MR750 whole body system. The anatomical T1 volumes have 168×256×256 voxel size with 1.2×0.9375 ×0.9375mm³ resolution.

A multiband DTI EPI acquisition (Setsompop et al., 2011) developed at the CFMRI employed three simultaneous slice excitations to acquire data with three diffusion sensitizations (at b-values b=1000/2000/3000 s/mm²) for 30, 45 and 65 different diffusion gradients (respectively) uniformly distributed over a unit sphere. Several baseline (b=0) images were also recorded. The data were reconstructed offline using the CFMRI's multiband reconstruction routines. The DWI datasets have 100×100×72 matrix size with 2×2×2mm³ resolution. Whole brain BOLD resting-state data were acquired over thirty axial slices using an echo planar imaging (EPI) sequence (flip angle = 70°, slice thickness=4mm, slice gap=1mm, FOV=24cm, TE= 30 ms, TR = 1.8 s, matrix size = 64 × 64 × 30). Further details are available in Wong et al. (2013). All data were pre-processed using the standard pre-processing analysis pathway at the CFMRI (as described in Wong et al. (2013)). Nuisance terms were removed from the resting-state BOLD time series through multiple linear regression. These nuisance regressors included: i) linear and quadratic trends, ii) six motion parameters estimated during image coregistration and their first derivatives, iii)

RETROICOR (2nd order Fourier series) (Glover et al., 2000) and RVHRCOR (Chang & Glover, 2009) physiological noise terms calculated from the cardiac and respiratory signals, and iv) the mean BOLD signals calculated from white matter and CSF regions and their first respective derivatives, where these regions were defined using partial volume thresholds of 0.99 for each tissue type and morphological erosion of two voxels in each direction to minimize partial voluming with gray matter.

4.2 Joint DWI and HRA tractography

The data for every subject with T1 HRA, DWI and rsfMRI datasets was analyzed twice, first using independent processing of each modality, and then using the joint modality approach developed in this paper. The addition of HRA coupling into the diffusion estimation and tractography process not only provides a significant boost to the overall level of detail that can be captured but, more importantly, shows features that are not apparent when the modalities are analyzed independently. Figure 2 shows details of the equilibrium probability map obtained from a single modality DWI dataset using several different views in panel (a) and compares them with the same views of the map produced from the joint HRA+DWI coupling matrix in panel (b). The jointly estimated maps clearly show improvements in image quality – the two fold increase in linear image resolution provides more small scale detail and greater noise suppression. The localization of white matter fiber bundles is clearly enhanced significantly in the jointly estimated maps.

These joint estimation improvements can also be seen in tractography results, shown in Figure 3. The unified DWI-HRA estimation procedure is again able to detect additional details in overall fiber tract distribution compared to the DWI procedure performed independently as well as providing increased resolution of the tracts.

This improvement is even more pronounced if one constructs a volume generated from the trac counts in every voxel produced by GO-ESP whole brain tractography (as shown in Figure 4). Both the HCP and CFMRI sets of tracs were produced using 5,000,000 seeds. The joint DWI+HRA processing clearly provides significantly enhanced level of details, allowing reconstruction of subtle white and gray matter high-resolution spatial variations, while at the same time significantly increasing the directional information available from diffusion data.

4.3 Joint structural, functional and effective eigenmodes

Using joint connectivity matrices allows us to generate eigenmodes that can be instrumental in finding and understanding the most important structural and functional dependency patterns present in the underlying data and can help to uncover and quantitatively characterize an effective information exchange that happens on different scales of the brain and modulates the overall brain performance.

Figure 5 shows several structural connectivity eigenmodes that were produced by running DWI+HRA GO-ESP tractography and using streamlines to generate the eigenmode (or streamline) coupling matrix that includes connections between distant voxels (Eqn 8). Because the streamline coupling matrix contains the number of connections between every

pair of voxels located both inside the white or gray matter of the brain and on the cortical surface, it provides volumetric probability weighted connectivity that is significantly more informative than binary on-off connectivity typically generated for cortical regions. Furthermore, because the seeding for GO-ESP tractography uses equilibrium and transitional probabilities to sample spatial and angular distributions of tracts, it ensures the consistency with both the diffusion and anatomical data volumes that were acquired. The eigenmodes of the streamline coupling matrix can be viewed as interconnected regions of a brain that are only loosely connected with other regions. The structure of these eigenmodes includes multiple modality constraints, hence, can provide a more comprehensive description and ranking of the connectivity patterns reflecting the input from multiple modalities.

Selected functional nonlinear EFD eigenmodes obtained using FMRI + HRA connectivity matrix are shown in Figure 6 (b). Those modes are similar to EFD modes generated solely from rsFMRI data shown in Figure 6 (a) and reported in Frank & Galinsky (2016) but have more details and show better overall spatial resolution due to the addition of high resolution anatomical details in FMRI EFD coupling.

Combining DWI, FMRI and HRA dataset through the joint coupling matrix Eqn 4 produces effective connectivity eigenmodes Figure 6(c) that spread through the entire brain volume, covering both gray and white matter areas, hence complimenting cortical activation regions available from FMRI with white matter structural pathways available from diffusion data.

We would like to emphasize that in contrast to functional modes estimated from single modality rsFMRI processing where the signal reflects BOLD activity happening mostly in the gray matter regions, the effective connectivity modes generated by multiple modalities incorporate not only gray matter regions, but may also include white matter as well. This does *not* mean that our joint modality processing detects BOLD activity in the white matter. The extension of the modes into the WM is a manifestation of the fact that both functional and structural connectivity are related to a common origin – the brain neural structure – and often functional and structural dependences may be deduced (although with limited degree of accuracy and reliability) one from the other (Skudlarski et al., 2008; Honey et al., 2009b).

The common underlying nature of both structural and functional modes can be clearly seen when plotting mode power (or eigenvalue) as a function of mode number as shown in Figure 7. The plot shown includes 200 structural eigenmodes and 180 functional EFD modes obtained from DWI+HRA and FMRI+HRA coupling matrices. Both structural and functional dependencies show power law decay with the same exponent that is close to -1.2 . This type of power law dependence can typically be associated with a manifestation of scale-free organization of brain networks (Beggs & Timme, 2012).

The effective connectivity eigenmodes provide a simple and efficient way to construct a whole brain volumetric parcellation by assigning each voxel to a mode that has the largest contribution to this voxel. Two parcellation examples are shown in Figures 8 and 9. Figure 8 uses for analysis locally (UCSD CFMRI) acquired datasets and Figure 9 is based on the publicly available HCP data volumes. Both figures were produced by generating high

resolution volumes (with the same resolutions as the correspondent HRA volumes, i.e. $168 \times 256 \times 256$ for Figure 8 and $176 \times 256 \times 176$ for Figure 9) that contain in each voxel the number of streamlines going through this voxel. The high resolution volumes were used to extract the shapes shown in figures using different thresholds. The parcellation is constructed from the high resolution effective connectivity eigenmodes.

5 Conclusion

In this paper we presented a new theory for the joint estimation of the structural-functional brain modes that we have applied to the three primary neuro-MRI modalities - high resolution anatomical (HRA) data, diffusion tensor imaging (DTI) data, and resting state functional MRI (rsfMRI) data. The approach is rooted in our previous theoretical formulations of the SWD, GO-ESP, and EFD methods, which utilize our general theory of Entropy Spectrum Pathways (ESP) (Frank & Galinsky, 2014), whose central concept is that relationships between local and global aspects of a lattice (e.g., a 3D image or a 4D time dependent image) are characterized by the relationship, or *coupling*, between local elements (i.e. voxels). The SWD is a straightforward characterization of the intensity variations in HRA image volume in terms of a spherical wave decomposition (Galinsky & Frank, 2014). The GO-ESP technique uses the SWD to characterize the diffusion signal in each voxel from DWI acquisitions wherein a region of q -space is sampled (Galinsky & Frank, 2015). These local (i.e. voxel) diffusion profiles are then used to construct couple matrices that, through the ESP theory, provide optimal spatial pathways that can be used to drive the geometric optics based tractography. In the EFD method for fMRI, spatial-temporal coupling matrices from the 4D data are used to generate optimal space-time paths from which brain networks are constructed (Frank & Galinsky, 2016). In this paper we have developed a general theory of structural-functional brain modes that integrates these methods through a generalization of the coupling structure of the data to incorporate the different modalities, and then by modifying the individual algorithms to incorporate the coupling between modalities.

Our computational implementation demonstrates a significant improvement of mode reconstruction accuracy and an appearance of new levels of detail. The fiber pathway reconstruction of joint modality processing offers of a more than twofold improvement of the DWI spatial resolution and the ability to resolve crossing fibers at or below 10° angular resolution (Galinsky & Frank, 2016a). The resting state brain network modes, eigenmodes, and tractography generated provide more than four times the improvement in spatial resolution. Moreover, this joint estimation procedure allowed us to demonstrate the novel finding of a scale-free organization of brain structural and functional networks that follow virtually identical power laws. Further exploration of this finding may help to uncover important structure-function relations in human brain development.

In addition to providing an overall increase in resolution, accuracy, level of detail and information content that can provide valuable insight into structure-function relations of interest in basic neuroimaging studies, this method also holds the potential to enhance the clinical utility of these individual neuro-MRI methods. The current procedure of analyzing these data separately poses a significant challenge for practicing clinicians faced with the task of visually integrating the information from these complex image acquisitions. This new

method provides a robust and accurate method for integrating these data to provide a more accurate assessment of brain structure and function that is nonetheless amenable to clear visualization and statistical assessment via non-linear registration that are critical to the development of viable clinical protocols.

Acknowledgments

LRF and VLG were supported by NSF grants DBI-1143389, DBI-1147260, EF-0850369, PHY-1201238 and NIH grant R01 MH096100. The authors thank Dr Alec Wong and Dr Tom Liu at the UCSD CFMRI and Dr Scott Sorg at the VA San Diego Health Care System for providing the diffusion weighted and the resting state imaging data. Data were provided [in part] by the Human Connectome Project, WU-Minn Consortium (Principal Investigators: David Van Essen and Kamil Ugurbil; 1U54MH091657) funded by the 16 NIH Institutes and Centers that support the NIH Blueprint for Neuroscience Research; and by the McDonnell Center for Systems Neuroscience at Washington University. Data collection and sharing for this project was provided by the Human Connectome Project (HCP; Principal Investigators: Bruce Rosen, M.D., Ph.D., Arthur W. Toga, Ph.D., Van J. Weeden, MD). HCP funding was provided by the National Institute of Dental and Craniofacial Research (NIDCR), the National Institute of Mental Health (NIMH), and the National Institute of Neurological Disorders and Stroke (NINDS). HCP data are disseminated by the Laboratory of Neuro Imaging at the University of Southern California.

References

- Balls GT, Frank LR. A simulation environment for diffusion weighted MR experiments in complex media. *Magn Reson Med*. 2009; 62(3):771–778. [PubMed: 19488991]
- Baxter GT, Frank LR. A computational model for diffusion weighted imaging of myelinated white matter. *NeuroImage*. 2013 Jul; 75(C):204–212. [PubMed: 23507381]
- Beggs J, Timme N. Being critical of criticality in the brain. *Frontiers in Physiology*. 2012; 3:163. Retrieved from <http://journal.frontiersin.org/article/10.3389/fphys.2012.00163>. doi: 10.3389/fphys.2012.00163 [PubMed: 22701101]
- Bell A, Sejnowski T. An information maximization approach to blind separation and blind deconvolution. *Neural Comput*. 1995 Nov; 7(6):1129–1159. [PubMed: 7584893]
- Burda Z, Duda J, Luck J, Waclaw B. Localization of the maximal entropy random walk. *Phys Rev Lett*. 2009; 102(16):160602. [PubMed: 19518691]
- Calhoun VD, Liu J, Adali T. A review of group ICA for fMRI data and ICA for joint inference of imaging, genetic, and ERP data. *Neuroimage*. 2009 Mar; 45(1 Suppl):S163–172. [PubMed: 19059344]
- Calhoun VD, Potluru VK, Phlypo R, Silva RF, Pearlmutter BA, Caprihan A, ... Adali T. Independent component analysis for brain FMRI does indeed select for maximal independence. *PLoS ONE*. 2013; 8(8):1–8.
- Cammoun L, Gigandet X, Meskaldji D, Thiran JP, Sporns O, Do KQ, ... Hagmann P. Mapping the human connectome at multiple scales with diffusion spectrum MRI. *Journal of Neuroscience Methods*. 2012 Jan; 203(2):386–397. [PubMed: 22001222]
- Chang C, Glover GH. Effects of model-based physiological noise correction on default mode network anti-correlations and correlations. *Neuroimage*. 2009 Oct; 47(4):1448–1459. [PubMed: 19446646]
- Daubechies I, Roussos E, Takerkart S, Benharrosh M, Golden C, D'Ardenne K, ... Haxby J. Independent component analysis for brain fMRI does not select for independence. *P Natl Acad Sci USA*. 2009 Jun; 106(26):10415–10422.
- Deco G, Jirsa V, McIntosh AR, Sporns O, Kötter R. Key role of coupling, delay, and noise in resting brain fluctuations. *Proceedings of the National Academy of Sciences of the United States of America*. 2009 Jun; 106(25):10302–10307. [PubMed: 19497858]
- Deco G, Jirsa VK, McIntosh AR. Emerging concepts for the dynamical organization of resting-state activity in the brain. *Nature Reviews Neuroscience*. 2011 Jan; 12(1):43–56. [PubMed: 21170073]
- Deco G, McIntosh AR, Shen K, Hutchison RM, Menon RS, Everling S, Jirsa VK. Identification of Optimal Structural Connectivity Using Functional Connectivity and Neural Modeling. *The Journal of Neuroscience*. 2014 Jun; 34(23):7910–7916. [PubMed: 24899713]

- Dosenbach NUF, Fair DA, Miezin FM, Cohen AL, Wenger KK, Dosenbach RAT, ... Petersen SE. Distinct brain networks for adaptive and stable task control in humans. *Proceedings of the National Academy of Sciences of the United States of America*. 2007 Jun; 104(26):11073–11078. [PubMed: 17576922]
- Douaud G, Groves AR, Tamnes CK, Westlye LT, Duff EP, Engvig A, ... Johansen-Berg H. A common brain network links development, aging, and vulnerability to disease. *Proc Natl Acad Sci USA*. 2014 Dec; 111(49):17648–17653. [PubMed: 25422429]
- Enßlin TA, Frommert M, Kitaura FS. Information field theory for cosmological perturbation reconstruction and nonlinear signal analysis. *Phys Rev D*. 2009 Nov.80(10):105005.
- Feynman RP. Space-Time Approach to Quantum Electrodynamics. *Physical Review*. 1949; 76(6):769–789.
- Frank LR, Galinsky VL. Information pathways in a disordered lattice. *Phys Rev E*. 2014 Mar. 89:032142. Retrieved from <http://link.aps.org/doi/10.1103/PhysRevE.89.032142>. doi: 10.1103/PhysRevE.89.032142
- Frank LR, Galinsky VL. Detecting spatio-temporal modes in multivariate data by entropy field decomposition. *Journal of Physics A Mathematical General*. 2016 Sep.49:395001.doi: 10.1088/1751-8113/49/39/395001
- Frank LR, Galinsky VL. Dynamic Multiscale Modes of Resting State Brain Activity Detected by Entropy Field Decomposition. *Neural Comput*. 2016 Sep; 28(9):1769–1811. [PubMed: 27391678]
- Galinsky VL, Frank LR. Automated Segmentation and Shape Characterization of Volumetric Data. *NeuroImage*. 2014 May.92:156–168. Retrieved from <http://www.sciencedirect.com/science/article/pii/S1053811914000834> doi:<http://dx.doi.org/10.1016/j.neuroimage.2014.01.053>. [PubMed: 24521852]
- Galinsky VL, Frank LR. Simultaneous multi-scale diffusion estimation and tractography guided by entropy spectrum pathways. *IEEE Trans Med Imaging*. 2015 May; 34(5):1177–1193. [PubMed: 25532167]
- Galinsky VL, Frank LR. The Lamellar Structure of the Brain Fiber Pathways. *Neural Computation*. 2016a; 28:1–24. [PubMed: 26599715]
- Galinsky VL, Frank LR. Symplectomorphic registration with phase space regularization by entropy spectrum pathways. *Med Imag Analysis*. 2016b (submitted).
- Glover GH, Li TQ, Ress D. Image-based method for retrospective correction of physiological motion effects in fMRI: RETROICOR. *Magn Reson Med*. 2000 Jul; 44(1):162–167. [PubMed: 10893535]
- Groves AR, Beckmann CF, Smith SM, Woolrich MW. Linked independent component analysis for multimodal data fusion. *Neuroimage*. 2011 Feb; 54(3):2198–2217. [PubMed: 20932919]
- Hagmann P, Cammoun L, Gigandet X, Meuli R, Honey CJ, Wedeen VJ, Sporns O. Mapping the Structural Core of Human Cerebral Cortex. *PLoS Biology*. 2008; 6(7):e159. [PubMed: 18597554]
- Honey CJ, Kotter R, Breakspear M, Sporns O. Network structure of cerebral cortex shapes functional connectivity on multiple time scales. *Proceedings of the National Academy of Sciences*. 2007 Jun; 104(24):10240–10245.
- Honey CJ, Sporns O, Cammoun L, Gigandet X, Thiran JP, Meuli R, Hagmann P. Predicting human resting-state functional connectivity from structural connectivity. *Proceedings of the National Academy of Sciences*. 2009a Feb; 106(6):2035–2040.
- Honey CJ, Sporns O, Cammoun L, Gigandet X, Thiran JP, Meuli R, Hagmann P. Predicting human resting-state functional connectivity from structural connectivity. *Proc Natl Acad Sci USA*. 2009b Feb; 106(6):2035–2040. [PubMed: 19188601]
- Hyvarinen A, Oja E. Independent component analysis: algorithms and applications. *Neural Networks*. 2000; 13(4–5):411–430. [PubMed: 10946390]
- Jaynes E. Information Theory and Statistical Mechanics. *Physical Review*. 1957a; 106(4):620–630.
- Jaynes E. Information theory and statistical mechanics. II. *Physical Review*. 1957b; 108(2):171.
- Keil B, Blau JN, Biber S, Hoecht P, Tountcheva V, Setsompop K, ... Wald LL. A 64-channel 3t array coil for accelerated brain mri. *Magnetic Resonance in Medicine*. 2013; 70(1):248–258. Retrieved from <http://dx.doi.org/10.1002/mrm.24427>. DOI: 10.1002/mrm.24427 [PubMed: 22851312]
- McMillan B. The basic theorems of information theory. *Ann Math Stat*. 1953; 24(2):196–219.

- Mueller S, Keeser D, Samson AC, Kirsch V, Blautzik J, Grothe M, ... Meindl T. Convergent Findings of Altered Functional and Structural Brain Connectivity in Individuals with High Functioning Autism: A Multimodal MRI Study. PLoS ONE. 2013; 8(6):e67329. [PubMed: 23825652]
- Setsompop K, Gagoski BA, Polimeni JR, Witzel T, Wedeen VJ, Wald LL. Blipped-controlled aliasing in parallel imaging for simultaneous multislice echo planar imaging with reduced g-factor penalty. Magn Res Med. 2011 Aug; 67(5):1210–1224.
- Setsompop K, Kimmlingen R, Eberlein E, Witzel T, Cohen-Adad J, McNab J, ... Wald L. Pushing the limits of in vivo diffusion {MRI} for the human connectome project. NeuroImage. 2013; 80(0): 220–233. Retrieved from <http://www.sciencedirect.com/science/article/pii/S1053811913005788> (Mapping the Connectome) doi:<http://dx.doi.org/10.1016/j.neuroimage.2013.05.078>. [PubMed: 23707579]
- Shannon C. A mathematical theory of communication. Bell Syst Tech J. 1948; 27:379423, 623656.
- Skudlarski P, Jagannathan K, Calhoun VD, Hampson M, Skudlarska BA, Pearlson G. Measuring brain connectivity: diffusion tensor imaging validates resting state temporal correlations. Neuroimage. 2008 Nov; 43(3):554–561. [PubMed: 18771736]
- Sotiropoulos SN, Moeller S, Jbabdi S, Xu J, Andersson JL, Auerbach EJ, ... Lenglet C. Effects of image reconstruction on fiber orientation mapping from multichannel diffusion mri: Reducing the noise floor using sense. Magnetic Resonance in Medicine. 2013; 70(6):1682–1689. Retrieved from <http://dx.doi.org/10.1002/mrm.24623>. DOI: 10.1002/mrm.24623 [PubMed: 23401137]
- Van Essen DC, Smith SM, Barch DM, Behrens TE, Yacoub E, Ugurbil K. for the WU-Minn HCP Consortium. The WU-Minn Human Connectome Project: An overview. NeuroImage. 2013 Oct; 80(C):62–79. [PubMed: 23684880]
- Van Essen DC, Ugurbil K, Auerbach E, Barch D, Behrens TE, Bucholz R, ... Yacoub E. The Human Connectome Project: a data acquisition perspective. Neuroimage. 2012 Oct; 62(4):2222–2231. [PubMed: 22366334]
- Wedeen VJ, Hagmann P, Tseng WY, Reese TG, Weisskoff RM. Mapping complex tissue architecture with diffusion spectrum magnet ic resonance imaging. Magn Reson Med. 2005 Dec; 54(6):1377–1386. [PubMed: 16247738]
- Wong CW, Olafsson V, Tal O, Liu TT. The amplitude of the resting-state fMRI global signal is related to EEG vigilance measures. Neuroimage. 2013; 83:983–990. [PubMed: 23899724]
- Zalesky A, Fornito A, Cocchi L, Gollo LL, Breakspear M. Time-resolved resting-state brain networks. Proceedings of the National Academy of Sciences of the United States of America. 2014 Jul; 111(28):10341–10346. [PubMed: 24982140]

Appendix A: EFD summary

The information Hamiltonian $H(d, s)$ can be written (Enßlin et al., 2009) as

$$H(d, s) = H_0 - j^\dagger s + \frac{1}{2} s^\dagger D^{-1} s + H_i(d, s) \quad (9)$$

where H_0 is essentially a normalizing constant that can be ignored, D is an information propagator, j is an information source, and $\dagger$ means the complex conjugate transpose. H_i is an interaction term (Enßlin et al., 2009)

$$H_i = \sum_{n=1}^{\infty} \frac{1}{n!} \int \cdots \int \Lambda_{s_1 \cdots s_n}^{(n)} s_1 \cdots s_n ds_1 \cdots ds_n \quad (10)$$

where $\Lambda_{s_1 \dots s_n}^{(n)}$ terms describe the interaction strength.

When the source term j , the linear information propagator D , and the nonlinear interaction terms $\Lambda_{s_1 \dots s_n}^{(n)}$ are all known or at least some more or less accurate approximations can be used for their description, the IFT approach provides an effective, powerful, and mathematically elegant way to find an unknown signal s either by using the classical solution at the minimum of Hamiltonian ($\delta H / \delta s = 0$) or with the help of summation methods (e.g. with the help of Feynman diagrams (Feynman, 1949; Enßlin et al., 2009)).

But there is a whole class of problems where those terms are unknown and too complex for deriving effective and accurate approximations. In this case the ESP method (Frank & Galinsky, 2014), based on the principal of maximum entropy (Jaynes, 1957a,b), provides a general and effective way to introduce powerful prior information using coupling between different spatio-temporal points that is available from the data itself. This is accomplished by constructing a so called *coupling matrix* that characterizes the relation between locations i and j in the data

$$Q_{ij} = e^{-\gamma_{ij}} \quad (11)$$

Here the γ_{ij} are Lagrange multipliers that describe the relations and depend on some function of the space-time locations i and j . The eigenvalues λ_k and eigenvectors $\phi^{(k)}$ of the coupling matrix Q

$$\sum_j Q_{ij} \phi_j^{(k)} = \lambda_k \phi_i^{(k)} \quad (12)$$

then formally define the transition probability from location j to location i of the k 'th mode (or path as it is often called in the random walk theory) as

$$p_{ijk} = \frac{Q_{ji} \phi_i^{(k)}}{\lambda_k \phi_j^{(k)}} \quad (13)$$

For each transition matrix Eqn 13 there is a unique stationary distribution associated with each mode k :

$$\mu^{(k)} = [\phi^{(k)}]^2 \quad (14)$$

that satisfies

$$\mu_i^{(k)} = \sum_j \mu_j^{(k)} p_{ijk} \quad (15)$$

where $\mu^{(1)}$, associated with the largest eigenvalue λ_1 , corresponds to the maximum entropy stationary distribution (Burda et al., 2009).

The EFD approach (Frank & Galinsky, 2016) adds those coupling matrix priors into the information Hamiltonian Eqn 9 by expanding the signal s into a Fourier expansion using $\{\phi^{(k)}\}$ as the basis functions

$$s_i = \sum_k^K [a_k \phi_i^{(k)} + a_k^\dagger \phi_i^{\dagger, (k)}] \quad (16)$$

In this ESP basis the information Hamiltonian Eqn 9 can be written as

$$H(d, a_k) = -j_k^\dagger a_k + \frac{1}{2} a_k^\dagger \Lambda a_k + \sum_{n=1}^{\infty} \frac{1}{n!} \sum_{k_1}^K \cdots \sum_{k_n}^K \tilde{\Lambda}_{k_1 \dots k_n}^{(n)} a_{k_1} \cdots a_{k_n} \quad (17)$$

where matrix Λ is the diagonal matrix $\text{Diag}\{\lambda_1, \dots, \lambda_K\}$, composed of the eigenvalues of the coupling matrix, and j_k is the amplitude of k th mode in the expansion of the source j

$$j_k = \int j \phi^{(k)} ds \quad (18)$$

and the new interaction terms $\tilde{\Lambda}^{(n)}$ are

$$\tilde{\Lambda}_{k_1 \dots k_n}^{(n)} = \int \cdots \int \Lambda_{s_1 \dots s_n}^{(n)} \phi^{(k_1)} \cdots \phi^{(k_n)} ds_1 \cdots ds_n \quad (19)$$

For the nonlinear interaction terms $\Lambda_{s_1 \dots s_n}^{(n)}$ the EFD method again takes coupling into account through factorization of $\Lambda^{(n)}$ in powers of the coupling matrix

$$\Lambda_{s_1 \dots s_n}^{(n)} = \frac{\alpha^{(n)}}{n} \sum_{p=1}^n \prod_{\substack{m=1 \\ m \neq p}}^n Q_{pm} \quad (20)$$

where $\alpha^{(n)} \lesssim 1 / \max (j_k^n / \lambda_k)$, which results in

$$\tilde{\Lambda}_{k_1 \dots k_n}^{(n)} = \frac{\alpha^{(n)}}{n} \sum_{p=1}^n \left(\frac{1}{\lambda_{k_p}} \prod_{m=1}^n \lambda_{k_m} \right) \int \left(\prod_{r=1}^n \phi^{k_r} \right) ds \quad (21)$$

Thus the EFD approach provides a very simple expression for the classical solution for the amplitudes a_k

$$\Lambda a_k = \left(j_k - \sum_{n=1}^{\infty} \frac{1}{n!} \sum_{k_1}^K \dots \sum_{k_n}^K \tilde{\Lambda}_{kk_1 \dots k_n}^{(n+1)} a_{k_1} \dots a_{k_n} \right) \quad (22)$$

through the eigenvalues and eigenvectors of coupling matrix (that may also include some noise corrections (Frank & Galinsky, 2016; Frank & Galinsky, 2016)).

Appendix B: Coupling matrices

For the HRA dataset we define a simple intensity weighted nearest neighbors coupling matrix as

$$Q_{ij}^H = e^{-\gamma_{ij}} = \begin{cases} d_i^H d_j^H & \text{nearest neighbors} \\ 0 & \text{not connected} \end{cases} \quad (23)$$

For DWI data, the GO-ESP procedure uses the spin density function $G(\mathbf{r}, \mathbf{R})$ expressed with the help of the spherical wave decomposition as

$$G(\mathbf{r}, \mathbf{R}) = 4\pi \sum_{l=0}^{\infty} \sum_{m=-l}^l i^l Y_l^m(\hat{\mathbf{R}}) g_{lm}(\mathbf{r}, R), \quad (24)$$

$$g_{lm}(\mathbf{r}, R) = \int W(\mathbf{r}, \mathbf{q}) j_l(qR) Y_l^{m*}(\hat{\mathbf{q}}) d\mathbf{q}. \quad (25)$$

and generate the symmetrized scale dependent coupling matrix Q_{ij}^D as

$$Q_{ij}^D(\ell) = Q_{ji}^D(\ell) = \frac{1}{2}[G(\mathbf{r}_i, (\mathbf{r}_i - \mathbf{r}_j)\ell) + G(\mathbf{r}_j, (\mathbf{r}_j - \mathbf{r}_i)\ell)], \quad (26)$$

where ℓ represents the dimensionless ratio of scales of dynamic displacement $\mathbf{R}$ to the spatial (voxel) scales $\mathbf{r}$, $j_l(qR)$ is the spherical Bessel function of order l and $Y_l^m(\hat{\mathbf{q}}) = Y_l^m(\Omega_{\hat{\mathbf{q}}}) = Y_l^m(\theta_q, \phi_q)$ is the spherical harmonic with θ_q and ϕ_q being the polar and azimuthal angles of the vector $\mathbf{q}$, and similarly for the vector $\mathbf{R}$, and $W(\mathbf{r}, \mathbf{q})$ is the DW1 signal (see Galinsky & Frank (2015) for more details).

For rsfMRI the EFD procedure employs the frequency ω dependent spatial coupling matrix $Q_{ij}^F(\omega)$ as

$$Q_{ij}^F(\omega_0) = \mathcal{R}_{ij}^n d_i^F(\omega_0) d_j^F(\omega_0), \quad (27)$$

$$Q_{ij}^F(\omega_l) = \mathcal{R}_{ij}^n (\phi_i^{(1)}(\omega_0) d_j^F(\omega_l) + \phi_j^{(1)}(\omega_0) d_i^F(\omega_l)), \quad (28)$$

here $d_i^F(\omega)$ is the temporal Fourier mode of the rsfMRI data d^F with the frequency ω , $\phi_i^{(1)}(\omega_0)$ is the eigenvector of $Q^F(\omega_0)$ that corresponds to the largest eigenvalue, and $\mathcal{R}_{ij}$ can include some function of the pair correlations taken to the n th power, for example a simple mean of the pair correlations, that is equivalent to a product of signal means ($\bar{d}^F$) for a periodic signal

$$\mathcal{R}_{ij} = \frac{1}{T} \int_0^T C_{ij}(t) dt \equiv T \bar{d}_i^F \bar{d}_j^F \quad (29)$$

or a maximum correlation of mean subtracted signal

$$\mathcal{R}_{ij} = \max_{0 \leq t \leq T} |C_{ij}(t) - T \bar{d}_i^F \bar{d}_j^F| \quad (30)$$

where $C_{ij}(t)$ is the pair correlations

$$C_{ij}(t) \equiv \int d_i^F(t - \tau) d_j^F(\tau) d\tau \quad (31)$$

The EFD procedure can then be extended to incorporate information from all of the modalities simultaneously by incorporate these single modality coupling matrices Q_{ij}^H, Q_{ij}^D and Q_{ij}^F in Eqn 4 to generate the intermodality coupling matrix $\mathcal{Q}_{ij}$.

To investigate long range structural, functional and effective connection patterns that span both gray and white matter regions, we generate the connectivity matrix using structural, functional and effective streamlines produced by GO-ESP tractography. For structural tractography we employ the nearest neighbor connectivity matrix generated from DWI and HRA datasets and follow the same formalism as was used for single modality DWI tractography.

For functional tractography the same notion of entropy change was used as in Galinsky & Frank (2015)

$$S_i = - \sum_k \mu^{(k)} \sum_j p_{ijk} \ln p_{ijk} \quad (32)$$

assuming that both equilibrium μ and transitional probabilities p_{ij} were obtained from the functional nearest neighbor coupling matrix $Q_{ij}^F(\omega_0)$ using Eqn 14 and Eqn 13. This global entropy field was obtained under the Markovian assumption in the limit of long pathway lengths (or large times) (Shannon, 1948; McMillan, 1953) and describes the global flow of information. The same formalism of linearizing of the Fokker-Planck equation with a potential in the form of the global entropy Eqn 32 and finding the characteristics solution using the Hamiltonian set of equations as was used in Galinsky & Frank (2015) for DWI tractography produces GO-ESP functional tracking. The streamline angular distribution is shaped in this case by the correlation function of the functional signal.

Figure 1.

A working demonstration example of joint estimation workflow showing extraction of a single structural eigen mode and a single functional eigen mode using HRA, DWI and FMRI HCP datasets.

Figure 2.

Comparison of equilibrium probability maps obtained from a single modality DWI dataset (**a**) with equilibrium probability maps extracted using coupling matrix based on both DWI and HRA datasets (**b**). A significant enhancement of white matter localization as well as significant overall image quality improvement due to signal-to-noise ratio increase can clearly be seen in all panels of (**b**). Close-up panels (**c**) and (**d**) of the lower left quadrant of the axial images in (**a**) and (**b**) make the enhancements even more obvious.

Figure 3.

Comparison of a set of tracts produced by GO-ESP tractography from a single modality DWI dataset (**a**) with an equivalent set of tracts obtained when coupling matrix was defined using both DWI and HRA datasets (**b**). Panels (**c**) and (**d**) show the close ups for the trac count volumes generated using 5,000,000 total seeds to run GO-ESP tractography, then counting tracts in every voxel and thresholding at 2,000 tracts (that is zeroing all voxels with less than 2,000 tracts). The color encoding uses the mean direction of tracts in every voxel. The unified DWI-HRA approach clearly shows additional spatial and angular details as well as new tracts that were absent in DWI-only GO-ESP tractography.

Figure 4.

Shapes of trac counts in every voxel generated by a whole brain GO-ESP tractography using only DWI datasets (**a** and **c**) and both DWI and HRA datasets (**b** and **d**). CFMRI data acquired on a 3T GE Signa scanner with diffusion data of matrix size $(x, y, z) = (100, 100, 72)$ and isotropic resolution of 8mm^3 and T1-weighted anatomical images with matrix size $(x, y, z) = (168, 256, 256)$ and resolution of $1.2 \times 0.9375 \times 0.9375\text{mm}^3$ were used in panels **a** and **b**, and HCP datasets acquired on a Siemens 3T system (the special connectome scanner at MGH) with diffusion data matrix of size $(x, y, z) = (140, 140, 96)$ and isotropic spatial resolution of 3.375mm^3 and T1-weighted anatomical images with matrix size $(x, y, z) = (176, 256, 176)$ and 1mm^3 isotropic resolution were used in panels **c** and **d**. The volumes were generated from tractography generated from 5,000,000 seeds then counting tracts in every voxel and thresholding at 1,000 tracts (that is zeroing all voxels with less than 1,000 tracts). For coloring scheme the mean direction of tracts in every voxel is used. The panels **b** and **d** clearly show a significant increase in the level of details allowing resolution of structure and connectivity of white matter bundles not attainable in diffusion datasets along.

Figure 5.

Several structural eigenmodes of DWI-HRA connectivity matrix. Each eigenmode outlines interconnected region where random walker will spend most of the time (property quantitatively described by shown equilibrium probability map). Those modes are only loosely connected with other regions, that is each eigenmode defines different connectivity pattern ranked accordingly to mode power (shown in Figure 7).

Figure 6.

Several nonlinear EFD eigenmodes that were obtained using single modality rsfMRI dataset (a), using joint rsfMRI-HRA connectivity matrix (b), and using both functional (rsfMRI) and structural (DWI+HRA) connectivity matrices – effective connectivity eigenmodes – (c). Both the original rsfMRI EFD modes in (a) and the rsfMRI-HRA EFD modes in (b) clearly show the BOLD activation patterns with improved localization of modes in the areas of gray matter and refined details appearing in (b). The effective connectivity eigenmodes in (c) show the additional connectivity through white matter tracts.

Figure 7.

Log-log plot of power in structural (red solid line) and functional (green dash-dot line) modes as a function of mode number. Thin blue dashed line shows $n^{-1.2}$ dependence. Both functional and structural spectra show the same scale-free power law behavior, with faster decay of functional modes for mode numbers above 100 due to loss of resolution.

Figure 8.

Whole brain volumetric parcellation of the CFMRI HRA+DWI+FMRI datasets produced by effective connectivity eigenmodes that were generated using joint functional (rsFMRI) and structural (DWI+HRA) connectivity matrix. Panels (a–c) show parcellation using 20 of the first most significant modes, panels (d–f) use 80 of the most significant modes, and panels (g–i) apply parcellation using 160 modes. The shapes shown in all panels are obtained by counting the number of streamlines in each voxel after performing whole brain tractography with 5,000,000 total seed, and using different thresholds for the number of streamlines from 100 in (a,d,g), to 1000 in (b,e,h), to 1500 in (c,f,i). Panels (c,f,i) contain volume cut to show the internal structure of the modes.

Figure 9.

Whole brain volumetric parcellation of the HCP HRA+DWI+FMRI datasets produced by effective connectivity eigenmodes that were generated using joint functional (rsfMRI) and structural (DWI+HRA) connectivity matrix. Panels (a–c) show parcellation using 20 of the first most significant modes, panels (d–f) use 80 of the most significant modes, and panels (g–i) apply parcellation using 160 modes. The shapes shown in all panels are obtained by counting the number of streamlines in each voxel after performing whole brain tractography with 5,000,000 total seeds, and using different thresholds for the number of effective connectivity mode streamlines from 100 in (a,d,g), to 1000 in (c,f,i), to 1800 in (b,e,h). Panels (c,f,i) contain volume cut to show the internal structure of the modes.