Published in final edited form as:

Nano Today. 2019 April ; 25: 156–. doi:10.1016/j.nantod.2019.03.009.

Corrigendum to “3D printed bionic nanodevices” [Nano Today 11 (2016) 330–350]

Yong Lin Kong^{a,*}, Maneesh K. Gupta^b, Blake N. Johnson^c, and Michael C. McAlpine^{d,*}

^aKoch Institute for Integrative Cancer Research, Massachusetts Institute of Technology, Cambridge, MA 02139, USA

^bAir Force Research Laboratories, Wright-Patterson Air Force Base, OH 45433, USA

^cDepartment of Industrial and Systems Engineering, Virginia Tech, Blacksburg, VA 24061, USA

^dDepartment of Mechanical Engineering, University of Minnesota, Minneapolis, MN 55455, USA

The authors regret there is a typo in Figure 3. The unit of the x-axis should be “ μm ” rather than “mm”. This error occurred during editing, when the fonts were changed to “Arial” in Adobe Illustrator, in which the micron symbol (μ) is written with the “symbol” font of an “m” character. The corrected figure is included as followed:

The authors would like to apologise for any inconvenience caused.

*Corresponding authors. yongkong@mit.edu (Y.L. Kong), mcalpine@umn.edu (M.C. McAlpine).