Erratum: Concurrent measures of contralateral suppression of transient-evoked otoacoustic emissions and of auditory steady-state responses [J. Acoust. Soc. Am. 140(3), 2027–2038 (2016)]

Ian B. Mertes^{a)} and Marjorie R. Leek^{b)}

Research Service 151, VA Loma Linda Healthcare System, 11201 Benton Street, Loma Linda, California 92357, USA

(Received 26 January 2017; accepted 31 January 2017; published online 8 February 2017)

[<http://dx.doi.org/10.1121/1.4976303>]

[JFL]

Pages: 781–782

Because of an error on the part of the authors, an incorrect scaling factor was applied to the magnitudes of the fast Fourier transforms of the transient-evoked otoacoustic emission (TEOAE) waveforms. The result was that the TEOAE signal and noise floor magnitudes for the no contralateral acoustic stimulation (*no CAS*) and contralateral acoustic stimulation (*CAS*) conditions reported in Fig. 4 (left panel), Fig. 5 (top panel), and Table I of this paper were approximately 6.43 dB lower than their true values. Corrected versions (Figs. 4 and 5 and Table I) are shown below (note that the contour of the figures did not change from those in the original paper because all values were increased by the same amount). This error did not affect the signal-to-noise ratios (SNRs) or the magnitudes of TEOAE contralateral suppression reported in the original paper because these are relative values, and so the discussion and conclusions of the original paper did not change.

TABLE I. Descriptive statistics for TEOAE group data for the parameters of signal magnitude, noise-floor magnitude, and SNR. Results are displayed to facilitate comparison between the *no CAS* and *CAS* conditions for each parameter. Means, minimums, and maximums are in dB SPL. SNRs and SDs are in dB.^a

Parameter	Condition	Mean	SD	Minimum	Maximum
Signal	<i>no CAS</i>	−11.0	6.2	−16.4	4.2
	<i>CAS</i>	−12.8	6.5	−18.4	2.9
Noise Floor	<i>no CAS</i>	−35.7	1.5	−38.2	−32.5
	<i>CAS</i>	−35.5	2.5	−38.8	−29.1
SNR	<i>no CAS</i>	24.7	5.4	19.8	38.6
	<i>CAS</i>	22.7	5.7	18.2	37.4

^aSound pressure level (SPL); standard deviation (SD).

FIG. 4. (Color online) Recorded TEOAE and auditory steady-state response (ASSR) spectra (left and right panels, respectively) for one representative subject. Solid lines represent responses obtained in the *no CAS* condition. Dotted lines represent responses obtained in the *CAS* condition. The filled gray regions represent the recording noise floors.

^{a)}Current address: Department of Speech and Hearing Science, University of Illinois at Urbana-Champaign, 901 South Sixth Street, Champaign, Illinois 61820, USA. Electronic mail: imertes@illinois.edu

^{b)}Also at Department of Otolaryngology—Head and Neck Surgery, Loma Linda University Health, 11234 Anderson Street, Loma Linda, California 92354, USA.

FIG. 5. Magnitudes of TEOAEs and ASSRs (top and bottom panels, respectively) for each individual subject. Responses in the *no CAS* and *CAS* conditions are represented by black and white bars, respectively. The recording noise floors are represented by gray bars; noise floors in the *no CAS* and *CAS* conditions are on the left and right side, respectively, for each individual subject. The magnitudes displayed here represent the mean computed across the two replicate measurements obtained from each subject.