Peshala P. T. Gamage¹

Biomedical Acoustics Research
Laboratory (BARL),
Department of Mechanical and
Aerospace Engineering,
College of Engineering and Computer Science,
University of Central Florida,
ENGR 1, Room 428,
12760 Pegasus Boulevard,
Orlando, FL 32816
e-mail: peshala@knights.ucf.edu

Fardin Khalili

Biomedical Acoustics Research
Laboratory (BARL),
Department of Mechanical and
Aerospace Engineering,
College of Engineering and Computer Science,
University of Central Florida,
ENGR 1, Room 428,
12760 Pegasus Boulevard,
Orlando, FL 32816
e-mail: fardin@knights.ucf.edu

M. D. Khurshidul Azad

Biomedical Acoustics Research
Laboratory (BARL),
Department of Mechanical and
Aerospace Engineering,
College of Engineering and Computer Science,
University of Central Florida,
ENGR 1, Room 428,
12760 Pegasus Boulevard,
Orlando, FL 32816
e-mail: khurshid@knights.ucf.edu

Hansen A Mansy

Biomedical Acoustics Research
Laboratory (BARL),
Department of Mechanical and
Aerospace Engineering,
College of Engineering and Computer Science,
University of Central Florida,
ENGR 1, Room 428,
12760 Pegasus Boulevard,
Orlando, FL 32816
e-mail: hansen.mansy@ucf.edu

Modeling Inspiratory Flow in a Porcine Lung Airway

Inspiratory flow in a multigeneration pig lung airways was numerically studied at a steady inlet flow rate of $3.2 \times 10^{-4} \text{ m}^3/\text{s}$ corresponding to a Reynolds number of 1150 in the trachea. The model was validated by comparing velocity distributions with previous measurements and simulations in simplified airway geometries. Simulation results provided detailed maps of the axial and secondary flow patterns at different cross sections of the airway tree. The vortex core regions in the airways were visualized using absolute helicity values and suggested the presence of secondary flow vortices where two counter-rotating vortices were observed at the main bifurcation and in many other bifurcations. Both laminar and turbulent flows were considered. Results showed that axial and secondary flows were comparable in the laminar and turbulent cases. Turbulent kinetic energy (TKE) vanished in the more distal airways, which indicates that the flow in these airways approaches laminar flow conditions. The simulation results suggested viscous pressure drop values comparable to earlier studies. The monopodial asymmetric nature of airway branching in pigs resulted in airflow patterns that are different from the less asymmetric human airways. The major daughters of the pig airways tended to have high airflow ratios, which may lead to different particle distribution and sound generation patterns. These differences need to be taken into consideration when interpreting the results of animal studies involving pigs before generalizing these results to humans.
[DOI: 10.1115/1.4038431]

1 Introduction

Understanding airflow dynamics in lung airways is important for studies of drug delivery, particle deposition, airway disease, high-frequency ventilation, and breath sound generation. Investigating the flow in the airways is yet challenging due to the complex geometry of the airways as well as the transient nature of the airflow during the respiration cycle. The flow was studied in airways with different levels of geometrical complexity including two [1–3] and multiple [4–8] generations. While experimental investigations dealt with relatively simple geometries, computational fluid dynamics (CFD) has enabled detailed analysis of flow in the more complex geometries. The latter elucidated important characteristics of the airflow, such as axial velocity profiles,

secondary velocity patterns, pressure drop, flow dividing ratios, and turbulence characteristics in the branching network [9–11].

One of the earliest studies of flow in the lung airways [2] performed smoke flow visualization as well as velocity profile measurements in a simple two-generation bifurcation model to define flow patterns during inspiration and expiration. Later experiments [1,12–14] documented velocity distributions and pressure drops at different flow rates. While these studies used simplified airway geometries up to three generations based on known models [15,16], more recent experimental studies provided detailed velocity measurements in realistic lung airways using advanced measurement techniques such as particle image velocimetry [4] and magnetic resonance gas velocimetry [6].

Computational fluid dynamics was also utilized to investigate the flow in the lung airways and the results demonstrated the capability of CFD in simulating the detailed flow field. Early CFD studies were performed for simplified airway models [10,17–19] that were based on Weibel and Horsfield models where the

¹Corresponding author.

Manuscript received August 2, 2017; final manuscript received October 31, 2017; published online March 19, 2018. Assoc. Editor: Ching-Long Lin.

airways were represented by cylindrical ducts with smooth transitions at the bifurcation region. The results of these studies helped predict the fundamental flow patterns in typical airway bifurcations and were validated by comparison with experimental data. With the advances in imaging techniques such as computed tomography and magnetic resonance imaging along with improved ability to extract three-dimensional (3D) airway geometries from these images, more anatomically accurate airway geometries became available for CFD simulations [5,7,20]. Recent CFD studies showed that the flow patterns in simplified geometries can significantly differ from actual cases [4,6,18], which highlighted the importance of using realistic airway geometries in CFD simulations.

Due to the limitations of in vivo human experiments, animal models are often used to study relevant airflow phenomena. For example, several studies used different animal models to study lung airway diseases [21–24] and sound transmission for different lung abnormalities [25]. A numerical study of airflow in an ovine lung [26] reported flow dissimilarities compared to simplified human airways. This suggested that studying flow characteristics in different species (e.g., certain animal models) is important, especially that airway geometry may significantly be different from the human airways [27,28]. These geometric differences are likely to affect flow dynamics that, in turn, the study results.

Pigs are often used in experimental studies of the lung airways. For example, some studies utilized pigs to investigate airway respiratory mechanics and other physical phenomena [29–31]. Other recent studies specifically investigated the geometrical details of domestic pig airways [27,28].

In the current study, a numerical investigation of flow dynamics is carried out in realistic pig airway geometry. The CFD code is first validated using available measurements [1] in simplified airway models, and then the airflow in pig airways is simulated for steady inspiratory flow. Both laminar and turbulent flow simulations are carried out. The effect of the turbulence generated in upper airways is investigated and special attention is given to secondary flows. The velocity distributions, secondary flow patterns, mass flow ratios, and pressure drop results are presented and discussed.

2 Numerical Methods

In previous CFD studies of human lung airways, the flow was assumed to be either laminar [18,32,33] or turbulent [7,32,34]. While the flow is known to be laminar in terminal airways due to low Reynolds numbers [35], it can be turbulent in larger airways. In addition, CFD [5] and experimental [4] studies of airflow in the human airways suggested that turbulence generated in upper airways influences inspiratory airflow patterns in the trachea and mainstem bronchi airways. Similar effects may exist in pig airways and, hence, both laminar and turbulent cases were investigated in the current study.

While the respiratory flow is time-dependent, several experimental and numerical studies suggested that the transient effects are small for moderate oscillation frequencies [36–38] that correspond to Womersley numbers (Wo) less than one. This condition may be written as

$$Wo = \frac{D}{2} \sqrt{\frac{\rho\omega}{\mu}} < 1 \quad (1)$$

where D , ρ , ω , and μ denote airway diameter, density, oscillation frequency, and dynamic viscosity, respectively.

Considering typical normal respiratory rates, Wo is less than unity for smaller airways where flow is laminar. When the flow is turbulent in larger airways, Womersley number is evaluated using the eddy viscosity [14] leading a much smaller Wo and, hence, the effect of unsteadiness is further reduced by the turbulence [36,39]. Some studies [39,40] also showed agreement between steady and unsteady conditions for inspiratory flow except during

the flow deceleration phase. In addition, steady flow simulations have been proven to have utility in providing insights about flow characteristics [5,11].

2.1 Governing Equations. If in the current study, simulations were performed assuming steady incompressible flow for both the laminar and turbulent cases, here, the governing equations consist of conservation of mass and momentum. When the flow is laminar, these equations take the form

$$\frac{\partial u_i}{\partial x_i} = 0 \quad (2)$$

$$\rho u_j \frac{\partial u_i}{\partial x_j} = -\frac{\partial P}{\partial x_i} + \mu \frac{\partial^2 u_i}{\partial x_j \partial x_j} \quad (3)$$

Here, the subscripts i and j denote the Cartesian tensor notations where the repeated subscripts denote summations over the three coordinates.

In Eqs. (2) and (3), U and P are the three-dimensional velocity vector and static pressure, respectively. The fluid properties were such that: the density, $\rho = 1.2 \text{ kg m}^{-3}$ and dynamic viscosity, $\mu = 1.85 \times 10^{-5} \text{ kg m/s}$.

For the turbulent flow simulation, Reynolds-averaged Navier–Stokes equations were used. Here, the velocity of the fluid is considered as the sum of the mean velocity u , and the fluctuating component u' , i.e., velocity = $u + u'$. The final form of the momentum equation in tensor notation will be

$$\rho u_j \frac{\partial u_i}{\partial x_j} = -\frac{\partial P}{\partial x_i} + \frac{\partial}{\partial x_j} \left(\mu \left(\frac{\partial u_i}{\partial x_j} + \frac{\partial u_j}{\partial x_i} \right) - \rho u'_i u'_j \right) \quad (4)$$

where $-\rho u'_i u'_j$ term can be expressed using Boussinesq approximation [41] as

$$-\rho u'_i u'_j = \mu_t \left(\frac{\partial u_i}{\partial x_j} + \frac{\partial u_j}{\partial x_i} - \frac{3}{2} \frac{\partial u_k}{\partial x_k} \delta_{ij} \right) - \frac{2}{3} \rho k \delta_{ij} \quad (5)$$

$$\omega = \rho k / \mu_t \quad (6)$$

In Eq. (5), k is the turbulent kinetic energy (TKE) and δ_{ij} represents Kronecker delta function. In Eq. (6), ω and μ_t denote the specific dissipation rate and turbulent dynamic viscosity, respectively.

In the current study, k – ω turbulence model was used, where additional transport equations for k and ω are solved to derive μ_t [41]. The k – ω turbulent model was selected because it tends to be more numerically stable and to produce converged solutions more rapidly than other models (such as the k – ϵ model) for low Reynolds numbers [41,42].

2.2 Boundary Conditions

2.2.1 Inlet Boundary Condition. The pig airway dimensions in the current investigation are comparable to those of humans [27]. Hence, boundary conditions that were previously used in humans would provide a good approximation. Consequently, a steady flow rate boundary condition of $3.2 \times 10^{-4} \text{ m}^3/\text{s}$ was imposed at the tracheal inlet, which corresponds to peak inspiratory flow in humans [5]. The turbulent intensity boundary condition at tracheal inlet was also specified to account for the turbulence generated in the upper airway region and allow investigating the effect of tracheal turbulence on the flow in smaller airways. Here, the inlet turbulent intensity was chosen as 5% based on previous experimental and numerical data of the human airways [5,7].

2.2.2 Outlet Boundary Condition. Different outlet boundary conditions can be specified. One approach is to set the static pressure boundary conditions at each outlet. However, the pressure at

Table 1 Calculation of discretization error

ϕ = Maximum velocity in the entire field (m/s)			
$N_1; N_2; N_3$	1,995,901; 1,118,020; 626,918		
r_{21} (refinement factor of N_2/N_1)	1.21	e_a^{21}	0.044%
r_{32} (refinement factor of N_3/N_2)	1.21	e_{ext}^{21}	0.001%
ϕ_1	3.2015	GCI_{fine}^{21}	0.001%
ϕ_2	3.2001	ϕ_{ext}^{32}	3.202
ϕ_3	3.1305	e_a^{32}	2.175%
P	20.2281	e_{ext}^{32}	0.045%
ϕ_{ext}^{21}	3.2015	GCI_{course}^{32}	0.056%

each outlet is usually unknown. Another approach is to impose flow division ratios at each outlet, which are also usually unknown. However, in a relatively recent study [43], pressure and flow boundary conditions were applied at outlets in flow simulation of a six-generation airway model with 13 outlets. The results showed small differences between the two approaches and it was concluded that a constant pressure boundary condition at outlets was suitable for flow simulations. Therefore, constant static pressure boundary condition of 0 Pa gauge pressure was imposed at the 93 outlets of the current study. Similar outlet boundary conditions have been used in other CFD studies of lung airways [7,11].

2.2.3 Wall Boundary Condition. Larger airway walls are relatively stiff because of their high cartilage content [18,44]. Hence, wall deflection in the current study was neglected. In addition, nonslip boundary condition was imposed at the airway wall. Similar wall boundary conditions were applied in previous studies [7,11,18,43].

2.3 Extracting Pig Airway Geometry. The pig airway geometry was extracted using thoracic computed tomography scan images taken from a domestic pig (Yorkshire–Landrace breed, weight~40 kg). These images had a resolution of 512×512 pixels (pixel size=0.8 mm) with an axial step of 1 mm. The 3D surface geometry of the airways was reconstructed using segmentation software ITK-SNAP [45]. The 3D geometry was saved in stereolithography format as a surface mesh.

2.4 Mesh Generation. The geometry was meshed using STAR CCM+ software [46]. The surface mesh was improved by smoothing and remeshing the surface. The mesh contained a total of $\sim 2 \times 10^6$ cells. This value was selected based on an uncertainty and discretization error calculations following ASME recommendations [47], which examined the maximum velocity of the entire field when the mesh is progressively refined. Table 1 shows the fine-grid convergence error (GCI_{fine}) of 0.001% (excluding modeling errors [47]) where the discretization error of the maximum velocity was less than 3%.

Accurate prediction of pressure drop in flows with separation depends on resolving the velocity gradients normal to the wall [48–50]. Prism layers allow the solver to resolve near wall flow accurately [46]. Hence, a four-layer prism layer mesh with a total thickness of 0.13 mm and layer stretching factor of 1.5 was applied near the boundaries (Fig. 1(c)). The y^+ value was maintained in the order of 1. A mesh quality check was performed using Star CCM+ before proceeding to the simulation and the mesh was topologically valid with no negative volume cells. A convergence criterion of 10^{-5} was used for all the flow variables.

2.5 Numerical Validation

2.5.1 Validation for a Simplified Symmetric Bifurcation. Simulations were validated by comparing the calculated velocity distributions with laser Doppler velocity measurements [1] of inspiratory flow in a single bifurcation. Here, the geometry of the

Fig. 1 (a) Meshed pig airway, (b) zoomed image of the mesh, and (c) zoomed image of a section with prism layer mesh

experimental study was reconstructed and simulations were performed at a Reynolds number of 1500, which matched that of the experiment.

Figure 2 shows the simulated and measured velocity distributions at different sections. Good agreement between the experimental and numerical results can be seen.

2.5.2 Validation of Pressure Drop. The numerical results were further validated by comparing the calculated pressure drop with the pressure drop measured in the current study for a simplified pig lung airway model (Fig. 3(b)) that was previously proposed [51]. Here, the pressure drop between the trachea and a midbronchus airway was measured using a differential pressure transducer (Model: DP 103-10, Validyne Engineering, Los Angeles, CA) as shown in Fig. 3(b). Comparison between the numerical and experimental pressure drop is displayed in Fig. 3(a) for three tracheal flow rates and showed good agreement with a maximum error of 5.54%.

3 Results and Discussion

3.1 Flow in a Three-Generation Airway. Secondary flow patterns in a simplified geometry were also investigated and compared with an earlier numerical study [19]. The latter investigated steady inspiratory airflow in a third-generation airway geometry based on fifth to seventh generations, where bifurcation angles in both generations were 70 deg and all bifurcations were in the same plane. The current study used the same geometry and boundary conditions as the earlier study to facilitate comparisons, but used a finer mesh to provide more flow details.

The axial and the secondary velocity profiles in the midsections of sixth and seventh generation daughter airways are shown in Fig. 4, and demonstrated flow patterns similar to the earlier study [19]. For example, two symmetric vortices were observed in sixth generation daughter airways, which are consistent with previous experimental observations in inspiratory flow [2].

3.2 Flow in a Model of the Pig Airways—Trachea and Main Bronchi. Figure 5(c) shows the model geometry while Fig. 5(a) shows a map of the axial velocity at a cross section that includes the trachea, the main bronchi, and part of the tracheal bronchus (that feeds the top right lung lobe). The axial flow at the tracheal entrance shows a developing flow profile with a relatively lowered maximum velocity and flatter velocity profile compared to Poiseuille flow. There is also a lowered velocity region around the tracheal bronchus entrance where a stagnation point is formed

Fig. 2 Comparison between simulated and measured velocity distributions at different bifurcation planes for an inlet $Re = 1500$

Fig. 3 (a) Pressure drop comparison between simulation and experiment and (b) simplified symmetric pig airway and pressure probe locations

at this flow branching. This lowered velocity region can also be seen in the isosurface of a velocity magnitude of 1.2 ms^{-1} as shown in Fig. 5(c). This lowered velocity region disappears when the tracheal bronchus is blocked (see Fig. 5(b)).

While the flow rate in the tracheal bronchus affects the flowrate in the trachea, it appeared to have small effects ($<1\%$) on the flow dividing ratio between the left and right bronchi (Table 2).

The bulk axial flow in the trachea is divided near the carina where majority of the flow is guided into the right main bronchus due, at least in part, to the smaller bifurcation angle between trachea and the right main bronchus, which is similar to the human airways geometry. It can also be seen (Fig. 5(a)) that as the flow

passes carina, the high velocity flow tends to move toward the inner walls of the left and right main bronchi due to the centrifugal force generated by the curved flow in the bronchi.

3.2.1 Secondary Flow in Main Bronchi. Secondary flows (perpendicular to the airway axis) are shown in Fig. 6(a) at the cross section of the mainstem bronchi, where two counter-rotating vortices were seen in each cross section. These vortices were not symmetric compared to the vortices reported in the previous simplified bifurcation geometries [19]. This nonsymmetric profile may be due to the irregular geometry of the realistic airways.

Fig. 4 (a) Velocity profile in the bifurcation plane, (b) secondary velocity vectors on section 1-1', (c) section 2-2', (d) section 3-3', (e) axial velocity profiles on section 1-1', (f) section 2-2', and (g) section 3-3'

Fig. 5 A map of the axial velocity at a cross section that includes the trachea and the main bronchi (a) with (b) without (blocked) tracheal bronchus. (c) Iso-surface of the mean velocity magnitude.

When the tracheal bronchus was blocked in the current study, the secondary flow patterns in main bronchi were more similar, and the secondary velocity magnitude was higher, which may be due the higher flow rates in this case.

3.2.2 Vortex Core Visualization in the Main Bronchi. To further visualize the 3D vortical structures generated by secondary flows, the absolute value of the helicity vector $|(\nabla \times U) \cdot U|$ can be used [52]. Figure 6(b) shows a zoomed view of the helicity in

Table 2 Mass flow ratios as a percentage of the tracheal and right mainstem mass flow rates

Airway	% of tracheal flow	% of right mainstem flow
Tracheal bronchus w/tracheal bronchus flow	8.00%	16.05%
Left main bronchi w/tracheal bronchus flow	42.15%	84.55%
Right main bronchi w/tracheal bronchus flow	49.85%	100%
Left main bronchi w/o tracheal bronchus flow	46.09%	85.49%
Right main bronchi w/o tracheal bronchus flow	53.91%	100%

Fig. 6 (a) Secondary velocity streamlines and axial velocity distributions at cross section of main bronchi and (b) a zoomed view of the helicity iso-surface and the secondary flow vectors near the carina

the neighborhood of the main carina where the streamlines highlight a counter-rotating vortex pair that is typical of Dean flow in each of the two mainstem bronchi.

3.3 Flow in More Distal Pig Airways. The axial flow velocity and streamlines are shown in Figs. 7 and 8 at 10 cross section for the right and left lungs, respectively. It can be seen that some sections (such as: 4-4', 7-7' in right lung and 2-2', 4-4', 6-6' in left lung) show secondary vortices resembling the Dean flow patterns. However, secondary flows in most of these sections showed less organized vortical structures compared to the flow in the simplified bifurcation (Fig. 4(b)). To further visualize vortical structures in the airways, helicity isosurfaces are shown in Fig. 9(a), which suggests the existence of vortical structures in the majority of the airways.

3.4 Comparison Between Laminar and Turbulent Results.

Figure 10(a) shows the axial velocity magnitude and secondary flow streamlines at several airway cross sections while Fig. 10(b) shows the axial velocity profiles at the same cross sections and a map of the axial velocity magnitude. The velocity profiles in the trachea (sections: a-a', b-b') show a developing flow pattern while the velocity distribution in the main daughters (sections: c-d', d-d') resemble Dean's type patterns. The results of Fig. 10 suggest that there is only a small velocity difference between laminar and turbulent flow was seen (e.g., maximum velocity difference was $\sim 0.1\%$).

To further investigate the turbulent flow characteristics, TKE was calculated (Fig. 9(b)). The highest TKE was near the carina where the flow bifurcates. Regions of high TKE were also seen at the inner walls of the main bronchi, which coincided with high

Fig. 7 The axial velocity and secondary flow streamlines at different cross section in right lung

Fig. 8 The axial velocity and secondary flow streamlines at different cross section in left lung

Fig. 9 (a) Absolute helicity iso-surface of the airway tree and (b) TKE distribution at a cross section of airway tree

Fig. 10 (a) Velocity distribution at airway sections for laminar and turbulent ($k-\omega$) models and (b) axial velocity profiles in the trachea and mainstem bronchi

velocity regions (Fig. 10(b)). It can be also seen in Fig. 9(b) that the turbulent kinetic energy is approximately zero in the distal airways, which suggests that the flow in these airways approaches laminar flow conditions.

3.5 Effects of Morphological Differences Between Pig and Human Airways on Airflow. There are geometrical differences between the pig and of human airways. Pig airway geometrical differences include the existence of a tracheal bronchus and monopodial bifurcation morphology of the two main bronchi, which tend to continue in the same general direction for several generations [28]. Our study showed that 8% of tracheal inlet flow goes to the tracheal bronchus while 49.8% and 42.1% of the flow is consumed by right and left lung, respectively. These ratios are different from humans. For example, a previous study [7] of a five-generation human airway model showed that flow ratios into the right and left lungs were approximately 56% and 44%, which were insensitive to the inlet Reynolds number. However, flow rate ratios of 54% and 46%, which are similar to the human ratios, were observed in the current

study when tracheal bronchus was blocked. This agreement is likely because the pig airway angles and diameters at the tracheal carina in the current study have similarly to humans [28]. A recent study [31] in small pigs (weight ~ 1 kg) reported the particle ventilation fractions to the right lung, left lung, and tracheal bronchus. Although the pigs in that study were much smaller than the current study, the reported particle ventilation fraction values were similar (maximum difference is $<1\%$) to the respective flow ratio values calculated in the current study. This may be because the particle ventilation fraction equals the flow ventilation fraction for particles with small Stokes number (<0.3) [31]. Hence, it may be concluded that particle ventilation fractions in to right and left lungs of human are likely similar to those of pig lung for particles with small Stokes number in absence of tracheal bronchus. However, for generations beyond the mainstem bronchi (section 1-1' in Fig. 7 and section 1-1' in Fig. 8), the highly asymmetric monopodial branching will affect flow rate ratios.

The flow rate distribution results shown in Fig. 11 suggest that higher percentage of the flow remains in the major daughters (i.e.,

Fig. 11 Flow ratio percentages in to different sections of the airway (refer Figs. 7 and 8 for location of the sections)

Fig. 12 Comparison of the pressure drop per unit length (box and whiskers plot)

right lung: sections 1-1', 3-3', 5-5' in Fig. 7 and left lung: sections 1-1', 4-4' in Fig. 8) while small fraction of the flow is delivered to lateral airways (i.e., the minor daughters). This is likely due to the monopodial bifurcation pattern in pig airway [28], which is different from that of humans. For example, at highly asymmetric bifurcations (e.g., sections 2-2', 4-4', 6-6' in Fig. 7 and 2-2', 3-3', 5-5' in Fig. 8) the flow ratio (minor/major daughter) is typically between 0.1 and 0.35 compared to 0.15–0.6 in the less asymmetric human airways [7]. Higher flow rates in major daughters (such as 3-3', 5-5', and 9-9' of Fig. 7) imply that higher number of particles (with small Stokes number) will travel more efficiently (compared to humans) through these branches to higher airway generations. Moreover, higher flow rates in main stem bronchi tended to spread high turbulent kinetic energy region further downstream from the carina (Fig. 11(b)). As turbulence is typically associated with higher mixing, more particle mixing may take place in pigs more than humans. Turbulent flow is also

widely speculated as a mechanism of breath sounds [53]. The wider spread of turbulence in the monopodial branching morphology can possibly causes sound sources to be distributed deeper into the airways and subsequently changing the spatial distribution and the propagation of breath sounds in the airways compared to that in human. These differences need to be taken into consideration when interpreting the results of animal studies involving pigs before generalizing these results for humans.

3.6 Pressure Drop in the Pig Airways. The pressure drop from the simulation was calculated for comparison with the Poiseuille pressure drop and the “real” pressure drop suggested by an earlier study [54] for symmetric airway bifurcations. In Poiseuille and real pressure drop calculations, the lung airways were first divided into segments of straight tubes. Each straight pipe had constant diameter (D) that equals the mean segment diameter, a

length (L) that includes the bifurcation transition zones, and a mass flow ($\dot{m}$) derived from the simulation results. The Poiseuille pressure drop, ΔP , was calculated from the dimensions of the segments and the mass flow rate using Eq. (7).

$$\Delta P = \frac{\dot{m} 128\mu L}{\rho \pi D^4} \quad (7)$$

The real pressure drop (ΔP_{real}) was calculated from Eq. (8) [54].

$$\Delta P_{\text{real}} = \frac{C}{4\sqrt{2}} \left(\text{Re} \frac{D}{L} \right)^{\frac{1}{2}} \Delta P \quad (8)$$

where Re is the Reynolds number and C is an empirical constant that equals 1.85 for symmetric bifurcations [54]. The viscous pressure drop from the simulation was determined as the drop in total pressure which denotes the energy loss in the Bernoulli equation [55]. In the simulation results, the pressure values at any cross section were not uniform. Hence, mass averaged pressures were used in the pressure drop calculations similar to previous studies [32]. The pressure drop results are plotted in Fig. 12 against the airway generation, where the generation number was determined by a previous study [27,28]. Figure 12 also shows a comparison with the predictions of Eqs. (7) and (8).

As can be seen in the figure, the pressure drop from the simulation tended to be between the predictions of Eqs. (7) and (8) in the vast majority of cases. The constant C , in Eq. (8), was set to 1.85 as recommended for symmetric bifurcations with bifurcation angles of 70 deg [54]. A later study suggested reducing the value of this constant by 33% [31] for slightly asymmetric bifurcations. In the current study, C values of 1.15 ± 0.13 (Mean $\pm$ SEM) would lead to agreement between our simulation results and Eq. (8) predictions. These values are 38% lower than those for symmetric airway bifurcations [54] and are comparable with those for asymmetric bifurcations [32]. The smaller values may be due, at least in part, to the fact that most bifurcations in the current study are highly nonsymmetric with relatively small deflection angles (< 15 deg) for the major daughter [27]. The lower values of C can be also due to the plug flow profile at the tracheal inlet, which is more realistic than the Poiseuille flow distribution assumed in deriving Eq. (8) [9].

4 Conclusion

Steady inspiratory flow in simplified airways bifurcations and in realistic models of pig airways was numerically studied using CFD for both laminar and turbulent cases. Secondary flows were observed where two counter-rotating vortices were seen in the daughter airways in the simplified model, resembling the Dean-type flow. However, the secondary flow patterns in the realistic pig airways varied significantly, where some daughters did not exhibit flow patterns with clear counter-rotating vortical structures. Results showed that only 8% of the inlet flow was consumed by the tracheal bronchus and that the flow ratios between the left and right mainstem bronchi were similar to human airways when the tracheal bronchus is open or blocked. To study the turbulent flow case, turbulent intensity was imposed at the tracheal inlet to account for the turbulence generated in upper airways. Turbulence was found to have insignificant effects on axial and secondary flow patterns at the considered flow rate. Furthermore, the flow tended to become laminar when it reaches higher airway generations. Flow rate distribution study showed that higher percentage of the total flow exists in the major daughters compared to minor daughters. The pressure drop in the simulation agreed with the predictions of Eq. (8) when the empirical constant C was assigned values comparable to those proposed for asymmetric bifurcations [32].

Funding Data

- National Institutes of Health (NIH) (Grant Nos. R01EB012142 and R43HL099053).

References

- [1] Farag, A., Hammersley, J., Olson, D., and Ng, T., 2000, "Mechanics of the Flow in the Small and Middle Human Airways," *ASME J. Fluids Eng.*, **122**(3), pp. 576–584.
- [2] Schroter, R., and Sudlow, M., 1969, "Flow Patterns in Models of the Human Bronchial Airways," *Respir. Physiol.*, **7**(3), pp. 341–355.
- [3] Rossmann Jr, C. A., 2015, "Pressure Loss Coefficients for Asymmetric Bifurcations of Pulmonary Airways With Predetermined Flow Distributions," *J. Bioeng. Biomed. Sci.*, **5**, p. 148.
- [4] Banko, A. J., Coletti, F., Schiavazzi, D., Elkins, C. J., and Eaton, J. K., 2015, "Three-Dimensional Inspiratory Flow in the Upper and Central Human Airways," *Exp. Fluids*, **56**, p. 117.
- [5] Lin, C. L., Tawhai, M. H., McLennan, G., and Hoffman, E. A., 2007, "Characteristics of the Turbulent Laryngeal Jet and Its Effect on Airflow in the Human Intra-Thoracic Airways," *Respir. Physiol. Neurobiol.*, **157**(2), pp. 295–309.
- [6] de Rochefort, L., Vial, L., Fodil, R., Maitre, X., Louis, B., Isabey, D., Caillibotte, G., Thiriet, M., Bittoun, J., Durand, E., and Shirlea-Apiou, G., 2007, "In Vitro Validation of Computational Fluid Dynamic Simulation in Human Proximal Airways With Hyperpolarized ^3He Magnetic Resonance Phase-Contrast Velocimetry," *J. Appl. Physiol.*, **102**(5), pp. 2012–2023.
- [7] Luo, H. Y., and Liu, Y., 2008, "Modeling the Bifurcating Flow in a CT-Scanned Human Lung Airway," *J. Biomech.*, **41**(12), pp. 2681–2688.
- [8] Lin, C. L., Tawhai, M. H., McLennan, G., and Hoffman, E. A., 2009, "Computational Fluid Dynamics," *IEEE Eng. Med. Biol. Mag.*, **28**(3), pp. 25–33.
- [9] Wells, A., Jones, I., Hamill, S., and Bordas, R., 2017, "The Prediction of Viscous Losses and Pressure Drop in Models of the Human Airways," *Int. J. Numer. Methods Biomed. Eng.*, **33**, pp. 2898–2916.
- [10] Liu, Y., So, R. M. C., and Zhang, C. H., 2003, "Modeling the Bifurcating Flow in an Asymmetric Human Lung Airway," *J. Biomech.*, **36**(7), pp. 951–959.
- [11] Gemci, T., Ponyavin, V., Chen, Y., Chen, H., and Collins, R., 2008, "Computational Model of Airflow in Upper 17 Generations of Human Respiratory Tract," *J. Biomech.*, **41**(9), pp. 2047–2054.
- [12] Chang, H., and El Masry, O. A., 1982, "A Model Study of Flow Dynamics in Human Central Airways—Part I: Axial Velocity Profiles," *Respir. Physiol.*, **49**(1), pp. 75–95.
- [13] Isabey, D., and Chang, H., 1982, "A Model Study of Flow Dynamics in Human central Airways—Part II: Secondary Flow Velocities," *Respir. Physiol.*, **49**(1), pp. 97–113.
- [14] Pedley, T., 1977, "Pulmonary Fluid Dynamics," *Annu. Rev. Fluid Mech.*, **9**, pp. 229–274.
- [15] Weibel, E. R., 1963, *Geometry and Dimensions of Airways of Conductive and Transitory Zones*, Springer, Berlin.
- [16] Horsfield, K., Dart, G., Olson, D. E., Filley, G. F., and Cumming, G., 1971, "Models of the Human Bronchial Tree," *J. Appl. Physiol.*, **31**(2), pp. 207–217.
- [17] Yang, X. L., Liu, Y., So, R. M., and Yang, J. M., 2006, "The Effect of Inlet Velocity Profile on the Bifurcation COPD Airway Flow," *Comput. Biol. Med.*, **36**(2), pp. 181–94.
- [18] Nowak, N., Kakade, P. P., and Annapragada, A. V., 2003, "Computational Fluid Dynamics Simulation of Airflow and Aerosol Deposition in Human Lungs," *Ann. Biomed. Eng.*, **31**(4), pp. 374–390.
- [19] Liu, Y., So, R., and Zhang, C., 2003, "Modeling the Bifurcating Flow in a Human Lung Airway," *J. Biomech.*, **35**(4), pp. 465–473.
- [20] Freitas, R. K., and Schroder, W., 2008, "Numerical Investigation of the Three-Dimensional Flow in a Human Lung Model," *J. Biomech.*, **41**(1), pp. 2446–57.
- [21] Douglas, J. S., Dennis, M. W., Ridgway, P., and Bouhuys, A., 1972, "Airway Dilatation and Constriction in Spontaneously Breathing Guinea Pigs," *J. Pharmacol. Exp. Ther.*, **180**(1), pp. 98–109.
- [22] Churg Andrew, J. L. W., 2016, "A Model of Tobacco Smoke-Induced Airflow Obstruction in the Guinea Pig," *Chest J.*, **121**(5), pp. 188S–191S.
- [23] Kang, K. H., Morrow, J. D., Roberts, L. J., II, Newman, J. H., and Banerjee, M., 1993, "Airway and Vascular Effects of 8-Epi-Prostaglandin F2 Alpha in Isolated Perfused Rat Lung," *J. Appl. Physiol.*, **74**(1), pp. 460–465.
- [24] Nadel, J. A., and Widdicombe, J. G., 1962, "Effect of Changes in Blood Gas Tensions and Carotid Sinus Pressure on Tracheal Volume and Total Lung Resistance to Airflow," *J. Physiol.*, **163**(1), pp. 13–33.
- [25] Mansy, H., Royston, T., Balk, R., and Sandler, R., 2002, "Pneumothorax Detection Using Pulmonary Acoustic Transmission Measurements," *Med. Biol. Eng. Comput.*, **40**(5), pp. 520–525.
- [26] Kabilan, S., Lin, C.-L., and Hoffman, E. A., 2007, "Characteristics of Airflow in a CT-Based Ovine Lung: A Numerical Study," *J. Appl. Physiol.*, **102**(4), pp. 1469–1482.
- [27] Mansy, H. A., Azad, M. K., McMurray, B., Henry, B., Royston, T., and Sandler, R. H., 2015, "Investigating the Geometry of Pig Airways Using Computed Tomography," *SPIE Med. Imag.*, **9417**, p. 94172N.
- [28] Azad, M. K., Mansy, H. A., and Gamage, P. T., 2016, "Geometric Features of Pig Airways Using Computed Tomography," *Physiol. Rep.*, **4**, p. e12995.
- [29] Dai, Z., Peng, Y., Henry, B. M., Mansy, H. A., Sandler, R. H., and Royston, T. J., 2014, "A Comprehensive Computational Model of Sound Transmission Through the Porcine Lung," *J. Acoust. Soc. Am.*, **136**(3), pp. 1419–1429.
- [30] Peng, Y., Dai, Z., Mansy, H. A., Henry, B. M., Sandler, R. H., Balk, R. A., and Royston, T. J., 2016, "Sound Transmission in Porcine Thorax Through Airway Insonification," *Med. Biol. Eng. Comput.*, **54**(4), pp. 675–689.
- [31] Awadalla, M., Miyawaki, S., Alaiwa, M. H. A., Adam, R. J., Bouzek, D. C., Michalski, A. S., Fuld, M. K., Reynolds, K. J., Hoffman, E. A., Lin, C.-L., and Stoltz, D. A., 2014, "Early Airway Structural Changes in Cystic Fibrosis Pigs as a Determinant of Particle Distribution and Deposition," *Ann. Biomed. Eng.*, **42**(4), pp. 915–927.

- [32] van Ertbruggen, C., Hirsch, C., and Paiva, M., 2005, "Anatomically Based Three-Dimensional Model of Airways to Simulate Flow and Particle Transport Using Computational Fluid Dynamics," *J. Appl. Physiol.*, **98**(3), pp. 970–980.
- [33] Stapleton, K.-W., Guentsch, E., Hoskinson, M., and Finlay, W., 2000, "On the Suitability of $k-\epsilon$ Turbulence Modeling for Aerosol Deposition in the Mouth and Throat: A Comparison With Experiment," *J. Aerosol. Sci.*, **31**(6), pp. 739–749.
- [34] Zhang, Z., and Kleinstreuer, C., 2004, "Airflow Structures and Nano-Particle Deposition in a Human Upper Airway Model," *J. Comput. Phys.*, **198**(1), pp. 178–210.
- [35] Hardin, J., and Patterson, J., 1979, "Monitoring the State of the Human Airways by Analysis of Respiratory Sound," *Acta Astronaut.*, **6**(9), pp. 1137–1151.
- [36] Zhang, Z., and Kleinstreuer, C., 2002, "Transient Airflow Structures and Particle Transport in a Sequentially Branching Lung Airway Model," *Phys. Fluids*, **14**(2), pp. 862–880.
- [37] Fresconi, F. E., and Prasad, A. K., 2007, "Secondary Velocity Fields in the Conducting Airways of the Human Lung," *ASME J. Biomech. Eng.*, **129**(5), pp. 722–732.
- [38] Schroeder, A., and Willert, C. E., 2008, *Particle Image Velocimetry: New Developments and Recent Applications*, Vol. 112, Springer Science & Business Media, Berlin.
- [39] Kleinstreuer, C., and Zhang, Z., 2010, "Airflow and Particle Transport in the Human Respiratory System," *Annu. Rev. Fluid Mech.*, **42**, pp. 301–334.
- [40] Li, Z., Kleinstreuer, C., and Zhang, Z., 2007, "Simulation of Airflow Fields and Microparticle Deposition in Realistic Human Lung Airway Models—Part I: Airflow Patterns," *Eur. J. Mech.-B/Fluids*, **26**(5), pp. 632–649.
- [41] Wilcox, D. C., 1998, *Turbulence Modeling for CFD*, Vol. 2, DCW Industries, La Canada, CA.
- [42] Wilcox, D. C., 2008, "Formulation of the $k-x$ Turbulence Model Revisited," *AIAA J.*, **46**(11), pp. 2823–2838.
- [43] Ma, B., and Lutchien, K. R., 2006, "An Anatomically Based Hybrid Computational Model of the Human Lung and Its Application to Low Frequency Oscillatory Mechanics," *Ann. Biomed. Eng.*, **34**(11), pp. 1691–704.
- [44] Wall, W. A., and Rabczuk, T., 2008, "Fluid-Structure Interaction in Lower Airways of CT-Based Lung Geometries," *Int. J. Numer. Methods Fluids*, **57**(5), pp. 653–675.
- [45] Yushkevich, P. A., Piven, J., Hazlett, H. C., Smith, R. G., Ho, S., Gee, J. C., and Gerig, G., 2006, "User-Guided 3D Active Contour Segmentation of Anatomical Structures: Significantly Improved Efficiency and Reliability," *Neuroimage*, **31**(3), pp. 1116–1128.
- [46] CD-adapco, 2017, "Star-CCM+ User Manual," CD-adapco, Melville, NY, accessed Nov. 17, 2017, <http://www.cd-adapco.com/products/star-ccm/documentation>
- [47] Celik, I. B., Ghia, U., Roache, P. J., and Christopher, 2008, "Procedure for Estimation and Reporting of Uncertainty Due to Discretization in CFD Applications," *ASME J. Fluids Eng.*, **130**(7), p. 078001.
- [48] Khalili, F., Gamage, P. P. T., and Mansy, H. A., 2017, "Hemodynamics of a Bileaflet Mechanical Heart Valve With Different Levels of Dysfunction," *J. Appl. Biotechnol. Bioeng.*, **2**(5), p. 00044.
- [49] Eckelmann, H., 1974, "The Structure of the Viscous Sublayer and the Adjacent Wall Region in a Turbulent Channel Flow," *J. Fluid Mech.*, **65**(3), pp. 439–459.
- [50] Ariff, M., Salim, S. M., and Cheah, S. C., 2009, "Wall $y+$ Approach for Dealing With Turbulent Flow Over a Surface Mounted Cube—Part 2: High Reynolds Number," *Seventh International Conference on CFD in the Minerals and Process Industries CSIRO*, Melbourne, Australia, Dec. 9–11, pp. 1–9.
- [51] Azad, M. K., and Mansy, H. A., 2016, "Generation of Pig Airways Using Rules Developed From the Measurements of Physical Airways," *J. Bioeng. Biomed. Sci.*, **6**(4), p. 203.
- [52] Degani, D., Seginer, A., and Levy, Y., 1990, "Graphical Visualization of Vortical Flows by Means of Helicity," *AIAA J.*, **28**(8), pp. 1347–1352.
- [53] Olson, D. E., and Hammersley, J. R., 1985, "Mechanisms of Lung Sound Generation," *Semin. Respir. Med.*, **6**(3), pp. 171–179.
- [54] Pedley, T., Schroter, R., and Sudlow, M., 1970, "Energy Losses and Pressure Drop in Models of Human Airways," *Respir. Physiol.*, **9**(3), pp. 371–386.
- [55] Young, D. F., Munson, B. R., Okiishi, T. H., and Huebsch, W. W., 2010, *A Brief Introduction to Fluid Mechanics*, Wiley, Hoboken, NJ.