Published in final edited form as:

J Quant Spectrosc Radiat Transf. 2017 February ; 188: 200–213. doi:10.1016/j.jqsrt.2016.02.006.

A FDTD solution of scattering of laser beam with orbital angular momentum by dielectric particles: Far-field characteristics

Wenbo Sun^{a,*}, Yongxiang Hu^b, Carl Weimer^c, Kirk Ayers^a, Rosemary R. Baize^b, Tsengdar Lee^d

^aScience Systems and Applications Inc., Hampton, VA 23666, USA

^bNASA Langley Research Center, Hampton, VA 23681, USA

^cBall Aerospace and Technologies Corp., Boulder, CO 80301, USA

^dNASA Headquarters, Washington, DC 20546, USA

Abstract

Electromagnetic (EM) beams with orbital angular momentum (OAM) may have great potential applications in communication technology and in remote sensing of the Earth-atmosphere system and outer planets. Study of their interaction with optical lenses and dielectric or metallic objects, or scattering of them by particles in the Earth-atmosphere system, is a necessary step to explore the advantage of the OAM EM beams. In this study, the 3-dimensional (3D) scattered-field (SF) finite-difference time domain (FDTD) technique with the convolutional perfectly matched layer (CPML) absorbing boundary conditions (ABC) is applied to calculate the scattering of the purely azimuthal (the radial mode number is assumed to be zero) Laguerre-Gaussian (LG) beams with the OAM by dielectric particles. We found that for OAM beam's interaction with dielectric particles, the forward-scattering peak in the conventional phase function (P11) disappears, and light scattering peak occurs at a scattering angle of $\sim 15^\circ$ to 45° . The disappearance of forward-scattering peak means that, in laser communications most of the particle-scattered noise cannot enter the receiver, thus the received light is optimally the original OAM-encoded signal. This feature of the OAM beam also implies that in lidar remote sensing of the atmospheric particulates, most of the multiple-scattering energy will be off lidar sensors, and this may result in an accurate profiling of particle layers in the atmosphere or in the oceans by lidar, or even in the ground when a ground penetration radar (GPR) with the OAM is applied. This far-field characteristics of the scattered OAM light also imply that the optical theorem, which is derived from plane-parallel wave scattering case and relates the forward scattering amplitude to the total cross section of the scatterer, is invalid for the scattering of OAM beams by dielectric particles.

Keywords

Electromagnetic beams; Orbital angular momentum; Scattering; Remote sensing

*Corresponding author. wenbo.sun-1@nasa.gov (W.Sun).

1. Introduction

An electromagnetic (EM) wave can carry not only translational motion energy but also angular momentum around the propagation direction. There are two forms of angular momentum: light spin angular momentum (SAM) related to polarized electromagnetic field vector's spinning around the EM beam axis and the orbital angular momentum (OAM) related to the spatial field distribution (wave-front helical shape) of light [1–8]. Light's OAM can be generated by propagating through a spiral phase plate [2], diffracting on a fork-like or pitchfork hologram [3–6], applying a q-plate with a SAM sign-change [7,8], or converting a Hermite-Gaussian beam into a Laguerre-Gaussian beam by using two cylindrical lenses [1]. Light's OAM has potential applications in manipulation of particles in optical tweezers [9], high-bandwidth information encoding in optical communication [10], high-dimensional quantum information encoding [11–13], and optical detection [14]. In this study, we will explore the potential of the Laguerre-Gaussian (LG) beams having the OAM for remote sensing of the Earth-atmosphere system and outer planets. To explore the advantage of the OAM of light in remote sensing applications we must firstly study the interaction of light beam having the OAM with optical lenses and dielectric or metallic objects, or scattering of it by surfaces or particles in the Earth-atmosphere system. Scattering of light beam with the OAM has been studied in many previous works (e.g. [15–20]), but none of these has ever reported the light scattering phase matrix elements (e.g. [21]) for the OAM beam's scattering by dielectric particles, which are the most important parameters for radiative transfer and remote sensing studies. Our objective in this work is to study the scattering of laser beam with the OAM by dielectric particles, with emphasis on the light scattering phase matrix elements, which has significance for remote sensing of clouds and aerosols in the atmosphere. The algorithm we applied to calculate the scattering of the OAM laser beam by dielectric particles is introduced in Section 2. Numerical results and discussions are shown in Section 3. Conclusion is given in Section 4.

2. Methodology

Since our study is not only for spherical particles as reported in [15–20], we use the 3-dimensional (3D) scattered-field (SF) finite-difference time domain (FDTD) technique [21–24] with the convolutional perfectly matched layer (CPML) absorbing boundary conditions (ABC) [25] to calculate the scattering of the OAM laser beam by dielectric particles of any shapes. Technical details of the FDTD method used in this study can be found in Sun et al. [21–24,26,27]. The accuracy of the FDTD method is documented in [21,24,26]. The only difference of this study from previous work [22–24] in the numerical modeling of light scattering is that the incident light is a Laguerre-Gaussian beam with electric field amplitude approximated by [1]

$$E(r, \varphi, z) = \frac{C_{Lp}}{w(z)} \left(\frac{r\sqrt{2}}{w(z)} \right)^{|L|} \exp\left(-\frac{r^2}{w^2(z)}\right) L_p^{|L|} \left(\frac{2r^2}{w^2(z)} \right) \exp\left(ik\frac{r^2}{2R(z)}\right) \exp(iL\varphi) \exp[i(2p + |L| + 1)\zeta(z)], \quad (1)$$

where C_{Lp} is a normalization constant, $L_p^{|L|}$ are the generalized Laguerre polynomials, the radial index $p \geq 0$ and the azimuthal index is L . ϕ is the azimuth angle around the central axis of the beam; r is the radial distance from the center axis of the beam; z is the axial distance from the beam's narrowest point (the "waist"); $w(z)$ is the radius at which the field amplitude drops to $1/e$ of their axial values, which has a form $w(z) = w_0 \sqrt{1 + (z/z_R)^2}$, where $Z_R = \pi w_0^2 / \lambda$, λ is the wavelength, and $w_0 = w(0)$ is the waist size of the beam; $R(z)$ is the radius of curvature of the beam's wave fronts, which has a form $R(z) = z[1 + (z_R/z)^2]$; and $\zeta(z)$ is the Gouy phase shift, which defines a phase shift differing from that for a plane wave and has a form $\zeta(z) = \arctan(z/z_R)$. In this study, we use the purely azimuthal (the radial mode number p is assumed to be zero) Laguerre-Gaussian (LG) beams for the modeling. When $L=0$, this is a regular Gaussian beam with maximum amplitude at the central axis. When $L \neq 0$, there is phase delay as function of ϕ around the central axis of the beam, which results in a spiral wave front of the EM beam and thus the beam has the OAM.

In this study, we assume that a dielectric particle is positioned at the center of the FDTD computational domain, as illustrated in Fig. 1. The laser beam is incident in the z -direction and its central axis is at a distance of d from the center of the computational domain. The FDTD computational domain is bounded by the CPML, which numerically absorbs the scattered light to truncate the computational domain to a limited 3D space. Although the FDTD method can calculate light's interaction with particles of any shapes, we firstly use a spherical particle in this study to simplify the problem for an easier understanding of the physics in the results. We do calculations for different particle sizes and assume laser beams of various waist sizes with their central axis positioned at different locations in the computational domain, to observe a systematic scattering pattern change caused by the particle and laser beam parameter variations. The calculated scattering properties of the particle under various incidence conditions are normalized by the incident rate of the original laser beam in free-space within the particle's projected area, as illustrated in Fig. 2.

In Fig. 2, $I_{inc}(x, y) = \frac{1}{2c\mu_0} |E|^2(r, \phi, z)$ (where c is light speed in free space and is the permeability of free space) denotes the flux of the laser beam at a position (x, y) on a plane z crossing the beam's incident direction. In this study, the waist of the beam is assumed to be at $z=0$, the particle center is set at $(0, 0, 0)$, so this $I_{inc}(x, y) = \frac{1}{2c\mu_0} |E|^2(r, \phi, 0)$.

3. Results and discussions

3.1. Spherical particles

In this study, we assume a spherical particle with a refractive index of $1.31 + 0.01i$ is under the incidence of a Laguerre-Gaussian beam with $p=0$, and $L=0, 1, 2$, and 3 , respectively. In the FDTD simulations, the Laguerre-Gaussian beam is assumed to be polarized in x and y direction, respectively. The far-field single-scattering properties of the particle under the beam's incidence is calculated with the near-field x -polarized and y -polarized values transformed from the time series of the fields from the FDTD calculations [21]. The FDTD spatial cell size is set as $\Delta s = \lambda/20$, where λ is the incident wavelength [21,26]. The CPML is set to be $6\Delta s$ thick and a free space of $6\Delta s$ is set between the particle surface and the CPML

inner surface [26]. The time step for the FDTD simulation is set to be $\Delta t = \Delta z/(2c)$, where c is light speed in free space [21,26].

We use a Laguerre-Gaussian beam of $p=0$ and $L=0,1,2$, and 3, respectively, to study the characteristics of a dielectric particle's scattering to light beams with the OAM. Fig. 3 shows the electric field of a Laguerre-Gaussian beam of $p=0$ and $L=0, 1, 2$, and 3, respectively, in free space on the x - o - y ($z=0$) plane (a cut of the beam facing the observer) at a FDTD time step of 600. The beam has a waist size of $w_0 = 20\lambda$ s and propagates in z direction. The FDTD computational domain has $101 \times 101 \times 101$ cubic cells including the spatial cells in the CMPL. The electric field shown here is normalized by $(C_{Lp}/\text{unit of length})$, therefore it has no unit. We can see the electric field phase change around the central axis of the beam for $L > 0$. This phase change is the reason for the angular momentum around the propagation direction, which appears as the wave-front helical shape of light [1–8].

Fig. 4 shows the phase matrix elements (see [21] for phase matrix elements calculation method in the FDTD model) of a sphere with a size parameter ($x=\pi D/\lambda$, where D denotes the diameter of the particle) of 6 under the incidence of a Laguerre-Gaussian laser beam of $p=0$ and $L=0, 1, 2$, and 3, respectively. The laser beam waist is $w_0=60\lambda$ s, and the central axis of the beam is at $d=0$ from the particle center (i.e. center of the computational domain). We can see that the particle's scattering of the beams with the OAM ($L > 0$) is very different from that of a regular Gaussian beam ($L=0$) in all elements of the phase matrix. The OAM beam unusually pushes the forward-scattering peak back to side-scattering angles by $\sim 15^\circ$ to 45° , depending on the L value. Also, the OAM makes other normalized phase matrix elements P22/P11, P33/P11, and P44/P11 significantly different from those for a regular Gaussian beam ($L=0$) in the neighborhood of back-scattering direction.

Note here that spheres are a very special case of scatterer. In particular, when the sphere is very small and lies on the beam axis, the angular momentum per photon will not be altered by scattering. Thus, one should expect no light at all to be scattered in the exact forward or backward directions for LG beams with $|L| > 0$. However, a non-spherical particle, or moving the sphere off the beam axis, breaks this symmetry and allows some light to be scattered into the exact forward and backward directions. It should be pointed out that the special case of no light in the forward/backward directions depends on the rotational symmetry of the particle, this is the symmetry dependence of scattering of OAM beams as discussed, e.g. in [28].

When the central axis of the beam is off the center of the particle by 15λ s and 30λ s, Figs. 5 and 6 show that the differences in phase matrix elements between the OAM beams and the regular Gaussian beam are reduced. This is because when the particle is close to the edge of the beam with the OAM, the EM field phase change within the range of the particle is reduced. More uniform incident field phase makes the scattering pattern closer to a beam with $L=0$. For a larger particle with a size parameter of 12, Figs. 7–9 show similar results to those in Figs. 4–6, which means the scattering characteristics of beams with the OAM is a common phenomenon for different particle sizes. The extinction efficiencies, scattering efficiencies, absorption efficiencies, and asymmetry factors for the cases in Figs. 4–6 and Figs. 7–9 are listed in Tables 1 and 2, respectively. We can see that for the case of $x=6$ (Table

1), the increase of the OAM order from $L=0$ to $L=3$ monotonically decreases the extinction efficiency, scattering efficiency, and asymmetry factor, but increases the absorption efficiency, wherever the location of the particle in the beam. However, when $x=12$ (Table 2) the increase of the OAM order from $L=0$ to $L=3$ monotonically increases the extinction efficiency, scattering efficiency, and absorption efficiency, but only decreases the asymmetry factor. This demonstrates the complicated nature of particle's scattering to EM beams with the OAM, and worthy of being further studied.

3.2. Non-spherical particles

For the scattering of the laser with the OAM by non-spherical particles, we assume two spheres touching each other and having the same size and refractive index under the radiation by a Laguerre-Gaussian laser beam of $p=0$ and $L=0, 1, 2$, and 3 , respectively. The laser beam waist is $w_0=90$ nm. The size parameter of each sphere is $x=6$. When a particle is nonspherical, not only its position relative to the laser beam, but also its orientation plays a role in the light scattering. We firstly calculate cases as illustrated in Fig. 10, the particle longer axis is parallel to the laser beam central axis. Fig. 11 shows the phase matrix elements of a double-sphere system with a refractive index of $m=1.31$ under the radiation of laser beam modes of $L=0, 1, 2$, and 3 , respectively. The distance of the central axis of the beam from the particle center is $d=0$ nm. The particle longer axis is parallel to the laser beam central axis. We can see that the double-sphere system scatters similar patterns in all phase matrix elements to those of spherical particles in Figs. 4 and 7, with only the secondary maxima in PH different from the PH of spherical particles. When the refractive index of the particle is 1.45 , Fig. 12 shows that all these scattering patterns are similar to those in Fig. 11, but have some difference in magnitude. When the particle is off the central axis of the laser beam by $d=30$ nm, Figs. 13 and 14 show that the scattering phase matrix elements are similar to those in Figs. 6 and 9 for spherical particles, with only the secondary maxima in P11 different from the P11 of spherical particles. These results demonstrate that when the longer axis of a nonspherical particle is in the direction of laser incidence, the OAM laser scattering pattern of the particles are similar to those of spherical particles.

When the longer axis of the nonspherical particle orientates in a direction perpendicular to the laser radiation, as illustrated in Fig. 15, we calculate for three conditions of the particle positions and orientations as illustrated in Fig. 16. Figs. 17 and 18 show the phase matrix elements of a double-sphere system with a refractive index of 1.31 and 1.45 , respectively, under the OAM laser beam mode of $L=0, 1, 2$, and 3 , respectively. The distance of the central axis of the beam from the particle center is $d=0$ nm. The particle longer axis is perpendicular to the laser beam central axis as illustrated in Fig. 16 (a). We can see that the light scattering patterns of $L=0, 1$, and 3 generally follow the aforesaid cases, but the P11 of $L=2$ is different from the group. This is because when $L=2$, as shown in Fig. 3(c), the volume integrals of the fields (from which the scattered field is calculated [21]) in each sphere of the double-sphere system keep same phase at any time, resulting in adding of the scattered light from each sphere in the forward direction. However, when L increases to 3 , the forward scattering intensity is greatly decreased. Also, from Figs. 11, 12, 17 and 18, we can know that if the nonspherical particles are randomly oriented, even for $L=2$, the forward-scattering peak will be significantly reduced.

The phase matrix elements of a double-sphere system under the OAM laser beam mode of $L=0, 1, 2$, and 3 , respectively, at an orientation as illustrated in Fig. 16 (b) and (c) are shown in Figs. 19 and 20, and Figs. 21 and 22, for a refractive index of 1.31 and 1.45 , respectively. We can see these are also similar to those in Figs. 6 and 9 for spherical particles. When the particle is off the central axis of the laser beam, the light phase variation with the particle space is reduced, the OAM laser scattering is closer to that of regular Gaussian beam. Phase difference within the particle space is the critical reason for the disappearance of forward-scattering peak in the OAM laser cases.

Another significant characteristics of the scattered OAM laser is that its P_{22} element is not equal to P_{11} even when the particle is spherical, as shown in Figs. 4–7. This is distinctly different from natural light and laser beams with $L=0$. The $P_{22}/P_{11} < 1$ means that even a spherical particle can depolarize the OAM laser beam due to the asymmetric wave phase on the cross-section of the laser beam inside the particle. This special characteristics of the OAM laser, however, may bring in difficulties in using depolarization ratio to distinguish between spherical and nonspherical particles.

The scattering and asymmetry factors for the cases in Figs. 11–14 and Figs. 17–22 are listed in Tables 3–6, respectively. When the particle is on the central axis of the laser beam, scattering efficiencies significantly change with the OAM mode L . However, when the particle is off the central axis of the laser beam, scattering efficiencies are closer to the case when the particle is under a regular Gaussian beam radiation. Note here that there are numerical errors in the FDTD technique [26]. These errors can be attributed to the numerical dispersion of the finite-difference analog, the approximation of a specific particle shape by a pseudo structure constructed by cubic grid cells, the representation of the near field by the discretized data that do not account for the field variation within each cell, and reflections from the numerical boundary conditions [21–26]. These errors are dependent on the grid size, the cell number in the free space between the scatterer and the absorbing boundary, the cell number in the absorbing boundary, etc. [26]. Therefore, the phase matrix elements, and extinction, scattering, and absorption efficiencies, and asymmetry factors calculated in this study may have several percent of errors. But these errors cannot alter our conclusions from this study.

Moreover, the disappearance of forward-scattering peak as shown by the PH curves is a very good feature of the EM beams with the OAM for communications with laser in the atmosphere or oceans. This property of the OAM laser beam means that, in laser communications most of the particle-scattered noise cannot enter the receiver, thus the received light is optimally the original OAM-encoded signal. This feature of the OAM beam may also have significance in lidar/radar remote sensing of the Earth-atmosphere system or outer planets. The pushing back of the forward-scattering peak in light scattering will keep most of the multiple-scattering energy off lidar/radar sensors in cloud/aerosol remote sensing applications. This may give an accurate profiling of particle layers in the atmosphere or in the oceans, or even have applications for technologies like ground penetration radar (GPR).

4. Conclusion

In this study, we found that an unusual scattering pattern occurs when laser beam has the OAM. For OAM beam's interaction with dielectric particles, the forward peak in the conventional phase function (P11) disappears, and light scattering peak occurs at a scattering angle of $\sim 15^\circ$ to 45° , depending on particle sizes. The disappearance of forward-scattering peak means that, in laser communications most of the particle-scattered noise cannot enter the receiver, thus the received light is optimally the original OAM-encoded signal. This feature of the OAM beam also implies that in lidar/radar remote sensing of the atmospheric particulates, most of the multiple-scattering energy will be off lidar/radar sensors, and this may result in an accurate profiling of particle layers in the atmosphere or in the oceans, or even in the ground when a ground penetration radar (GPR) with the OAM is applied. This far-field characteristics of the scattered OAM light also imply that the optical theorem, which is derived from planeparallel wave scattering case and relates the forward scattering amplitude to the total cross section of the scatterer, is invalid for the scattering of OAM beams by dielectric particles.

Acknowledgment

This work is supported by NASA ESTO ACT project "Lidar Orbital Angular Momentum Sensor".

References

- [1]. Allen L, Beijersbergen MW, Spreeuw RJC, Woerdman JP. Orbital angular momentum of light and the transformation of Laguerre-Gaussian laser modes. *Phys Rev A* 1992;45:8185–9. [PubMed: 9906912]
- [2]. Beijersbergen MW. Helical-wavefront laser beams produced with a spiral phase plate. *Opt Commun* 1994;112:321–7. 10.1016/0030-4018(94)90638-6.
- [3]. Bazhenov VY, Vasnetsov MV, Soskin MS. Laser beams with screw dislocations in their wavefronts. *JETP Lett* 1990;52:429–31.
- [4]. Bazhenov VY, Soskin MS, Vasnetsov MV. Screw dislocations in light wavefronts. *J Mod Opt* 1992;39:985–90. 10.1080/09500349214551011.
- [5]. Heckenberg NR, McDuff R, Smith CP, Rubinsztein-Dunlop H, Wegener MJ. Laser beams with phase singularities. *Opt Quantum Electron* 1992;24:S951–62. 10.1007/BF01588597.
- [6]. Soskin MS, Gorshkov V, Vasnetsov MV, Malos J, Heckenberg N. Topological charge and angular momentum of light beams carrying optical vortices. *Phys Rev A* 1997;56:4064–75. 10.1103/PhysRevA.56.4064.
- [7]. Marrucci L, Manzo C, Paparo D. Optical spin-to-orbital angular momentum conversion in inhomogeneous anisotropic media. *Phys Rev Lett* 2006;96:163905. 10.1103/PhysRevLett.96.163905.
- [8]. Karimi E, Piccirillo B, Nagali E, Marrucci L, Santamato E. Efficient generation and sorting of orbital angular momentum eigenmodes of light by thermally tuned q-plates. *Appl Phys Lett* 2009;94: 231124. 10.1063/13154549.
- [9]. Friese MEJ, Enger J, Rubinsztein-Dunlop H, Heckenberg N. Optical angular-momentum transfer to trapped absorbing particles. *Phys Rev A* 1996;54:1593–6. 10.1103/PhysRevA.54.1593. [PubMed: 9913630]
- [10]. Gibson G, Courtial J, Padgett Mj, Vasnetsov M, Pas'Ko V, Barnett SM, Franke-Arnold S. Free-space information transfer using light beams carrying orbital angular momentum. *Opt Express* 2004;12:5448556.
- [11]. Malik M. Influence of atmospheric turbulence on optical communications using orbital angular momentum for encoding. *Opt Express* 2012;20:13195. 10.1364/OE.20.013195(2012).

- [12]. Boyd RW, Jha A, Malik M, O'Sullivan C, Rodenburg B, Gauthier DJ. Quantum key distribution in a high-dimensional state space: exploiting the transverse degree of freedom of the photon. *Proc SPIE Adv Photonics Quantum Comput Mem Commun IV* 2011;7948: 79480L. 10.1117/12.873491.
- [13]. Barreiro JT, Wei TC, Kwiat PG. Beating the channel capacity limit for linear photonic superdense coding. *Nat Phys* 2008;4: 282–6. 10.1038/nphys919.
- [14]. Foo G, Palacios DM, Swartzlander Ga Jr.. Optical vortex coronagraph. *Opt Lett* 2005;30:3308–10. [PubMed: 16389814]
- [15]. van de Nes AS, Torok P. Rigorous analysis of spheres in Gauss-Laguerre beams. *Opt Express* 2007;15:13360.
- [16]. Garbin V, Volpe G, Ferrari E, Versluis M, Cojoc D, Petrov D. Mie scattering distinguishes the topological charge of an optical vortex. *New J Phys* 2009;11:013046.
- [17]. Zambrana-Puyalto X, Vidal X, Molina-Terriza G. Excitation of single multipolar modes with engineered cylindrically symmetric fields. *Opt Express* 2012;20:24536–44.
- [18]. Rury AS, Freeling R. Mie scattering of purely azimuthal Laguerre-Gauss beams: angular-momentum-induced transparency. *Phys Rev A* 2012;86:053830.
- [19]. Zambrana-Puyalto X, Molina-Terriza G. The role of the angular momentum of light in Mie scattering. Excitation of dielectric spheres with Laguerre-Gaussian modes. *J Quant Spectrosc Radiat Transf* 2013;126:50–5.
- [20]. Kiselev AD, Plutenko DO. Mie scattering of Laguerre-Gaussian beams: photonic nanojets and near-field optical vortices. *Phys Rev A* 2014;89:043803.
- [21]. Sun W, Loeb NG, Fu Q. Finite-difference time domain solution of light scattering and absorption by particles in an absorbing medium. *Appl Opt* 2002;41:5728–43. [PubMed: 12269573]
- [22]. Sun W, Pan H, Videen G. General finite-difference time-domain solution of an arbitrary electromagnetic source interaction with an arbitrary dielectric surface. *Appl Opt* 2009;48:6015–25. [PubMed: 19881669]
- [23]. Sun W, Videen G, Lin B, Hu Y, Fu Q. Beyond Snel's law: refraction of a nano-beam of light. *J Quant Spectrosc Radiat Transf* 2011;112:174–6.
- [24]. Sun W, Videen G, Fu Q, Hu Y. Scattered-field FDTD and PSTD algorithms with CPML absorbing boundary conditions for light scattering by aerosols. *J Quant Spectrosc Radiat Transf* 2013;131:166–74.
- [25]. Roden JA, Gedney SD. Convolutional PML (CPML): an efficient FDTD implementation of the CFS-PML for arbitrary media. *Microw Opt Technol Lett* 2000;27:334–9.
- [26]. Sun W, Fu Q, Chen Z. Finite-difference time domain solution of light scattering by dielectric particles with a perfectly matched layer absorbing boundary condition. *Appl Opt* 1999;38:3141–51. [PubMed: 18319902]
- [27]. Sun W, Videen G, Lin B, Hu Y. Modeling light scattered from and transmitted through periodic structures on a substrate. *Appl Opt* 2007;46:1150–6. [PubMed: 17304315]
- [28]. Nieminen TA, Asavei T, Loke VLY, Heckenberg NR, Rubinsztein-Dunlop H. Symmetry and the generation and measurement of optical torque. *J Quant Spectrosc Radiat Transf* 2009;110:1472–82.

Fig. 1.

Illustration of a particle positioned at the center of the FDTD computational domain and a laser beam with its central axis at a distance of d from the center of the computational domain. The FDTD computational domain is bounded by the CPML.

Fig. 2.

Illustration of the energy rate of a laser beam intercepted by a particle with a projected area PA positioned at a distance from the central axis of the beam, where $I_{inc}(x, y)$ denotes the flux of the laser beam at a position (x, y) on a plane crossing the beam.

Fig. 3. Electric field of a Laguerre-Gaussian beam of $p=0$ and (a) $L=0$, (b) $L=1$, (c) $L=2$, and (d) $L=3$, respectively, in free space on the x - y ($z=0$) plane (a cut of the beam facing the observer) at a FDTD time step of 600. The beam has a waist size of $w_0=20 \text{ } \mu\text{m}$ and propagates in z direction. The FDTD computational domain has $101 \times 101 \times 101$ cubic cells including the spatial cells in the CMPL. The electric field shown here is normalized by $(C_{Lp}/\text{unit of length})$.

Fig. 4.

Phase matrix elements of a sphere with a size parameter $x=6$ under the incidence of a Laguerre-Gaussian beam with $p=0$. The laser waist is $w_0 = 60 \text{ } s$, where $s = \lambda/20$. The beam mode is $L=0, 1, 2$, and 3 , respectively. The distance of the central axis of the beam from the particle center is $d=0 \text{ } s$.

Fig. 5.
Same as Fig. 4 but for $d = 15^\circ$.

Fig. 6.
Same as Fig. 4 but for $d=30$ s.

Fig. 7.

Phase matrix elements of a sphere with a size parameter $x = 12$ under the incidence of a Laguerre-Gaussian beam with $p=0$. The laser waist is $w_0 = 60 \text{ } \mu\text{s}$, where $\text{ } \mu\text{s} = \lambda/20$. The beam mode is $L=0, 1, 2$, and 3 , respectively. The distance of the central axis of the beam from the particle center is $d = 0 \text{ } \mu\text{s}$.

Fig. 8.
Same as Fig. 7 but for $d = 15$ s.

Fig. 9.
Same as Fig. 7 but for $d = 30$ s.

Fig. 10.

Illustration of a double-sphere system under the incidence of a Laguerre-Gaussian beam. The distance of the central axis of the beam from the particle center is d . Particle longer axis is parallel to the laser beam central axis.

Fig. 11.

Phase matrix elements of a double-sphere system with a size parameter $x=6$ for each sphere under the incidence of a Laguerre-Gaussian beam with $p=0$. The refractive index of the particle is $m=1.31$. The laser waist is $w_0 = 90 \text{ } \mu\text{s}$, where $\text{s}=\lambda/20$. The beam mode is $L=0, 1, 2$, and 3 , respectively. The distance of the central axis of the beam from the particle center is $d=0 \text{ } \mu\text{s}$. The particle longer axis is parallel to the laser beam central axis.

Fig. 12.

Same as in Fig. 11, but for a particle with a refractive index of 1.45.

Fig. 13.

Phase matrix elements of a double-sphere system with a size parameter $x=6$ for each sphere under the incidence of a Laguerre-Gaussian beam with $p=0$. The refractive index of the particle is $m=1.31$. The laser waist is $w_0=90A_s$, where $A_s=A/20$. The beam mode is $L=0,1,2$, and 3, respectively. The distance of the central axis of the beam from the particle center is $d=30A_s$. The particle longer axis is parallel to the laser beam central axis.

Fig. 14.

Same as in Fig. 13, but for a particle with a refractive index of 1.45.

Fig. 15.

Illustration of a double-sphere system under the incidence of a Laguerre-Gaussian beam. The distance of the central axis of the beam from the particle center is d . Particle longer axis is perpendicular to the laser beam central axis.

Fig. 16.

A double-sphere system under the incidence of a Laguerre-Gaussian beam. Particle longer axis is perpendicular to the laser beam central axis. (a) Particle is positioned on the central axis of the laser. (b) and (c) Particle is positioned off the central axis of the laser and has different orientations.

Fig. 17.

Phase matrix elements of a double-sphere system with a size parameter $x=6$ for each sphere under the incidence of a Laguerre-Gaussian beam with $p=0$. The refractive index of the particle is $m=1.31$. The laser waist is $w_0=90\ s$, where $s=\lambda/20$. The beam mode is $L=0, 1, 2$, and 3 , respectively. The distance of the central axis of the beam from the particle center is $d=0\ s$. The particle longer axis is perpendicular to the laser beam central axis as illustrated in Fig. 16 (a).

Fig. 18.

Same as in Fig. 17, but for a particle with a refractive index of 1.45.

Fig. 19.

Phase matrix elements of a double-sphere system with a size parameter $x=6$ for each sphere under the incidence of a Laguerre-Gaussian beam with $p=0$. The refractive index of the particle is $m=1.31$. The laser waist is $w_0=90 \text{ s}$, where $s=\lambda/20$. The beam mode is $L=0, 1, 2$, and 3 , respectively. The distance of the central axis of the beam from the particle center is $d=30 \text{ s}$. The particle longer axis is perpendicular to the laser beam central axis as illustrated in Fig. 16 (b).

Fig. 20.

Same as in Fig. 19, but for a particle with a refractive index of 1.45.

Fig. 21.

Phase matrix elements of a double-sphere system with a size parameter $x=6$ for each sphere under the incidence of a Laguerre-Gaussian beam with $p=0$. The refractive index of the particle is $m=1.31$. The laser waist is $w_0=90\text{ }\mu\text{m}$, where $\mu=\lambda/20$. The beam mode is $L=0, 1, 2$, and 3 , respectively. The distance of the central axis of the beam from the particle center is $d=30\text{ }\mu\text{m}$. The particle longer axis is perpendicular to the laser beam central axis as illustrated in Fig. 16 (c).

Fig. 22.

Same as in Fig. 21, but for a particle with a refractive index of 1.45.

Table 1:

Extinction, scattering, and absorption efficiencies, and asymmetry factors of a sphere with a size parameter $x=6$ under the incidence of a Laguerre- Gaussian beam with $p=0$. The laser waist is $w_0=60 \text{ } s$, where $s=\lambda/20$. The beam mode is $L=0, 1, 2$, and 3 , respectively.

$d \text{ (} s \text{)}$	L	Q_e	Q_s	Q_a	g
0	0	3.559279	3.333581	0.225698	0.873580
0	1	3.420234	3.164093	0.256141	0.769067
0	2	3.005170	2.722185	0.282985	0.659581
0	3	2.297978	2.015577	0.282401	0.547983
15	0	3.559684	3.333494	0.226190	0.872645
15	1	3.466528	3.231345	0.235183	0.831567
15	2	3.377274	3.126543	0.250731	0.779118
15	3	3.193164	2.928336	0.264829	0.722993
30	0	3.560636	3.332988	0.227648	0.869913
30	1	3.494175	3.270129	0.224046	0.864365
30	2	3.460235	3.228238	0.231997	0.836171
30	3	3.394458	3.152315	0.242143	0.799945

Table 2:

Extinction, scattering, and absorption efficiencies, and asymmetry factors of a sphere with a size parameter $x=12$ under the incidence of a Laguerre-Gaussian beam with $p=0$. The laser waist is $w_0=60 \text{ s}$, where $s=\lambda/20$. The beam mode is $L=0, 1, 2$, and 3 , respectively.

$d \text{ (s)}$	L	Q_e	Q_s	Q_a	g
0	0	1.457113	1.074362	0.382751	0.768548
0	1	2.176632	1.737726	0.438906	0.703314
0	2	3.065328	2.533468	0.531860	0.659965
0	3	3.951805	3.301477	0.650328	0.612869
15	0	1.490409	1.104745	0.385664	0.764353
15	1	1.999755	1.574397	0.425358	0.713068
15	2	2.514024	2.037590	0.476434	0.680191
15	3	3.091216	2.551691	0.539525	0.650445
30	0	1.582972	1.188701	0.394270	0.753810
30	1	1.713558	1.312488	0.401071	0.734372
30	2	1.910082	1.488099	0.421983	0.715034
30	3	2.310121	1.854249	0.455872	0.688102

Table 3:

Scattering efficiencies and asymmetry factors of a double-sphere system with a size parameter $x=6$ for each sphere under the incidence of a Laguerre-Gaussian beam with $p=0$. The laser waist is $w_0=90\ s$, where $s=\lambda/20$. The beam mode is $L=0, 1, 2$, and 3 , respectively. The refractive index of the particle is 1.31 . The particle longer axis is parallel to the central axis of the laser.

$d\ (s)$	L	Q_s	g
0	0	1.764834	0.740123
0	1	6.995956	0.803999
0	2	10.064387	0.672818
0	3	3.861228	0.499483
30	0	1.805497	0.741356
30	1	2.409713	0.766161
30	2	3.946892	0.784270
30	3	5.519612	0.768348

Table 4:

Scattering efficiencies and asymmetry factors of a double-sphere system with a size parameter $x=6$ for each sphere under the incidence of a Laguerre-Gaussian beam with $p=0$. The laser waist is $w_0=90\ s$, where $s=\lambda/20$. The beam mode is $L=0, 1, 2$, and 3 , respectively. The refractive index of the particle is 1.45 . The particle longer axis is parallel to the central axis of the laser.

$d\ (s)$	L	Qs	g
0	0	5.407433	0.850362
0	1	2.252197	0.483014
0	2	12.566621	0.576903
0	3	17.441421	0.394973
30	0	5.405363	0.847137
30	1	4.394901	0.805326
30	2	3.782311	0.676974
30	3	5.697247	0.587549

Table 5:

Scattering efficiencies and asymmetry factors of a double-sphere system with a size parameter $x=6$ for each sphere under the incidence of a Laguerre-Gaussian beam with $p=0$. The laser waist is $w_0=90 \text{ } \mu\text{s}$, where $s=\lambda/20$. The beam mode is $L=0, 1, 2$, and 3 , respectively. The refractive index of the particle is 1.31 . The particle longer axis is perpendicular to the central axis of the laser.

$d \text{ (} \mu\text{s)}$	Particle Orientation	L	Qs	g
0	Fig. 16(a)	0	2.967388	0.854734
0	Fig. 16(a)	1	4.037460	0.850882
0	Fig. 16(a)	2	3.296866	0.804054
0	Fig. 16(a)	3	3.321610	0.751902
30	Fig. 16(b)	0	2.995136	0.854837
30	Fig. 16(b)	1	3.274485	0.850619
30	Fig. 16(b)	2	3.394140	0.848168
30	Fig. 16(b)	3	3.472086	0.833894
30	Fig. 16(c)	0	2.967490	0.853599
30	Fig. 16(c)	1	3.352568	0.857945
30	Fig. 16(c)	2	3.999486	0.851507
30	Fig. 16(c)	3	3.917828	0.834429

Table 6:

Scattering efficiencies and asymmetry factors of a double-sphere system with a size parameter $x=6$ for each sphere under the incidence of a Laguerre-Gaussian beam with $p=0$. The laser waist is $w_0=90 \mu\text{m}$, where $s=w_0/20$. The beam mode is $L=0, 1, 2$, and 3 , respectively. The refractive index of the particle is 1.45 . The particle longer axis is perpendicular to the central axis of the laser.

$d (\mu\text{m})$	Particle Orientation	L	Q_s	g
0	Fig. 16(a)	0	3.181831	0.132156
0	Fig. 16(a)	1	3.649354	0.101828
0	Fig. 16(a)	2	4.180013	0.613991
0	Fig. 16(a)	3	4.518441	0.628603
30	Fig. 16(b)	0	3.191042	0.131315
30	Fig. 16(b)	1	3.553355	0.111488
30	Fig. 16(b)	2	3.328361	0.698562
30	Fig. 16(b)	3	3.105210	0.692489
30	Fig. 16(c)	0	3.208284	0.128258
30	Fig. 16(c)	1	3.368882	0.129200
30	Fig. 16(c)	2	3.960641	0.110833
30	Fig. 16(c)	3	4.261651	0.614934